


MAXHUB XBoard V7 Series

Model: C9850

Experience the ultimate in video conferencing and collaboration with the MAXHUB XBoard V7 series. Powered by a Windows PC module, this all-in-one design device seamlessly integrates an AI camera system, cutting-edge audio processing, interactive whiteboarding, and an intuitive meeting launcher, all housed within a single comprehensive collaboration display. This powerful combination enhances the dynamism of meetings and introduces a flexible and creative interaction to your organization.



Professional 4K Display

High color accuracy, $\Delta E \leq 1.5$
Wide color gamut, NTSC 90%




Precise Touch

Intelligent Touchscreen Technology
Revolutionary writing experience,
Windows Ink supported




BYOM Anytime

Embrace seamless efficiency
enabled by MAXHUB Share
App or wireless dongle




Smart Whiteboard

Direct annotation
Real-time collaboration




Get Spatial with Sound

8-mic array, 15 meters pick-up
range. Multiple AI-enhanced
audio algorithms




Built-in Speaker

2 × 10W + 20W speaker
2.1 sound channel



AI Camera System

50 MP camera
4.5x digital zoom, 99° ultra-wide FOV



Peak Performance

Unleash the power with MT71 series
PC module. 12th Gen Intel Processor
with Windows system, stably smooth

Display	
Model	C9850
Screen Size (Inch)	98
Aspect Ratio	16:9
Panel	ADS
Backlight	DLED
Brightness (Typ.)	350 nits
Glass	Zero parallax 3mm thickness 9H tempered
Surface Technology	Anti-glare, 25% haze
Resolution	3840 × 2160
Refresh Rate	60 Hz
Contrast Ratio	5000:1
Viewing Angle (H × V)	178° / 178°
Color Gamut	90% NTSC
Display Orientation	Landscape
Response Time	6.5 ms
Life Time	>50,000 hours
Operation Hours (Hours / Day)	16 / 7
Display Color	1.07B (10 bit)
Color Accuracy	Delta E ≤ 1.5
Sensor	Ambient light sensor
Pixel Pitch	0.4875(H) × 0.4875(V) mm
Display Area	2158.85(H) × 1214.35(V) mm

Connectivity	
I/O Ports (Interactive Display)	
HDMI IN × 2	Up to 4K@60Hz, HDCP 2.2, CEC
USB 2.0 × 1	For system upgrades
USB 3.0 × 2	For external peripherals
USB Type-C IN × 1	USB 2.0, supports DP 1.2 input, wireless dongle pairing, and BYOD
TOUCH 2.0 × 1	USB 2.0 Type B
AUDIO IN × 1	3.5mm Jack
AUDIO OUT × 1	3.5mm Jack
RS232 × 1	Baud rate 9600
RJ45 IN × 1	Mic in, microphone cascade, AES67 protocol
I/O Ports (MT71S/MT71P PC Module)	
HDMI OUT × 1	Up to 4K@30Hz
USB 2.0 × 3	For external peripherals
USB 3.0 × 3	For external peripherals
RJ45 IN × 1	10M/100M/1000Mbps
MIC IN × 1	3.5 mm Jack, input for microphone
PC Module Slot	Module slot × 1
PC Module System	Windows10 IOT (64bit)
Wi-Fi Slot	Module slot × 1
Wi-Fi (MT71S/MT71P PC Module)	Wi-Fi 6 supported 802.11ax, 2.4GHz/5GHz
Bluetooth (MT71S/MT71P PC Module)	5.2

Touch System	
Touch Technology	Intelligent Touchscreen Technology (infrared recognition)
Touch Point	50 points touch
Object Recognition Range	≥1.5 mm
Accuracy	±0.5 mm
Response Time	≤2.5 ms
Writing Height	≤1 mm
System (Touch Return)	Windows11/Windows10/Windows8/Windows7/Android/Linux/Mac OS X/Chrome OS
Feature	Windows Ink / Direct Annotation / Palm Rejection / Sharp Erase Multi-input Recognition / Handwriting Recognition

Camera	
Quantity	1
Resolution	50 MP
Zoom	4.5x digital zoom
Field of View	99° (Diagonal) 86° (Horizontal) 69° (Vertical)
Position	Built-in ejection
Feature	Personalized presets Auto framing Speaker tracking

Audio	
Sound Channel	2.1
Speaker Power	2 × 10W + 20W
Microphone	
Quantity	8-mic array
Pick-up Angle	180°
Pick-up Range	0~15m
Feature	Intelligent audio fence AI spatial sound AEC (Auto echo cancellation) ANC (AI noise cancellation) AGC (Auto gain control)

Feature	
System OS	MAXHUB OS 7.0 powered by Windows
Screen Share	MAXHUB Share Support BYOM / Miracast / Airplay / Chromecast / P2P
Device Management	MAXHUB Pivot
Protocol Control	RS232 / IP control Supports integration with Crestron / Extron / Q-sys
Special Features	Microsoft Intune

Accessory		Physical Specification	
Power Cord	3m × 1	Dimension (W × H × D)	2227 × 1325 × 94 mm
HDMI Cable	1.5m × 1	Shipping Dimension (W × H × D)	2406 × 1461 × 280 mm
Stylus	× 2	Thickness of machine and wall mount	140 mm
Wall Mount	WIB9060H	Wall-hanging Screw Spec	M8 × 25 mm
Wireless Adapter	SI07B	VESA	800 × 600 mm
		Net Weight	97.2 Kg
		Gross Weight	121.35 Kg
Environmental Conditions		Power	
Operating Temperature	0°C~40°C	Power Supply	200V~ 50Hz 2.0A
Storage Temperature	-20°C~60°C	Standby Power	≤ 0.5 W
Operating Humidity	10%~90%RH	Power Consumption (Typ.)	320 W
Storage Humidity	10%~90%RH		
Altitude	Below 5000 meters		

Certification	
EMC	Class B
IP Rating	IP5X design standards

Warranty	
3 years warranty	

Optional Module	
Pluggable PC Module	MT71S / MT71P
Mobile Stand	ST23C
Wireless Dongle	WT13
 MT71S / MT71P  ST41B  ST23C  WT13	

Statement	
Size and weight vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product. The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance.Should the above-mentioned change in the document become necessary, the document may be updated without written notice.	

MAXHUB

Where Inspiration Moves Ahead.



www.maxhub.com/en/



sales@maxhub.com



<https://www.youtube.com/c/MAXHUB>



<https://www.facebook.com/MAXHUB.Global>



<https://www.linkedin.com/company/maxhub-overseas/>