

X1

GNSS RECEIVER

Smaller & Stronger For Field Tasks



STRONG GNSS PERFORMANCE

To ensure superior GNSS performance in every corner of the world, the X1 is equipped with a high-precision GNSS engine for simultaneously tracking GPS, BDS, GLONASS, Galileo, QZSS, IRNSS & SBAS. Adopted with anti-interference technology, the X1 offers reliable positioning in any complex environments.

COMPREHENSIVE WORK MODES

In order to meet different user demands, X1 supports comprehensive working modes - 8GB storage for static measurement, enhanced UHF module for 15km internal UHF mode and longer external radio mode, 4G modem for internal GSM mode and Bluetooth connection to PDA CORS mode.

EASY-TO-USE DESIGN

In addition to basic functions, the X1 GNSS receiver is also designed with abundant features to smooth your work. 60° IMU tilt for higher efficiency, NFC for faster connection, 6700mAh batteries for 20hrs operation, webUI for easier data download & upgrade, IP68 protection for harsh work surroundings and ultra-small size of $\Phi 133.5 \times 67$ mm to light your burden.

SATELLITES TRACKING

BDS	B1I, B2I, B3I, B1C, B2a, B2b ¹
GPS	L1 C/A, L1C, L2P, L2C, L5
GLONASS	G1, G2, G3
Galileo	E1, E5a, E5b
QZSS	L1, L2, L5
IRNSS	L5
SBAS	WAAS, EGNOS, SDCM, BDSBAS, GAGAN
L-Band	Upgradeable
Cold start	<30s
RTK Initialization Time	<5s(typical)
RTK initialization reliability	>99.9%
Re-acquisition	<1s

ACCURACY

Standalone	1.5m Horizontally 2.5m Vertically
DGPS	0.4m Horizontally 0.8m Vertically
Static post-processing	2.5mm+0.5ppm Horizontally 5mm+0.5ppm Vertically
RTK	8mm+1ppm Horizontally 15mm+1ppm Vertically
SBAS	< 1.0 m 3D RMS
Time Accuracy	20ns
Tilt surveying	< 2.5cm, within 60° tilt

DATA FORMAT

Data output format	- NMEA-0183 - RINEX 3.02/3.04 - Binary format *.xyz
Data update rate	1~50Hz selectable
Correction data format	- RTCM v3.3/3.2/3.1/3.0 - CMR
Supported protocols	Ntrip client, Ntrip Server, Ntrip Caster, TCP

COMMUNICATION

4G modem	FDD-LTE B1/B3/B5/B7/B8 TDD-LTE B38/B39/B40/B41 TDSCDMA B34/B39 WCDMA B1/B2/B5/B8 GSM B2/B3/B5/B8 CDMA1x/CDMA2000 BC0/BC1
UHF modem ²	- Working range: 5km – 15km ³ , in ideal environments - Frequency range: 410-470MHz - Protocol: TRIMATLK, TRANSEOT, SATEL, TRIMARK3, etc. - Channel spacing: 25KHz - Transmit power: 0.5W/1W selectable
Bluetooth	BT4.0 dual mode
NFC	Support NFC connection
WiFi	802.11 a/b/g/n/ac
Interface	- 1 7-pin lemo port for RS232 transmission and power supply - 1 SIM card slot for 4G - 1 TNC connector for UHF antenna - 1 Type-C USB port for static data download & firmware upgrade

USER INTERACTION

Indicators	4 LEDs indicating battery/charging, satellite tracking, correction data transmission, and 4G status/static recording
Button	2 buttons for power and function
WebUI	- Accessible via Wi-Fi - Support configuration, status checking, data transfer, data storage and system upgrade

ELECTRICAL

Power consumption	2.0 W ⁴
Input voltage	DC 9~28V
Battery	- 6700 mAh, over 20 hours working time - Fast charge of 2.5 hours charging time

PHYSICAL

Size	Φ133.5 mm × 67 mm
Weight	870 g
Storage	8 GB ⁵
Housing material	Magnesium-aluminum alloy
Speaker (optional)	For voice broadcast of real-time status

ENVIRONMENTAL

Working temperature	-40 °C to +65 °C
Storage temperature	-55 °C to +85 °C
Humidity	100% non-condensing
Waterproof & dustproof	IP68
Drop	Designed to survive a 2m drop onto concrete

1. The BDS B2b signal is reserved for future upgrade.
2. The enhanced UHF modem is not compatible with the normal UHF modem on the market. For different user needs, SingularXYZ also provides normal UHF as an option compatible with UHF of other brands. Please clarify your requirements when placing the order.
3. The maximum working range of the enhanced UHF modem is 15km in ideal environments.
4. The power consumption of X1 varies with the different work modes.
5. Storage can be expanded to 32GB according to user demands.

All specifications are subject to change without notice.

©2023 SingularXYZ Intelligent Technology Ltd. All rights reserved. SingularXYZ[®] is the official trademark of SingularXYZ Intelligent Technology Ltd., registered in People's Republic of China, EU. All other trademarks are the property of their respective owners.