

RACKS BRAX.®

COMPATIBILITY POCKET GUIDE

FOR

CANYON
CANYON
O F F - R O A D

FAST ON!
FAST OFF!

AWNING AND ACCESSORY
MODELS

CLICK OR TAP ON AN AWNING/ACCESSORY BELOW
TO TAKE YOU TO THE PAGE TO FIND OUT WHAT YOU NEED

CANYON OFF-ROAD® ALUMINIUM HARDSHELL SIDE AWNING 2 x 3m 3

CANYON OFF-ROAD® HARDSHELL SHOWER TENT AWNING 4

CANYON OFF-ROAD® ALUMINIUM HARDSHELL SIDE AWNING *2 x 3m*

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard*
ADAPTOR NEEDED	8192 – HD Awning Adaptor Plate (DOUBLE)*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	SUPPLIED BRACKET WILL REQUIRE DRILLING (1) ONE HOLE TO MATCH 40-52 MM SPACING ON HD HITCH.
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8304 – HD Adjustable Brackets Short (DOUBLE)*; OR 8306 – HD Adjustable Brackets Long (DOUBLE)*.
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts ⁺ ✓ LOCKED GARAGES ✓ WORKSHOP WALLS
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts ⁺ ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA

⁺NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

CANYON OFF-ROAD® HARDSHELL SHOWER TENT AWNING

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard*
ADAPTOR NEEDED	8192 – HD Awning Adaptor Plate (DOUBLE)*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	SUPPLIED BRACKET WILL REQUIRE DRILLING (1) ONE HOLE TO MATCH 40-52 MM SPACING ON HD HITCH.
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR
	8304 – HD Adjustable Brackets Short (DOUBLE)*; OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts ⁺
✓ LOCKED GARAGES	
✓ WORKSHOP WALLS	
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts ⁺
✓ OPEN CARPORTS	
✓ PUBLIC/SHARED GARAGE AREA	

⁺NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.