GP17500E



GP SERIES

Commercial/Residential Portable Generators

A/C Rated Output Watts 17,500 A/C Maximum Output Watts 26,250

Model 5735-0

UPC Number: 696471057355

Emissions Certification: Not for sale in

California or Canada.




features

- GENERAC OHVI OVERHEAD VALVE INDUSTRIAL ENGINE WITH FULL PRESSURE LUBRICATION AND SPIN-ON FILTER
- HIGH PERFORMANCE ALTERNATOR
- RESIN FUEL TANK WITH FUEL GAUGE
- FIXED HANDLES
- 12.3" PNEUMATIC WHEELS
- 1.25" HARDENED STEEL TUBE CRADLE
- CIRCUIT BREAKER PROTECTED OUTLETS
- LOW TONE MUFFLER

customer connections

Circuit Breakers			
М	(1) 20A		
N	(1) 20A GFCI		
0	(4) 30A		
Other Features			
н	Hour Meter with		

Idle Control



GP17500E

specifications

Product Series	GP17500E
Model	5735-0
Configuration/Emissions	49-State
A/C Rated Output Watts:	17500
A/C Maximum Output Watts:	26250
A/C Voltage	120/240VAC
A/C Frequency	60 Hz
Rated 120/240 VAC Amperage	72.9
Max 120/240 VAC Amperage	109.4
Engine Displacement	992cc
Engine Type	OHVI
Engine RPM	3600
Recommended Oil	5W30
Lubrication Method	Full Pressure
Choke Type	Manual Lever
Fuel Shut Off	Manual Lever
Idle Control	No Load Low Speed
Starting Method	Electric
Battery	Included
Battery Size	12VDC 365 CCA
Low Oil Shutdown Method	Low Pressure

Start Switch Type	3-Position
Switch Location	On Engine
Single-Point Lifting Eye	Included
Fuel Gauge	Built-In
Fuel Tank Capacity (Gal)	16
Fuel Tank Capacity (Liters)	60.56
Run Time at 50% (Hours)	10
Cord Set	No
Handle Style	Fixed
Wheel type	12.3" Pneumatic Wheels
Maintenance Kit	Sold Separately
Warranty - Residential	2 Year
Warranty - Commercial	1 Year

dimensions and weights

Length (L)	48.5
Width (W)	30.75
Height (H)	38.5
Extended Length (EL)	n/a
Carton Length	49.25
Carton Width	23.25
Carton Height	31
Unit Weight (lbs)	390
Shipping Weight (lbs)	400

