



STA PUT® STAINLESS PLUMBERS PUTTY TECHNICAL SPECIFICATION

Job Name _____	Item # _____
Location _____	
Engineer _____	Contractor _____
PO # _____	Tag _____
Representative _____	

DESCRIPTION

A plumbing sealing and caulking compound for setting plumbing fixtures, bowls, faucets, basin cocks, strainers, plugs, and sink frames. Will not stick to fingers or hands. Always the same smooth, uniform appearance from top to bottom of container with superior sealing qualities. **Sta put** will not harden, crumble, crack or shrink. It is flexible and stretchable, spreads easily, and can be molded into rings or shaped to the precise configuration needed. It provides a gas proof, fume proof, odor proof, insect proof and watertight seal. Meets or exceeds Federal Specification TT-P-1536.

APPROVALS AND LISTINGS

- Meets Federal Specification TT-P-1536.

APPLICATION / USES

- Used for setting bowls, fixtures, faucets, basin cocks, strainers, plugs, sink frames as well as many other sealing and caulking jobs.
- Professional non-hardening putty for sealing and caulking.

*For special applications which may not be covered on this or other Oatey literature, please contact Oatey Technical Services Department by phone 1-800-321-9532, or fax 1-800-321-9535, or visit our technical database web-site at www.Oatey.com

PHYSICAL PROPERTIES / INGREDIENTS

PHYSICAL/CHEMICAL PROPERTIES

Appearance/color/odor	Beige color with very mild vegetable oil odor
Specific Gravity	2.00 - 2.05
Solubility in Water	Insoluble

MATERIAL SAFETY INFORMATION

FOR MORE INFORMATION ON THIS PRODUCT, REQUEST SAFETY DATA SHEET (SDS) #1618E

For Delivery by Fax	Call 1-800-321-9535
Internet	See SDS section of www.Oatey.com
HMIS® ratings	Health: 0 Flammability: 0 Physical hazard: 0

This product is not classified as hazardous as defined by OSHA 29 CFR 1910.1200.



PRODUCT SELECTOR

STA PUT STAINLESS PLUMBERS PUTTY

✓	Product Number	Size	Packing	Weight
	25101	14 oz.	24	22.9 lbs.
	25103	3 lbs.	12	38.5 lbs.
	25105	5 lbs.	6	32.0 lbs.
	25110	7 lbs.*	6	45.0 lbs.

*Plastic Pail with Handle

PRECAUTIONS

DO NOT USE STA PUT IN DIRECT CONTACT WITH MARBLE, GRANITE OR OTHER POROUS STONE, CERAMICS OR MANUFACTURED SUBSTITUTES. USE HERCULES STA PUT ULTRA INSTEAD. DO NOT USE STA PUT IN DIRECT CONTACT WITH ABS PLASTIC.

DIRECTIONS

Take out required amount and form the putty to the approximate shape needed. **Sta put** can be rolled between the palms of your hands to form a long cord-like shape. Lay out on the surface being sealed, overlapping the ends. Place the fixture over the bead, attach and tighten down the fasteners for the fixture. Enough **Sta put** should be used so that some excess putty is squeezed out from all around the fixture ensuring that a continuous seal has been made. Wipe off the excess; no additional sealer is needed. Use this method for setting bowls, fixtures, faucets, basin cocks, strainers, plugs, sink frames, toilet perimeters and other sealing and caulking applications.