



## SNOW BLOWERS

60V BATTERY / POWER CLEAR® SINGLE-STAGE / SNOWMASTER® / POWER MAX® TWO-STAGE / POWER TRX HEAVY-DUTY

# FEAR NO STORM



†Based on average TraQline dollar share for snow blower market from 2013 – March 2022

# 60V<sup>MAX</sup> FLEX-FORCE POWER SYSTEM<sup>®</sup>

## EVERY SINGLE JOB. ONE SINGLE BATTERY.



### POWER CLEAR<sup>®</sup>

Gives you the edge in speed, quality, and convenience.



#### 60V POWER CLEAR<sup>®</sup> SELF-PROPEL POWER CURVE<sup>®</sup> TECHNOLOGY

Delivers a self-propelled experience with a ground engaging paddle powering through compacted snow with ease. *Select models.*



#### SNOWDRIFT STRENGTH

Bust through 2-9" of heavy, wet snow, throwing it up to 12 m / 40 feet.



#### CRUSH SNOW TO THE CURB

60V Flex-Force Power System<sup>®</sup> - one powerful battery system, 50+ unbeatable tools.



### POWER MAX<sup>®</sup>

Three battery ports where the gas tank used to be.



#### POWER UP

All the features you love – Quick Stick<sup>®</sup> chute control, rugged 15" / 38 cm tires, anti-clogging system, and more.



#### GO THREE ROUNDS WITH OLD MAN WINTER

The only snow blower with three battery ports, this machine has all the power you need to get the job done right.



#### ZERO COMPROMISES

Same rugged, heavy-duty steel construction as Toro gas-powered snow blowers, with LED lights, hardened gears and no shear pins to break.



| 60V MAX <sup>*</sup> BATTERY SNOW BLOWERS |                                                 |                                                     |                                                |                                                          |                                                                        |                                                                                                      |                                                                                                      |
|-------------------------------------------|-------------------------------------------------|-----------------------------------------------------|------------------------------------------------|----------------------------------------------------------|------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
|                                           | POWER SHOVEL <sup>*</sup><br>60V                | SINGLE-STAGE<br>POWER CLEAR <sup>*</sup><br>60V E21 | SINGLE-STAGE<br>POWER CLEAR<br>60V E21         | SP SINGLE-STAGE<br>POWER CLEAR<br>60V E21<br><b>NEW!</b> | COMMERCIAL<br>SP SINGLE-STAGE<br>POWER CLEAR<br>60V E21<br><b>NEW!</b> | TWO-STAGE<br>POWER MAX <sup>*</sup><br>60V E24                                                       | TWO-STAGE<br>POWER MAX HA<br>60V E26                                                                 |
| MODEL                                     | 39909                                           | 39901                                               | 39902                                          | 39921                                                    | 39922T                                                                 | 39924                                                                                                | 39926                                                                                                |
| CLEARING WIDTH                            | 12" / 30.5 cm                                   | » 21" / 53.3 cm                                     | 21" / 53.3 cm                                  | 21" / 53.3 cm                                            | » 21" / 53.3 cm<br>w/ Extended Life<br>Paddles                         | » 24" / 61.0 cm                                                                                      | » 26" / 66.0 cm                                                                                      |
| CLEARING CAPACITY**                       | Decks, steps, patios<br>and up to 4 parked cars | » Up to 12 parked cars                              | » Up to 18 parked cars<br>(9 cars per battery) | Up to 15 parked cars                                     | Up to 15 parked cars                                                   | » Up to 24 parked cars<br>(12 cars per battery)<br>Up to 15 cars more with<br>additional 3rd battery | » Up to 30 parked cars<br>(15 cars per battery)<br>Up to 15 cars more with<br>additional 3rd battery |
| SNOW CUT DEPTH                            | 6" / 15.2 cm                                    | » 12" / 30.5 cm                                     | 12" / 30.5 cm                                  | 12" / 30.5 cm                                            | 12" / 30.5 cm                                                          | » 20" / 50.8 cm                                                                                      | 20" / 50.8 cm                                                                                        |
| BATTERY                                   | 1 x 2.5 ah                                      | » 1 x 7.5 ah                                        | » 2 x 6.0 ah                                   | 1 x 7.5 ah + 1 x 2.5 ah                                  | N/A                                                                    | 2 x 6.0 ah                                                                                           | » 2 x 7.5 ah                                                                                         |
| CHARGE TIME                               | 60 min                                          | 180 min                                             | 150 min                                        | 180 min                                                  | N/A                                                                    | 150 min                                                                                              | 180 min                                                                                              |
| THROWING DISTANCE**                       | Up to 25' / 7.6 m                               | » Up to 40' / 12.2 m                                | Up to 40' / 12.2 m                             | Up to 30' / 9.1 m                                        | Up to 30' / 9.1 m                                                      | » Up to 45' / 13.7 m                                                                                 | Up to 45' / 13.7 m                                                                                   |
| AUGER SYSTEM                              | Power Curve                                     | Patent Pending<br>Power Edge™                       | Patent Pending<br>Power Edge                   | » Power Curve <sup>®</sup><br>Self-Propel                | Power Curve<br>Self-Propel                                             | » Power Max<br>Anti-Clogging System                                                                  | Power Max<br>Anti-Clogging System                                                                    |
| AUGER DIAMETER                            | 6.5" / 16.5 cm                                  | » 7" / 17.8 cm                                      | 7" / 17.8 cm                                   | » 8.5" / 21.6 cm                                         | 8.5" / 21.6 cm                                                         | » 11" / 27.9 cm                                                                                      | 11" / 27.9 cm                                                                                        |
| IMPELLER DIAMETER                         | -                                               | -                                                   | -                                              | -                                                        | -                                                                      | 11" / 27.9 cm                                                                                        | 11" / 27.9 cm                                                                                        |
| AUGER GEARBOX                             | -                                               | -                                                   | -                                              | -                                                        | -                                                                      | » Hardened Gears;<br>No Shear Pins                                                                   | Hardened Gears;<br>No Shear Pins                                                                     |
| HANDLE                                    | -                                               | Adjustable                                          | Adjustable                                     | Ergonomic                                                | » Reinforced &<br>Ergonomic                                            | Standard                                                                                             | » Heavy-Duty                                                                                         |
| DEFLECTOR                                 | -                                               | Locking                                             | Locking                                        | Locking                                                  | Locking                                                                | Single                                                                                               | Single                                                                                               |
| CHUTE CONTROL                             | -                                               | Quick Turn                                          | Quick Turn                                     | Chute Mounted                                            | Chute Mounted                                                          | » Quick Stick <sup>®</sup>                                                                           | Quick Stick                                                                                          |
| CHUTE CONSTRUCTION                        | -                                               | Sub Zero Curved Chute                               | Sub Zero Curved Chute                          | » High Capacity Chute                                    | High Capacity Chute                                                    | » Steel                                                                                              | Steel                                                                                                |
| TIRES                                     | -                                               | 6 7/8" x 2"<br>17.5 cm x 5.1 cm                     | 6 7/8" x 2"<br>17.5 cm x 5.1 cm                | » 7" / 17.8 cm                                           | 7" / 17.8 cm                                                           | » 15" / 38.1 cm                                                                                      | 15" / 38.1 cm                                                                                        |
| HAND WARMERS                              | -                                               | -                                                   | -                                              | -                                                        | -                                                                      | -                                                                                                    | » Standard                                                                                           |
| LIGHT                                     | -                                               | Panoramic LED                                       | Panoramic LED                                  | Panoramic LED                                            | Panoramic LED                                                          | LED                                                                                                  | LED                                                                                                  |
| WARRANTY***                               | 3-Year Limited,<br>3-Year Battery               | 2-Year Limited,<br>3-Year Battery                   | 2-Year Limited,<br>3-Year Battery              | 2-Year Limited,<br>3-Year Battery                        | 2-Year Limited,<br>3-Year Battery                                      | 3-Year Limited,<br>3-Year Battery                                                                    | 3-Year Limited,<br>3-Year Battery                                                                    |
| BARE TOOL MODEL #                         | 39909T                                          | 39901T                                              | 39901T                                         | 39921T                                                   | -                                                                      | -                                                                                                    | 39926T                                                                                               |

» Enhanced or step-up feature

\*Battery manufacturer rating = 60V maximum and 54V typical usage. Actual voltage varies with load. \*\*Throw distance and clearing capacity will vary with conditions. \*\*\*See retailer for complete warranty details.



## POWER SHOVEL<sup>®</sup>

Easy to maneuver, convenient, cordless  
and complete snow clearing.

# POWER CLEAR®

## SINGLE-STAGE SNOW BLOWERS

**Tackle small driveway, walkway and patio jobs in no time with Power Clear.**

The perfect blend of power and efficiency to get the job done fast. Plus a compact design for easy storage leaves room in the garage for what matters most.

SURFACE TYPE MODERATE SLOPE CARS / DRIVEWAY



|                    | POWER CLEAR® SINGLE-STAGE                    |                                   |                                                                                                      |                                           |                                              |                             |
|--------------------|----------------------------------------------|-----------------------------------|------------------------------------------------------------------------------------------------------|-------------------------------------------|----------------------------------------------|-----------------------------|
|                    | POWER CLEAR®<br>518 ZR/ZE<br><b>NEW!</b>     | POWER CLEAR<br>721 R/E            | COMMERCIAL<br>POWER CLEAR<br>721 R-C                                                                 | COMMERCIAL<br>POWER CLEAR<br>821 R-C      | POWER CLEAR<br>721 QZE                       | POWER CLEAR<br>821 QZE      |
| MODEL              | 38474 / 38475                                | 38752 / 38753                     | 38754                                                                                                | 38755                                     | 38756                                        | 38757                       |
| CLEARING WIDTH     | 18" / 45.7 cm                                | » 21" / 53.3 cm                   | » 21" / 53.3 cm<br>w/ Extended Life Paddles                                                          | 21" / 53.3 cm<br>w/ Extended Life Paddles | 21" / 53.3 cm                                | 21" / 53.3 cm               |
| SNOW CUT DEPTH     | 12" / 30.5 cm                                | » 12.5" / 31.2 cm                 | 12.5" / 31.2 cm                                                                                      | 12.5" / 31.2 cm                           | 12.5" / 31.2 cm                              | 12.5" / 31.2 cm             |
| ENGINE             | 99cc Toro Premium OHV                        | » 212cc Toro Premium OHV          | 212cc Toro Premium OHV                                                                               | » 252cc Toro Premium OHV                  | 212cc Toro Premium OHV                       | » 252cc Toro Premium OHV    |
| DRIVE SYSTEM       | Rotor Propelled                              | » Self-Propelled<br>Power Propel® | Self-Propelled Power Propel                                                                          | Self-Propelled Power Propel               | Self-Propelled Power Propel                  | Self-Propelled Power Propel |
| STARTING           | Recoil / Electric                            | Recoil / Electric                 | Recoil                                                                                               | Recoil                                    | Electric                                     | Electric                    |
| THROWING DISTANCE* | Up to 25' / 7.6 m                            | » Up to 35' / 10.7 m              | Up to 35' / 10.7 m                                                                                   | » Up to 40' / 12.2 m                      | Up to 35' / 10.7 m                           | » Up to 40' / 12.2 m        |
| AUGER SYSTEM       | Power Curve                                  | Power Curve                       | Power Curve                                                                                          | Power Curve                               | Power Curve                                  | Power Curve                 |
| HANDLE             | Standard                                     | » Ergonomic                       | » Reinforced &<br>Ergonomic Handle                                                                   | Reinforced &<br>Ergonomic Handle          | Ergonomic                                    | Ergonomic                   |
| DEFLECTOR          | Locking                                      | Locking                           | Locking                                                                                              | Locking                                   | Locking                                      | Locking                     |
| CHUTE CONTROL      | Chute Mounted                                | Chute Mounted                     | Chute Mounted                                                                                        | Chute Mounted                             | » Quick Chute                                | Quick Chute                 |
| TIRES              | 6" x 1.5" / 15.2 x 3.8 cm                    | » 7" x 1.75" / 17.8 x 4.4 cm      | 7" x 1.75" / 17.8 x 4.4 cm                                                                           | 7" x 1.75" / 17.8 x 4.4 cm                | 7" x 1.75" / 17.8 x 4.4 cm                   | 7" x 1.75" / 17.8 x 4.4 cm  |
| WARRANTY**         | 2-Year Limited<br>2-Year Guaranteed to Start |                                   | 2-Year Limited Residential, 1-Year Limited Commercial<br>2-Year Guaranteed to Start Residential Only |                                           | 2-Year Limited<br>2-Year Guaranteed to Start |                             |

» Enhanced or step-up feature



## Win Winter with America's #1 Snow Blower Brand

Power Clear single-stage snow blowers are loaded with big time power in a compact size. Its light weight and ergonomic handle make this powerhouse so easy to maneuver.

\*Throw distance and clearing capacity will vary with conditions. \*\*See retailer for complete warranty details.  
†Based on average TraQline dollar share for snow blower market from 2013 – March 2021.

POWER CLEAR®  
SINGLE-STAGE

**IDEAL FOR** Driveways that can hold up to 9 cars and 2-9" / 5-23 cm of snow with limited garage storage



### POWER TO BLAST THROUGH SNOW

Toro's powerful 4-cycle OHV engines give you the power to slice through snow in no time and throw it 40 feet/12 m.†



### GET A MOVE ON

Keep moving to get done faster with self-propel Power Propel® system. The unique scraper pulls you through the snow. Select models.



### SHREDS SNOW FAST

Efficiently shreds through snow while reducing clogging with the curved rubber paddles and housing of Power Curve® Technology.

# POWER MAX® & POWER MAX® HD

## TWO-STAGE SNOW BLOWERS

Take National Weather Service major winter storm warnings, chew 'em up and spit 'em out. Power Max and Power Max HD snow blowers are unbeatable in any storm.

Take control of big snow jobs this winter with Power Max and Power Max HD. These two-stage snow blowers clear wide paths with speed and ease.

SURFACE TYPE MODERATE SLOPE CARS / DRIVEWAY



### Power Clear 821 QZE

252cc Toro Premium OHV Engine  
Self-Propelled Power Propel®  
21" / 53 cm Clearing Width



### Power Max 826 OHAE

Hand Warmers Standard  
Heavy Duty Handle Construction  
26" / 66 cm Clearing Width

### POWER MAX® COMPACT TWO-STAGE

|                    | POWER MAX<br>824 OE              | POWER MAX<br>826 OAE             | POWER MAX<br>826 OHAE            |
|--------------------|----------------------------------|----------------------------------|----------------------------------|
| MODEL              | 37798                            | 37799                            | 37802/37805                      |
| CLEARING WIDTH     | 24" / 61.0 cm                    | » 26" / 66.0 cm                  | 26" / 66.0 cm                    |
| SNOW CUT DEPTH     | 20" / 50.8 cm                    | 20" / 50.8 cm                    | 20" / 50.8 cm                    |
| ENGINE             | 252cc Toro Premium OHV           | 252cc Toro Premium OHV           | 252cc Toro Premium OHV           |
| DRIVE SYSTEM       | Self-Propelled                   | » Triggerless Steering           | Triggerless Steering             |
| STARTING           | Electric                         | Electric                         | Electric                         |
| THROWING DISTANCE* | Up to 45' / 13.7 m               | Up to 45' / 13.7 m               | Up to 45' / 13.7 m               |
| AUGER SYSTEM       | Power Max Anti-Clogging          | Power Max Anti-Clogging          | Power Max Anti-Clogging          |
| AUGER DIAMETER     | 11" / 27.9 cm                    | 11" / 27.9 cm                    | 11" / 27.9 cm                    |
| IMPELLER DIAMETER  | 11" / 27.9 cm                    | 11" / 27.9 cm                    | 11" / 27.9 cm                    |
| AUGER GEARBOX      | Hardened Gears,<br>No Shear Pins | Hardened Gears,<br>No Shear Pins | Hardened Gears,<br>No Shear Pins |
| HANDLE             | Standard                         | Standard                         | » Heavy-Duty                     |
| DEFLECTOR          | Single                           | Single                           | Single                           |
| CHUTE CONTROL      | Quick Stick®                     | Quick Stick                      | Quick Stick                      |
| TIRES              | 15" / 38.1 cm                    | 15" / 38.1 cm                    | 15" / 38.1 cm                    |
| HAND WARMERS       | -                                | -                                | » ✓                              |
| LED LIGHT          | -                                | » ✓                              | ✓                                |
| WARRANTY**         | 3-Year Limited                   | 3-Year Limited                   | 3-Year Limited                   |



### Power Max H

Commercial-Grade  
All-Steel Construction  
16" / 40.6 cm Tires



### Power Max H

30" / 76 cm Clearing Width  
302cc Toro Premium OHV Engine  
Double Deflector  
Hand Warmers Standard

### POWER MAX® COMPACT TWO-STAGE

**IDEAL FOR** Larger driveways that can hold 6-14 parked cars and 6-20" / 15-50 cm of snow at a time



#### POWER UP

Optimal performance and years of dependable use with the 252cc Toro premium 4-cycle OHV engine.



#### TRIGGERLESS STEERING

No triggers to pull or levers to break! Turn the machine and the wheel intelligently disengages to assist you through for effortless turns.



#### CHUTE CONTROL

Quickly change the chute and deflector direction with a single, smooth motion thanks to the Quick Stick® chute control.



## HD 828 OAE

Auger Gear Box  
Position  
S



## HD 1030 OHAE

ing Width  
um OHV Engine

Standard

| POWER MAX® HEAVY-DUTY TWO-STAGE |                                    |                                    |                                    |                                         |                                         |
|---------------------------------|------------------------------------|------------------------------------|------------------------------------|-----------------------------------------|-----------------------------------------|
|                                 | POWER MAX HD<br>828 OAE            | POWER MAX HD<br>1030 OHAE          | POWER MAX HD<br>1232 OHXE          | COMMERCIAL<br>POWER MAX HD<br>1428 OHXE | COMMERCIAL<br>POWER MAX HD<br>1432 OHXE |
| MODEL                           | 38838                              | 38830                              | 38842                              | 38843                                   | 38844                                   |
| CLEARING WIDTH                  | 28" / 71.1 cm                      | » 30" / 76.2 cm                    | » 32" / 81.3 cm                    | 28" / 71.1 cm                           | » 32" / 81.3 cm                         |
| SNOW CUT DEPTH                  | 21" / 53.3 cm                      | 21" / 53.3 cm                      | 21" / 53.3 cm                      | 21" / 53.3 cm                           | 21" / 53.3 cm                           |
| ENGINE                          | 252cc Toro Premium OHV             | » 302cc Toro Premium OHV           | » 375cc Toro Premium OHV           | » 420cc Toro Premium OHV                | 420cc Toro Premium OHV                  |
| DRIVE SYSTEM                    | Triggerless Steering               | Triggerless Steering               | » Power Steering                   | Power Steering                          | Power Steering                          |
| STARTING                        | Electric                           | Electric                           | Electric                           | Electric                                | Electric                                |
| THROWING DISTANCE¹              | Up to 45' / 13.7 m                 | » Up to 49' / 14.9 m               | » Up to 57' / 17.4 m               | » Up to 60'+ / 18.3 m+                  | Up to 60'+ / 18.3 m+                    |
| AUGER SYSTEM                    | Power Max Anti-Clogging            | Power Max Anti-Clogging            | Power Max Anti-Clogging            | Power Max Anti-Clogging                 | Power Max Anti-Clogging                 |
| AUGER DIAMETER                  | 14" / 35.6 cm                      | 14" / 35.6 cm                      | 14" / 35.6 cm                      | 14" / 35.6 cm                           | 14" / 35.6 cm                           |
| IMPELLER DIAMETER               | 14" / 35.6 cm                      | 14" / 35.6 cm                      | 14" / 35.6 cm                      | 14" / 35.6 cm                           | 14" / 35.6 cm                           |
| AUGER GEARBOX                   | Commercial-Grade,<br>No Shear Pins | Commercial-Grade,<br>No Shear Pins | Commercial-Grade,<br>No Shear Pins | Commercial-Grade,<br>No Shear Pins      | Commercial-Grade,<br>No Shear Pins      |
| HANDLE                          | Heavy-Duty                         | Heavy-Duty                         | Heavy-Duty                         | » Commercial                            | Commercial                              |
| DEFLECTOR                       | Single                             | Double                             | Double                             | Double                                  | Double                                  |
| CHUTE CONTROL                   | Quick Stick®                       | Quick Stick                        | Quick Stick                        | Quick Stick                             | Quick Stick                             |
| TIRES                           | 16" / 40.6 cm                      | 16" / 40.6 cm                      | 16" / 40.6 cm                      | 16" / 40.6 cm                           | 16" / 40.6 cm                           |
| HAND WARMERS                    | -                                  | » ✓                                | ✓                                  | ✓                                       | ✓                                       |
| LED LIGHT                       | ✓                                  | ✓                                  | ✓                                  | ✓                                       | ✓                                       |
| WARRANTY**                      | 3-Year Limited                     | 3-Year Limited                     | 3-Year Limited                     | » 5-Year Limited /<br>1-Year Commercial | 5-Year Limited /<br>1-Year Commercial   |

### POWER MAX® HEAVY-DUTY TWO-STAGE

**IDEAL FOR** Larger driveways that can hold up to 20 parked cars and 9-21" / 23-53 cm of snow at a time



**NO SHEAR PINS!**  
No need to replace shear pins in the cold with Toro's hardened gears and commercial-grade auger gearbox.



**PRECISION MOVES**  
Smooth, tight turns are a snap with power steering.



**DOUBLE CHUTE DEFLECTOR**  
Place the snow with greater precision, such as right next to your fence line, or throw the distance with a double deflector.

# POWER TRX HEAVY-DUTY

## TRACKED TWO-STAGE SNOW BLOWERS

**When a monster storm is roaring in, you need a beast of a snow blower to roar back.**

Winter gets out of your way as you throw snow 60+ feet/18+ m. It all starts with a single-button, electric start. Our biggest engine for your snowiest jobs on long driveways, up slopes and through the teeth of winter.

**SURFACE TYPE**   **MODERATE SLOPE**   **CARS / DRIVEWAY**



### POWER TRX HEAVY-DUTY TWO-STAGE

|                           | COMMERCIAL<br>POWER TRX HD<br>1428 OHXE                      | COMMERCIAL<br>POWER TRX HD<br>1432 OHXE                    |
|---------------------------|--------------------------------------------------------------|------------------------------------------------------------|
| <b>MODEL</b>              | <b>38890</b>                                                 | <b>38891</b>                                               |
| <b>CLEARING WIDTH</b>     | 28" / 71.1 cm                                                | » 32" / 81.3 cm                                            |
| <b>SNOW CUT DEPTH</b>     | 21" / 53.3 cm                                                | 21" / 53.3 cm                                              |
| <b>ENGINE</b>             | 420cc Toro Premium OHV                                       | 420cc Toro Premium OHV                                     |
| <b>DRIVE SYSTEM</b>       | » Self-Propelled Hydrostatic Transmission and Power Steering | Self-Propelled Hydrostatic Transmission and Power Steering |
| <b>STARTING</b>           | Electric                                                     | Electric                                                   |
| <b>THROWING DISTANCE*</b> | Up to 60' + / 18.3 m+                                        | Up to 60' + / 18.3 m+                                      |
| <b>AUGER SYSTEM</b>       | Power Max Anti-Clogging                                      | Power Max Anti-Clogging                                    |
| <b>AUGER DIAMETER</b>     | 14" / 35.6 cm                                                | 14" / 35.6 cm                                              |
| <b>IMPELLER DIAMETER</b>  | 14" / 35.6 cm                                                | 14" / 35.6 cm                                              |
| <b>AUGER GEARBOX</b>      | Commercial-Grade, No Shear Pins                              | Commercial-Grade, No Shear Pins                            |
| <b>HANDLE</b>             | Commercial                                                   | Commercial                                                 |
| <b>DEFLECTOR</b>          | Double                                                       | Double                                                     |
| <b>CHUTE CONTROL</b>      | Quick Stick®                                                 | Quick Stick                                                |
| <b>TIRES</b>              | Tracked                                                      | Tracked                                                    |
| <b>HAND WARMERS</b>       | ✓                                                            | ✓                                                          |
| <b>LED LIGHT</b>          | ✓                                                            | ✓                                                          |
| <b>WARRANTY**</b>         | 5-Year Limited,<br>1-Year Commercial                         | 5-Year Limited,<br>1-Year Commercial                       |

### Power TRX HD 1428 OHXE / 1432 OHXE

Self-Propelled Hydrostatic Transmission  
Tracked Driven for Ultimate Performance  
Commercial Grade All-Steel Construction  
420cc Toro Premium OHV Engine



#### POWER TRX HEAVY-DUTY TWO-STAGE

**IDEAL FOR** Extra-large driveways, heavy accumulation and making quick work of 10"+ / 25.4 cm+ of snow



#### UNMATCHED STABILITY

Track driven allows you to handle the steepest slopes or dig into hard packed snow.



#### SMOOTH HANDLING AND LOW MAINTENANCE

Hydrostatic transmission allows for self-propelled operation with infinitely variable speed.



#### ADJUST WITH EASE

Push the Quick-Adjust auger housing lever to adjust your housing up for climbing and transport, flat to blow snow off a driveway or down to dig deep snow.



# SNOWMASTER®

## SNOW BLOWERS

**Tear through the roughest snow and ice in record time.**

Easy enough for anyone in your household to handle, and still powers through tough, end-of-driveway snow.

SURFACE TYPE



MODERATE SLOPE



CARS / DRIVEWAY



# CORDED ELECTRIC

## SNOW BLOWERS

**Make small snow clearing jobs a snap.**

An ideal choice for sidewalks, steps, decks and small driveways.

STEPS, DECKS AND SIDEWALKS



CARS / DRIVEWAY



|                     | SNOWMASTER®                  |                              |
|---------------------|------------------------------|------------------------------|
|                     | SNOWMASTER 724 QXE           | SNOWMASTER 824 QXE           |
| MODEL               | 36002                        | 36003                        |
| CLEARING WIDTH      | 24" / 61.0 cm                | 24" / 61.0 cm                |
| SNOW CUT DEPTH      | 18" / 45.7 cm                | 18" / 45.7 cm                |
| ENGINE              | 212cc Toro Premium OHV       | » 252cc Toro Premium OHV     |
| DRIVE SYSTEM        | Self-Propelled Personal Pace | Self-Propelled Personal Pace |
| STARTING            | Electric                     | Electric                     |
| THROWING DISTANCE** | Up to 40' / 12.2 m           | » Up to 45' / 13.7 m         |
| AUGER SYSTEM        | In-Line Two-Stage            | In-Line Two-Stage            |
| AUGER DIAMETER      | 10" / 25.4 cm                | 10" / 25.4 cm                |
| IMPELLER DIAMETER   | 10" / 25.4 cm                | 10" / 25.4 cm                |
| CHUTE CONTROL       | Quick Stick®                 | Quick Stick                  |
| TIRES               | 11" / 27.9 cm                | 11" / 27.9 cm                |
| WARRANTY***         | 3-Year Limited               | 3-Year Limited               |

|                             | CORDED ELECTRIC   |                     |
|-----------------------------|-------------------|---------------------|
|                             | POWER SHOVEL®     | 1800 POWER CURVE®   |
| MODEL                       | 38361             | 38381               |
| CLEARING WIDTH              | 12" / 30.5 cm     | » 18" / 45.7 cm     |
| WEIGHT                      | 13 lbs / 5.9 kg   | 26 lbs / 11.8 kg    |
| THROWING DISTANCE**         | Up to 20' / 6.1 m | » Up to 30' / 9.1 m |
| CHUTE CONTROL               | –                 | » Quick Lever       |
| DEFLECTOR                   | –                 | » Locking           |
| DEPTH OF SNOW CUT, ONE PASS | 6" / 15.2 cm      | » 10" / 25.4 cm     |
| WARRANTY***                 | 2-Year Limited    | 2-Year Limited      |

» Enhanced or step-up feature

\*\*Throw distance and clearing capacity will vary with conditions.  
\*\*\*See retailer for complete warranty details.

# FREE EXTRA YEAR ENGINE WARRANTY

on qualifying snow blowers with Toro engines when you purchase a maintenance kit.

Purchase of kit must be at same time as snow blower. Product must be registered to activate warranty extension. Offer applies only to snow blowers with Toro engines. For residential use only, not valid on commercial use. See dealer or [toro.com](http://toro.com) for complete warranty details and maintenance kit compatible with snow blower purchased.



**Maintenance Kit 138-0698**

Single-Stage Models 38474, 38475

**Maintenance Kit 138-0704**

Two-Stage Models 38801, 38802, 38806, 38830, 38840, 38841, 38842

**Maintenance Kit 138-0699**

Single-Stage Models 38741, 38742, 38744, 38752, 38753, 38756, 38757  
Two-Stage Models 36001, 36002, 36003, 37779, 37780, 37781, 37793, 37797, 37798, 37799, 37802, 38805, 38838

# TORO®

490-0870 ©2022 The Toro Company All Rights Reserved.  
Specifications subject to change without notice and without incurring obligation. Products depicted are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features.