

Echo Pro 3000

Innovation is soundly protected

PN: UPOL-OL300EP-CG01B

EAN: 6422956009489



Specifications

Capacity	3000 VA / 2400 W
Type	On-line
Input	
Nominal Voltage	220-240 VAC
Accepted Voltage Range	80 - 300 VAC
Nominal frequency	50Hz / 60 Hz - user selectable
Frequency Range	40 ~ 70 Hz
Input surge protection	565 Joules
Power Factor	≥ 0.99 @ nominal voltage (100% load)
Output	
Nominal Voltage	208/220/230/240 VAC – user selectable
AC Voltage Regulation (Batt. Mode)	± 1%
Frequency Range (Batt. Mode)	50 Hz / 60Hz ± 0.5 Hz
Current Crest Ratio	3:1
Harmonic Distortion	≤ 3 % THD (Linear Load) ≤ 5 % THD (Non-linear Load)
Waveform (Batt. Mode)	Pure Sinewave
Transfer time	Typical 0 ms Eco mode 4 ms
Outlets type	4 x Schuko and Hard Wiring
Overload protection	
Line mode	105%-110%, warning only (No shutdown) 110%-120%, transfer to bypass after 60s >120%, Transfer to bypass immediately
Battery mode	105%-110%, warning only (No shutdown) 110%-120%, shutdown after 10s >120%, shutdown immediately
Bypass mode	110%-130%, warning only >130%, shutdown immediately



4 x Schuko outlets and Hard Wiring



ECO Mode for Energy Saving



Pure sine wave output

- Online (double conversion)
- Pure sine wave output
- Wide Input Range (80V-300V)
- Up to 96% Efficiency Rates
- Software management
- HID USB, RS2322, SNMP port communication
- Generator Compatible
- Auto-restart
- Auto-charge
- Low noise level

Efficiency

To AC Mode	88%
To Battery Mode	85%
ECO Mode	96%
LCD Display	Load Capacity, Load & Battery level, AC mode, Battery mode, Fault indicators
Alarm	Load Capacity, Load & Battery level, AC mode, Battery mode, Fault indicators

Environement

Humidity	0-90 % (non-condensing)
Temperature	0-40°C
Noise level	Less than 40dB

Battery

Battery Type & Number	6 x GP07122L PN: BTVACFUBBTO2LCG01B
Typical Recharge Time	4 hours up to 90% capacity
Running time on battery (minutes)	25% Load - 18 min 50% Load - 7 min 75% Load - 2 min 100% Load - 1 min



Management


Connection ports	HID USB, RS232, EPO, SNMP
Software	http://www.powermonitor.software/#PowerGuideSoftware

Physical

Product dimensions	416 x 196 x 342 mm
Product weight	21.3 kg
Retail Pack Dimensions	519 x 295 x 458 mm
Retail Pack Weight	22.1 kg



Running time on battery



Logistics

Carton Box Size (LxWxH)	519 x 295 x 458 mm
Pieces in the Carton Box	1
Net & Gross weight / CTN	N.W.: 21.3 kg / G.W.: 22.1 kg



Certificates

RoHS **CE**
2011/65/EU

