



- 1 On/Off switch 2 Led line/battery/fault 3 Power cable 4 Input thermal protection 5 Output sockets with child protection and blackout protection  
6 Filtered output socket with child protection 7 USB Port

#### Main Specifications

- Personal Computer, Modem/Router, Cash Register, Pos
- Automatic Voltage Regulation circuit (AVR)
- Easy replacement batteries
- Rear slots for wall mounting
- Output sockets with child protection for blackout protection

- Output sockets with child protection for overvoltage protection
- USB port
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.



#### Specifications

UPS Model	ERA PLUS STRIP 800
Code	FGCERAPLST800
Nominal power	800 VA
Max Computer Power Application	560 W
Technology	Line Interactive with stabilizer
Cooling	Natural
Audible noise	< 40 dBA to 1 m
Input connection	Fixed cable with Schuko plug
Outlets	3 UPS outputs Schuko/Italian +3 only filtered outputs Schuko/Italian
Dimension (UPS) WxHxD	16x9,5x30,5 cm
Dimension (with packing) WxHxD	22x14x32,4 cm
Weight	2,5 Kg
<b>Input</b>	
Number of phases	1Ph+N
Nominal voltage	Single-phase 230Vac
Input voltage range	+20%/-25%
Nominal frequency	50/60 Hz (automatic selection)
Input frequency range	+/-5%
<b>Output</b>	
Number of phases	1Ph+N
Nominal voltage	Single-phase 230Vac
Active Power	240 W
Voltage regulation (Line mode)	AVR (Automatic Voltage Regulation)
Voltage regulation (Battery mode)	+/-5%
Frequency	50/60 Hz (automatic selection)
Inverter waveform	Modified sinewave
Overload capability	< 130%
Transfer time	2 ms (typical)
<b>Battery</b>	
Type	Lead acid, sealed, maintenance free
Backup time (typical)	10-40 min
<b>Environmental specification</b>	
Working temperature	From 0 to 40 °C (recommended from 20 to 25 °C)
Humidity	< 95% without condensation
Maximum altitude	3000 m
IP protection	IP20
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)

© 2023 Tecnoware Power Systems. The technical data may change without prior notice.

Available on request with input/output nominal voltage 110Vac or 120Vac and with input plug and output sockets for specific country.