

MAXUM

Next Generation
DC Commercial Door Operator
JHDC Hoist



Scan to learn more about
the JHDC Hoist

Faster. Simpler. Smarter.

LiftMaster

POWERED BY myQ

JHDC HOIST

LiftMaster® is pioneering MAXUM, the next generation of innovation for commercial door automation. This all-new commercial door operator is a state-of-the-art platform that introduces next-level versatility in a sleek, purpose-built design that's easier to install and service. With unrivaled performance and intelligence, the new line-up will help today's commercial facilities take the next step toward a smarter future.

Models available for up to 700 lb., 1200 lb. and 2200 lb. doors.

Popular Features

Manual Hoist Operation

Quickly switch to manual operation to easily move door with included hoist chain.

Smooth Start/Stop Operation

Extends the life of the operator and door hardware.

Faster Speed

Average of 12" per second opening on sectional doors, and 8-9" per second on rolling steel doors.

Floor Level Wall Controller

4-line LCD display gives you access to more information at all times. Bringing programming, troubleshooting and diagnostics down to the floor level will save you time and money.

Battery Backup Capable

Allows for seamless operation when power is out.

Advanced Diagnostics and Troubleshooting

Receive real-time feedback and alerts, allowing for fast troubleshooting and reduced downtime.

Built-in myQ + Wi-Fi® Capabilities

Connect to myQ Facility via Wi-Fi for visibility into what is happening at your door and control it from your web browser. No need for additional hubs or accessories. Know what accessories activate the door (remote, keypad, etc.)



Security+ 2.0 on Board Radio Receiver

Manage up to 90 remotes.

Motor

Built with a high efficiency motor and gearbox. Delivers robust performance with the flexibility to move your sectional or rolling door applications.

Lighter Weight

Easier installation at up to 20 lbs. lighter than comparable AC operators.

Control Board

Designed to have everything at your fingertips. Color coded, push-to-release terminals allow for easy and secure wiring, no tools necessary.

3 Monitored Entrapment Protection Inputs

Protect up to 3 entrapment protection points with every installation.

UL® Listed

LiftMaster Commercial Door Operators are listed to ANSI/CAN/UL325 Standard for USA/Canada and are certified to NOM/IFETEL Standards for Mexico.

Industrial-Grade Design

Durable metal chassis frame and plastic E-Box offers strength and flexibility with installation. E-Box hinge design allows for easy cover removal for enhanced accessibility.

Connect and stay on top with myQ Facility.

Enhanced Features

- Door Monitor and Control
- Enhanced Diagnostics and Error Codes
- Cycle Counts (Operator Absolute & Service)
- Simple device provisioning process, stable connection to the cloud
- Timely sensing throughout door travel
- Cloud Access Control
- Transmitter Management:
Unlock 1,000 learned transmitter capabilities to track specific people tied to those transmitters



myQ Facility is a cloud-based solution that keeps you up to date and in control of all of your facility's access points. This allows you to work smarter, improve efficiencies and reduce expenses.*

*When linked with an access control, Powered by myQ, cellular data or Wi-Fi connection required. Test equipment regularly and follow safety instructions.

Included Accessories

CPS-U

Monitored Through-Beam Photo Eye

The CPS-U is a proven design photo eye and engineered for ease of alignment at installation; max. range: 30 ft.

NEMA 4X units include CPS-UN4.



DCWALLCTL

Floor Level Wall Controller

Menu based user interface allows you to scroll through, edit and save options and settings easily. 4-line LCD display gives you convenient access to even more information in seconds.

Faster Setup and Added Personalization: Allows the user to only access settings and options needed for installation.

Increased Security: This user interface gives customers peace of mind by requiring a password-protected code to access any door and alter speed settings.



Default text language is English (Spanish and French selectable in menu)

Recommended Accessories

Edges and Wireless Edge Devices

A contact edge sensor stops and/or reverses a moving door when sensing an obstruction in its pathway. Add the LMWEKITU to eliminate the need for wiring between LiftMaster Monitored Resistive Edges and our new Commercial Door Operators.

Loop Detectors/Loops (LPEXP)

Loops prevent the door from closing on a vehicle in its path with strong sensors and wires installed in the ground. Add the LOOPDETLMD detector, which plugs into the board for ease of installation.

Auxiliary Relay Board (AUXREL)

Easy to install accessory board for auxiliary limit switches, lights, bells, horns, strobes, and other devices.

Red/Green Light (RGL-CTL)

18 red/green high-intensity LEDs: Suitable for single lane operations and clear visibility.

Monitored Light Curtain (LC36M)

Provides up to 33 ft. of protection range and a minimum of 36 in. of height coverage to keep your equipment safe.

Cable Tension Monitors

K41-0157-000-Commercial CTM (Right)

K41-0156-000-Commercial CTM (Left)

Easy to install. Provides additional door and operator protection by reversing a closing door if excess cable slack is detected.

Chain Tensioner (Spreader Bar)

CHAITENSDC - 1" Chain Tensioner

CHAITENS125DC - 1.25" Chain Tensioner

Battery Backup (DC7AH)

Provides battery power in case of power outage. Two batteries and mounting bracket included.

Sectional Doors 12-Tooth (700/1200) & 10-Tooth (2200)						
Drum Diameter	Door Sprocket for Desired Speed					
	For 10-12 in/sec Door Speed			For 9-10 in/sec Door Speed		
	Sprocket Tooth Count	1 in. Bore 1/4 in. Keyway	1.25 in. Bore 1/4 in. Keyway	Sprocket Tooth Count	1 in. Bore 1/4 in. Keyway	1.25 in. Bore 1/4 in. Keyway
4"	16-Tooth	71-1550B16LGH	71-1550B16QGH	24-Tooth	71-1550B24LGH	71-1550B24QGH
5.25" - 5.75" & 8.5" (Vertical Lift)	24-Tooth	71-1550B24LGH	71-1550B24QGH	32-Tooth	71-1550B32LGH	71-1550B32QGH
6.375" - 11"	32-Tooth	71-1550B32LGH	71-1550B32QGH	42-Tooth	71-1550B42LGH	71-1550B42QGH
13.5"	42-Tooth	71-1550B42LGH	71-1550B42QGH	56-Tooth	71-1550B56LGH	71-1550B56QGH
Not Sure	24-Tooth	71-1550B24LGH	71-1550B24QGH	32-Tooth	71-1550B32LGH	71-1550B32QGH

Rolling Doors 12-Tooth				
Operator Series	Uninsulated - Max 20ft Height - 8-9 in/sec Door Speed		Insulated - Max 20ft Height - 8-9 in/sec Door Speed	
	Door Weight	Sprocket Tooth Count	Door Weight	Sprocket Tooth Count
700	up to 450 lbs	50-Tooth	up to 450 lbs	60-Tooth
	450 to 700 lbs	72-Tooth		
1200	1200 to 1800 lbs	72-Tooth	450 to 900 lbs	72-Tooth
	1800 to 2200 lbs			

Rolling Doors 10-Tooth (Standard for JHDC 2200 - Available as accessory kit for 700/1200 - part #71-1550B10LGH)				
Operator Series	Uninsulated - Max 20ft Height - 8-9 in/sec Door Speed		Insulated - Max 20ft Height - 8-9 in/sec Door Speed	
	Door Weight	Sprocket Tooth Count	Door Weight	Sprocket Tooth Count
700	up to 450 lbs	42-Tooth	up to 450 lbs	50-Tooth
	450 to 700 lbs	56-Tooth		
1200	700 to 1200 lbs	56-Tooth	450 to 900 lbs	60-Tooth
2200	1200 to 1800 lbs	56-Tooth	900 to 2200 lbs	72-Tooth
	1800 to 2200 lbs	72-Tooth		

Features

Mechanic

- 24VDC Motor Drive
- 65:1 Gearbox with #50 Chain
- Dynamic braking standard on all MAXUM operators. 2200 series operators include electromechanical holding brake
- Dual Handing: Right or left no longer required for order
- Mounted Keyhole Slots: Created for installers to easily access and fasten the operator to the wall
- Removable Front Cover
- Captive E-Box Screws: Remain in place when opening and removing cover

Power

120Vac 1PH/240Vac 1/3PH; 480Vac 3PH; 208Vac 3PH (via transformer); 600Vac 3PH (via transformer)

Temperature Range

Without heater	-4°F (-20°C) to +149°F (65°C)
With heater (HTR)	-40°F (-40°C) to +149°F (65°C)

Business Partners

For Sales | 800.282.6225

For Technical Support | 800.528.2806

For Billing | 800.323.2276

To Learn More | [LiftMaster.com](https://www.liftmaster.com)

Dimensions

- Operator 700 lb. / 9.8" W x 25.7" H x 12.1" D
- Operator 1200 lb. / 9.8" W x 26.0" H x 12.1" D
- Operator 2200 lb. / 11.6" W x 33.1" H x 12.6" D
- Floor Level Wall Controller / 3.6" W x 8.2" H x 1.7" D

Warranty

- 5 Years Limited Warranty
- Photoeyes - 1 Year
- Replacement Parts - 1 Year
- LCD Wall Control - 1 Year

MAXUM Operator

- Standard Duty - 5 YEARS / 85,000 Cycles*
- Extended Duty - 5 YEARS / 130,000 Cycles*

Carton Contents

- Operator
- Antenna
- CPS-U (NEMA 4X units include CPS-UN4)
- DCWALLCTL
- 25 ft. of hoist chain (additional chain can be purchased separately)

*Cycle count measurement will commence at the start of the warranty period; however, cycle counts will not be used to determine warranty eligibility until conclusion of the first two (2) years of limited warranty period. LiftMaster, the LiftMaster logo, myQ and the myQ logo are registered trademarks of The Chamberlain Group LLC. UL® and the UL logo are trademarks of UL LLC. © 2025 All Rights Reserved. Wi-Fi® is a registered trademark of Wi-Fi Alliance.