# KERN **CH 50K100**



The classic among manual hanging scales – perfect for rapid weighing of higher loads



| Category          |                  |
|-------------------|------------------|
| Brand             | KERN             |
| Product categoriy | Industrial scale |
| Product group     | Hanging scale    |
| Product family    | CH               |

| Measuring System                             |                                |
|--|--------------------------------|
| Construction type of the scale               | Single-range balance           |
| Weighing system                              | Strain gauge                   |
| Weighing capacity [Max]                      | 50 kg                          |
| Readability [d]                              | 0,1 kg                         |
| Reproducibility                              | 0,1 kg                         |
| Linearity                                    | ± 0,2 kg                       |
| Resolution                                   | 500                            |
| Adjustment options                           | Adjusting with external weight |
| Recommended adjusting weight                 | 20 kg (M3)                     |
| Possible calibration points                  | 20 kg                          |
| Stabilization time                           | 2 s                            |
| Warm-up time                                 | 10 min                         |
| Maximum creep (15 minutes)                   | 200 g                          |
| Maximum creep (30 minutes)                   | 400 g                          |
| Eccentric/Off-centre loading is not possible | /                              |
| Default unit                                 | kg                             |
| Units  | kg<br>Ib<br>N                  |
| Internal measuring frequency                 | 5 Hz                           |
| Tolerance (% of [Max])                       | 0,5%                           |

| Display              |       |
|----------------------|-------|
| Display type         | LCD   |
| Display backlight    | no    |
| Display digit height | 11 mm |

| Construction                               |                |
|--|----------------|
| Dimension housing (W×D×H)                  | 90×30×176,5 mm |
| Dimensions completely mounted (W×D×H)      | 90×30×283 mm   |
| Dimensions housing - width (A)             | 90 mm          |
| Dimensions housing - depth (B)             | 30 mm          |
| Dimensions housing - height/<br>length (C) | 176,5 mm       |
| Dimensions - total height/total length (D) | 283 mm         |
| Material housing                           | plastic        |
| Material load hook                         | steel          |
| Material display housing                   | plastic        |
| Load cells - number                        | 1              |

| Functions  |                |
|--|----------------|
| Underfloor weighing  | None           |
| Function for averaging under unstable weighing conditions      | ✓              |
| Hold function  | ✓              |
| Auto-off interval(s) in battery mode/rechargeable battery mode | 3:30 min       |
| Auto-off interval(s) in mains power mode                       | 3 min          |
| Tare function  | manual (multi) |
| Number of keys for operation                                   | 3              |

| Power Supply               |                    |
|----------------------------|--------------------|
| Supplied power supply      | Battery            |
| Battery / accumulator type | Alkali(-Manganese) |
| Battery                    | 9 V block          |
| Battery connection         | 9V Bloc            |
| Battery operating time     | 80 h               |
| Battery voltage            | 9 V                |

| Environmental conditions    |       |
|-----------------------------|-------|
| Ambient temperature [Min]   | 5 °C  |
| Ambient temperature [Max]   | 35 °C |
| Humity of environment [Max] | 80 %  |
| Storage temperature [Max]   | 60 °C |

## KERN **CH 50K100**



The classic among manual hanging scales – perfect for rapid weighing of higher loads

| Approval   |   |
|------------|---|
| CE mark    | ✓ |
| TÜV-tested | ✓ |

| Services (optional)   |          |
|---|----------|
|   |          |
| Article number for adjustment at the location of installation | 961-248  |
| Article number for DAkkS calibration                          | 963-128H |
| Article number for certificate of                             | 969-517  |

| Packing & Shipping           |                |
|------------------------------|----------------|
| Delivery time                | 1 d            |
| Dimensions packaging (W×D×H) | 225×150×70 mm  |
| Shipping method              | Parcel service |
| Net weight approx.           | 0,35 kg        |
| Gross weight approx.         | 0,65 kg        |
| Shipping weight              | 0,615 kg       |

## Pictograms

#### **STANDARD**











### OPTION

