

RACKS **BRAX.**

COMPATIBILITY POCKET GUIDE

FOR

DRIFTA
STOCKTON

**FAST ON!
FAST OFF!**

AWNING AND ACCESSORY
MODELS

CLICK OR TAP ON AN AWNING/ACCESSORY BELOW
TO TAKE YOU TO THE PAGE TO FIND OUT WHAT YOU NEED

DRIFTA® STOCKTON 180 FREESTANDING AWNING 3

DRIFTA® STOCKTON 270 FREESTANDING AWNING 4

DRIFTA® STOCKTON 270 HEAVY DUTY FREESTANDING AWNING *with LED lights* 5

DRIFTA® STOCKTON SIDE AWNING *2.0m, 2.5m* 6

DRIFTA® STOCKTON 180 FREESTANDING AWNING

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	9000 – XD Hitch (DOUBLE)*
	*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	SUPPLIED BRACKETS FROM DRIFTA® WILL WORK WITH THE XD HITCH RANGE.
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	9100 – XD Adjustable Brackets Short (DOUBLE)*; OR 9104 – XD Side Twist Bracket Short Foot (DOUBLE)*.
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	9102 – XD Adjustable Brackets Long (DOUBLE)*; OR 9106 – XD Side Twist Bracket Long Foot (DOUBLE)*.
	*ROOF RACKS WITH PERIMETER LIPS REQUIRE PACKERS TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO ROOF RACK GUIDE FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	9010 – XD Wall Mounts ⁺ ✓ LOCKED GARAGES ✓ WORKSHOP WALLS
UNSECURED LOCATION	9011 – XD Lockable Wall Mounts ⁺ ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA
	⁺ NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

DRIFTA® STOCKTON 270 FREESTANDING AWNING

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	3
HITCHES NEEDED	8182 – HD Hitch (TRIPLE)

BRACKETS OPTIONAL

MOUNTING POINTS	3
BRACKETS NEEDED	SUPPLIED BRACKETS FROM DRIFTA® REQUIRE 1 x 8.5MM HOLE TO BE DRILLED PER BRACKET TO ACHIEVE 2 BRACKET HOLES AT 50MM CENTRES.
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8305 – HD Adjustable Brackets Short (TRIPLE)*; OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8307 – HD Adjustable Brackets Long (TRIPLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE [PACKERS](#) TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts ⁺ ✓ LOCKED GARAGES ✓ WORKSHOP WALLS
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts ⁺ ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA

⁺NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

DRIFTA® STOCKTON 270 HEAVY DUTY
FREESTANDING AWNING *with LED lights*

HITCHES **REQUIRED MINIMUM FOR FAST ON, FAST OFF!**

MOUNTING POINTS	3
HITCHES NEEDED	9001 – XD Hitch (TRIPLE)

BRACKETS **OPTIONAL**

MOUNTING POINTS	3
BRACKETS NEEDED	SUPPLIED BRACKETS FROM DRIFTA® MUST USE EITHER OF ONE OF 2 PAIRS OF VERTICAL HOLES. • THE XD BODY WILL FIT THE UPPER AND LOWER HOLES IN THE DRIFTA BRACKET. • THE XD HOLDER WILL FIT THE UPPER AND LOWER MOUNTING TRACKS IN THE DRIFTA AWNING SPINE.
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	9101 – XD Adjustable Brackets Short (TRIPLE)*; OR 9105 – XD Side Twist Bracket Short Foot (TRIPLE)*.
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	9103 – XD Adjustable Brackets Long (TRIPLE)*; OR 9107 – XD Side Twist Bracket Long Foot (TRIPLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS **OPTIONAL**

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	9010 – XD Wall Mounts ⁺ ✓ LOCKED GARAGES ✓ WORKSHOP WALLS
UNSECURED LOCATION	9011 – XD Lockable Wall Mounts ⁺ ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA

⁺NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

DRIFTA® STOCKTON SIDE AWNING 2.0m, 2.5m

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard*
ALSO WORKS WITH	8162*, 8180*

*WILL ALSO WORK WITH THE TRIPLE VERSIONS.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	SUPPLIED BRACKETS FROM DRIFTA® WILL WORK WITH THE HD HITCH RANGE.
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8304 – HD Adjustable Brackets Short (DOUBLE)*; OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION	8160 – HD Wall Mounts+ ✓ LOCKED GARAGES ✓ WORKSHOP WALLS
UNSECURED LOCATION	8161 – HD Lockable Wall Mounts+ ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA

+NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.