



Vero

Enjoy true comfort for a perfect atmosphere,
with energy savings! We do more, so you do less.



iA Plus
(Inverter Algorithm Plus)



Ionizer



ECO Mode



GEAR Mode



Wi-Fi
Standard



Follow Me



Hotel Menu



Central Control



Remote on/off



HEPA Filter



Triple Action Filter



Ultra Silence Mode at 20dB(A)



Golden Fin

Model			VERI-09WFI/VERO-09	VERI-12WFI/VERO-12	VERI-18WFI/VERO-18	VERI-24WFI/VERO-24
Cooling Capacity (Btu/h)			9.000 (3.100-11.600)	12.000 (3.800-14.200)	18.000 (6.600-21.400)	24.000 (10.300-30.000)
Cooling Capacity (kWatt)			2.64 (0.91-3.40)	3.52 (1.11-4.16)	5.28 (1.82-6.15)	7.03 (2.08-7.91)
Heating Capacity (Btu/h)			10.000 (2.800-11.500)	13.000 (3.700-14.400)	19.000 (4.400-23.900)	25.000 (5.200-32.300)
Heating Capacity (kWatt)			2.93 (0.82-3.37)	3.81 (1.08-4.22)	5.57 (1.29-6.74)	7.33 (1.61-7.91)
Seasonal Efficiency (In accordance to EN14825)	Cooling	Pdesign (kW)	2.6	3.5	5.3	7.0
		Energy Class	A++	A++	A++	A++
		SEER	6.2	6.1	7.0	6.4
		Annual Power Consumption (kWh/year)	146	201	265	383
	Heating (Middle Zone)	Pdesign (kW)	2.3	2.5	4.2	4.9
		Energy Class	A	A+	A+	A+
		SCOP	3.8	4.0	4.0	4.0
		Annual Power Consumption (kWh/year)	846	876	1.470	1.715
	Heating (Warm Zone)	Pdesign (kW)	2.1	2.4	4.5	5.3
		Energy Class	A+++	A+++	A+++	A+++
		SCOP	5.1	5.1	5.1	5.1
		Annual Power Consumption (kWh/year)	577	659	1.235	1.455
Voltage/Frequency/Phase (V/Hz/Ph)			220-240/50/1	220-240/50/1	220-240/50/1	220-240/50/1
Current Input (A)		Cooling	3.47 (0.40-5.40)	5.38 (0.50-6.90)	6.70 (0.70-9.80)	10.50 (1.40-15.00)
		Heating	3.53 (0.50-5.20)	4.42 (0.40-6.90)	7.10 (0.95-10.20)	9.30 (1.30-13.70)
Power Input (kW)		Cooling	0.80 (0.10-1.24)	1.24 (0.13-1.58)	1.55 (0.15-2.25)	2.42 (0.34-3.45)
		Heating	0.81 (0.12-1.20)	1.02 (0.10-1.68)	1.63 (0.22-2.35)	2.13 (0.30-3.15)
Air Flow Volume (High/Medium/Low) (m³/h)			451/325/255	575/493/454	800/600/500	1.090/770/610
Noise Level [dB(A)]		Indoor unit (Silent/Low/Medium/High)	20/25.5/29/37	21/25/29/37.5	20/31/37/41	21/34.5/37/46
		Outdoor unit	55.5	55.5	56	62
Sound Power Level [dB(A)]		Indoor unit	54	56	56	62
		Outdoor unit	62	64	65	67
Dehumidifying Volume		(L/h)	1.2	1.6	2.0	2.8
		(L/νμέρα)	28.8	38.4	48.0	67.2
Compressor Type			ROTARY	ROTARY	ROTARY	ROTARY
Liquid line Gas line			1/4" 3/8"	1/4" 3/8"	1/4" 1/2"	3/8" 5/8"
Fuses (A)			10	10	16	16
Signal Wires (Noxmm²)			5x1.5	5x1.5	5x1.5	5x2.5
Dimensions (WxDxH) (mm)		Indoor unit	726x210x291	805x208x295	969x241x320	1.083x244x336
		Outdoor unit	720x270x495	720x270x495	874x330x554	955x342x673
Net Weight (kg)		Indoor/Outdoor	7.8/23.2	8.4/23.2	11.2/33.5	13.6/43.9
Refrigerant/Charge (g)			R32/550	R32/550	R32/1.100	R32/1.450
Outdoor Operation Temperature Range (°C)		Cooling	-15~50	-15~50	-15~50	-15~50
		Heating	-15~24	-15~24	-20~24	-20~24