



HOW TO INSTALL TROLMASTER CONTROLLER WITH VERTX 600 SERIES FOR COMMERCIAL GROW SPACE

Trolmaster® is a registered trademark of the TrolMaster Agro Instruments Co., Ltd. (Trolmaster). This Document is not endorsed or approved by TrolMaster Agro Instruments Co., Ltd. This Document is for Instruction purpose only.

Step 1: Choose Right Controller & Accesories

1. Trolmaster Hydro-X Environment Control System (HCS-1)

Required QTY – 1



**Controls total 512 light
(256 lights per Channel)**

2. Lighting Control Adapter F (LMA-14)

Required QTY – 1 (if using 1 per channel – 256 lights)

Required QTY – 2 (If using 2 channels – 512 lights)



3. RJ12 to PushLock Waterproof Connector converter cable (ECS-5)

(ECS-5)

Required per Light



Each Light Require 1 ECS-5 Connector


Step 2 : Install Trolmaster HCS-1 on wall using instruction

- 1) Install Trolmaster HCS-1 on wall with power plug**
- 2) Connect LMA-14 Adapter to Line 1**
- 3) Connect 3 in 1 sensor to sensor on trolmaster controller**



Step 3 : Connectivity of ECS-5 Cable Set to LMA-14 Connector


RJ12 to PushLock Waterproof Connector converter cable and another end of RJ12 connection to splitter.




Step 4 : Connectivity of ECS-5 Cable Set

1) Connect Push Connector to Driver Assembly of VertX 600

Push Connector to VertX 600 Driver



1) DIAGRAM



Trolmaster® is a registered trademark of the TrolMaster Agro Instruments Co., Ltd. (Trolmaster). This Document is not endorsed or approved by TrolMaster Agro Instruments Co., Ltd. This Document is for Instruction purpose only.