



NETWORK VIDEO SURVEILLANCE

Preisliste Q3 2019
EUR exkl. Mwst



H.265+ IR Mini Dome Network Camera

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	  MS-C2983-PB	2MP 1920*1080 @ 30fps	Fixed Lens 2.8mm	H124° D144° V68°	Color: 0.002Lux @F1.2	Super WDR 140dB	20m	N/A	252,00	* Built-in PoE Port * Built-in Microphone * Support SD card, up to 256G * Support 3-axis design * Support H.265+/H.265/H.264+/H.264
	 MS-C5383-PB	5MP 2592*1944 @ 20fps	Fixed Lens 2.8mm	H113° D143° V83°	Color: 0.005Lux @F1.2	Super WDR 120dB	20m	N/A	262,00	Optional: * Lens 3.6/6mm * Black Housing * Video Content Analysis: 40,00 €
	A71	162*124*78mm, 531g							31,00	* Aluminum alloy * For wall or vertical structure

H.265+ Vandal-proof Mini Dome Network Camera

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	  MS-C2973-PB	2MP 1920*1080 @ 30fps	Fixed Lens 2.8mm	H123° D142° V68°	Color: 0.002Lux @F1.2	Super WDR 140dB	25m	IP67 IK10	260,00	* Support PoE * Built-in Microphone * Support SD card, up to 256G * Support 3-axis design * Support H.265+/H.265/H.264+/H.264
	 MS-C5373-PB	5MP 2592*1944 @ 20fps	Fixed Lens 2.8mm	H111° D141° V82°	Color: 0.005Lux @F1.2	Super WDR 120dB	25m	IP67 IK10	268,00	Optional: * Lens 3.6mm * Black Housing * Multi port: Alarm I/O, Audio I/O, DC 12V : 40,00 € * Video Content Analysis: 40,00 €
	A71	162*124*78mm, 531g							31,00	* Aluminum alloy * For wall or vertical structure
	A73	115*122.5*10mm, 28g							10,00	* ABS+PC * For side outlet
	A74	121.5*116.5*37.2mm, 60g							39,00	* ABS+PC * For cable management

H.265+ Weather-proof Mini Dome Network Camera (Included Junction Box)

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	  MS-C2975-PB	2MP 1920*1080 @ 30fps	Fixed Lens 2.8mm	H123° D142° V68°	Color: 0.002Lux @F1.2	Super WDR 140dB	25m	IP67 IK10	270,00	* Support PoE * Built-in Microphone * Support SD card, up to 256G * Support 3-axis design * Included Junction Box * Support H.265+/H.265/H.264+/H.264
	 MS-C5375-PB	5MP 2592*1944 @ 20fps	Fixed Lens 2.8mm	H113° D144° V84°	Color: 0.005Lux @F1.2	Super WDR 120dB	25m	IP67 IK10	275,00	Optional: * Lens 3.6mm * Black Housing * Video Content Analysis: 40,00 €
	A71	162*124*78mm, 531g							31,00	* Aluminum alloy * For wall or vertical structure

H.265+ AF Motorized Mini Dome Network Camera (Included Junction Box)

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	  MS-C2975-EPB	2MP 1920*1080 @ 30fps	AF lens 2.8-8.4mm	H111°~H48° D130°~D55° V60°~V27°	Color: 0.002Lux @F1.2	Super WDR 140dB	35m	IP67 IK10	379,00	* Built-in PoE Port , DC12V * Built-in Microphone * Support SD card, up to 256G * Support 3-axis design * Included Junction Box * Support H.265+/H.265/H.264+/H.264
	 MS-C5375-EPB	5MP 2592*1944 @ 20fps	AF lens 2.8-8.4mm	H101°~H42° D129°~D53° V74°~V31°	Color: 0.005Lux @F1.2	Super WDR 120dB	35m	IP67 IK10	393,00	Optional: * Black Housing * Video Content Analysis: 40,00 €
	A71	162*124*78mm, 531g							31,00	* Aluminum alloy * For wall or vertical structure

H.265+ Mini Bullet Network Camera

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	  MS-C2963-PB	2MP 1920*1080 @ 30fps	Fixed Lens 4mm	H81° D93° V46°	Color: 0.002Lux @F1.2	Super WDR 140dB	30m	IP67	298,00	* Built-in PoE Port * Support SD card, up to 256G * Support 3-axis design * Support H.265+/H.265/H.264+/H.264 Optional: * High Frame Rate: 45,00 € (-R Series: 2MP@60fps) * Video Content Analysis: 40,00 €
	 MS-C5363-PB	5MP 2592*1944 @ 20fps	Fixed Lens 4mm	H75° D94° V56°	Color: 0.005Lux @F1.2	Super WDR 120dB	30m	IP67	309,00	
	MS-C8163-PB	8MP(4K) 3840x2160 @ 15fps	Fixed Lens 4mm	H90° D104° V51°	Color: 0.01Lux @F1.2	Super WDR 120dB	30m	IP67	367,00	
	A63	134*127*40mm, 620g							39,00	* Aluminum alloy * For cable management * IP66-Rated Weather-proof

H.265+ Vandal-proof Mini Bullet Network Camera (Included Junction Box)

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	  MS-C2964-PB	2MP 1920*1080 @ 30fps	Fixed Lens 2.8mm	H123° D142° V68°	Color: 0.002Lux @F1.2	Super WDR 140dB	30m	IP67 IK10	290,00	* Support PoE * Support SD card, up to 256G * Support 3-axis design * Support H.265+/H.265/H.264+/H.264 Optional: * Lens 3.6mm/6mm * Video Content Analysis: 40,00 €
	 MS-C5364-PB	5MP 2592*1944 @ 20fps	Fixed Lens 2.8mm	H113° D144° V84°	Color: 0.005Lux @F1.2	Super WDR 120dB	30m	IP67 IK10	307,00	

H.265+ Vandal-proof Motorized Mini Bullet Network Camera

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	  MS-C2964-FPB	2MP 1920*1080 @ 30fps	Motorized lens 2.7-13.5mm	H88°~H32° D102°~D37° V49°~V18°	Color: 0.002Lux @F1.2	Super WDR 140dB	50m	IP67 IK10	401,00	* Support Built-in PoE Port, DC 12V * Support SD card, up to 256G * Support 3-axis design * Support H.265+/H.265/H.264+/H.264 Optional: * High Frame Rate: (-R Series: 2MP@60fps): 45,00 € (-T Series: 2MP@90fps+Super WDR Pro): 45,00 € (-Q Series: 2MP@120fps): 120,00 € (-H Series: 5MP@30fps) : 45,00 € * P-Iris: 20,00 € * Video Content Analysis: 40,00 €
	 MS-C5364-FPB	5MP 2592*1944 @ 20fps	Motorized lens 2.7-13.5mm	H84°~H30° D105°~D37° V62°~V22°	Color: 0.005Lux @F1.2	Super WDR 120dB	50m	IP67 IK10	422,00	
	MS-C8164-FPB	8MP(4K) 3840x2160 @ 15fps	Motorized lens 3.3-12mm	H101°~H39° D116°~D46° V56°~V21°	Color: 0.01Lux @F1.2	Super WDR 120dB	50m	IP67 IK10	475,00	
	A63	134*127*40mm, 620g							39,00	* Aluminum alloy * For cable management * IP66-Rated Weather-proof

NEW 180° Panoramic H.265+ Mini Bullet Network-Camera

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	MS-C5365-PB	5MP 2592x1944 @ 30fps	Fixed Lens 1.68mm	H180° D95°	Color: 0.005Lux @F1.2	Super WDR 120dB	15m	IP67 IK10	375,00	* Support Built-in PoE Port, DC 12V * Support SD card, up to 256G * Support 3-axis design * Support H.265+/H.265/H.264+/H.264 * Support Built-in Mic * Support Video Content Analysis

H.265+ Motorized Pro Bullet Network Camera

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	  MS-C2962-FPB	2MP 1920*1080 @30fps	Motorized lens 2.7-13.5mm	H93°~H33° D107°~D38° V52°~V18°	Color: 0.002Lux @F1.2	Super WDR 140dB	60m	IP67 (IK10)	444,00	* Built-in PoE Port * Integrated Cable Management * Support SD card, up to 256G * Support 3-axis design * Support H.265+/H.265/H.264+/H.264 * Multi port: Alarm I/O, Audio I/O, DC 12V
	 MS-C5362-FPB	5MP 2592*1944 @20fps	Motorized lens 2.7-13.5mm	H90°~H31° D114°~D38° V67°~V23°	Color: 0.005Lux @F1.2	Super WDR 120dB	60m	IP67 (IK10)	463,00	Optional: * Lens 7-22mm (100m IR Distance): 55,00 € * High Frame Rate: (-R Series: 2MP@60fps): 45,00 € (-T Series: 2MP@90fps+Super WDR Pro): 45,00 € (-Q Series: 2MP@120fps): 120,00 € (-H Series: 5MP@30fps): 45,00 € * P-Iris: 20,00 € * IK10: 20,00 € * Video Content Analysis: 40,00 €
	MS-C8162-FPB	8MP(4K) 3840*2160 @15fps	Motorized lens 3.3-12mm	H101°~H39° D116°~D46° V56°~V21°	Color: 0.01Lux @F1.2	Super WDR 120dB	60m	IP67 (IK10)	490,00	Optional: * Lens 7-22mm (100m IR Distance): 55,00 € * High Frame Rate: (-R Series: 2MP@60fps): 45,00 € (-T Series: 2MP@90fps+Super WDR Pro): 45,00 € (-Q Series: 2MP@120fps): 120,00 € (-H Series: 5MP@30fps): 45,00 € * P-Iris: 20,00 € * IK10: 20,00 € * Video Content Analysis: 40,00 €
Default (Version A)		134*127*40mm, 510g		Optional (Version B)			φ107.9*19mm, 133g		* Aluminum alloy * For cable management * IP66-Rated Weather-proof	

12X H.265+ AF Motorized Pro Bullet Network Camera

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	  MS-C2962-EPB	2MP 1920*1080 @30fps	AF Lens 5.3~64mm	H61°~H5° D69°~D5° V36°~V2°	Color: 0.002Lux @F1.2	Super WDR 140dB	80m	IP67	483,00	* Built-in PoE Port * Integrated Cable Management * Support SD card, up to 256G * Support 3-axis design * Support H.265+/H.265/H.264+/H.264 * Multi port: Alarm I/O, Audio I/O, DC 12V
	 MS-C5362-EPB	5MP 2592*1944 @20fps	AF Lens 5.3~64mm	H57°~H4° D69°~D5° V44°~V1°	Color: 0.005Lux @F1.2	Super WDR 120dB	80m	IP67	489,00	Optional: * High Frame Rate: (-R Series: 2MP@60fps): 45,00 € (-T Series: 2MP@90fps+Super WDR Pro): 45,00 € (-Q Series: 2MP@120fps): 120,00 € (-H Series: 5MP@30fps): 45,00 € * Video Content Analysis: 40,00 €
Default (Version A)		134*127*40mm, 510g		Optional (Version B)			φ107.9*19mm, 133g		* Aluminum alloy * For cable management * IP66-Rated Weather-proof	

4K H.265+ Motorized Pro Bullet Camera

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	MS-C8262-FPB (1/1.8")	8MP(4K) 3840*2160 @30fps	Motorized lens 3.6-10mm	H110°~H46° D126°~D54° V61°~V25°	Color: 0.006Lux @F1.2	Super WDR 120dB	60m	IP67 (IK10)	650,00	* Built-in PoE Port * Integrated Cable Management * Support SD card, up to 256G * Support 3-axis design * Support H.265+/H.265/H.264+/H.264 * Multi port: Alarm I/O, Audio I/O, DC 12V Optional: * P-Iris: 20,00 € * IK10: 20,00 € * Video Content Analysis: 40,00 €
Default (Version A)		134*127*40mm, 510g		Optional (Version B)			φ107.9*19mm, 133g		* Aluminum alloy * For cable management * IP66-Rated Weather-proof	

H.265+ Motorized Pro Dome Network Camera

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
 	  MS-C2972-FPB	2MP 1920*1080 @30fps	Motorized lens 2.7-13.5mm	H93°~H33° D107°~D38° V52°~V18°	Color: 0.002Lux @F1.2	Super WDR 140dB	50m	IP67 IK10	434,00	* Built-in PoE Port * Integrated Cable Management * Support SD card, up to 256G * Support 3-axis design * Support H.265+/H.265/H.264+/H.264 * Multi port: Built-in Mic, Alarm I/O, Audio out, DC 12V
	 MS-C5372-FPB	5MP 2592*1944 @20fps	Motorized lens 2.7-13.5mm	H90°~H31° D114°~D38° V67°~V23°	Color: 0.005Lux @F1.2	Super WDR 120dB	50m	IP67 IK10	455,00	Optional: * Lens 7-22mm (80m IR Distance): 55,00 € * High Frame Rate: (-R Series: 2MP@60fps): 45,00 € (-T Series: 2MP@90fps+Super WDR Pro): 45,00 € (-Q Series: 2MP@120fps): 120,00 € (-H Series: 5MP@30fps): 45,00 € * P-Iris: 20,00 € * Video Content Analysis: 40,00 € * Smoked Dome Cover AC-72
	MS-C8172-FPB	8MP(4K) 3840x2160 @15fps	Motorized lens 3.3-12mm	H101°~H39° D116°~D46° V56°~V21°	Color: 0.01Lux @F1.2	Super WDR 120dB	50m	IP67 IK10	499,00	
	A72	240*160*136mm, 560g							39,00	* Aluminum alloy * For wall or parapet installation
	A75	155.5*167*33.5mm, 200g							39,00	* Aluminum alloy * For cable management
	A76	Ø136*300mm, 620g							69,00	* Aluminum alloy * For ceiling or vertical structure * Pendant Pipe length can be extended with A76-L
	A76-L	Ø34*300mm, 315g							39,00	* Aluminum alloy * Used as extensions for pendant mount * Applicable Model: A76

H.265+ Fisheye Network Camera

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	MS-C5374-PB	5MP 2592*1944 @30fps	Fixed Lens 1.25mm	Ceiling Mount: 360° Wall Mount: 180° Flat Mount: 360°	Color: 0.005Lux @F1.2	Super WDR 120dB	15m	IP67 IK10	399,00	* Support PoE, DC12V * Support SD card, up to 256G * Support H.265+/H.265/H.264+/H.264 * Support Built-in Mic Optional: * Video Content Analysis: 40,00 €
	MS-C9674-PB (1/1.7")	12MP 4000*3000 @25fps	Fixed Lens 1.98mm	Ceiling Mount: 360° Wall Mount: 180° Flat Mount: 360°	Color: 0.01Lux @F1.2	Super WDR 120dB	15m	IP67 IK10	750,00	* Support PoE * Support SD card, up to 256G * Support H.265+/H.265/H.264+/H.264 * Support Alarm I/O * Support Built-in Mic & 1 Audio Output Optional: * Video Content Analysis: 40,00 €
	A72	240*160*136mm, 560g							39,00	* Aluminum alloy * For wall or parapet installation
	A75	155.5*167*33.5mm, 200g							39,00	* Aluminum alloy * For cable management
	A76	Ø136*300mm, 620g							69,00	* Aluminum alloy * For ceiling or vertical structure * Pendant Pipe length can be extended with A76-L
	A76-L	Ø34*300mm, 315g							39,00	* Aluminum alloy * Used as extensions for pendant mount * Applicable Model: A76

H.265+ Auto Back Focus Pro Box Network Camera

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	  MS-C2951-PB	2MP 1920*1080 @ 30fps	Optional	N/A	Color: 0.002Lux @F1.2	Super WDR 140dB	N/A	N/A	350,00	* Support PoE * Support SD card, up to 256G * Support H.265+/H.265/H.264+/H.264 * Multi port: RS485, Alarm I/O, Audio I/O, DC 12V Optional: * High Frame Rate: (-R Series: 2MP@60fps): 45,00 € (-T Series: 2MP@90fps+Super WDR Pro): 45,00 € (-Q Series: 2MP@120fps): 120,00 € (-H Series: 5MP@30fps): 45,00 € * Video Content Analysis: 40,00 € * Support Auto Back Focus: 75,00 € (Except MS-C5351/C8151-PB)
	  MS-C2851-PB (1/2")	2MP 1920*1080 @ 30fps	Optional	N/A	Color: 0.001Lux @F1.2	Super WDR 140dB	N/A	N/A	395,00	
	 MS-C5351-PB	5MP 2592*1944 @ 20fps	Optional	N/A	Color: 0.005Lux @F1.2	Super WDR 120dB	N/A	N/A	340,00	
	MS-C8151-PB	8MP(4K) 3840x2160 @ 15fps	Optional	N/A	Color: 0.01Lux @F1.2	Super WDR 120dB	N/A	N/A	365,00	
	A51		380*150*H mm (H is adjustable), 1988g						135,00	* Aluminum alloy * Robust housing to defend cameras from being damaged.

Available Lens

Iris	Model	ImageSize (inch)	Focal Length (mm)	Price	Remark
DC	TV033105D.IR-B-S	1/2.5" Zoom Lens	3.3-10.5	87,00	For all pro box camera except MS-C2851-PB
	TT02812D.IR-SD	1/2.7" Zoom Lens	2.8-12	46,00	
	NV0560D.IR-C	1/2.7" Zoom Lens	5-60	150,00	
P-Iris	TT02812P.IR-SD	1/2.7" Zoom Lens	2.8-12	55,00	
	NV03105P.IR-B-S	1/2.7" Zoom Lens	3-10.5	92,00	
	NV0722P.IR-B-S	1/2.7" Zoom Lens	7-22	101,00	
	NV0560P.IR-C	1/2.7" Zoom Lens	5-60	188,00	
DC	HV03610D.IR-S	1/1.8" Zoom Lens	3.6-10	116,00	Only for MS-C2851-PB
	HV03617D.IR-S	1/1.8" Zoom Lens	3.6-17	260,00	
P-Iris	HV03610P.IR-S	1/1.8" Zoom Lens	3.6-10	104,00	
	HV03617P.IR-S	1/1.8" Zoom Lens	3.6-17	251,00	
	HV1250P.IR-S	1/1.8" Zoom Lens	12-50	271,00	

12X H.265+ Mini PoE PTZ Bullet Network Camera

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
 	Starlight Super WDR MS-C2961-EPB	2MP 1920*1080 @30fps	AF Lens 5.3~64mm	H61°~H5° D69°~D5° V36°~V2°	Color: 0.002Lux @F1.2	Super WDR 140dB	100m	IP66	655,00	* Support PoE * Support SD card, up to 256G * Support H.265+/H.265/H.264+/H.264 * 12x optical zoom * 360° Pan Range; -45°~30° Tilt, Proportional Zoom * PTZ Position Display * 3D positioning * 255 Preset Points, 8 Patrols
	Starlight MS-C5361-EPB	5MP 2592*1944 @20fps	AF Lens 5.3~64mm	H57°~H4° D69°~D5° V44°~V1°	Color: 0.005Lux @F1.2	Super WDR 120dB	100m	IP66	679,00	* Support DC + PoE + Alarm (Version A, Default) DC + PoE + Audio (Version B, Optional) DC + Audio + Alarm (Version C, Optional) Optional: * High Frame Rate: 45,00 € (-R Series: 2MP@60fps) (-H Series: 5MP@30fps) * Video Content Analysis: 40,00 € * Wall Mount Bracket (Default) Pedestal Mount Bracket (Optional)
	A62			134*127*40mm, 510g					39,00	* Aluminum alloy * For cable management * IP66-Rated Weather-proof

Coming Soon

12X H.265+ Mini PoE PTZ Dome Network Camera

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	MS-C2971-X12RPB	2MP 1920*1080 @60fps	AF Lens 5.3~64mm	H61°~H5° D69°~D5° V36°~V2°	Color: 0.002Lux @F1.2	Super WDR 140dB	80m	IP66 IK10	740,00	* Support PoE * Support H.265+/H.265/H.264+/H.264 * 12x/23x Optical Zoom * 360° endless Pan, -5°~185° Tilt * 255 Preset Points * 8 Patrols, up to 48 presets each patrol * 4 Patterns
	MS-C2971-X23RPB	2MP 1920*1080 @60fps	AF Lens 5~117mm	H60°~H3° D69°~D4° V35°~V2°	Color: 0.002Lux @F1.2	Super WDR 140dB	80m	IP66 IK10	780,00	* Support SD card, up to 256G * Multi port: Alarm I/O, Audio I/O, DC 12V
	MS-C5371-X12HPB	5MP 2592*1944 @30fps	AF Lens 5.3~64mm	H57°~H4° D69°~D5° V44°~V1°	Color: 0.005Lux @F1.2	Super WDR 120dB	80m	IP66 IK10	815,00	* Support SD card, up to 256G * Multi port: Alarm I/O, Audio I/O, DC 12V
	MS-C5371-X23HPB	5MP 2592*1944 @30fps	AF Lens 5~117mm	H55°~H3° D68°~D4° V42°~V2°	Color: 0.005Lux @F1.2	Super WDR 120dB	80m	IP66 IK10	860,00	Optional: * Video Content Analysis: 40,00 €
	A43		Junction Box				195*164*80mm, 1000g		69,00	* Aluminum alloy * For cable management * IP67-Rated Weather-proof * Applicable Model: A41, A42
	A77		Wall Mount				262*185*138mm, 650g		69,00	* Aluminum alloy * For wall or parapet installation
	A78		Recessed Mount				256*256*94mm, 715g		79,00	* Aluminum alloy * For in- ceiling installation
	A79		Pendant Mount				256*256*245mm, 850g		69,00	* Aluminum alloy * For ceiling or vertical structure

Coming Soon

30X H.265+ PoE Speed Dome Network Camera

	Model	Resolution	Lens	Field of View	Ultra Low-light	WDR	IR Distance	IP&IK Rating	Price	Features
	MS-C2941-X30RPB	2MP 1920*1080 @60fps	AF Lens 4.7~141mm	H62°~H3° D70°~D3° V37°~V1°	Color: 0.002Lux @F1.2	Super WDR 140dB	250m	IP66 IK10	1398,00	* Support PoE * Support H.265+/H.265/H.264+/H.264 * 30x/36x/42x Optical Zoom * 360° endless Pan, 90° auto flip Tilt * 255 Preset Points * 8 Patrols, up to 48 presets each patrol * 4 Patterns
	MS-C5341-X30HPB	5MP 2592*1944 @30fps	AF Lens 4.7~141mm	H58°~H3° D71°~D3° V44°~V2°	Color: 0.005Lux @F1.2	Super WDR 120dB	250m	IP66 IK10	1450,00	* Support SD card, up to 256G * Multi port: RS485, Alarm I/O 2/2, Audio I/O, AC 24V * 6KV Surge Protection Optional: * Video Content Analysis: 40,00 €
	A41 (Default)		Wall Mount				200*129*100mm, 400g		N/A	* Aluminum alloy * For wall or parapet installation
	A42 (Optional)		Pendant Mount				116.5*225mm, 650g		N/A	* Aluminum alloy * For ceiling or vertical structure
	A43		Junction Box				195*164*80mm, 1000g		69,00	* Aluminum alloy * For cable management * IP67-Rated Weather-proof * Applicable Model: A41, A42

4K H.265+ PoE NVR 1000 Series

	Model	MP Support	Synchronous playback	PoE Ports	HDD Support	Local display		Alarm I/O	Price	Features
						HDMI	VGA			
	PoE MS-N1009-UPT	3840*2160 (4K/8MP)	2*8MP 3*5MP 8*1080P 9*720P	4	1*10TB	✓	N/A	N/A	410,00	1*RJ45 100M/1000M 2*USB2.0 interfaces DC 48V 1.25A Power

4K H.265+ PoE NVR 5000 Series

	Model	MP Support	Synchronous playback	PoE Ports	HDD Support	Local display		Alarm I/O	Price	Features
						HDMI	VGA			
	PoE MS-N5008-UPT	3840*2160 (4K/8MP)	2*8MP 3*5MP 4*4MP 8*1080P 8*720P	8	2*10TB	✓	✓	4/1	690,00	1*RJ45 100M/1000M 1*USB 3.0 interfaces 2*USB 2.0 interfaces 1*RCA Audio output
	PoE MS-N5016-UPT	3840*2160 (4K/8MP)	2*8MP 3*5MP 4*4MP 8*1080P 16*720P	16	2*10TB	✓	✓	4/1	855,00	

4K H.265+ PoE NVR 7000 Series

	Model	MP Support	Synchronous playback	PoE Ports	HDD Support	Local display		Alarm I/O	Price	Features
						HDMI	VGA			
	PoE MS-N7016-UPH	3840*2160 (4K/8MP)	4*8MP 6*5MP 8*4MP 16*1080P 16*720P	16	4*10TB	✓	✓	16/4	1080,00	1*RJ45 100M/1000M 1*RCA Audio input 1*RCA Audio output 1*RS-485 Series Port for PTZ 1*RS-232 Series Port for Console 1*RS-485 Series Port for Keyboard 1*USB 3.0 interfaces 2*USB 2.0 interfaces RAID 0/1/5/6/10 Storage
	PoE MS-N7032-UPH	3840*2160 (4K/8MP)	4*8MP 6*5MP 8*4MP 16*1080P 32*720P	24	4*10TB	✓	✓	16/4	1160,00	

24/7 HDD

Picture	Model		LP in €	Remark
	WD1000	WD 24/7 HDD for Video Surveillance	145,00	
	WD2000		190,50	
	WD3000		228,00	

4K H.265+ Mini NVR 1000 Series

	Model	MP Support	Synchronous playback	RAID	HDD Support	Local display		Audio Alarm	Price	Features
						HDMI	VGA			
	MS-N1009-UT	3840*2160 (4K/8MP)	2*8MP 3*5MP 8*1080P 9*720P	N/A	2*2TB (2.5"HDD)	✓	N/A	N/A	346,00	1*RJ45 100M/1000M 2*USB 2.0 interfaces 2*SATA HDD(2.5") support
	MS-N1009-UNT	3840*2160 (4K/8MP)	2*8MP 3*5MP 8*1080P 9*720P	N/A	1*10TB (3.5"HDD)	✓	N/A	N/A	364,00	1*RJ45 100M/1000M 2*USB 2.0 interfaces 1*SATA HDD(3.5") support

4K H.265+ Pro NVR 5000 Series


	Model	MP Support	Synchronous playback	RAID	HDD Support	Local display		Alarm I/O	Price	Features
						HDMI	VGA			
	MS-N5008-UT	3840*2160 (4K/8MP)	2*8MP 3*5MP 4*4MP 8*1080P 8*720P	N/A	2*10TB	✓	✓	4/1	506,00	1*RJ45 100M/1000M 1*USB 3.0 interfaces 2*USB 2.0 interfaces 1*RCA Audio output
	MS-N5016-UT	3840*2160 (4K/8MP)	2*8MP 3*5MP 4*4MP 8*1080P 16*720P	N/A	2*10TB	✓	✓	4/1	540,00	1*RJ45 100M/1000M 1*USB 3.0 interfaces 2*USB 2.0 interfaces 1*RCA Audio output

4K H.265+ Pro NVR 7000 Series

	Model	MP Support	Synchronous playback	RAID	HDD Support	Local display		Alarm I/O	Price	Features
						HDMI	VGA			
	MS-N7016-UH	3840*2160 (4K/8MP)	4*8MP 6*5MP 8*4MP 16*1080P 16*720P	0/1/5/6/10	4*10TB	✓	✓	16/4	889,00	2*RJ45 100M/1000M 1*RCA Audio input 1*RCA Audio output 1*RS-485 Series Port for PTZ
	MS-N7032-UH	3840*2160 (4K/8MP)	4*8MP 6*5MP 8*4MP 16*1080P 32*720P	0/1/5/6/10	4*10TB	✓	✓	16/4	938,00	1*RS-232 Series Port for Console 1*RS-485 Series Port for Keyboard 1*USB 3.0 interfaces 2*USB 2.0 interfaces

4K H.265+ Pro NVR 8000 Series

	Model	MP Support	Synchronous playback	RAID	HDD Support	Local display		Alarm I/O	Price	Features
						HDMI	VGA			
	MS-N8032-UH	3840*2160 (4K/8MP)	4*8MP 6*5MP 8*4MP 16*1080P 32*720P	0/1/5/6/10	8*10TB	2*HDMI	2*VGA	16/4	1140,00	2*RJ45 100M/1000M 1*RCA Audio input 2*RCA Audio output 1*eSATA interface 1*RS-485 Series Port for PTZ
	MS-N8064-UH	3840*2160 (4K/8MP)	4*8MP 6*5MP 8*4MP 16*1080P 32*720P	0/1/5/6/10	8*10TB	2*HDMI	2*VGA	16/4	1503,00	1*RS-232 Series Port for Console 1*RS-485 Series Port for Keyboard 1*USB 3.0 interfaces 2*USB 2.0 interfaces

Accessories			
Image	Model	Description	Price
	A71	Wall Mount Bracket * Net Weight: 530g Dimension: 162*124*78mm * Installation Environment: Used to install camera on a wall or vertical structure * Applicable Model: IR Mini Dome, Vandal-proof Mini Dome, Weather-proof Mini Dome, AF Motorized Mini Dome	31,00
	A72	Wall Mount Bracket * Net Weight: 560g Dimension: 240*160*136mm * Installation Environment: For wall or parapet installation * Applicable Model: Pro Dome, Fisheye Camera	39,00
	AC-72	Smoked Dome Cover * Net Weight: 39g Dimension: Ø100*56mm (4 inch) * Installation Environment: For concealing where a camera is pointed. * Applicable Model: Pro Dome	39,00
	A73	Adapter Plate * Net Weight: 28g Dimension: 115*122.5*10mm * Installation Environment: For the installation that cable need to be routed through the side outlet * Applicable Model: Vandal-proof Mini Dome	10,00
	A74	Junction Box * Net Weight: 60g Dimension: 121.5*116.5*37.2mm * Installation Environment: For the containing of electrical connections which need to be concealed from sight and deter tampering. * Applicable Model: Vandal-proof Mini Dome	39,00
	A75	Junction Box * Net Weight: 200g Dimension: 155.5*167*33.5mm * Installation Environment: For the containing of electrical connections which need to be concealed from sight and deter tampering. * Applicable Model: Pro Dome, Fisheye Camera	39,00
	A76	Pendant Mount * Net Weight: 620g * Dimension: Ø136*300mm (Pendant Pipe length can be extended with A76-L) * Installation Environment: Used to install cameras on an ceiling or vertical structure. * Applicable Model: Fisheye Camera	69,00
	A76-L	Extension Lever * Net Weight: 315g * Dimension: Ø34*300mm * Installation Environment: Used as extensions for pendant mount. * Applicable Model: A76	39,00
	A62	Junction Box * Net Weight: 510g Dimension: 134*127*40mm * IP66-Rated Weather-proof * Installation Environment: For the containing of electrical connections which need to be concealed from sight and deter tampering. * Applicable Model: Pro Bullet, Mini PTZ Bullet	39,00
	A63	Junction Box * Net Weight: 620g Dimension: 134*127*40mm * IP66-Rated Weather-proof * Installation Environment: For the containing of electrical connections which need to be concealed from sight and deter tampering. * Applicable Model: Mini Bullet, Motorized Mini Bullet, Vandal-proof Motorized Mini Bullet	39,00
	A01	Pole Mount with Stainless Steel Straps * Net Weight: 720g Dimension: 170*51.5*152.6mm * Installation Environment: For strapping cameras on poles between 102-127 (4.1-5 inches) in diameter * Applicable Model: Mini Bullet, Motorized Mini Bullet, Vandal-proof Mini Bullet, Panoramic Mini Bullet, A41, A62, A63, A71, A72, A77	39,00
	A02	Internal Corner Bracket * Net Weight: 540g * Dimension: 170*23.2*205.3mm * Installation Environment: For mounting cameras on an internal corner * Applicable Model: Mini Bullet, Motorized Mini Bullet, Vandal-proof Motorized Mini Bullet, Weather-proof Mini Dome, AF Motorized Mini Dome, A71, A72	39,00
	A03	External Corner Bracket * Net Weight: 900g Dimension: 170*152.6*76.3mm * Installation Environment: For mounting cameras on an external corner * Applicable Model: Mini Bullet, Motorized Mini Bullet, Vandal-proof Mini Bullet, Panoramic Mini Bullet, A41, A62, A63, A71, A72, A77	39,00

Accessories

Image	Model	Description	Price
	A41	Wall Mount * Net Weight: 400g Dimension: 200*129*100mm * Installation Environment: For wall or parapet installation * Applicable Model: Speed Dome Camera	69,00
	A42	Pendant Mount * Net Weight: 650g Dimension: 116.5*225mm * Installation Environment: For ceiling or vertical structure * Applicable Model: Speed Dome Camera	69,00
	A43	Junction Box * Net Weight: 1000g Dimension: 195*164*80mm * IP67-Rated Weather-proof * Installation Environment: For the containing of electrical connections which need to be concealed from sight and deter tampering. * Applicable Model: A41, A42	69,00
	A77	Wall Mount * Net Weight: 650g * Dimension: 262*185*138mm * Installation Environment: For wall or parapet installation * Applicable Model: Mini PTZ Dome	69,00
	A78	Recessed Mount * Net Weight: 715g * Dimension: 256*256*94mm * Installation Environment: For in- ceiling installation * Applicable Model: Mini PTZ Dome	79,00
	A79	Pendant Mount * Net Weight: 850g * Dimension: 256*256*245mm * Installation Environment: For ceiling or vertical structure * Applicable Model: Mini PTZ Dome	69,00
	A51	Protective Housing with the Wall Mount Bracket * Net Weight: 1988g * Dimension: 380*150*H mm (H is adjustable) * Installation Environment: Robust housing to defend cameras from being damaged in all challenging environments * Applicable Model: Pro Box camera	135,00

