



# ESiGO 8Pro

PROFESSIONAL PORTABLE POWERED SPEAKER

**8** WOOFER  
TWO WAY

**190W**  
CLASS D



**4**  
DSP

ACTIVE SPEAKER

BI-AMPLIFIER

TWS 5.0

MODE

- 2-way Active speaker.
- 8" LF woofer and 1" HF compression driver.
- Frequency response : 60Hz-19kHz
- Built-in 3 Channels mixer.
  - 2 CH Mic/line mono combo (XLR/TRS)
  - 1 CH AUX 1 x RCA(L/R) / 1 x 3.5mini jack
  - Input channel functions CH1, 2 selection switch used for guitar signal input.
- Built-in Line Output : XLR
- Bi-Amplifier CLASS-D / 190 Watts. (MAX)
- Bluetooth TWS (True Wireless Stereo) Version 5.0
- DSP 4 mode : Music, Live, Monitor, Speech
- Battery run time: Up to 10 hours (depending on usage)
- Coverage angle (H x V) : 100° x 60°
- Operating voltage : AC 100-240V 50/60Hz / DC 15V



Applications: outdoor performances, presentations, parties, events, fitness...



## SPECIFICATIONS

### AUDIO

|                        |                                        |
|------------------------|----------------------------------------|
| Speaker type           | Portable 2-way active speaker          |
| Drivers                | LF 8" woofer, HF 1" compression driver |
| Frequency response     | 60Hz-19KHz                             |
| Maximum SPL            | 113dB                                  |
| Sensitivity 1w/1m      | 95dB                                   |
| Coverage angle (H x V) | 100° x 60°                             |
| Amplifier              | Bi-Amplifier CLASS-D                   |
| Amplifier rating       | 190W (MAX)                             |
| THD                    | <0.1% 20Hz-20KHz                       |
| Operating voltage      | AC 100-240V 50/60Hz / DC 15V           |

### CONNECTION

|                           |                                                                       |
|---------------------------|-----------------------------------------------------------------------|
| Input                     | 2 Mic/line mono combo (XLR/TRS)   AUX 1 x RCA(L/R) / 1 x 3.5mini jack |
| - Input channel functions | CH1, 2 selection switch used for guitar signal input                  |
| Output                    | XLR                                                                   |
| EQ                        | High, Bass, ±15dB                                                     |

### Media Player

|                   |            |
|-------------------|------------|
| Bluetooth Version | TWS 5.0    |
| Bluetooth Range   | >15 Meters |

### DSP Processor

|                    |                                                                       |
|--------------------|-----------------------------------------------------------------------|
| Dsp mode           | 1. Music, 2.Live, 3.Monitor, 4.Speech                                 |
| Sampling frequency | 48KHz, MIC Lowcut, Crossover, Limiter, Talkover, Reverb, Parameter EQ |

### BATTERY

|                      |                                                                          |
|----------------------|--------------------------------------------------------------------------|
| Rechargeable Battery | 7800mAh Lithium Battery                                                  |
| Battery run time     | 9-10 hours (Vol. 25%) / 6-8 hours (Vol. 50%) / 3.5-5 hours (Vol. 80% up) |
| Recharge Time        | Approximately 4 hours                                                    |

### GENERAL

|                    |                      |
|--------------------|----------------------|
| Enclosure          | ABS                  |
| Grille material    | Metal                |
| Color              | Black                |
| Dimensions (H*W*D) | 398.76 x 270 x 280mm |
| Weight             | 8kgs                 |

VERIFICATION OF COMPLIANCE : CE and RoHS

## SOUND VISION CO., LTD.

99/189 Soi Kamnan Tinnakorn, Sala Klang,  
Bang Kruai, Nonthaburi 11130 Thailand

Email : [info@soundvision.co.th](mailto:info@soundvision.co.th)

Support : 02-433-9988

LINE Official : @soundvision

[www.soundvisionpro.com](http://www.soundvisionpro.com)

