

Asphalt Rake



NEED HELP? CONTACT US!

Have product questions? Need technical support? Please feel free to contact us:

> Technical Support and E-Warranty Certificate www.vevor.com/support

This is the original instruction, please read all manual instructions carefully before operating. VEVOR reserves clear interpretation of our user manual. The appearance of the product shall be subject to the product you received. Please forgive us that we won't inform you again if there is any technology or software updates on our product.

Important Information:

Please read these instructions thoroughly before use. Failure to follow instructions may result in equipment damage, malfunction, or even injury or death to personnel.

A Warning A

- The Rake is designed for cutting submerged, partially emergent, or emergent aquatic vegetation from underwater. Any other use is strictly prohibited. Before using the Rake, please read this manual carefully tounderstand the proper use of the unit.
- The Rake teeth have sharp edges.

A SAFETY FIRST: A



Keep out of reach of children.

Do not use it with children in the immediate area. IMPORTANT: We are not responsible for equipment damage or failure, losses, injury, or death resulting from failure to follow safety precautions, misuse, or abuse of equipment.

PRODUCT CONTENTS:


No.	Name	Q'TY	Picture
1	Rake Head with Handle	1	Wasanama -
2	Middle Pole	1	·
3	Handle/Black End Cap	1	
4	Rope	1	
5	Floats	2	Marie 1967 1967 1967
6	Velcro Straps	4	

Assembly & Instructions

Step 1

Handle Assembly: Press the spring-loaded buttons on one end of the handle connector and slide it halfway into one of the handles and rotate it until the buttons snap into the holes in the handle.

Repeat this process for the other half of the handle.




Step 2

To expand the rake head, press down on the spring loaded buttons and push forward until fully open, and springs lock into place.



Step 3

Flotation devices are most effective when the two outermost velcro straps are attached to the two outer teeth of the rake head.





02 03

Operating Instructions

Cast & Retrieve


The Cast and Retrieve option is great for removing weeds, algae, or debris (both floating and submerged).

Weed, Algae & Debris Removal

The 9' handle is designed for skimming or removing aquatic weeds, and algae from shore.

Beach Grooming

Remove the rope and floats, and you have a professional-grade rake to asily groom your beach sand.



Model No.	CY-SF14	
Weight	2.55 kg	
Size	102.4*36"	

Manufacturer: Shanghaimuxinmuyeyouxiangongsi

Address: Shuangchenglu 803nong11hao1602A-1609shi, baoshanqu, shanghai 200000 CN.

Imported to AUS: SIHAO PTY LTD. 1 ROKEVA STREETEASTWOOD NSW 2122 Australia

Imported to USA: Sanven Technology Ltd. Suite 250, 9166 Anaheim Place, Rancho Cucamonga, CA 91730



YH CONSULTING LIMITED. C/O YH Consulting Limited Office 147, Centurion House, London Road, Staines-upon-Thames, Surrey, TW18 4AX



E-CrossStu GmbH Mainzer Landstr.69, 60329 Frankfurt am Main.



Technical Support and E-Warranty Certificate www.vevor.com/support



Technical Support and E-Warranty Certificate www.vevor.com/support

ASPHALT RAKE

Model:CY-SF14

We continue to be committed to provide you tools with competitive price. "Save Half", "Half Price" or any other similar expressions used by us only represents an estimate of savings you might benefit from buying certain tools with us compared to the major top brands and does not necessarily mean to cover all categories of tools offered by us.

You are kindly reminded to verify carefully when you are placing an order with us if you are actually saving half in comparison with the top major brands.