

KODAK PIXPRO FZ55

DIGITAL CAMERA



FZ55 FRIENDLY ZOOM

Meet the FZ55, Friendly Zoom from the new KODAK PIXPRO collection of digital cameras. This compact point and shoot is a step up model with rechargeable lithium-ion battery. One-touch HD video, 28mm wide-angle lens and a host of features and shooting modes let you express your inner creativity. KODAK PIXPRO Digital Cameras – Tell your story.

FEATURES:

- 5X Optical Zoom
- 28 mm Wide Angle
- 16 MP
- 2.7" LCD
- 1080p Full HD Video
- Li-ion Battery
- Slim Design



Available Colors:

- BLACK
- RED
- BLUE

Images are simulated.



KODAK PIXPRO FZ55

DIGITAL CAMERA

SPECIFICATIONS	FZ55
Effective Image Sensor Pixels	16.35 Megapixels
Total Image Sensor Pixels	16.76 Megapixels [1/2.3"(CMOS)]
Lens	
Focal Length	5.1 mm (Wide) — 25.5 mm (Tele)
[35mm film equivalent]	[28 mm (Wide) — 140 mm (Tele)]
F number	F3.9 (Wide) — F6.3 (Tele)
Lens Construction	8 groups 8 elements
Optical Zoom	5x
Focusing Range	Normal: (Wide) 60cm — ∞ (Tele) 100 cm — ∞ Macro: 5 cm — ∞ (Wide Only)
Anti-Handshake	Digital Image Stabilization
Digital Zoom	6x Digital Zoom (Combined Zoom: 30x)
Number of Recording Pixels	
Still Image	(4:3) 16MP: 4608x3456, 10MP: 3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080
Movie	1920x1080: 30fps, 1280x720: 60/30fps, 640x480: 30fps, High Speed Movie 640x480: 120fps
Image Compression	Best, Fine, Normal
File Format	
Still Image	Exif 2.3 (JPEG)
Movie	MOV [Image: Motion JPEG; Audio: Linear PCM (Monaural)]
Shooting Modes	M, P, Auto, Face Beautifier, Movie, Panorama, SCN
SCN Modes	ASCN, Landscape, Sport, Beach, Sunset, Fireworks, Night Landscape, Snow, Children, Portrait, Party, Night Portrait, Pet, Image Stabilization
Detection Features	Face, Smile, Blink, Cat, Dog
Photo Touch-up	Red-Eye Removal, Skin Soften, Eye Brightening, Eye Enlargement
HDR (High Dynamic Range)	Yes
Panorama Capture	0° - 180° (Horizontal)
LCD Display	2.7 inch (230K Pixels)
ISO Sensitivity	Auto, ISO 100/200/400/800/1600/3200
AF Method	Single AF, Multi-AF (TTL 9-point), Object Tracking, Face Detection
Exposure Metering Method	Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE
Exposure Control Method	Program AE (AE-Lock Available)
Exposure Compensation	+/- 3EV in 1/3 Step Increments
Shutter Speed	1/2000 - 4 Seconds (Manual: 30 Seconds)
Continuous Shooting	Yes
Playback Modes	Single Photo, Index (9/16 Thumbnails) Slide Show, Date, Zoom (Approx. x2 - x8)
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual, Color Temp. Setting (1900K-10000K)
Flash	
Flash Method	Internal
Flash Modes	Auto, Red-Eye Reduction, Fill Flash, Force Off, Slow Synchro, Red-Eye Reduction + Slow Synchro
Shooting Range	(Wide) Approx. 0.3 m - 3.9 m (ISO800); (Tele) Approx. 1.2 m - 2.4 m (ISO800)
Recording Media	Internal Memory: Approx. 63MB SD/SDHC/SDXC Card (Up to 512GB Support) [MMC Card Not Supported]
Other Features	Multi-Language Support (27 Languages)
Jacks	USB 2.0 (Type-C)
Power	Rechargeable Li-ion Battery LB-012, 3.7V 700mAh, In-Camera Charging
Shooting Capability (Battery Performance)	Approx. 200 Shots (Based on CIPA Standards) Approx. 1 hr 30 min for Video (@ 1080/30fps)
Operation Environment	Temperature: 32° - 104°F / 0° - 40°C, Humidity: 0 - 90%
Dimensions (WxHxD)	Approx. 3.60 x 2.23 x 0.90 in. / 91.5 x 56.5 x 22.9 mm (Based on CIPA Standards)
Weight	Approx. 3.7 oz. / 106g (Body Only)
Supplied Accessories	Rechargeable Li-ion Battery, Type-C USB cable, Wrist Strap, Service Card, Quick Start Guide, Warranty Card

JK Imaging Ltd.

14067 Stage Road, Santa Fe Springs, CA 90670 USA
(888)978-0806

© 2024 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company.
All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0066.0430.en.05

To learn more about KODAK PIXPRO Digital Cameras:
visit: kodakpixpro.com

