

Item #: 178UBB48GT Project: \_\_\_\_\_

Qty: \_\_\_\_\_ Date: \_\_\_\_\_ Approval: \_\_\_\_\_

## Avantco UBB-48-GT 48" Black Underbar Height Narrow Solid Door Back Bar Refrigerator with Galvanized Top and LED Lighting

Item #178UBB48GT



### Technical Data

|                          |                 |
|--------------------------|-----------------|
| Width                    | 48 3/4 Inches   |
| Depth                    | 24 7/16 Inches  |
| Height                   | 34 13/16 Inches |
| Power Cord Length        | 106 Inches      |
| Interior Width           | 36 1/4 Inches   |
| Left Door Opening Width  | 16 7/16 Inches  |
| Packaging Width          | 51 1/4 Inches   |
| Right Door Opening Width | 16 7/16 Inches  |
| Shelf Width              | 17 5/8 Inches   |
| Interior Depth           | 18 1/2 Inches   |

### Features

- Galvanized steel countertop with stainless steel interior and black coated steel exterior
- LED interior lighting
- Four adjustable epoxy-coated steel shelves can be removed to fit two 1/2 kegs
- Preprogrammed digital temperature controls featuring auto-defrost function for easy setup
- 115V; 3/7 hp; R290 refrigerant

### Certifications



5-15P



ETL, US




ETL Sanitation

## Technical Data

|                             |                                                                                                                                                   |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Nominal Depth               | Narrow                                                                                                                                            |
| Packaging Depth             | 27 1/2 Inches                                                                                                                                     |
| Shelf Depth                 | 18 1/8 Inches                                                                                                                                     |
| Interior Height             | 29 Inches                                                                                                                                         |
| Packaging Height            | 41 3/4 Inches                                                                                                                                     |
| Amps                        | 3.5 Amps                                                                                                                                          |
| Hertz                       | 60 Hz                                                                                                                                             |
| Phase                       | 1 Phase                                                                                                                                           |
| Voltage                     | 115 Volts                                                                                                                                         |
| Wattage                     | 325 Watts                                                                                                                                         |
| Access Type                 | Doors                                                                                                                                             |
| BTU (LBP)                   | 974 BTU                                                                                                                                           |
| Capacity                    | (2) 1/2 Kegs<br>13 cu. ft.                                                                                                                        |
| Capacity (per Shelf)        | 88 lb.                                                                                                                                            |
| Casters                     | Without Casters                                                                                                                                   |
| Compressor Location         | Side Mounted                                                                                                                                      |
| Countertop Type             | Galvanized Steel                                                                                                                                  |
| Door Style                  | Swing                                                                                                                                             |
| Door Type                   | Solid                                                                                                                                             |
| Exterior Finish             | Black                                                                                                                                             |
| Features                    | Automatic Electric Defrost<br>Digital Temperature Controller<br>Food Rated<br>LED Lighting<br>Lighted Interior<br>Removable Magnetic Door Gaskets |
| Horsepower                  | 3/7 hp                                                                                                                                            |
| Insulation Material         | Polyurethane Foam                                                                                                                                 |
| Material                    | Black Coated Steel / Stainless Steel                                                                                                              |
| Maximum Ambient Temperature | 90 Degrees F                                                                                                                                      |
| Net Weight                  | 231 lb.                                                                                                                                           |
| Number of 12 oz. Bottles    | 196 Bottles                                                                                                                                       |
| Number of 12 oz. Cans       | 144 Cans                                                                                                                                          |
| Number of Doors             | 2 Doors                                                                                                                                           |
| Number of Kegs              | 2 Kegs                                                                                                                                            |
| Number of Shelves           | 4 Shelves                                                                                                                                         |
| Plug Type                   | NEMA 5-15P                                                                                                                                        |
| Refrigerant Capacity        | 2.5 oz.                                                                                                                                           |
| Refrigerant Type            | R-290                                                                                                                                             |
| Shelf Material              | Epoxy-Coated Steel                                                                                                                                |
| Starting Amps               | 10.5 Amps                                                                                                                                         |
| Starting Wattage            | 975 Watts                                                                                                                                         |
| Temperature Range           | 33 - 40 Degrees F                                                                                                                                 |
| Top Capacity                | 353 lb.                                                                                                                                           |
| Top Type                    | Below Counter                                                                                                                                     |

## Plan View



## Notes & Details

Optimize the space behind your bar by adding refrigerated storage with this Avantco UBB-48-GT 48" underbar height narrow back bar refrigerator! Providing 13 cu. ft. of interior storage space, the unit fits up to (2) 1/2 kegs and houses 4 shelves that each accommodate up to 88 lb. The epoxy-coated steel shelves are perfect for storing and organizing beverages for your bar service, from bottles of ale and beer to cans of crisp ciders. Plus, with a narrow design, the unit fits in spaces other units can't, helping you to maximize the space you have available.

The interior, made of strong 201 type stainless steel, is accessible through two solid doors. For overall durability, the unit's exterior is made with black coated steel and is topped with a galvanized steel surface. This galvanized top design is ideal for built-in bars.

This back bar refrigerator ensures optimal performance by operating with a 3/7 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3, making it an energy-efficient choice for your business. The foamed-in-place polyurethane insulation provides the refrigerator with additional structural integrity and ensures that all beverages held in the unit remain at cool temperatures and are ready for immediate service to customers! The unit requires a 115V electrical connection for operation and even comes with adjustable feet for simple, convenient leveling.

**⚠ WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).