

PRODUCT INFO

NRX REFRIGERATOR DRAWER SERIES

Meet the NRX Drawer Fridge – the ultimate cooling solution for boats and compact spaces. With its sleek slide-out design, it's built to fit where others can't, making it effortless to access your provisions. Stylish, efficient, and designed for life on the move, the NRX is the essential upgrade for your adventures.

**3-IN-1
SOLUTION**

**SUPERIOR ENERGY
EFFICIENCY**

**SMART MODULAR
INTERIOR**



Mobile living made easy.



EFFORTLESS DESIGN, EXCEPTIONAL PERFORMANCE

The NRX Drawer Fridge combines smart design with ultimate practicality. Its frameless door and full-width handle bring modern style, while the slide-out drawer makes accessing your provisions simple and hassle-free. Inside, the modular layout adapts to your needs, and the removable freezer compartment creates extra space for taller bottles or larger items in seconds.

Built for efficiency, the NRX is up to 20% more energy-efficient than comparable fridges, with an electronically controlled compressor and fan speed for quiet, economical operation. Whether you're chilling drinks or deep-freezing essentials, the NRX is the perfect balance of style, performance, and practicality.

Benefits with NRX Series

- Customizable Storage: Modular interior with adjustable partitions and versatile storage trays.
- Convenient Slide-Out Design: Smooth, self-closing drawer with easy access from any angle via a full-width handle.
- 3-in-1 Cooling Solution: Use as a fridge-freezer combination, or remove the freezer compartment for full fridge or freezer capacity.
- Elegant Front Panel Options: Frameless door available in dark silver or stainless steel finishes.
- Energy-Efficient Performance: Premium variable-speed compressor with Eco, Performance, and Silent modes.
- Secure and Practical Features: Two-point locking system (NRX-S only) with winter ventilation mode and optional modular installation frame.

REFRIGERATION TECHNOLOGY	Compressor
REFRIGERANT TYPE	R600a
TEMPERATURE RANGE	12°C to 0°C Fridge -5°C to -15°C Freezer
INPUT VOLTAGE	12/24 V DC
INCLUDED	Wire Basket x 1 Horizontal Divider x 1 Vertical Divider x 1 Upper Door Tray x 1 Removable Freezer Compartment x 1



1. Well equipped interior

Freezer, dividers, wire basket, door tray – it's all there



2. Compact, light & efficient compressor

Offering unparalleled energy efficiency and installation capabilities.



3. Touch control panel

Flush-mounted inside the cabinet, with integrated LED light bar.

From 0.22kw
per 24 Hour



Dometic NRX C Drawer Series

Frameless door with dark grey front panel and full-width handle.



Dometic NRX S Drawer Series

Frameless stainless steel 316 door with and full-width handle.

	MODEL	NRXD 50C	NRXD 50S	NRXD 60C	NRXD 60S	
NRXD 50S		Material	Frameless door with dark grey front panel and full-width plastic handle.	Frameless SS 316 door with full-width SS handle.	Frameless door with dark grey front panel and full-width plastic handle.	Frameless SS 316 door with full-width SS handle.
		Capacity:				
		– Total capacity	46.0 L		58.0 L	
		– Total capacity (freezer compartment removed)	44.0 L		55.0 L	
NRXD 50C		– Refrigerator compartment	41.6 L		51.9 L	
		– Freezer compartment	4.4 L		6.1 L	
		Connections	12/24 V DC; 100-240v AC with optional power supply accessory			
		Supply battery protection (12 V)				
NRXD 60S		– End-of-discharge voltage	10.4 V			
		– Cut-in voltage	11.7 V			
		Supply battery protection (24 V)				
		– End-of-discharge voltage	22.8 V			
NRXD 60C		– Cut-in voltage	24.2 V			
		Climate class	T			
		Storage temperature range:				
		– Refrigerator	0 °C to +12 °C			
		– Freezer compartment	–15 °C to –5 °C			
		– Freezer mode	–6 °C			
		Intended ambient temperature use	+16 °C to +43 °C			
		Refrigerant	R600a, Refrigerant quantity: 12 g CO ₂ equivalent: 0.000 t Global warming potential (GWP): 3		R600a, Refrigerant quantity: 12 g CO ₂ equivalent: 0.000 t Global warming potential (GWP): 3	
		Noise emission (EN60704)	40–45 dB(A)			
		Dimensions (W × H × D)	380 x 525 x 510 mm		448 x 525 x 537 mm	
		Weight	NRXD C: 18.9 kg NRXD S: 19.6 kg		NRXD C: 20.3 kg NRXD S: 21 kg	
		Product	Ref. No.			
		Dometic NRXD 50C	9620017636			
		Dometic NRXD 60C	9620017635			
		Dometic NRXD 50S	9620017633			
		Dometic NRXD 60S	9620017634			
		Optional extras	Ref. No.			
		Universal flush-mount frame, NRX 50C (Black powder coating, SUS430)	9620012874			
		Universal flush-mount frame, NRX 50S (SUS316)	9620012877			
		Universal flush-mount frame, NRX 60C (Black powder coating, SUS430)	9620012875			
		Universal flush-mount frame, NRX 60S (SUS316)	9620012881			
		Dometic DPS-R 135, Mains adapter for refrigerators	9620013449			
		Universal flush mount fixing kit can be used for flush mount & standard installation.				