



# CoreLine panel

## RC132V G5 43S/840 WIA W60L60 NOC ELB3

CoreLine panel, 34 W, 600x600 mm, 4300 lm, 4000 K, Wireless, Interact Ready, ELB3h

Philips CoreLine panel Gen5 delivers on the CoreLine promise of innovation, easy installation and excellent illumination. Designed as a direct replacement for functional luminaires in general lighting applications, this LED panel light's innovative MultiLumen feature offers a choice of three lumen packages in a single luminaire. This makes it easy to select the right product, gives you the flexibility respond to customer preferences on site, and means fewer product codes on stock. Installing this CoreLine RC132V LED panel is quick and easy too, thanks to a quick connector or Wieland connector. Interact Ready luminaires with integrated wireless communications are also available in this CoreLine range, ready to be used with Interact gateways, sensors and software.

### Product data

General Information		Glow-wire test	
Light source replaceable	No	EU RoHS compliant	Temperature 650 °C, duration 30 s
Number of gear units	1 unit		Yes
Driver included	Yes	Light Technical	
Product family code	RC132V [CORELINE PANEL]	Luminous Flux	4,300 lm
Connectivity	Interact Ready	Saturated Red (R9)	<50
Lighting Technology	LED	Correlated Color Temperature (Nom)	4000 K
Value ladder	Performance	Luminous Efficacy (rated) (Nom)	128 lm/W
CE mark	Yes	Color rendering index (CRI)	≥80
Warranty period	5 years	Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Flammability mark	For mounting on normally flammable surfaces	Stroboscopic effect visibility measure (SVM)	0.4
ENEC mark	ENEC mark	Light source color	840 neutral white

CoreLine panel

Optic type	Beam angle 120°
Luminaire light beam spread	120°
Unified glare rating CEN	22
Operating and Electrical	
Input Voltage	220–240 V
Line Frequency	50 or 60 Hz
Inrush current	4.8 A
Inrush time	0.056 ms
Power Consumption	34 W
Power Factor (Fraction)	0.9
Connection	Push-in connector 5-pole
Cable	–
Number of products on MCB of 16 A type B	50
Temperature	
Ambient temperature range	0 to +35 °C
Controls and Dimming	
Dimmable	Yes
Driver/power unit/transformer	Wireless driver Interact System ready
Control interface	Wireless
Constant light output	No
Mechanical and Housing	
Housing Material	Steel
Reflector material	Acrylate
Optic material	Polystyrene
Optical cover material	Acrylate
Fixation material	–
Housing Color	White
Optical cover finish	Opal
Overall length	595 mm
Overall width	595 mm
Overall height	70 mm
Dimensions (Height x Width x Depth)	70 x 595 x 595 mm
Approval and Application	
Ingress protection code	IP20/44 [Finger-protected; wire-protected, splash-proof]

Mech. impact protection code	IK03 [0.3 J]
Sustainability rating	–
Protection class IEC	Safety class II
Photobiological risk	Photobiological risk group 0 @200mm to EN62778
Photobiological risk specification	0.2 m
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38, 0.38) SDCM≤3
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life	5 %
50000 h	
Lumen maintenance at median useful life*	L90
50000 h	
Lumen maintenance at median useful life*	L75
100000 h	
Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	1%
Suitable for random switching	Yes
Product Data	
Order product name	RC132V G5 43S/840 WIA W60L60 NOC ELB3
Full product name	RC132V G5 43S/840 WIA W60L60 NOC ELB3
Full product code	872016901389600
Order code	910505102369
Material Nr. (12NC)	910505102369
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169013896
Numerator - Packs per outer box	1
EAN/UPC - Case	8720169013896

## CoreLine panel

### Dimensional drawing

