ecobee for Pro

Simple design. Serious savings. Trusted by Pros.

Meet the all-new Smart Thermostat Lite. Made for simplicity with input from contractors, it's easy to install and use, hardwired for reliability, built to last, and designed to save your customers up to 23%* on their heating and cooling costs. Best of all, it's exclusive to Pros.



ecobee for Bryant Smart Thermostat LITE



InteliSense EB-STATE7IBR-01

Why Pros love us.

InteliSense™ Technology

Pair this smart thermostat with InteliSense-enabled Preferred™ Series equipment, and with an opt-in to data sharing from your homeowner, you can have access to critical performance data. The performance data is available via the connected portal and Service Technician app for remote troubleshooting and system performance analysis.

Hardwired - Batteries not required.

Avoid call backs with the Smart Thermostat Lite - it's hardwired and doesn't need batteries, reducing the risk of product failures.

Works with most HVAC systems.

The Smart Thermostat Lite is easy to install and works with most HVAC systems up to 4H/2C, radiant heating, multi-stage, and dual-fuel.

Full accessory control.

Easily support and control one-wire HVAC accessory devices like a humidifier, dehumidifier, or ventilator.

Industry-leading warranty.

Add peace of mind with the Smart Thermostat Lite. That means an extended five-year warranty when installed by you, a professional.

Why customers love us.

InteliSense Technology

Pairing this smart thermostat with InteliSense-enabled equipment means technicians can gather system data to monitor performance and help protect your investment. It also allows for quicker and more efficient service when you need it.

Help them save.

Customers can save up to 23%* every year on heating and cooling costs with the Smart Thermostat Lite. That's around \$250** in savings per year!

Control anytime, anywhere.

Easily control the Smart Thermostat Lite on the beautifully designed touchscreen or through an Android or iOS device by downloading the top-rated ecobee app.

ENERGY STAR® approved.

Get top-of-the-line energy savings with ENERGY STAR®certified Smart Thermostats. In 2024, ecobee was named ENERGY STAR® Partner of the Year. (The fourth year in a row!)

Works with popular smart home systems.

Conveniently pairs with Apple HomeKit, Google Assistant, and Alexa.

Support Hours

For thermostat: Available 8am-11pm (Mon-Fri) and 9am-9pm (Sat-Sun). 1.866.518.6740 support@ecobee.com | ecobee.com/contractors

For heating and cooling equipment: Available 8am-5pm (Mon-Fri). 1.800.428.4326 | Bryant.com



Heating & Cooling Systems



ecobee for Pro

Smart Thermostat LITE

Compatibility

Works with most 24 VAC HVAC equipment: Gas, oil, electric, dual-fuel, forced air Conventional (2H/2C) Heat Pump(4H/2C) Boilers

PTACs or fan coil units with up to three fan speeds

HVAC accessory support

Control a one-wire HVAC accessory device like a humidifier, dehumidifier, or ventilator. (HRV/ERV)

Note: Self-powered accessories will require an additional 24V isolation relay.

Wire Terminals

C G/PEK Y1 Y2 ACC OB Rc Rh W1

W2

Connectivity and security

Wi-Fi: 802.11 b/g/n/ax @ 2.4GHz Bluetooth 5.0, A2DP, LE WPA, WPA2, WPA3 encryption methods DHCP (dynamic) or static IP addressing 168-bit SSL encryption 915MHz radio

Power consumption

3 VA

Bandwidth

5MB/Mo

Powering method

Hardwired. Power Extender Kit enables you to reliably power your thermostat if a C-wire is not available. PEK sold separately. Note: Use of the PEK will disable InteliSense technology.

Display

2.8" full-color touch screen LCD 240 x 320 pixel display

Thermostat sensors

Temperature Humidity

Sustainability

ENERGY STAR® Certified
Fully recyclable or compostable packaging
Mercury-free
Arsenic-free
PVC-free
RoHS compliant

Features

Multi-speed fan support Control through iOS and Android apps and Apple Watch

Temperature range

Desired: 45° F to 120° F (7° C to 49° C)
Display: 32° F to 120° F (0° C to 49° C)
Sensitivity: +/- 1° F (+/- 0.5° C)

Operating: 14° F to 122° F (-10° C to 50° C)

Humidity range

Display: 20% to 90% RH Sensitivity: +/- 5% RH

Operating: 5% to 95% RH (non-condensing)

Storage

Temperature: -4° F to 113° F (-20° C to 45° C) Humidity: 5% to 95% RH (non-condensing)

What's in the box

ecobee Smart Thermostat Lite Backplate Screws and drywall plugs Trim plate/adaptor plate Quick start guide

Warranty (Pro install only)

Industry-leading five-year warranty

Product dimensions

Smart Thermostat Length: 92 mm (3.62 in) Width: 92 mm (3.62 in) Depth: 23mm (0.91 in)

Trim Plate

Length: 112mm (4.42 in) Width: 170mm (6.70 in) Height: 8mm (0.32 in)









A Carrier Company