

SL**AP-PBMM0X 32"

500nit Digital Signage Monitor



Key Feature

- FHD Resolution
- 500nits
- 7 × 24 Operation
- HDMI Input
- USB Media Playback
- Built-In Speaker
- Slim and Light Design
- Landscape & Portrait Installation support
- VESA Mounting Interface
- Anti-Glare Open cell

Specification

Model	SL32AP-PBMM0X
Display	
Screen Size (Diagonal)	32 inch
Native Resolution	1920 (H) × 1080 (V)
Aspect Ratio	16 : 9
Brightness	500 cd/m ²
Contrast	≥ 1200:1
View Angle	178°(H) / 178°(V)
Display Color	16.7M
Response Time	8ms
Anti-Glare	25%Haze
Operation Time	7 × 24H
Life Time (Light Source)	50,000 Hrs (Typ.)

Interface	
Input	HDMI × 2
Output	-
External Control	-
Networks	-
Others	USB × 1
Built-In Speaker	8W × 2 (8Ω)

Power	
Power supply	AC 100~240V 50/60Hz 1A
Power consumption	≤ 70W
Standby	0.5W

Environment	
Operation Temperature	0°C~40°C
Operation Humidity	20%~80% RH
Storage Temperature	-20°C~60°C
Storage Humidity	10%~80% RH

Specification

Model	SL32AP-PBMM0X
Physical	
Color	Black
On bezel （off bezel） (mm)	16.2(L/R)/16.2(T)29.1 (B)
Tempered Glass	-
Body Dimension w/o Stand (W×H×D, mm)	735.9x216x487.7
Set Weight w/o Stand	3.5 Kg
Package Dimension (W×H×D, mm)	795x135x516
Package Weight	6 Kg
VESA Mounting	200 × 100

Dimension Drawing

SL32AP-PBMM0X

Unit: mm

