



Contactor, Definite Purpose, 50A, 3 pole, 30HP at 575VAC, 3 phase, 440/480VAC 50/60Hz coil, open

8910DPA53V06

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Definite Purpose Contactor	
Line Rated Current	50 A	
Number of Poles	3P	
Pole contact composition	3 NO	
Range of Product	DPA	

Complementary

Maximum Horse Power Rating	3 hp 115 V AC, 1 phase	
	10 hp 230 V AC, 1 phase	
	15 hp 230 V AC, 3 phase	
	30 hp 460 V AC, 3 phase	
	30 hp 575 V AC, 3 phase	
Locked rotor rated current	300 A 277 V AC	
	250 A 460 V AC	
	200 A 575 V AC	
[Ue] rated operational voltage	600 V AC	
[Uc] control circuit voltage	440 V AC 50 Hz	
	480 V AC 60 Hz	
Phase	3 phase	
Electrical Connection	Quick connect terminals	
	Box lugs	
Height	4.1 in (105 mm)	
Width	2.6 in (65 mm)	
Depth	3.7 in (93 mm)	

Environment

Product Certifications	UL Recognized
	CSA

Ordering and shipping details

Category	US1CP1B21345
Discount Schedule	CP1B
GTIN	785901081128
Returnability	Yes
Country of origin	CN

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.70 in (6.858 cm)	
Package 1 Width	3.80 in (9.652 cm)	
Package 1 Length	4.30 in (10.922 cm)	
Package 1 Weight	25.440 oz (721.212 g)	
Unit Type of Package 2	CAR	
Number of Units in Package 2	8	
Package 2 Height	8.20 in (20.828 cm)	
Package 2 Width	5.90 in (14.986 cm)	
Package 2 Length	9.00 in (22.86 cm)	
Package 2 Weight	13.060 lb(US) (5.924 kg)	

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better


Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions

Use Again

○ Repack and remanufacture		
Take-back	No	

Dimensions Drawings

Approximate Dimensions



Technical Illustration

Wiring diagram

