## 24-Inch Panel Ready Dishwasher





**DDW24G9000AP/DA** - Panel Ready





## Features & Benefits

- Kitchen Fit Sliding Door hinge system for a seamless design
- Storm Wash+  $^{\scriptscriptstyle\mathsf{TM}}$  with Built-In Water Softener & AutoRelease  $^{\scriptscriptstyle\mathsf{TM}}$
- 9 programs + 8 options with downloadable programs
- Adjustable racks and tines for flexible loading (14 pace settings)
- · 40 dBa for library-level quiet
- · SmartThings Wi-Fi connectivity with AI Energy mode
- · Visual floor light
- Electronic control panel
- · ENERGY STAR Most Efficient
- · ADA Certified

Controls	
CONTROL TYPE	Hidden Touch
WI-FI + SMARTTHINGS	Yes
Features	
CAPACITY (PLACE SETTING)	14
TUB MATERIAL	Stainless Steel
NOISE LEVEL (DBA)	40
CUTLERY BASKET	Yes
THIRD RACK	Yes

Dishwasher	
MAXIMUM DOOR PANEL WEIGHT (KG)	4.5 - 12
SABBATH MODE	Yes
WATER CONSUMPTION	3.2 gallons/ cycle
WATER SOFTNER	Yes
TUB LIGHT	Yes
FLOOR INFO LIGHT	Yes
STORM WASH+	Yes
TOTAL PROGRAMS	9
PROGRAMS	Normal, Heavy, Auto, Delicate, Preblast, Express 60', Self Clean, Plastic, Download
TOTAL OPTIONS	8
OPTIONS	StormWash+, Lower Rack (Half Load), Sanitize, Smart Control, Delayed Start, AI Energy Saving, Auto Open, Sabbath Mode
AUTORELEASE™ DRYING	Yes
HEATER	Hidden
END-OF-CYCLE INDICATOR	Yes
LEAKAGE SENSOR	Yes
CANCEL AND DRAIN	Yes
Weights & Dimensions	
NET WEIGHT (LB)	94.8
SHIPPING WEIGHT (LB)	103.6
PRODUCT DIMENSIONS (W x H x D IN INCHES)	23 3/8 x 32 1/8 to 35 1/8 x 22 3/4
CUTOUT DIMENSIONS (W X H IN INCHES)	35 ¼ x 23 5/8 to 23 7/8 x 32 ½
Technical Details	
ELECTRICAL REQUIREMENTS	120V, 60 Hz, 15A
Warranty	
FULL COVERAGE	2 Years
Accessories (Optional)	
DW-T24PNASR	Panel Kit, Silver Stainless
DW-T24PNAMS	Panel Kit, Graphite Stainless

## 24-Inch Panel Ready Dishwasher



Product Dimensions		
A - (IN/MM)	28 ¾ to 29 % / 730 to 760	
B - (IN/MM)	<sup>11</sup> % to % / 18 to 22 Recommend <sup>13</sup> % / 20	
C - (IN/MM)	21 ¾ / 552	
D - (IN/MM)	23 ¾ / 595	
E - (IN/MM)	32 1/8 / 815	
F - (IN/MM)	Total Height 32 ½ to 33 ½ / 815 to 860 (Without Sub Foot) 33 ½ to 35 ½ / 860 to 895 (With Sub Foot)	
G - (IN/MM)	23 3/8 / 594	
H - (IN/MM)	2 ½ to 5 ½ / 55 to 130 (Without Sub Foot) 3 ½ to 6 ½ / 100 to 165 (With Sub Foot)	
I - (IN/MM)	3 ½ / 90	
J - (IN/MM)	Leg Height 0 to 1 ¾ / 0 to 45 (Without Sub Foot) 1 ¾ to 3 ½ / 45 to 80 (With Sub Foot)	
K - (IN/MM)	2 / 50	
L - (IN/MM)	4 % / 125	
M - (IN/MM)	23 % to 23 % / 600 to 608	
N - (IN/MM)	22 % / 575	
O - (IN/MM)	32 ¼ to 35 ¼ / 820 to 895	
P - (IN/MM)	3 % / 100	
Q - (IN/MM)	2 / 50	
	· · · · · · · · · · · · · · · · · · ·	



