



ADJUST-A-BALL CLAMP POST

- WARNING** This indication alerts you to the fact that ignoring the contents described herein can result in potential serious injury or death if not followed.
- CAUTION** This indication alerts you to the fact that ignoring the contents described herein can or will result in material damage and/or personal injury.
- ATTENTION** This indication alerts you to the fact that if you ignore this detail you will affect the performance or functionality of the product.

All Ciro products are designed for "easy assembly" and/or "plug and play". We recommend a competent mechanic install our products, using standard mechanical procedures to assure a safe and successful installation. Read completely and understand the instructions prior to starting installation.

NOTE: Ciro products are designed and manufactured under very strict quality control. Ciro warrants that products sold to the original purchaser shall be free from any defects in materials and workmanship for a period of 3 (three) years from the date of purchase, and a limited lifetime warranty against LED failure. Ciro will have no obligation if the customer cannot show proof of purchase. Warranty will not be granted unless the part is properly installed, unmodified and maintained. Ciro will not be liable for any consequential and incidental damages, including labor, or non-Ciro products. Please visit Ciro3d.com for our complete warranty policy.

Included Items:



Installation Instructions:

1. Park on a level surface and shut off motorcycle. Ensure engine has time to cool before installing.
2. Remove existing post from clamp mount, (customer supplied). You will reuse the existing screw and washer to mount the new base.
3. Mount the base to your perch mount with the existing screw and loosely tighten. The base will change rotation position.
4. Attach the stem to the base using a supplied screw and washer. Loosely tighten. The stem will change up and down position. With both slightly loose, decide on best position and tighten both screws securely.
5. The cap will determine the rotation your accessory will have. To change the tilt, remove accessory and loosen the cap screw and rotate and retighten.

NOTE: For detailed instructions for installing Ciro accessories, see instructions included with the product.

