



Art.no. 308031-402
EAN 7320047559341



Efficient robust downlight with several luminous fluxes.

- Installation** Luminaire for ceiling installation. Ceiling bracket with bayonet fitting on 2 levels. Connection from above or via a surface-mounted cable in 3 possible directions.
- Connection** Terminal block 3x2.5 mm² or 5x2.5 mm² when dimming. Integrated driver for flexible installation. Onward connection possible.
- Design** Luminaire body and reflector ring of cast aluminium. Glass of PMMA.
- Reflector** Reflector of matt anodised aluminium.
- Light distribution** Asymmetrical.
- Standard colour** Anthracite grey (Gris 900 Sablé).
- Miscellaneous** CLO (Constant Light Output) ensures the luminaire provides the same amount of light for the duration of its rated-life.

Rondo G3 surface mounted Wallwasher

Asymmetrical, Surface mounted, DALI, Matt

DESIGN

Colour Anthracite grey	Reflector Matt
Weight, kg 3.4	Height, mm 189
Diameter, mm 193	

TECHNICAL DATA

Installation Surface mounted	Protective class 1
IK rating 08	IP rating 66
Min. ambient temperature, °C -40	Max. ambient temperature, °C 25
Light control DALI	Brand of driver Philips

ELECTRICAL DATA

MCB B10A 18	MCB B16A 30
MCB C10A 31	MCB C16A 51
AM Yes	Power on last level Yes
Stand by W 0.5	Rated supply voltage, V 220-240
Mains frequency, Hz 0, 50, 60	Start W 32
Average W 34.5	End W 35
Power factor, 100 % 0.99	Surge protection CM, kV/kA 10
Surge protection DM, kV/kA 6	THD, % 8
Current leakage 0.200	SVM 0.070
PstLm 0.040	

LIGHTING DATA

Energy class, LED module E	Light distribution Asymmetrical
Lumen output 2264	lm/W 72
Lumen maintenance L100 B50, h 100 000	Lumen maintenance 100 000 h L100
Lumen maintenance at 50 000 h 1	LED driver, h/max failure % 100000/10
CLO function on Yes	CLO time, h 100 000
SDCM 3	CRI 80
CCT, K 3000	DALI generation dali-2