cisco Meraki

Meraki Go GX50 Datasheet

Meraki Go Router Firewall Plus

GX50

Performance

- Firewall Throughput 500+ Mbp/s
- Client VPN Throughput 300 Mbps
- VPN Tunnels 50
- · Recommended for 50 clients

Interfaces

- WAN Interface: 1x 10/100/1000 BASE-T Ethernet (RJ45)
- LAN interfaces: 4x 10/100/1000 BASE-T Ethernet (RJ45)

Network and Security Services

- · Stateful firewall
- · Port Forwarding
- · DHCP services
- DNS based security powered by Cisco Umbrella (additional subscription required)
- Client VPN
- Site-to-Site VPN (GX50 to GX50 only)

Environment

- Operating temperature: 32 °F to 113 °F (0 °C to 45 °C)
- · Humidity: 5 to 95% non-condensing
- · Kensington lock hard point

Power

Power Load

18W DC Power Supply Included	5 Watts idle 14 Watts max
Physical Dimensions • 1.1 x 5.1 x 9.4 in / 27 x 130 x 239 mm, not including deskmount feet or mount plate	 Warranty 1 year hardware warranty (US and Japan) 2 year hardware warranty (UK and EU)
Weight • 1.74 lb / 0.79 kg	LED Indicators
In the Box GX50-HW: Meraki Go Security Gateway Wall mount and screw kit Quick start guide PSU and ethernet cable	Model List / Accessories GX50-HW-XX Security Gateway - Desktop GA-PWR-50WAC 50W Replacement Laptop Style Adapter for GX50 XX = US/UK/EU

Cisco Systems, Inc. | 500 Terry A. Francois Blvd, San Francisco, CA 94158 | (415) 432-1000 | help@meraki-go.com