



Simplify and Strengthen Your Security

Security Solution Guide



Simplify and strengthen your security

How safe is your network?

In today’s digital landscape, cyber threats are evolving at an alarming rate. With over 8 billion data breaches reported in 2023* alone, the need for robust network security has never been more critical. Cybercriminals continuously refine their tactics, targeting vulnerabilities in both traditional IT infrastructure and cloud-based systems. The surge in remote work and increased reliance on digital services have exposed businesses of all sizes to unprecedented risks. Small and medium-sized businesses (SMBs) are particularly vulnerable, often lacking the resources to effectively counter these sophisticated threats. It’s crucial to implement a security solution that not only addresses current risks but also adapts to emerging threats efficiently and cost-effectively.














*Source: <https://www.itgovernance.co.uk/blog/list-of-data-breaches-and-cyber-attacks-in-2023>

Effective and scalable protection

Zyxel believes it’s really important to make protecting the network as simple as possible, and it’s why we’ve been developing a new range of unified security gateways that provide all the protection that small businesses need, without the complexity. By deploying one of our firewall appliances at the bridge between your network and the internet, you can safeguard against threats such as viruses and ID theft, repel spam emails, and apply simple rules that will govern what sort of content can be sent across the connection. The new USG LITE 60AX gives you firewall protection and automatic security for your whole setup without the need for a licensing fee.



Find the ideal appliance for your business

	Ultimate H	Ultimate	Flexibility	Effortless
Users	USG FLEX H	ATP	USG FLEX	USG LITE
Up to 500				
Up to 350	USG FLEX 700H			
Up to 150				
Up to 50				
Up to 25	USG FLEX 200H USG FLEX 200HP	ATP200	USG FLEX 200	
Up to 10				
Up to 5	USG FLEX 100H USG FLEX 100HP	ATP100	USG FLEX 100 USG FLEX 100AX	
				
	USG FLEX 50H USG FLEX 50HP		USG FLEX 50 USG FLEX 50AX	
				
				USG LITE 60AX SCR 50AXE

Zyxel security solutions

USG FLEX H Firewalls

The high-performance USG FLEX H series provides 3x firewall/UTM/VPN throughput and PoE+ interfaces to prepare for the multi-G era. It offers multi-layered protection against cyber threats through Zyxel AI cloud and extends the same security to remote networks with enhanced SecuExtender. Get enterprise-grade security at lightning speed for your small or mid-sized business.

USG FLEX Firewalls

The USG FLEX series provides cloud-based management and collaborative protection for small and mid-sized businesses. It offers powerful UTM performance with automatic responses to expand protection from firewalls to access points, all while minimizing computing power usage.

ATP Firewalls

The ZyWALL ATP Firewall Series is empowered with smart cloud intelligence giving seamless protection against all those Advanced Persistent Threats, achieving ultimate in-depth defense of future unknown attacks.

Security Router

The USG LITE series is a secure cloud-managed router that offers business-class firewall, VPN gateway, blazingly fast WiFi, and built-in security to safeguard against ransomware and other threats. It's a perfect solution for teleworkers or small businesses/offices looking for easy-to-manage and subscription-free network security.






Security services and licenses






Find the perfect licensing option for your security devices with our flexible options tailored to meet your business needs. Our security licenses cover a range of solutions, including security, connectivity, management, reporting, and vertical-specific licenses. With our expert guidance and support, you can rest assured that your business is fully protected from all potential security threats, now and in the future.

Security services and licenses

For purchase/renewal of licenses, go directly on our new e-commerce platform Zyxel Marketplace or contact our reseller.

Services	Key Features
Security Service	
Anti-Virus/Malware	Scan files for viruses, Trojan, worms, malwares before they reach your network. <ul style="list-style-type: none">Stream-based scan technology without file size limitationDaily data feed of top-ranked threats
Anti-Spam/Email Security	Fast detect with cloud-based database/mail fingerprints to block spam/phishing mail with malicious contents <ul style="list-style-type: none">IP reputation filter provides low latency reactionSupport black/white listing for custom policiesCloud-based database provide real-time protection
Web Filtering	Cloud-based real-time access control for inappropriate, unproductive, illegal and malicious websites <ul style="list-style-type: none">Categorized website access management for increased efficiencyGranular policies controlled by IP address, user, group, or schedule
IPS	Deep-packet inspection across all ports and protocols at gateway to against known attacks from network <ul style="list-style-type: none">Shields vulnerabilities before they can be exploited and eliminates the operational pains of emergency patchingCustomized signature support to create your own rulesConstant signature auto-updates
Application Patrol	Automatically categorize and manage the network applications usage <ul style="list-style-type: none">Granular policies control by IP address, user, group, scheduleProfile based policy to ensure network quality and easy manage business rule
Geo Enforcer	Manage network traffic by mapping IP address to geographical regions to prevent fraud or cyber attacks <ul style="list-style-type: none">Geographical visibility for traffic statistics and logsIPv6 address supportAutomatic IP/geography database update

Services	Key Features
Security Service	
Sandboxing 	Cloud-based sandbox technology against unknown threats <ul style="list-style-type: none"> • Comprehensive inspection for a wide range file types • Cloud-based sandbox provide instant protection without needing a dedicated hardware or software upgrade
Reputation Filter 	Block botnet infection and prevent drive-by download from infected websites <ul style="list-style-type: none"> • IP/URL feeds to detect/block botnet commands and control activities • Cloud-based URL feeds to block access to anomalous websites • IP-based reputation filter • Supports 10 Cyber Threat Categories • Inbound & Outbound traffic filtering • Blacklist and whitelist support
Secure WiFi 	<ul style="list-style-type: none"> • Secure tunnel and managed AP service • L2 access between home and office network • Enforcing 2FA with Google Authenticator • WPA2 Enterprise (802.1x) supported
Cloud Security Service	
Astra 	<ul style="list-style-type: none"> • Cloud-based service and email protection for Office 365, G Suite and on-premise e-mail • Stop unwanted spam, phishing and malware with real-time threat intelligence • No change to your existing infrastructure, zero maintenance • Reduce management overhead and stop wasting IT admin resources • Respond faster with web management and monitoring
Vertical Solutions	
Hotspot Management 	<ul style="list-style-type: none"> • Authentication with Wall Garden • Advertisement and SMS billing & free time service accounting for guest • Support SP350E printer manager support purple WiFi and third-party social log in • Billing replenishment

Services	Key Features
Vertical Solutions	
Managed AP Service 	<ul style="list-style-type: none"> • Integrated AP controller as central management to provide flexible deployment options • AP auto discovery and provisioning • AP forwarding compatibility
Device High Availability Pro 	<ul style="list-style-type: none"> • Device failure detection and notification • Configuration auto-sync and link monitoring • Smart handover through dedicated Heartbeat Link • NAT/Firewall/VPN Sessions synchronization
VPN Client Software	
SecuExtender VPN Client 	<ul style="list-style-type: none"> • Secure and reliable remote access, preserving business operations and data integrity • Supports both IPSec/SSL VPN and secure authentication methods • Simple to deploy with remote VPN wizard (IKEv2 preferred) • Runs on both Windows and macOS operating systems
Network Premium	
Single Sign-On 	<ul style="list-style-type: none"> • Simplified single sign in to multiple resources • Improved user experience without repetitive logging in between various web browsers • Login mechanism works with any protocol, not just HTTP
Management & Reporting	
Cloud CNM SecuReporter 	<ul style="list-style-type: none"> • Multidimensional analytics on abnormal behaviors • SecuPilot AI-powered insights for unmatched network visibility • Cloud-based real-time monitoring and alerts • Effective event correlation and user behavior analytics • Intuitive dashboard and customizable report















Pick a bundle.

No more hassle

License by bundle

A bundle license consists of multiple services that are grouped together. They are designed for your best convenience when you need to ensure your network is

empowered with holistic functionality such as seamless threat protection or full connectivity features. Pick the right bundle and experience less hassle.

		Security										Connectivity			
Pack	Firewall Series	Licensed Service										Licensed Service			
		Anti-Malware/ Virus	Web Filtering/ Content Filtering	Sandboxing	Reputation Filter	IPS/IDP	Application Patrol	Email Security/ Anti-Spam	SecuReporter	Security Profile Sync	Collaborative Detection & Response	Ransomware Prevention Premium	Network Premium	Secure WiFi	Nebula Professional Pack
															
		Scan files at the gateway for viruses and other threats	Block access to malicious or risky web sites	Cloud-based sandbox technology against unknown threats	Block botnet infection and prevent drive-by download from infected websites via IP and URL detection	Deep-packet inspection against known attacks from network	Automatically categorize and manage the network application usage	Fast detection to block spam/phishing mail with malicious contents	Cloud-based security analytics and report with 30-day log retention	An easy-to-use tool to help business sync up security profiles across multiple networks	Automatically contain threats at the network edge	Real-time updated threat intelligence	Simplified single sign in to multiple resources	Secure tunnel and managed AP service	A full feature set of cloud configuration, deployment, moniing and management
Gold Security Pack	USG FLEX H*2	●	●	●	●	●	●	●	●	●	●		●	●	●
	ATP	●	●	●	●	●	●	●	●	●	●		●	●	●
	USG FLEX*1	●	●	●	●	●	●	●	●	●	●		●	●	●
UTM Security Pack	USG FLEX*1	●	●			●	●	●	●	●	●		●		
Entry Defense Pack	USG FLEX H				●				●						●*3 (Priority Support Only)
Content Filter Pack	USG FLEX 50(AX)		●						●	●			●		
	USG20(W)-VPN		●						●	●			●		
Elite Pack	USG LITE SCR		●									●			●












*1: USG FLEX 50(AX) is not supported for Gold and UTM Security Pack

*2: Network Premium, Collaborative Detection & Response, and Secure WiFi for USG FLEX H series will be available later and are subject to changes without notice.

*3: Priority Support is available to customers with a Pro Pack organization or those using USG FLEX H series firewalls with Gold Security Pack or Entry Defense Pack licenses. Eligible customers can open support tickets for prioritized assistance.


















Licensed service by model

Security

Compatible Security Appliances	Licensed Service										
	Web Filtering/ Content Filtering	Application Patrol	Anti-Malware/Virus	IPS/IDP	Email Security/ Anti-Spam	Security Profile Sync	Collaborative Detection & Response	SecuReporter	Sandboxing	Reputation Filter	SecuExtender VPN Client
											
	Block access to malicious or risky web sites	Automatically categorize and manage the network application usage	Scan files at the gateway for viruses and other threats	Deep-packet inspection against known attacks from network	Fast detection to block spam/phishing mail with malicious contents	An easy-to-use tool to help business sync up security profiles across multiple networks	Automatically contain threats at the network edge	Cloud-based security analytics and report with 30-day log retention	Cloud-based sandbox technology against unknown threats	Block botnet infection and prevent drive-by download from infected websites via IP and URL detection	SSL VPN and IPSec VPN remote access tool
USG FLEX 50H/100H/200H/500H/700H*	•	•	•	•	•	•		•	•	•	•
ATP100(W)/200	•	•	•	•	•	•	•	•	•	•	•
ATP500/700/800	•	•	•	•	•	•	•	•	•	•	•
USG FLEX 50(AX)	•					•		•			•
USG FLEX 100(AX/W)	•	•	•	•	•	•	•	•	•	•	•
USG FLEX 200	•	•	•	•	•	•	•	•	•	•	•
USG FLEX 500/700	•	•	•	•	•	•	•	•	•	•	•
USG LITE 60AX	•	•									
SCR 50AXE	•	•									

*: Network Premium, Security Profile Sync, Collaborative Detection & Response, and Secure WiFi for USG FLEX H series will be available later and are subject to changes without notice.

Connectivity

Compatible Security Appliances	Licensed Service						Licensed Service										
	Secure WiFi	Network Premium	Hotspot Management	Concurrent Device Upgrade	Nebula Professional Pack	Nebula Plus Pack	Amazon VPC	Microsoft Azure	Managed AP Service	Two-Factor Authentication	Threat Management	Geo Enforcer	SSL (HTTPS) Inspection	Device Insight	Device High Availability Pro	Zyxel One Network	Nebula Base Pack
																	
	Secure tunnel and managed AP service	Simplified single sign in to multiple resources	Various Network Access Control	Top up allowed number of connected clients	A full feature set of cloud configuration, deployment, monitoring and management	A new feature set includes the most frequently requested advanced features	Easy network integration with AWS	Easy network integration with Azure	AP auto discovery and provisioning	Add an extra layer of protection to mitigate the risk of credential leakage or brute force attack	Prevent ransomware, intrusion, exploit, dark web, ads, VPN proxy and mail fraud & phishing	Manage network traffic by mapping IP address to geographical regions	Unlock encrypted sessions, scan encrypted packets, find threats, and block them	Deploy agentless scanning of the network for discovery and classification of devices	Device failure detection and failover	A Unified installation tool for Zyxel switches, WLAN and gateways	License-free feature set with a rich set of management features
USG FLEX 50H/100H/200H/500H/700H*					•	•				•		•	•	•	•		•
ATP100(W)/200	•	•			•		•	•	•	•		•	•	•		•	
ATP500/700/800	•	•			•		•	•	•	•		•	•	•	•	•	
USG FLEX 50(AX)		•			•	•	•	•	•	•		•		•		•	•
USG FLEX 100(AX/W)	•	•			•	•	•	•	•	•		•	•	•		•	•
USG FLEX 200	•	•	•		•	•	•	•	•	•		•	•	•		•	•
USG FLEX 500/700	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•
USG LITE 60AX					•						•	•					
SCR 50AXE					•						•	•					

*: Network Premium, Security Profile Sync, Collaborative Detection & Response, and Secure WiFi for USG FLEX H series will be available later and are subject to changes without notice.

Specifications

ZyWALL USG FLEX H Firewalls

Model		USG FLEX 50H/50HP	USG FLEX 100H/100HP	USG FLEX 200H/200HP
Hardware Specifications				
Network interfaces	100M/1G Ethernet (RJ-45)	5	8	6
	100M/1G/2.5G Ethernet (RJ-45)	-	-	2
	1G/2.5G/5G/10G Ethernet (RJ-45)	-	-	-
	1G SFP/10G SFP+	-	-	-
	IEEE 802.3at (PoE+) Port	Port 5 (50HP only)	Port 8 (100HP only)	Port 2 (2.5G, 200HP only)
Total PoE budget (watts)		30	30	30
USB 3.0 Type-A		1	1	1
Console port		Yes (RJ-45)	Yes (RJ-45)	Yes (RJ-45)
Rack-mountable		-	-	Yes
Fanless		Yes	Yes	Yes
System Capacity & Performance ^{*1}				
SPI firewall throughput (Mbps) ^{*2}		2,000	4,000	6,500
VPN throughput (Mbps) ^{*3}		500	900	1,200
IPS throughput (Mbps) ^{*4}		1,000	1,500	2,500
Anti-Malware throughput (Mbps) ^{*4}		600	1,000	1,800
UTM throughput (Anti-Malware and IPS) ^{*4}		600	1,000	1,800
Max. TCP concurrent sessions ^{*5}		100,000	300,000	600,000
Max. concurrent IPsec VPN tunnels ^{*6}		20	50	100
Recommended gateway-to-gateway IPsec VPN tunnels		5	20	50
Concurrent SSL VPN users		15	25	50
VLAN interface		8	16	32
Key Features				
Security Service ^{*7}	Anti-Malware	Yes	Yes	Yes
	IPS	Yes	Yes	Yes
	Application Patrol	Yes	Yes	Yes
	Web Filtering	Yes	Yes	Yes
	Reputation Filter	Yes	Yes	Yes
	SecuReporter	Yes	Yes	Yes
	Sandboxing	Yes	Yes	Yes
	Security Profile Sync	Yes	Yes	Yes
	Device Insign	Yes	Yes	Yes
	Security WiFi ^{*8}	Yes	Yes	Yes
	SSL (HTTPS) Inspection	Yes	Yes	Yes
	Two-Factor Authentication	Yes	Yes	Yes
	VPN	IKEv2/IPSec, SSL	IKEv2/IPSec, SSL	IKEv2/IPSec, SSL
VPN, Management & Connectivity	Nebula Centralized Management	Yes	Yes	Yes
	Device HA	-	-	Yes
Power Requirements				
Power input		50H: 12V D 50HP: 19V DC,3.42 A	100H: 12V DC, 2A 100HP: 19V DC,3.42A	200H: 12V DC, 2A 200HP: 19V DC,3.42A
Max. power consumption (Watt Max.)		50H: 8.86 50HP: 48.65	100H: 17 100HP: 51.2	200H: 22 200HP: 62
Heat dissipation (BTU/hr)		50H: 32.42 50HP: 175.73	100H: 40.365 100HP: 194.5	200H: 58.75 200HP: 191.9
Physical Specifications				
Item	Dimensions (WxDxH)(mm/in.)	216 x 143 x 33/8.50 x 5.63 x 1.30	216 x 143 x 33/8.50 x 5.63 x 1.30	272 x 185 x 36/10.7 x 7.30 x 1.42
	Weight (kg/lb.)	50H: 1.02/ 2.26 50HP: 1.04/ 2.31	100H: 1.04/2.30 100HP:1.05/2.31	200H: 1.50/3.31 200HP: 1.52/3.35
Packing	Dimensions (WxDxH)(mm/in.)	278 x 189 x 99/10.94 x 7.44 x 3.89	278 x 189 x 99/10.94 x 7.44 x 3.89	427 x 247 x 73/16.81 x 9.72 x 2.87
	Weight (kg/lb.)	50H: 1.27/2.80 50HP: 1.55/3.41	100H: 1.62/3.57 100HP: 1.91/4.21	200H: 2.43/5.36 200HP: 2.68/5.92
Included accessories		• Power adapter • Power cord (50HP only) • RJ-45 - RS-232 cable for console connection	• Power adapter • Power cord (100HP only) • RJ-45 - RS-232 cable for console connection	• Power adapter • Power cord (200HP only) • RJ-45 - RS-232 cable for console connection • Rack mounting kit (optional, by regions)
Environmental Specifications				
Operating	Temperature	0°C to 40°C/32°F to 104°F	0°C to 40°C/32°F to 104°F	0°C to 40°C/32°F to 104°F
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)	10% to 90% (non-condensing)
Storage	Temperature	-30°C to 70°C/-22°F to 158°F	-30°C to 70°C/-22°F to 158°F	-30°C to 70°C/-22°F to 158°F
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)	10% to 90% (non-condensing)
MTBF (hr)		50H: 40°C/ 596100.85308 hr 25°C/ 945046.81927 hr 50HP: 40°C/ 402515.716 hr 25°C/ 665839.12962 hr	100H: 40°C/ 353878.1057 hr 25°C/ 602150.9604 hr 100HP: 40°C/ 289845.2327 hr 25°C/ 518347.4294 hr	200H: 40°C/ 306768.409 hr 25°C/ 528037.0106 hr 200HP: 40°C/ 227747.9662 hr 25°C/ 392638.3847 hr
Acoustic noise		-	-	-
Certifications				
EMC		FCC Part 15 (Class B), CE EMC (Class B), RCM (Class B), BSMI	FCC Part 15 (Class B), CE EMC (Class B), RCM (Class B), BSMI	FCC Part 15 (Class B), CE EMC (Class B), RCM (Class B), BSMI
Safety		LVD (EN62368-1), BSMI	LVD (EN62368-1), BSMI	LVD (EN62368-1), BSMI

*: This matrix with firmware uOS110 or later.

*1: Actual performance may vary depending on system configuration, network conditions, and activated applications.
*2: Maximum throughput based on RFC 2544 (1,518-byte UDP packets).
*3: VPN throughput measurement are based on RFC 2544 (1,424-byte UDP packets); IMIX: UDP throughput based on a combination of 64 byte, 512 byte, and 1424 byte packet sizes.

*4: Anti-Malware (with Express Mode) and IPS throughput is measured using the industry standard HTTP performance test (1,460-byte HTTP packets). Testing done with multiple flows.
*5: Maximum sessions are measured using the industry standard iXIA IxLoad testing tool.
*6: Including Gateway-to-Gateway and Client-to-Gateway.
*7: With Zyxel service license to enable or extend the feature capacity.
*8: Available in Q2, 2024.

ZyWALL USG FLEX H Firewalls

Model		USG FLEX 500H	USG FLEX 700H
Hardware Specifications			
Network interfaces	100M/1G Ethernet (RJ-45)	8	8
	100M/1G/2.5G Ethernet (RJ-45)	4	2
	1G/2.5G/5G/10G Ethernet (RJ-45)	-	2
	1G SFP/10G SFP+	-	2
	IEEE 802.3at (PoE+) Port	Port 3, 4 (2.5G)	Port 3, 4 (10G)
Total PoE budget (watts)		30	30
USB 3.0 Type-A		1	1
Console port		Yes (RJ-45)	Yes (RJ-45)
Rack-mountable		Yes	Yes
Fanless		-	-
System Capacity & Performance ^{*1}			
SPI firewall throughput (Mbps) ^{*2}		10,000	15,000
VPN throughput (Mbps) ^{*3}		2,000	3,000
IPS throughput (Mbps) ^{*4}		4,500	7,000
Anti-Malware throughput (Mbps) ^{*4}		3,000	4,000
UTM throughput (Anti-Malware and IPS) ^{*4}		3,000	4,000
Max. TCP concurrent sessions ^{*5}		1,000,000	2,000,000
Max. concurrent IPsec VPN tunnels ^{*6}		300	1,000
Recommended gateway-to-gateway IPsec VPN tunnels		150	300
Concurrent SSL VPN users		150	500
VLAN interface		64	128
Key Features			
Security Service ^{*7}	Anti-Malware	Yes	Yes
	IPS	Yes	Yes
	Application Patrol	Yes	Yes
	Web Filtering	Yes	Yes
	Reputation Filter	Yes	Yes
	SecuReporter	Yes	Yes
	Sandboxing	Yes	Yes
	Security Profile Sync	Yes	Yes
	Device Insign	Yes	Yes
	Security WiFi ^{*8}	Yes	Yes
	SSL (HTTPS) Inspection	Yes	Yes
	Two-Factor Authentication	Yes	Yes
	VPN	IKEv2/IPSec, SSL	IKEv2/IPSec, SSL
VPN, Management & Connectivity	Nebula Centralized Management	Yes	Yes
	Device HA	Yes	Yes
Power Requirements			
Power input		19V DC, 4.736A	100-240V AC, 50/60Hz, 2A
Max. power consumption (Watt Max.)		68	86.7
Heat dissipation (BTU/hr)		211.3	235
Physical Specifications			
Item	Dimensions (WxDxH)(mm/in.)	300 x182 x 43.5/11.81 x 7.17 x 1.71	430 x 250 x 43.5/16.93 x 9.84 x 1.71
	Weight (Kg/lb.)	1.64/3.62	3.14/6.93
Packing	Dimensions (WxDxH)(mm/in.)	350 x 149 x 244/13.78 x 5.87 x 9.61	512 x 395 x 162/20.16 x 15.55 x 6.38
	Weight (kg/lb.)	2.93/6.46	4.90/10.81
Included accessories		• Power cord • RJ-45 to RS-232 cable for console connection • Rack mounting kit	• Power cord • RJ-45 to RS-232 cable for console connection • Rack mounting kit
Environmental Specifications			
Operating	Temperature	0°C to 40°C/32°F to 104°F	0°C to 40°C/32°F to 104°F
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)
Storage	Temperature	-30°C to 70°C/-22°F to 158°F	-30°C to 70°C/-22°F to 158°F
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)
MTBF (hr)		40°C/ 346653.298 hr 25°C/ 491775.8384 hr	40°C/ 431877.9743 hr 25°C/ 669031.2966 hr
Acoustic noise		16.86dBA on < 25degC Operating Temperature, 43.76dBA on full FAN speed	16.86dBA on < 25degC Operating Temperature, 43.76dBA on full FAN speed
Certifications			
EMC		FCC Part 15 (Class A), CE EMC (Class A), RCM (Class A), BSMI	FCC Part 15 (Class A), CE EMC (Class A), RCM (Class A), BSMI
Safety		LVD (EN62368-1), BSMI	LVD (EN62368-1), BSMI

*: This matrix with firmware uOS110 or later.

*1: Actual performance may vary depending on system configuration, network conditions, and activated applications.
*2: Maximum throughput based on RFC 2544 (1,518-byte UDP packets).
*3: VPN throughput measurement are based on RFC 2544 (1,424-byte UDP packets); IMIX: UDP throughput based on a combination of 64 byte, 512 byte, and 1424 byte packet sizes.

*4: Anti-Malware (with Express Mode) and IPS throughput is measured using the industry standard HTTP performance test (1,460-byte HTTP packets). Testing done with multiple flows.
*5: Maximum sessions are measured using the industry standard iXIA IxLoad testing tool.
*6: Including Gateway-to-Gateway and Client-to-Gateway.
*7: With Zyxel service license to enable or extend the feature capacity.
*8: Available in Q2, 2024.

ZyWALL ATP Firewalls

Model		ZyWALL ATP100*9	ZyWALL ATP100W	ZyWALL ATP200
Hardware Specifications				
Interfaces		3 x LAN/DMZ, 1 x WAN, 1 x SFP, 1 x OPT	3 x LAN/DMZ, 1 x WAN, 1 x SFP, 1 x OPT	4 x LAN/DMZ, 2 x WAN, 1 x SFP
USB 3.0 ports		1	1	2
Console port		Yes (RJ-45)	Yes (RJ-45)	Yes (DB9)
Rack-mountable		-	-	Yes
Fanless		Yes	Yes	Yes
System Capacity & Performance*1				
SPI firewall throughput (Mbps)*2		1,000	1,000	2,000
VPN throughput (Mbps)*3		300	300	500
IDP throughput (Mbps)*4		600	600	1,200
AV throughput (Mbps)*4		380	380	630
UTM throughput (AV and IDP)*4		380	380	630
Max. TCP concurrent sessions*5		300,000	300,000	600,000
Max. concurrent IPSec VPN tunnels*6		40	40	100
VLAN interface		8	8	16
Speedtest Performance				
SPI firewall throughput (Mbps)*7		850	850	900
Key Features				
Security Service	Sandboxing*8	Yes	Yes	Yes
	Web Filtering*8	Yes	Yes	Yes
	Application Patrol*8	Yes	Yes	Yes
	Anti-Malware*8	Yes	Yes	Yes
	IPS*8	Yes	Yes	Yes
	Reputation Filter*8	Yes	Yes	Yes
	Geo Enforcer	Yes	Yes	Yes
	SecuReporter*8	Yes	Yes	Yes
	Collaborative Detection & Response*8	Yes	Yes	Yes
	Device Insight	Yes	Yes	Yes
	Security Profile Sync (SPS)*8	Yes	Yes	Yes
	SSL (HTTPS) Inspection	Yes	Yes	Yes
VPN Features	Two-Factor Authentication	Yes	Yes	Yes
	VPN	IKEv2, IPSec, L2TP/IPSec	IKEv2, IPSec, L2TP/IPSec	IKEv2, IPSec, L2TP/IPSec
	Microsoft Azure	Yes	Yes	Yes
	Amazon VPC	Yes	Yes	Yes
WLAN Management	Default Number of Managed AP	8	8	8
	Recommend Max. AP in 1 AP Group	10	10	20
	Secure WiFi Service*8	Yes	Yes	Yes
	Maximum Number of Tunnel-Mode AP	6	6	10
Management & Connectivity	Maximum Number of Managed AP	24	24	40
	Nebula Cloud Mode	Yes	Yes	Yes
	Nebula Cloud Monitoring Mode	Yes	Yes	Yes
	Device HA Pro	-	-	-
	Link Aggregation (LAG)	-	-	-
	Concurrent Devices Logins (max.)	64	64	200
Power Requirements				
Power input		12 V DC, 2 A max.	12 V DC, 2 A max.	12 V DC, 2.5 A max.
Max. power consumption (watt)		12.5	12.5	13.3
Heat dissipation (BTU/hr)		42.65	42.65	45.38
Physical Specifications				
Item	Dimensions (WxDxH)(mm/in.)	216 x 143 x 33/8.50 x 5.80 x 1.30	216 x 147.3 x 33/8.50 x 5.80 x 1.30	272 x 187 x 36/10.7 x 7.36 x 1.42
	Weight (kg/lb.)	0.85/1.87	0.85/1.87	1.4/3.09
Packing	Dimensions (WxDxH)(mm/in.)	284 x 190 x 100/11.8 x 7.48 x 3.94	284 x 190 x 100/11.8 x 7.48 x 3.94	427 x 247 x 73/16.81 x 9.72 x 2.87
	Weight (kg/lb.)	1.4/3.09	1.4/3.09	2.42/5.34
Included accessories		• Power adapter • RJ-45 cable • RS-232 cable	• Power adapter • RJ-45 cable • RS-232 cable	• Power adapter • Rack mounting kit (optional, by regions)
Environmental Specifications				
Operating	Temperature	0°C to 40°C/32°F to 104°F	0°C to 40°C/32°F to 104°F	0°C to 40°C/32°F to 104°F
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)	10% to 90% (non-condensing)
Storage	Temperature	-30°C to 70°C/-22°F to 158°F	-30°C to 70°C/-22°F to 158°F	-30°C to 70°C/-22°F to 158°F
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)	10% to 90% (non-condensing)
MTBF (hr)		989,811(at 25°C) and 576,237(at 40°C)	989,811(at 25°C) and 576,237(at 40°C)	832,102(at 25°C) and 536,472(at 40°C)
Acoustic noise		-	-	-
Certifications				
EMC		FCC Part 15 (Class B), CE EMC (Class B), BSMI	FCC Part 15 (Class B), CE EMC (Class B), BSMI	FCC Part 15 (Class B), CE (Class B), C-Tick (Class B), BSMI
Safety		LVD (EN60950-1), BSMI	LVD (EN60950-1), BSMI	LVD (EN60950-1), BSMI

*: This matrix with firmware ZLD5.37 or later.

*1: Actual performance may vary depending on network conditions and activated applications.

*2: Maximum throughput based on RFC 2544 (1,518-byte UDP packets).

*3: VPN throughput measured based on RFC 2544 (1,424-byte UDP packets).

*4: AV (with Express mode) and IDP throughput measured using the industry standard HTTP performance test (1,460-byte HTTP packets). Testing done with multiple flows.

*5: Maximum sessions measured using the industry standard IXIA IxLoad testing tool.

*6: Including Gateway-to-Gateway and Client-to-Gateway.

*7: The Speedtest result is conducted with 1 Gbps WAN link in real world and it is subject to fluctuate due to quality of the ISP link.

*8: Enable or extend feature capacity with Zyxel service license.

*9: ATP100 rev1 is adapting new hardware design equipped with 4 x LAN/DMZ, 1 x WAN.

ZyWALL ATP Firewalls

Model		ZyWALL ATP500	ZyWALL ATP700	ZyWALL ATP800
Hardware Specifications				
Interfaces		7 (configurable), 1 x SFP	12 (configurable), 2 x SFP (configurable)	12 (configurable), 2 x SFP (configurable)
USB 3.0 ports		2	2	2
Console port		Yes (DB9)	Yes (DB9)	Yes (DB9)
Rack-mountable		Yes	Yes	Yes
Fanless		-	-	-
System Capacity & Performance*1				
SPI firewall throughput (Mbps)*2		2,600	6,000	8,000
VPN throughput (Mbps)*3		900	1,200	1,500
IDP throughput (Mbps)*4		1,700	2,200	2,700
AV throughput (Mbps)*4		900	1,600	2,000
UTM throughput (AV and IDP)*4		890	1,500	1,900
Max. TCP concurrent sessions*5		1,000,000	1,600,000	2,000,000
Max. concurrent IPSec VPN tunnels*6		300	1,000	1,000
VLAN interface		64	128	128
Speedtest Performance				
SPI firewall throughput (Mbps)*7		900	930	930
Key Features				
Security Service	Sandboxing*8	Yes	Yes	Yes
	Web Filtering*8	Yes	Yes	Yes
	Application Patrol*8	Yes	Yes	Yes
	Anti-Malware*8	Yes	Yes	Yes
	IPS*8	Yes	Yes	Yes
	Reputation Filter*8	Yes	Yes	Yes
	Geo Enforcer	Yes	Yes	Yes
	SecuReporter*8	Yes	Yes	Yes
	Collaborative Detection & Response*8	Yes	Yes	Yes
	Device Insight	Yes	Yes	Yes
	Security Profile Sync (SPS)*8	Yes	Yes	Yes
	SSL (HTTPS) Inspection	Yes	Yes	Yes
VPN Features	Two-Factor Authentication	Yes	Yes	Yes
	VPN	IKEv2, IPSec, L2TP/IPSec	IKEv2, IPSec, L2TP/IPSec	IKEv2, IPSec, L2TP/IPSec
	Microsoft Azure	Yes	Yes	Yes
	Amazon VPC	Yes	Yes	Yes
WLAN Management	Default Number of Managed AP	8	8	8
	Recommend Max. AP in 1 AP Group	60	200	300
	Secure WiFi Service*8	Yes	Yes	Yes
	Maximum Number of Tunnel-Mode AP	18	66	130
Management & Connectivity	Maximum Number of Managed AP	72	264	520
	Nebula Cloud Mode	Yes	Yes	Yes
	Nebula Cloud Monitoring Mode	Yes	Yes	Yes
	Device HA Pro	Yes	Yes	Yes
	Link Aggregation (LAG)	Yes	Yes	Yes
	Concurrent Devices Logins (max.)	300	1500	1500
Power Requirements				
Power input		12 V DC, 4.17 A	100 - 240 V AC, 50/60 Hz, 2.5 A max.	100 - 240 V AC, 50/60 Hz, 2.5 A max.
Max. power consumption (watt)		24.1	46	46
Heat dissipation (BTU/hr)		82.23	120.1	120.1
Physical Specifications				
Item	Dimensions (WxDxH)(mm/in.)	300 x 188 x 44/11.81 x 7.4 x 1.73	430 x 250 x 44/16.93 x 9.84 x 1.73	430 x 250 x 44/16.93 x 9.84 x 1.73
	Weight (kg/lb.)	1.65/3.64	3.3/7.28	3.3/7.28
Packing	Dimensions (WxDxH)(mm/in.)	351 x 152 x 245/13.82 x 5.98 x 9.65	519 x 392 x 163/20.43 x 15.43 x 6.42	519 x 392 x 163/20.43 x 15.43 x 6.42
	Weight (kg/lb.)	2.83/6.24	4.8/10.58	4.8/10.58
Included accessories		• Power adapter • Power cord • Rack mounting kit	• Power cord • Rack mounting kit	• Power cord • Rack mounting kit
Environmental Specifications				
Operating	Temperature	0°C to 40°C/32°F to 104°F	0°C to 40°C/32°F to 104°F	0°C to 40°C/32°F to 104°F
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)	10% to 90% (non-condensing)
Storage	Temperature	-30°C to 70°C/-22°F to 158°F	-30°C to 70°C/-22°F to 158°F	-30°C to 70°C/-22°F to 158°F
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)	10% to 90% (non-condensing)
MTBF (hr)		937,790(at 25°C) and 529,688(at 40°C)	947,737(at 25°C) and 444,931(at 40°C)	947,737(at 25°C) and 444,931(at 40°C)
Acoustic noise		24.5 dBA on < 25°C operating temperature, 41.5 dBA on full FAN speed	25.3 dBA on < 25°C operating temperature, 46.2 dBA on full FAN speed	25.3 dBA on < 25°C operating temperature, 46.2 dBA on full FAN speed
Certifications				
EMC		FCC Part 15 (Class A), CE EMC (Class A), C-Tick (Class A), BSMI	FCC Part 15 (Class A), CE EMC (Class A), C-Tick (Class A), BSMI	FCC Part 15 (Class A), CE EMC (Class A), C-Tick (Class A), BSMI
Safety		LVD (EN60950-1), BSMI	LVD (EN60950-1), BSMI	LVD (EN60950-1), BSMI

*: This matrix with firmware ZLD5.37 or later.

*1: Actual performance may vary depending on network conditions and activated applications.

*2: Maximum throughput based on RFC 2544 (1,518-byte UDP packets).

*3: VPN throughput measured based on RFC 2544 (1,424-byte UDP packets).

*4: AV (with Express mode) and IDP throughput measured using the industry standard HTTP performance test (1,460-byte HTTP packets). Testing done with multiple flows.

*5: Maximum sessions measured using the industry standard IXIA IxLoad testing tool.

*6: Including Gateway-to-Gateway and Client-to-Gateway.

*7: The Speedtest result is conducted with 1 Gbps WAN link in real world and it is subject to fluctuate due to quality of the ISP link.

*8: Enable or extend feature capacity with Zyxel service license.

*9: ATP100 rev1 is adapting new hardware design equipped with 4 x LAN/DMZ, 1 x WAN.

ZyWALL USG FLEX Firewalls

Model		USG FLEX 50	USG FLEX 50AX
Hardware Specifications			
WiFi standard		N/A	802.11 ax/ac/n/g/b/a
10/100/1000 Mbps RJ-45 ports		4 x LAN/DMZ, 1 x WAN	4 x LAN/DMZ, 1 x WAN
USB 3.0 ports		2	2
Console port		Yes (RJ-45)	Yes (RJ-45)
Rack-mountable		N/A	N/A
Fanless		Yes	Yes
System Capacity & Performance ¹			
SPI firewall throughput (Mbps) ²		350	350
VPN throughput (Mbps)		90	90
VPN IMIX throughput (Mbps) ³		40	40
Max. TCP concurrent sessions ⁴		20,000	20,000
Max. concurrent IPsec VPN tunnels ⁵		20	20
Recommended gateway-to-gateway IPsec VPN tunnels		5	5
VLAN interface		8	8
Speedtest Performance			
SPI firewall throughput (Mbps) ⁶		320	320
Key Features			
Security Service	Web Filtering ⁷	Yes	Yes
	SecuReporter ⁷	Yes	Yes
	Two-Factor Authentication	Yes	Yes
	Device Insight	Yes	Yes
	Security Profile Synchronize ⁷	Yes	Yes
VPN Features	VPN	IKEv2, IPsec, L2TP/IPsec	IKEv2, IPsec, L2TP/IPsec
	Microsoft Azure	Yes	N/A
	Amazon VPC	Yes	Yes
Management & Connectivity	Nebula Cloud Mode	Yes	Yes
	Nebula Cloud Monitoring Mode	Yes	Yes
	Easy Mode ⁸	Yes	Yes
	Concurrent Devices Logins ⁹	64	64
Power Requirements			
Power input		12 V DC, 2.0 A max.	12 V DC, 2.5 A max.
Max. power consumption (watt max.)		12	24.3
Heat dissipation (BTU/hr)		40.92	55.37
Physical Specifications			
Item	Dimensions (WxDxH)(mm/in.)	216 x 143 x 33/8.50 x 5.63 x 1.30	216 x 149.28 x 33/8.50 x 5.88 x 1.30
	Weight (Kg/lb.)	0.88/1.94	1.00/2.20
Packing	Dimensions (WxDxH)(mm/in.)	276 x 185 x 98/10.87 x 7.28 x 3.86	276 x 185 x 98/10.87 x 7.28 x 3.86
	Weight (kg/lb.)	1.41/3.11	1.53/3.37
Included accessories		• Power adapter • RJ-45 - RS-232 cable for console connection	• Power adapter with plug • RJ-45 - RS-232 cable for console connection • Antenna
Environmental Specifications			
Operating	Temperature	0°C to 40°C/32°F to 104°F	0°C to 40°C/32°F to 104°F
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)
Storage	Temperature	-30°C to 70°C/-22°F to 158°F	-30°C to 70°C/-22°F to 158°F
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)
MTBF (hr)		1110,795(at 25°C) and 655,130(at 40°C)	766,228(at 25°C) and 426,310(at 40°C)
Certifications			
EMC		FCC Part 15 (Class B), IC, CE EMC (Class B), RCM, BSMI	FCC Part 15 (Class B), IC EMC (Class B), CE EMC (Class B), RCM (Class B), BSMI
Safety		BSMI, UL	LVD (EN62368-1), BSMI

*: This matrix with firmware ZLD5.37 or later.

*1: Actual performance may vary depending on system configuration, network conditions, and activated applications.

*2: Maximum throughput based on RFC 2544 (1,518-byte UDP packets).

*3: VPN throughput measured based on RFC 2544 (1,424-byte UDP packets); IMIX: UDP throughput based on a combination of 64 byte, 512 byte and 1424 byte packet sizes.

*4: Maximum sessions measured using the industry standard IXIA IxLoad testing tool.

*5: Including Gateway-to-Gateway and Client-to-Gateway.

*6: The Speedtest result is conducted with 1 Gbps WAN link in real world and it is subject to fluctuate due to quality of the ISP link.

*7: With Zyxel service license to enable or extend the feature capacity.

*8: Only applicable when devices are in on-premise mode.

*9: This is the recommend maximum number of concurrent logged-in devices.

ZyWALL USG FLEX Firewalls

Model		USG FLEX 100 ^{*11}	USG FLEX 100AX
Hardware Specifications			
WiFi standard		N/A	802.11 ax/ac/n/g/b/a
10/100/1000 Mbps RJ-45 ports		4 x LAN/DMZ, 1 x WAN	4 x LAN/DMZ, 1 x WAN
USB 3.0 ports		1	1
Console port		Yes (RJ-45)	Yes (RJ-45)
Rack-mountable		N/A	N/A
Fanless		Yes	Yes
System Capacity & Performance ¹			
SPI firewall throughput (Mbps) ^{*2}		900	900
VPN throughput (Mbps) ^{*3}		270	270
VPN IMIX throughput (Mbps) ^{*3}		100	100
IPS throughput (Mbps) ^{*4}		540	540
Anti-Malware throughput (Mbps) ^{*4}		360	360
UTM throughput (Anti-Malware and IPS)(Mbps) ^{*4}		360	360
Max. TCP concurrent sessions ^{*5}		300,000	300,000
Recommended gateway-to-gateway IPsec VPN tunnels		20	20
Max. concurrent IPsec VPN tunnels ^{*6}		50	50
VLAN interface		8	8
Speedtest Performance			
SPI firewall throughput (Mbps) ^{*11}		848	848
Key Features			
Security Service	Sandboxing ^{*7}	Yes	Yes
	Web Filtering ^{*7}	Yes	Yes
	Application Patrol ^{*7}	Yes	Yes
	Anti-Malware ^{*7}	Yes	Yes
	IPS ^{*7}	Yes	Yes
	Reputation Filter ^{*7}	Yes	Yes
	Geo Enforcer ^{*7}	Yes	Yes
	SecuReporter ^{*7}	Yes	Yes
	Collaborative Detection & Response ^{*7}	Yes	Yes
	Device Insight	Yes	Yes
	Security Profile Sync ^{*7}	Yes	Yes
	SSL (HTTPS) Inspection	Yes	Yes
	Two-Factor Authentication	Yes	Yes
	Email Security	Yes	Yes
VPN Features	VPN	IKEv2, IPsec, L2TP/IPsec	IKEv2, IPsec, L2TP/IPsec
	Microsoft Azure	Yes	Yes
	Amazon VPC	Yes	Yes
WLAN Management	Default Number of Managed AP	8	8
	Recommend Max. AP in 1 AP Group	10	10
	Secure WiFi Service ^{*7}	Yes	Yes
	Maximum Number of Tunnel-Mode AP	6	6
Management & Connectivity	Maximum Number of Managed AP	24	24
	Nebula Cloud Mode	Yes	Yes
	Nebula Cloud Monitoring Mode	Yes	Yes
	Device HA Pro	N/A	N/A
	Link Aggregation (LAG)	N/A	N/A
	Hotspot Management ^{*7}	N/A	N/A
	Ticket Printer Support ^{*9} /Support Q'ty (max.)	N/A	N/A
	Concurrent Devices Logins (default/max.) ^{*7*8}	64	64
Power Requirements			
Power input		12 V DC, 2 A max.	12 V DC, 2.5 A max.
Max. power consumption (watt Max.)		12.5	24.3
Heat dissipation (BTU/hr)		42.65	55.37
Physical Specifications			
Item	Dimensions (WxDxH)(mm/in.)	216 x 147.3 x 33/8.50 x 5.80 x 1.30	216 x 149.28 x 33/8.50 x 5.88 x 1.30
	Weight (Kg/lb.)	0.85/1.87	1.00/2.20
Packing	Dimensions (WxDxH)(mm/in.)	284 x 190 x 100/11.18 x 7.48 x 3.94	284 x 190 x 100/11.18 x 7.48 x 3.94
	Weight (kg/lb.)	1.40/3.09	1.53/3.37
Included accessories		• Power adapter • RJ-45 - RS-232 cable for console connection	• Power adapter with plug • RJ-45 - RS-232 cable for console connection • Antenna
Environmental Specifications			
Operating	Temperature	0°C to 40°C/32°F to 104°F	0°C to 40°C/32°F to 104°F
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)
Storage	Temperature	-30°C to 70°C/-22°F to 158°F	-30°C to 70°C/-22°F to 158°F
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)
MTBF (hr)		989,810 (at 25°C) and 576,237 (at 40°C)	766,228(at 25°C) and 426,310(at 40°C)
Certifications			
EMC		FCC Part 15 (Class B), CE EMC (Class B), BSMI	FCC Part 15 (Class B), CE EMC (Class B), C-Tick (Class B), BSMI
Safety		LVD (EN60950-1), BSMI	LVD (EN60950-1), BSMI

*: This matrix with firmware ZLD5.37 or later.

*1: Actual performance may vary depending on system configuration, network conditions, and activated applications.

*2: Maximum throughput based on RFC 2544 (1,518-byte UDP packets).

*3: VPN throughput measurement are based on RFC 2544 (1,424-byte UDP packets); IMIX: UDP throughput based on a combination of 64 byte, 512 byte, and 1424 byte packet sizes.

*4: AV (with Express Mode) and IDP throughput measured using the industry standard HTTP performance test (1,460-byte HTTP packets). Testing done with multiple flows.

*5: Maximum sessions measured using the industry standard IXIA IxLoad testing tool.

*6: Including Gateway-to-Gateway and Client-to-Gateway.

*7: With Zyxel service license to enable or extend the feature capacity.

*8: This is the recommend maximum number of concurrent logged-in devices.

*9: With Hotspot Management license support.

*10: The Speedtest result is conducted with 1 Gbps WAN link in real world and it is subject to fluctuate due to quality of the ISP link.

*11: USG FLEX 100 rev1 is adopting a new hardware design equipped with 4 x LAN/DMZ, 1x WAN.

ZyWALL USG FLEX Firewalls

Model		USG FLEX 200	USG FLEX 500	USG FLEX 700
Hardware Specifications				
10/100/1000 Mbps RJ-45 ports		4 x LAN/DMZ, 2 x WAN, 1 x SFP	7 (configurable), 1 x SFP (configurable)	12 (configurable), 2 x SFP (configurable)
USB 3.0 ports		2	2	2
Console port		Yes (DB9)	Yes (DB9)	Yes (DB9)
Rack-mountable		Yes	Yes	Yes
Fanless		Yes	N/A	N/A
System Capacity & Performance ¹				
SPI firewall throughput (Mbps) ^{*2}		1,800	2,300	5,400
VPN throughput (Mbps) ^{*3}		450	810	1,100
VPN IMIX throughput (Mbps) ^{*3}		160	240	550
IPS throughput (Mbps) ^{*4}		1,100	1,500	2,000
Anti-Malware throughput (Mbps) ^{*4}		570	800	1,450
UTM throughput (Anti-Malware and IPS)(Mbps) ^{*4}		550	800	1,350
Max. TCP concurrent sessions ^{*5}		600,000	1,000,000	1,600,000
Recommended gateway-to-gateway IPsec VPN tunnels		50	150	250
Max. concurrent IPsec VPN tunnels ^{*6}		100	300	500
VLAN interface		16	64	128
Speedtest Performance				
SPI firewall throughput (Mbps) ^{††}		931	935	934
Key Features				
Security Service	Sandboxing ^{*7}	Yes	Yes	Yes
	Web Filtering ^{*7}	Yes	Yes	Yes
	Application Patrol ^{*7}	Yes	Yes	Yes
	Anti-Malware ^{*7}	Yes	Yes	Yes
	IPS ^{*7}	Yes	Yes	Yes
	Reputation Filter ^{*7}	Yes	Yes	Yes
	Geo Enforcer ^{*7}	Yes	Yes	Yes
	SecuReporter ^{*7}	Yes	Yes	Yes
	Collaborative Detection & Response ^{*7}	Yes	Yes	Yes
	Device Insight	Yes	Yes	Yes
	Security Profile Sync ^{*7}	Yes	Yes	Yes
	SSL (HTTPS) Inspection	Yes	Yes	Yes
	Two-Factor Authentication	Yes	Yes	Yes
	Email Security	Yes	Yes	Yes
VPN Features	VPN	IKEv2, IPsec, L2TP/IPsec	IKEv2, IPsec, L2TP/IPsec	IKEv2, IPsec, L2TP/IPsec
	Microsoft Azure	Yes	N/A	N/A
	Amazon VPC	Yes	Yes	Yes
WLAN Management	Default Number of Managed AP	8	8	8
	Recommend Max. AP in 1 AP Group	20	60	200
	Secure WiFi Service ^{*7}	Yes	Yes	Yes
	Maximum Number of Tunnel-Mode AP	10	18	130
	Maximum Number of Managed AP	40	72	520
Management & Connectivity	Nebula Cloud Mode	Yes	Yes	Yes
	Nebula Cloud Monitoring Mode	Yes	Yes	Yes
	Device HA Pro	N/A	Yes	Yes
	Link Aggregation (LAG)	N/A	Yes	Yes
	Hotspot Management ^{*7}	Yes	Yes	Yes
	Ticket Printer Support ^{*9} /Support Q'ty (max.)	Yes (SP350E)/10	Yes (SP350E)/10	Yes (SP350E)/10
	Concurrent Devices Logins (default/max.) ^{*7**}	200	200/300	500/2000
Power Requirements				
Power input		12 V DC, 2.5 A max.	12 V DC, 4.17 A	100-240 V AC, 50/60 Hz, 2.5 A max.
Max. power consumption (watt Max.)		13.3	24.1	46
Heat dissipation (BTU/hr)		45.38	82.23	120.1
Physical Specifications				
Item	Dimensions (WxDxH)(mm/in.)	272 x 187 x 36/10.7 x 7.36 x 1.42	300 x 188 x 44/16.93 x 7.4 x 1.73	430 x 250 x 44/16.93 x 9.84 x 1.73
	Weight (Kg/lb.)	1.4/3.09	1.65/3.64	3.3/7.28
Packing	Dimensions (WxDxH)(mm/in.)	427 x 247 x 73/16.81 x 9.72 x 2.87	351 x 152 x 245/13.82 x 5.98 x 9.65	519 x 392 x 163/20.43 x 15.43 x 6.42
	Weight (kg/lb.)	2.23 (W/O bracket)	2.83/6.24	4.8/10.58
		2.42 (W/ bracket)		
Included accessories		• Power adapter • Rack mounting kit	• Power adapter • Power cord • Rack mounting kit	• Power cord • Rack mounting kit
Environmental Specifications				
Operating	Temperature	0°C to 40°C/32°F to 104°F	0°C to 40°C/32°F to 104°F	0°C to 40°C/32°F to 104°F
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)	10% to 90% (non-condensing)
Storage	Temperature	-30°C to 70°C/-22°F to 158°F	-30°C to 70°C/-22°F to 158°F	-30°C to 70°C/-22°F to 158°F
	Humidity	10% to 90% (non-condensing)	10% to 90% (non-condensing)	10% to 90% (non-condensing)
MTBF (hr)		832,102(at 25°C) and 536,472(at 40°C)	937,790(at 25°C) and 529,688(at 40°C)	947,737(at 25°C) and 444,931(at 40°C)
Acoustic Noise		N/A	24.5 dBA on < 25°C operating temperature, 41.5 dBA on full FAN speed	24.5 dBA on < 25°C operating temperature, 41.5 dBA on full FAN speed
Certifications				
EMC		FCC Part 15 (Class B), CE EMC (Class B), C-Tick (Class B), BSMI (Class A),	FCC Part 15 (Class A), CE EMC (Class A), C-Tick (Class A), BSMI (Class A),	FCC Part 15 (Class A), CE EMC (Class A), C-Tick (Class A), BSMI (Class A),
Safety		LVD (EN60950-1), BSMI	LVD (EN60950-1), BSMI	LVD (EN60950-1), BSMI

*: This matrix with firmware ZLD5.37 or later.

*1: Actual performance may vary depending on system configuration, network conditions, and activated applications.

*2: Maximum throughput based on RFC 2544 (1,518-byte UDP packets).

*3: VPN throughput measurement are based on RFC 2544 (1,424-byte UDP packets); IMIX: UDP throughput based on a combination of 64 byte, 512 byte, and 1424 byte packet sizes.

*4: AV (with Express Mode) and IDP throughput measured using the industry standard HTTP performance test (1,460-byte HTTP packets). Testing done with multiple flows.

*5: Maximum sessions measured using the industry standard IXIA IxLoad testing tool.

*6: Including Gateway-to-Gateway and Client-to-Gateway.

*7: With Zyxel service license to enable or extend the feature capacity.

*8: This is the recommend maximum number of concurrent logged-in devices.

*9: With Hotspot Management license support.

*10: The Speedtest result is conducted with 1 Gbps WAN link in real world and it is subject to fluctuate due to quality of the ISP link.

*11: USG FLEX 100 rev1 is adopting a new hardware design equipped with 4 x LAN/DMZ, 1 x WAN.

USG LITE

Model		USG LITE 60AX	
Hardware Specifications			
WiFi standard		802.11 ax/ac/n/g/b/a	
CPU		Quad-core, 2.00GHz	
RAM / FLASH		1GB/512MB	
Ethernet ports	WAN	1 x 100/1000/2500 Mbps	
	LAN	1 x 100/1000/2500 Mbps 4 x 100/1000 Mbps	
System Capacity & Performance*1			
SPI firewall throughput (Mbps)*2		2,000	
Throughput with Application management on (Mbps)		2,000	
Throughput with Threat management on (Mbps)		2,000	
VPN throughput (Mbps)*3		300	
Max. TCP concurrent sessions*4		20,000	
Max. gateway-to-gateway IPsec VPN tunnels		3	
Max. concurrent IPsec VPN tunnels		5	
Max. remote VPN tunnels		5	
VLAN interface		4	
Wireless Features			
MIMO		MU-MIMO	
MU-MIMO		Open, WPA2-PSK, WPA3-Personal	
Fast roaming		802.11r/k/v	
MESH Networking		Smart Mesh	
Wireless bridge		Yes	
Site-wide SSID provisioning from Nebula cloud		Yes	
See wireless client info from the Nebula dashboard		Yes	
Auto / Fixed Channel Selection		Yes	
Security Features			
Ransomware/Malware Prevention		Yes	
Intrusion Blocker		Yes	
Dark Web Blocker		Yes	
Stop Mail Fraud & Phishing		Yes	
Block Ads		Yes	
Block VPN Proxy		Yes	
Firewall		Yes	
Country Restriction (GeoIP blocking)		Yes	
Exception list		Yes	
Custom allowed / blocked domain		Yes	
Traffic Management (applications & clients)		Yes	
Security event analytics		Nebula Threat Report	
Real-time threat intelligence*6		Yes	
Web Filtering (Content Filter)*6		Yes	
VPN Features			
Site2site VPN		IPSec	
Remote access VPN		Yes	
Networking Features			
WAN Type		DHCP/Static IP/PPPoE	
Reserve IP (static DHCP)		Yes	
Block clients		Yes	
NAT - Virtual server		Yes	
DHCP server and DHCP relay		Yes	
Dynamic DNS (DDNS)		Yes	
Static route		Yes	
Guest Network		Yes	
VLAN Segmentation		Yes	
Management			
Onboarding WAN setting method		Yes	
Site-wide SSID management		Yes	
Multi-site management		Yes	
Client report		Yes	
Firmware upgrade		Yes	
Remote support and diagnostics		Yes	
Keep device settings in the Nebula		Yes	
Live tools		Yes	
Event Log		Yes	
Nebula Pro Pack - Advance feature set*6		Yes	

Power Requirements		
Power input	12 V DC, 3.0 A	
Max. power consumption (watt max.)	31W	
Physical Specifications		
Item	Dimensions(L x W x H)(mm/in.)	161.7 x 65 x 229/6.37 x 2.56 x 9.02
	Weight(g/lb.)	707/1.56
Environmental Specifications		
Operating	Temperature	0°C to 40°C/32°F to 104°F
	Humidity	Humidity:5% to 95% (Non-condensing)
Storage	Temperature	-30°C to 70°C/-22°F to 158°F
	Humidity	5% to 95% (Non-condensing)
Certifications		
Certifications	CE, FCC, BSMI	

*1: Actual performance may vary depending on system configuration,network conditions, and activated applications.
*2: Maximum throughput is measured using FTP with a 2 GB file and 1,460-byte packets across multiple sessions.
*3: VPN throughput is measured based on RFC 2544 using 1,424-byte UDP packets.
*4: Maximum sessions are measured using the industry-standard IXIA IxLoad testing tool.
*5: Requiring Elite Pack.

SCR

Model		SCR 50AXE
Hardware Specifications		
CPU		Dual-core, 1.00 GHz, Cortex A53
RAM/FLASH		1 GB/256 MB
10/100/1000 Mbps RJ-45 ports		(1) WAN: 1 GbE RJ-45 port (4) LAN: 1 GbE RJ-45 ports
Fanless		Yes
System Capacity & Performance		
SPI firewall throughput LAN to WAN (Mbps)		900
Threat mgmt ON/App mgmt OFF (Mbps)		900
Wireless Specifications		
Standard compliance		IEEE 802.11 ax 6 GHz IEEE 802.11 ax/ac/n/a 5 GHz IEEE 802.11 ax/n/b/g 2.4 GHz
Wireless security		WPA2-PSK, WPA3-PSK
Wireless frequency		2.4/5/6 GHz
Radio		3
SSID number		4
WPS		Yes
No. of antenna		4 (internal)
Antenna gain		2.0 dBi @2.4 GHz 3.0 dBi @5 GHz 3.5 dBi @6 GHz
Data rate		2.4 GHz: up to 575 Mbps 5 GHz: up to 2400 Mbps 6 GHz: up to 2400 Mbps
Security Features		
Ransomware/Malware Prevention		Yes
Intrusion Blocker		Yes
Dark Web Blocker		Yes
Stop Mail Fraud & Phishing		Yes
Block Ads		Yes
Block VPN Proxy		Yes
Content Filter*		Yes
Firewall		Yes
Country Restriction (GeoIP)		Yes
Exception List		Yes
Custom Allowed/Blocked Domain		Yes
Traffic Management (Applications & Clients)		Yes
Security Event Analytics		Threat Management Report
VPN Features		
Site2site VPN		IPSec (site-to-site, spoke only)
Networking		
WAN type		DHCP/Static IP/PPPoE/PPPoE with static IP
Networking features		NAT - Virtual server DHCP IP/MAC binding Block clients Guest network**
IPTV passthrough		IGMP Proxy
Management		
Site-wide SSID management		Nebula
Multi-site management		Nebula
Topology*		Nebula
Diagnostics		Yes
Remote support**		Yes
Onboarding WAN setting method		WiFi
Power Requirements		
Power input		12 V DC, 2.0 A
Max. power consumption (watt max.)		21 W
Physical Specifications		
Item	Dimensions (WxDxH)(mm/in.)	178.0 x 54.6 (stand 68.2) x 242.2/7.00 x 2.14 (stand 2.68) x 9.54
	Weight (g/lb.)	651/1.44 (with stand)
Environmental Specifications		
Operating	Temperature	0°C to 40°C/32°F to 104°F
	Humidity	10% to 90% (non-condensing)
Storage	Temperature	-30°C to 70°C/-22°F to 158°F
	Humidity	10% to 95% (non-condensing)
Certifications		
Certifications		CE, FCC, BSMI

*: Requiring SCR Pro Pack license.
**: Available in Q3 2023.

Wireless Specifications

Model	USG FLEX	USG LITE	SCR
	USG FLEX 50/100AX	USG LITE 60AX	SCR 50AXE
Standard compliance	802.11 ax/ac/n/g/b/a	IEEE802.11 ax/ac/n/g/b/a	802.11 ax/ac/n/g/b/a
Wireless frequency	2.4/5 GHz	2.4/5 GHz	2.4/5/6 GHz
Radio	2	2	3
SSID number	4	8	4
Maximum transmit power (Max. total channel)	<ul style="list-style-type: none">US (FCC) 2.4 GHz: 29.8 dBm, 2 antennasUS (FCC) 5 GHz: 32.6 dBm, 2 antennasEU (ETSI) 2.4 GHz: 19.93 dBm (EIRP), 2 antennasEU (ETSI) 5 GHz: 22.99 dBm (EIRP), 2 antennas	<ul style="list-style-type: none">US(FCC) 2.4GHz: 29.98dBm,4 antennasUS(FCC)5GHz: 29.82dBm,4 antennasEU(ETSI)2.4GHz: 19.92dBm(EIRP),4 antennasEU(ETSI)5GHz: 29.90dBm(EIRP),4 antennas	<ul style="list-style-type: none">US (FCC) 2.4 GHz: 26.5 dBm, 2 antennasUS (FCC) 5 GHz: 29.5 dBm, 2 antennasUS (FCC) 6 GHz: 24.5 dBm, 2 antennasEU (ETSI) 2.4 GHz: 19.31 dBm (EIRP), 2 antennasEU (ETSI) 5 GHz: 25.24 dBm (EIRP), 2 antennasEU (ETSI) 6 GHz: 22.26 dBm (EIRP), 2 antennas
No. of antenna	2 detachable antennas	4 internal antennas	4 internal antennas
Antenna gain	3 dBi @2.4 GHz/5 GHz	3.65 dBi @2.4 GHz 4.63 dBi @5 GHz	2 dBi @2.4 GHz 3 dBi @5 GHz 3.5 dBi @6 GHz
Data rate	<ul style="list-style-type: none">2.4 GHz: up to 600 Mbps5 GHz: up to 1200 Mbps	<ul style="list-style-type: none">2.4 GHz: up to 1150 Mbps5 GHz: up to 4802 Mbps	<ul style="list-style-type: none">2.4 GHz: up to 575 Mbps5 GHz: up to 2400 Mbps6 GHz: up to 2400 Mbps
Frequency band	<div>2.4 GHz (IEEE 802.11 b/g/n)<ul style="list-style-type: none">USA (FCC): 2.412 to 2.462 GHzEurope (ETSI): 2.412 to 2.472 GHzTWN (NCC): 2.412 to 2.462 GHz5 GHz (IEEE 802.11 a/n/ac/ax)<ul style="list-style-type: none">USA (FCC): 5.150 to 5.250 GHz; 5.725 to 5.850 GHzEurope (ETSI): 5.15 to 5.35 GHz; 5.470 to 5.725 GHzTWN (NCC): 5.15 to 5.25 GHz; 5.725 to 5.850 GHz</div>	<div>2.4 GHz(IEEE 802.11 b/g/n/ac/ax)<ul style="list-style-type: none">USA (FCC): 2.412 to 2.462 GHzEurope (ETSI): 2.417 to 2.472 GhzTWN (NCC): 2.412 to 2.462 GHz5 GHz(IEEE 802.11 a/n/ac/ax)<ul style="list-style-type: none">USA (FCC): 5.150 to 5.250 GHz; 5.250 to 5.350 GHz; 5.470 to 5.725 GHz; 5.725 to 5.895 GHzEuropean (ETSI): 5.150 to 5.250 GHz; 5.250 to 5.350 GHz; 5.470 to 5.725 GHzTWN (NCC): 5.150 to 5.250 GHz; 5.250 to 5.350 GHz; 5.470 to 5.725 GHz; 5.725 to 5.850 GHz</div>	<div>2.4 GHz (IEEE 802.11 b/g/n/ax)<ul style="list-style-type: none">USA (FCC): 2.412 to 2.462 GHzEurope (ETSI): 2.412 to 2.472 GHzTWN (NCC): 2.412 to 2.462 GHz5 GHz (IEEE 802.11 a/n/ac/ax)<ul style="list-style-type: none">USA (FCC): 5.150 to 5.250 GHz; 5.250 to 5.350 GHz; 5.470 to 5.725 GHz; 5.725 to 5.850 GHzEuropean (ETSI): 5.150 to 5.350 GHz; 5.470 to 5.725 GHzTWN (NCC): 5.150 to 5.250 GHz; 5.250 to 5.350 GHz; 5.470 to 5.725 GHz; 5.725 to 5.850 GHz6 GHz (IEEE 802.11 ax)<ul style="list-style-type: none">USA (FCC): 5.925 to 7.125 GHzEuropean (ETSI): 5.925 to 6.425 GHz</div>
Receive sensitivity	<div>2.4 GHz:<ul style="list-style-type: none">11 Mbps ≤ -99 dBm54 Mbps ≤ -95 dBmHT20, MCS7 ≤ -90 dBmHT40, MCS7 ≤ -86 dBm5 GHz:<ul style="list-style-type: none">54 Mbps ≤ -90 dBmHT20, MCS7 ≤ -85 dBmHT40, MCS7 ≤ -81 dBmVHT20, MCS8 ≤ -90 dBm +/- 2 dBmVHT40, MCS9 ≤ -85 dBm +/- 2 dBmVHT80, MCS9 ≤ -68 dBm +/- 2 dBmHE20, MCS11 ≤ -61 dBm +/- 2 dBmHE40, MCS11 ≤ -58 dBm +/- 2 dBmHE80, MCS11 ≤ -55 dBm +/- 2 dBm</div>	<div>2.4 GHz:<ul style="list-style-type: none">11Mbps = -89dBm54Mbps = -76dBmHT20,MCS7 =-74dBmHT40,MCS7 =-71dBmVHT20,MCS8 =-74dBmVHT40,MCS9 =-65dBmHE20,MCS11 =-63dBmHE40,MCS11 =-60dBm5 GHz:<ul style="list-style-type: none">54Mbps =-76dBmHT20,MCS7 =-74dBmHT40,MCS7 =-71dBmVHT20,MCS8 =-71dBmVHT40,MCS9 =-65dBmVHT80,MCS9 =-62dBmHE20,MCS11 =-65dBmHE40,MCS11 =-62dBmHE80,MCS11 =-59dBmHE160,MCS11 =-56dBm</div>	<div>2.4 GHz:<ul style="list-style-type: none">11 Mbps ≤ -82 dBm54 Mbps ≤ -69 dBmHT20, MCS7 ≤ -68 dBmHT40, MCS7 ≤ -67 dBmVHT20, MCS8 ≤ -64 dBm +/- 2 dBmVHT40, MCS9 ≤ -62 dBm +/- 2 dBmHE20, MCS11 ≤ -58 dBm +/- 2 dBmHE40, MCS11 ≤ -55 dBm +/- 2 dBm5 GHz:<ul style="list-style-type: none">54 Mbps ≤ -72 dBmHT20, MCS7 ≤ -71 dBmHT40, MCS7 ≤ -68 dBmHT80, MCS7 ≤ -65 dBmVHT20, MCS8 ≤ -65 dBm +/- 2 dBmVHT40, MCS9 ≤ -62 dBm +/- 2 dBmVHT80, MCS9 ≤ -59 dBm +/- 2 dBmHE20, MCS11 ≤ -60 dBm +/- 2 dBmHE40, MCS11 ≤ -58 dBm +/- 2 dBmHE80, MCS11 ≤ -55 dBm +/- 2 dBmHE (80+80), MCS11 ≤ -52 dBm +/- 2 dBm6 GHz:<ul style="list-style-type: none">HE20, MCS11 ≤ -61 dBm +/- 2 dBmHE40, MCS11 ≤ -58 dBm +/- 2 dBmHE80, MCS11 ≤ -55 dBm +/- 2 dBmHE160, MCS11 ≤ -52 dBm +/- 2 dBm</div>

Compatibility & Accessories

Access Point

Product	Unified AP	Unified Pro AP
Models	<ul style="list-style-type: none">NWA5123-ACNWA5123-AC HD*WAC5302D-SWAC5302D-Sv2WAC500*WAC500H*	<ul style="list-style-type: none">WBE530*WAX300HWAX510D* <ul style="list-style-type: none">WAC6103D-IWAC6303D-SWAC6502D-EWAC6502D-SWAC6503D-SWAC6552D-SWAC6553D-E <ul style="list-style-type: none">WBE660SWAX650SWAX610DWAX630SWAX640S-6EWAX620D-6EWAX655E
Functions		
Central management	Yes	Yes
Auto provisioning	Yes	Yes
Data forwarding	Local bridge	Local bridge/Data tunnel
ZyMesh	Yes	Yes

*: Support both local bridge and data tunnel for data forwarding

Transceivers (Optional)

Model	Speed	Connector	Wavelength	Max. Distance	Optical Fiber Type	DDMI
SFP10G-SR*	10-Gigabit SFP+	Duplex LC	850 nm	300 m/328 yd	Multi Mode	Yes
SFP10G-LR*	10-Gigabit SFP+	Duplex LC	1310 nm	10 km/10936 yd	Single Mode	Yes
SFP-1000T	Gigabit	RJ-45	-	100 m/109 yd	Multi Mode	-
SFP-LX-10-D	Gigabit	Single LC	1310 nm	10 km/10936 yd	Single Mode	Yes
SFP-SX-D	Gigabit	Single LC	850 nm	550 m/601 yd	Multi Mode	Yes
SFP-BX1310-10-D*1	Gigabit	Single LC	1310 nm (TX) 1490 nm (RX)	10 km/10936 yd	Single Mode	Yes
SFP-BX1490-10-D*1	Gigabit	Single LC	1490 nm (TX) 1310 nm (RX)	10 km/10936 yd	Single Mode	Yes

*: Only USG2200-VPN supports 10-Gigabit SFP+
*1: SFP-BX1310-10-D and SFP-BX1490-10-D are must used in pairs.

VPN client subscription

Item	Description	Supported OS
SecuExtender Zero Trust IPsec/SSL VPN Client Subscription*	SecuExtender supports popular VPN protocols including IKEv2/EAP, SSL VPN. Building secure tunnel with industry-leading strong cipher, the SecuExtender guarantees your confidentiality and data integrity.	<ul style="list-style-type: none">Windows 10 64-bitWindows 11 64-bitmacOS 10.15 or above

*: One subscription license to activate IPsec or SSL VPN from selected OS Windows/macOS.

Corporate Headquarters

Zyxel Networks Corp.
Tel: +886-3-578-3942
Fax: +886-3-578-2439
Email: sales@zyxel.com.tw
www.zyxel.com

Europe

Zyxel Belarus Tel: +375 25 604 3739 Email: info@zyxel.by www.zyxel.by	Zyxel Norway Tel: +47 22 80 61 80 Fax: +47 22 80 61 81 Email: salg@zyxel.no www.zyxel.no
Zyxel BeNeLux Tel: +31 23 555 3689 Fax: +31 23 557 8492 Email: sales@zyxel.nl www.zyxel.nl www.zyxel.be	Zyxel Poland Tel: +48 223 338 250 Hotline: +48 226 521 626 Fax: +48 223 338 251 Email: info@pl.zyxel.com www.zyxel.pl
Zyxel Bulgaria (Bulgaria, Macedonia, Albania, Kosovo) Tel: +3592 4443343 Email: info@cz.zyxel.com www.zyxel.bg	Zyxel Romania Tel: +40 770 065 879 Email: info@zyxel.ro www.zyxel.ro
Zyxel Czech Republic Tel: +420 725 567 244 Tel: +420 606 795 453 Email: sales@cz.zyxel.com Support: https://support.zyxel.eu www.zyxel.cz	Zyxel Russia Tel: +7 499 705 6106 Email: info@zyxel.ru www.zyxel.ru
Zyxel Denmark A/S Tel: +45 39 55 07 00 Fax: +45 39 55 07 07 Email: sales@zyxel.dk www.zyxel.dk	Zyxel Slovakia Tel: +421 919 066 395 Email: sales@sk.zyxel.com Support: https://support.zyxel.eu www.zyxel.sk
Zyxel Finland Tel: +358 9 4780 8400 Email: myynti@zyxel.fi www.zyxel.fi	Zyxel Sweden A/S Tel: +46 8 55 77 60 60 Fax: +46 8 55 77 60 61 Email: sales@zyxel.se www.zyxel.se
Zyxel France Tel: +33 (0)4 72 52 97 97 Fax: +33 (0)4 72 52 19 20 Email: info@zyxel.fr www.zyxel.fr	Zyxel Switzerland Tel: +41 (0)44 806 51 00 Fax: +41 (0)44 806 52 00 Email: info@zyxel.ch www.zyxel.ch
Zyxel Germany GmbH Tel: +49 (0) 2405-6909 0 Fax: +49 (0) 2405-6909 99 Email: sales@zyxel.de www.zyxel.de	Zyxel Turkey A.S. Tel: +90 212 314 18 00 Fax: +90 212 220 25 26 Email: bilgi@zyxel.com.tr www.zyxel.com.tr
Zyxel Hungary & SEE Tel: +36 1 848 0690 Email: info@zyxel.hu www.zyxel.hu	Zyxel UK Ltd. Tel: +44 (0) 118 9121 700 Fax: +44 (0) 118 9797 277 Email: sales@zyxel.co.uk www.zyxel.co.uk
Zyxel Iberia Tel: +34 911 792 100 Email: ventas@zyxel.es www.zyxel.es	Zyxel Ukraine Tel: +380 89 323 9959 Email: info@zyxel.eu www.zyxel.ua
Zyxel Italy Tel: +39 011 230 8000 Email: info@zyxel.it www.zyxel.it	

Asia

Zyxel China (Shanghai) China Headquarters Tel: +86-021-61199055 Fax: +86-021-52069033 Email: sales@zyxel.cn www.zyxel.cn	Zyxel Middle East FZE Tel: +971 4 372 4483 Cell: +971 562146416 Email: sales@zyxel-me.com www.zyxel-me.com
Zyxel China (Beijing) Tel: +86-010-62602249 Email: sales@zyxel.cn www.zyxel.cn	Zyxel Philippine Email: sales@zyxel.com.ph www.zyxel.com.ph
Zyxel China (Tianjin) Tel: +86-022-87890440 Fax: +86-022-87892304 Email: sales@zyxel.cn www.zyxel.cn	Zyxel Singapore Tel: +65 6339 3218 Hotline: +65 6339 1663 Fax: +65 6339 3318 Email: sales@zyxel.com.sg www.zyxel.com.sg
Zyxel India Tel: +91-11-4760-8800 Fax: +91-11-4052-3393 Email: info@zyxel.in www.zyxel.in	Zyxel Taiwan (Taipei) Tel: +886-2-2739-9889 Fax: +886-2-2735-3220 Email: sales_tw@zyxel.com.tw www.zyxel.com.tw
Zyxel Kazakhstan Tel: +7 727 350 5683 Email: info@zyxel.kz www.zyxel.kz	Zyxel Thailand Tel: +66-(0)-2831-5315 Fax: +66-(0)-2831-5395 Email: info@zyxel.co.th www.zyxel.co.th
Zyxel Korea Corp. Tel: +82-2-890-5535 Fax: +82-2-890-5537 Email: sales@zyxel.kr www.zyxel.kr	Zyxel Vietnam Tel: (+848) 35202910 Fax: (+848) 35202800 Email: sales_vn@zyxel.com.tw www.zyxel.com/vn/vi/
Zyxel Malaysia Tel: +603 2282 1111 Fax: +603 2287 2611 Email: sales@zyxel.com.my www.zyxel.com.my	

The Americas

Zyxel USA North America Headquarters Tel: +1-714-632-0882 Fax: +1-714-632-0858 Email: sales@zyxel.com us.zyxel.com	Zyxel Brazil Tel: +55 (11) 3373-7470 Fax: +55 (11) 3373-7510 Email: comercial@zyxel.com.br www.zyxel.com/br/pt/
---	--



For more product information, visit us on the web at www.zyxel.com

Copyright © 2025 Zyxel and/or its affiliates. All rights reserved.
All specifications are subject to change without notice.

