


- (Eng) Installation guide
 (F) Guide d'installation
 (E) Guía de instalación

BHMA
CERTIFIED

A156.25 grade 1
Only with SALTO LA1T
mortise lock.

Ai 650 m 00 ff t x h r series
 Ai 656 m 00 ff t x h r
 Ai 658 m dd ff t x h r
 Ai 660 m 00 ff t x h r
 Ai 666 m 00 ff t x h r
 Ai 668 m dd ff t x h r



(Eng) Mortise Lock not included
 (F) Serrure à mortaiser non incluse
 (E) Cerradura de embutir no incluida

SALTO LT2Lxx Tubular Latch


"A2" version has to be installed always with the SALTO LT2L tubular latch.
 La versión "A2" solo se puede instalar con el picaporte tubular SALTO LT2L.

SALTO LT2Lxx Tubular latch With Ai6xxA2.. Only!

To be used only with SALTO compatible escutcheons!
 A utiliser uniquement avec les ensembles plaques-béquilles SALTO compatibles!
 ¡Utilizar solamente con escudos SALTO compatibles!



Ø25
 Ø1"



SALTO recommends the use of a mortise lock, with a maximum 4° pre-turn.

SALTO recommande d'utiliser des serrures à mortaiser avec un angle au repos de 4° maximum.

SALTO recomienda utilizar cerraduras con un pregiro máximo de 4°.


- (Eng) (*) Only for door thickness > 2-3/8" (60mm).
 (F) (*) Seulement pour portes de épaisseur > 2-3/8" (60mm).
 (E) (*) Solo para grosor de puerta > 2-3/8" (60mm).

AMOK function


CLICK HERE





(Eng) Select handing (F) Choisir le sens de la bêteuille (E) Seleccione mano




(Eng) Installation (F) Installation (E) Instalación







WIRELESS



Ai 650 m 00 ff t x h W series
 Ai 656 m 00 ff t x h W
 Ai 658 m dd ff t x h W
 Ai 660 m 00 ff t x h W
 Ai 666 m 00 ff t x h W
 Ai 668 m dd ff t x h W

