



**1 Install External Latch and Strike Plate**  
NTRF has a standard External Lock with a 2" (50mm) Strike Plate.

**2 Install Exterior Assembly**  
2.1 Cut the hole for the lock body.  
2.2 Cut the hole for the strike plate.  
2.3 Mark the hole for the strike plate.  
2.4 Mark the hole for the strike plate.  
2.5 Mark the hole for the strike plate.

**3 Install Interior Assembly**  
3.1 Cut the hole for the lock body.  
3.2 Cut the hole for the strike plate.  
3.3 Mark the hole for the strike plate.  
3.4 Mark the hole for the strike plate.  
3.5 Mark the hole for the strike plate.

**4 Install Interior Assembly**  
4.1 Cut the hole for the lock body.  
4.2 Cut the hole for the strike plate.  
4.3 Mark the hole for the strike plate.  
4.4 Mark the hole for the strike plate.  
4.5 Mark the hole for the strike plate.

**5 Install Interior Assembly**  
5.1 Cut the hole for the lock body.  
5.2 Cut the hole for the strike plate.  
5.3 Mark the hole for the strike plate.  
5.4 Mark the hole for the strike plate.  
5.5 Mark the hole for the strike plate.

**6 Install Interior Assembly**  
6.1 Cut the hole for the lock body.  
6.2 Cut the hole for the strike plate.  
6.3 Mark the hole for the strike plate.  
6.4 Mark the hole for the strike plate.  
6.5 Mark the hole for the strike plate.

**7 Install Batteries and Cover**  
7.1 Cut the hole for the lock body.  
7.2 Cut the hole for the strike plate.  
7.3 Mark the hole for the strike plate.  
7.4 Mark the hole for the strike plate.  
7.5 Mark the hole for the strike plate.

**8 Testing Operation**  
8.1 Cut the hole for the lock body.  
8.2 Cut the hole for the strike plate.  
8.3 Mark the hole for the strike plate.  
8.4 Mark the hole for the strike plate.  
8.5 Mark the hole for the strike plate.

**9 Test Locking Cycle**  
9.1 Cut the hole for the lock body.  
9.2 Cut the hole for the strike plate.  
9.3 Mark the hole for the strike plate.  
9.4 Mark the hole for the strike plate.  
9.5 Mark the hole for the strike plate.

**10 Test Locking Cycle**  
10.1 Cut the hole for the lock body.  
10.2 Cut the hole for the strike plate.  
10.3 Mark the hole for the strike plate.  
10.4 Mark the hole for the strike plate.  
10.5 Mark the hole for the strike plate.

**11 Test Locking Cycle**  
11.1 Cut the hole for the lock body.  
11.2 Cut the hole for the strike plate.  
11.3 Mark the hole for the strike plate.  
11.4 Mark the hole for the strike plate.  
11.5 Mark the hole for the strike plate.

**12 Test Locking Cycle**  
12.1 Cut the hole for the lock body.  
12.2 Cut the hole for the strike plate.  
12.3 Mark the hole for the strike plate.  
12.4 Mark the hole for the strike plate.  
12.5 Mark the hole for the strike plate.

[illegible]