

Single Pack SC12GH 220-240V 50Hz / 208-230V 60Hz CSIR

Codice Imballo Singolo: **195B4222**

Posizione	Titolo	Codice	Quantità
1	Compressor SC12GH	104G8261	1
2	Starting relay	117U6011	1
3	Starting capacitor (80µF 220V, 6.3mm)	117U5017	1
4	Cord relief	103N1004	1
5	Cover	103N2008	1
6	Bolt joint for one compressor M6 ø16mm	118-1917	1

Secop GmbH • Lise-Meitner-Straße 29 • 24941 Flensburg, Germany • Tel: +49 461 49410 • www.secop.com

Secop non si assume alcuna responsabilità per eventuali errori presenti in cataloghi, brochure e altro materiale stampato. Secop si riserva il diritto di modificare i propri prodotti senza preavviso. Ciò vale anche per i prodotti già ordinati, a condizione che tali modifiche possano essere apportate senza che siano necessarie modifiche successive alle specifiche già concordate. Tutti i marchi presenti in questo materiale sono di proprietà delle rispettive aziende. Secop e il logo Secop sono marchi di Secop GmbH. Tutti i diritti sono riservati.

Model

Designation	SC12GH	220-240V/50Hz 1~	208-230V/60Hz 1~	Sales code:	104G8261
-------------	---------------	-------------------------	-------------------------	-------------	-----------------

Compressor design

Oil type	Polyolester	Refrigerant(s)	R134a, R513A
Oil viscosity	22cST	Displacement	12,87cm³ / 0,79cu.in
Oil quantity	504cm³ / 17fl.oz	Compressors on pallet	80
Refr. charge - tech. limit	1300g / 45,9oz		
Free gas volume comp.	1510cm³ / 51,1fl.oz		
Weight	12,5kg / 27,6lbs		
Motor protection	1# internal		
Winding resistance main	4,4Ω (at 25°C)		
Winding resistance aux	14Ω (at 25°C)		
Max. winding temp.	125°C / 257°F		
Max. discharge temp.	130°C / 266°F		



General - Configurations with SC12GH

	Conf. 1	Conf. 2	Conf. 3	Conf. 4
Motorconfiguration	CSIR	CSIR	CSIR	CSIR
Power supply (nominal)	220-240V/50Hz	220-240V/50Hz	208-230V/60Hz	208-230V/60Hz
Number of phases	1	1	1	1
Voltage range	198-254V	198-254V	198-254V	198-254V
Approvals	VDE, UL, KC	VDE, UL	VDE, UL, KC	VDE, UL
Starting torque	HST	HST	HST	HST
Note	- / -			

Applications with SC12GH

	Conf. 1	Conf. 2	Conf. 3	Conf. 4
Refrigerant	R134a	R513A	R134a	R513A
Application	HBP	HBP	HBP	HBP
System cooling	fan 3m/s	fan 3m/s	fan 3m/s	fan 3m/s
Hot gas defrost	OK	OK	OK	OK
Long interval pull down	OK	OK	OK	OK

Electrical data - Configurations with SC12GH

	Conf. 1	Conf. 2	Conf. 3	Conf. 4
Starting device type	relay	relay	relay	relay
Run capacitor	-/-	-/-	-/-	-/-
Start capacitor	80μF	80μF	80μF	80μF
LRA (locked rotor amps / 4s)	19A	19A	18,3A	18,3A
RLA (rated load amps / 1s)	3,9A	3,9A	3,52A	3,52A
Cut in current	19A	19A	18,3A	18,3A


Model

Designation	SC12GH	220-240V/50Hz 1~ 208-230V/60Hz 1~	Sales code:	104G8261
-------------	---------------	--	-------------	-----------------


Compressor dimensions

Housing	A Height	209mm / 8,23in
	B Height	203mm / 7,99in
	C Length shell	218mm / 8,58in
	D Length w. cover	255mm / 10,04in
	E Width	151mm / 5,94in

Connectors	Suction X	Discharge Y	Process Z
Diameter [mm]	øi 10,11-10,29	øi 8,11-8,29	øi 6,11-6,29
(i:inside, o:outside) [in]	øi 0,4-0,41	øi 0,32-0,33	øi 0,24-0,25
Material	copper	copper	copper
Horizontal angle	±2° 37°	37°	143°
Vertical angle	±2° 30°	0°	150°
Position l/h/w [mm]	107/183/55	115/100/63	-107/183/55
[in]	4,2/7,2/2,2	4,5/3,9/2,5	-4,2/7,2/2,2
Straight tube l. [mm]	12	12	12
[in]	0,5	0,5	0,5




Compressor fixation




Baseplate	[mm]	[inch]
BI	204	8.03
Bw	150	5.9
øE	ø 9.7	ø 0.38
Large holes	[mm]	[inch]
LI	165	6.5
Lw	101.6	4
øL	ø 19	ø 0.75
Small holes	[mm]	[inch]
SI	170	6.7
Sw	70	2.76
øS	ø 16	ø 0.63
QI	127	5
Qw	127	5

Bolt joint



Snap-on



Mounting accessories

	one comp.	multi pack
Bolt joint M6 ø16mm	118-1917	118-1918
Bolt joint ø1/4" ø16mm	118-1946	
Bolt joint ø1/4" ø19mm	118-1949	
Snap-on ø7,3 ø16mm	118-1947	118-1919

Application notes

Provision for PE Grounding is located at the PE Stamp on the compressor

Model				
Designation	SC12GH	220-240V/50Hz	Conf. 1	Sales code: 104G8261

Configuration		Electrical accessories / wiring diagram	
Motorconfiguration	CSIR	CSIR	
Power supply (nominal)	220-240V/50Hz 1~		
Refrigerant	R134a		
Application	HBP		
Voltage range	198-254V		
Starting torque	HST		
Approvals	VDE		
	UL		
	KC		

Ambient/ machine room temperatures minimum /maximum




Ambient temperature range: 10 - 43°C / 50 - 110°F

Machine room temperature range: 10 - 48°C / 50 - 119°F

Compressor cooling: fan 3m/s

Operation Limits

Operation pressure range



Components

a2	relay	117U6011
c	start capacitor (80μF)	117U5017
d	cord relief	103N1004
b	plastic cover	103N2008

Model

Designation	SC12GH	220-240V/50Hz	Conf. 1	Sales code:	104G8261
-------------	--------	---------------	---------	-------------	----------

Optimization + standard conditions

R134a, 220V/50Hz, CSIR, fan 3m/s, VDE, UL, KC

Evaporating pressure (saturation temperature)					Condensing pressure (saturation temperature)						Power consumption			ASHRAE HBP
											Current consumption			
											Ref. mass flow			
	pe	pc	RGT	Tliq	W	[Btu/h]	[kcal/h]	COP	EER		P1	I	m	
					[W]			[W/W]	[Btu/Wh]	[kcal/W/h]	[W]	[A]	[kg/h]	
[°C]	7,2	54	35	46	1175,9	4016	1012,0	2,34	8,00	2,02	501,9	3,52	26,09	
[°F]	45	130	95	115										
[°C]	5	55	32	55	957,3	3269	823,9	1,97	6,71	1,69	487,1	3,47	23,59	cecomaf HBP
[°F]	41	131	90	131										
[°C]	5	50	20	50	998,2	3409	859,0	2,15	7,34	1,85	464,7	3,39	25,15	EN12900 HBP
[°F]	41	122	68	122										
[°C]	-7	54	35	46	583,7	1994	502,4	1,52	5,18	1,30	385,2	3,16	12,74	ASHRAE MBP
[°F]	20	130	95	115										
[°C]	-10	55	32	55	428,7	1464	368,9	1,20	4,11	1,04	356,3	3,08	10,37	cecomaf MBP
[°F]	14	131	90	131										
[°C]	-10	45	20	45	517,8	1768	445,7	1,49	5,08	1,28	348,4	3,06	12,12	EN12900 MBP
[°F]	14	113	68	113										

Model				
Designation	SC12GH	220-240V/50Hz	Conf. 2	Sales code: 104G8261

Configuration		Electrical accessories / wiring diagram		
Motorconfiguration	CSIR	CSIR		
Power supply (nominal)	220-240V/50Hz 1~			
Refrigerant	R513A			
Application	HBP			
Voltage range	198-254V			
Starting torque	HST			
Approvals	VDE			
	UL			

Ambient/ machine room temperatures minimum /maximum



Ambient temperature range: 10 - 43°C / 50 - 110°F

Machine room temperature range: 10 - 48°C / 50 - 119°F

Compressor cooling: fan 3m/s

Operation Limits

Operation pressure range



Components		
a2	relay	117U6011
c	start capacitor (80μF)	117U5017
d	cord relief	103N1004
b	plastic cover	103N2008

Model

Designation	SC12GH	220-240V/50Hz	Conf. 2	Sales code:	104G8261
-------------	--------	---------------	---------	-------------	----------

Optimization + standard conditions

R513A, 220V/50Hz, CSIR, fan 3m/s, VDE, UL

Evaporating pressure (saturation temperature)					Condensing pressure (saturation temperature)						Power consumption																																																																																																		
					Return gas temp.						Current consumption																																																																																																		
					Liquid temp.						Ref. mass flow																																																																																																		
					Cooling capacity						COP				EER				P1				I				r _m																																																																																		
					[W]						[Btu/h]						[kcal/h]						[W/W]						[Btu/Wh]						[kcal/Wh]						[W]						[A]						[kg/h]																																																								
pe					pc					RGT					T _{liq}					COP						EER						P1						I						r _m																																																																	
[°C]					[°F]					[°C]					[°F]					[W/W]						[Btu/Wh]						[kcal/Wh]						[W]						[A]						[kg/h]																																																											
7,2					54					35					46					1210,2						4133						1041,5						2,31						7,90						1,99						522,9						3,59						30,06						ASHRAE HBP																																			
45					130					95					115																																																																																														
5					55					32					55					970,8						3316						835,5						1,91						6,52						1,64						508,5						3,54						27,28						cecomaf HBP																																			
41					131					90					131																																																																																														
5					50					20					50					1013,9						3463						872,6						2,09						7,14						1,80						484,8						3,47						29,07						EN12900 HBP																																			
41					122					68					122																																																																																														
-7					54					35					46					613,9						2097						528,4						1,51						5,16						1,30						406,7						3,23						15,04						ASHRAE MBP																																			
20					130					95					115																																																																																														
-10					55					32					55					445,8						1523						383,7						1,18						4,03						1,02						377,6						3,14						12,33						cecomaf MBP																																			
14					131					90					131																																																																																														
-10					45					20					45					542,1						1852						466,6						1,47						5,03						1,27						368,3						3,11						14,37						EN12900 MBP																																			
14					113					68					113																																																																																														

Performance tables

R513A, 220V/50Hz, CSIR, fan 3m/s, VDE, UL

	pe		Cooling capacity			COP		EER			P1		I		m	
	[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]		[Btu/Wh]	[kcal/Wh]		[W]		[A]		[kg/h]	
[°C / °F]	-15	5	421,5	1440	362,8	1,27		4,34	1,09		331,5		2,99		10,33	
cond. pressure	-10	14	566,9	1936	487,9	1,54		5,26	1,32		368,3		3,11		13,94	
pc= 45/113	-5	23	737,1	2517	634,3	1,83		6,24	1,57		403,3		3,22		18,19	
return gas temp.	0	32	935,4	3195	805,0	2,15		7,34	1,85		435,4		3,31		23,20	
RGT= 32/90	5	41	1165,5	3980	1003,0	2,52		8,59	2,16		463,3		3,40		29,07	
liquid temp	15	59	1734,6	5924	1492,8	3,45		11,80	2,97		502,2		3,52		43,89	
Tliq= 45/113	20	68	2080,5	7105	1790,5	4,07		13,91	3,50		510,9		3,55		53,12	
[°C / °F]	-15	5	318,2	1087	273,8	0,96		3,27	0,82		332,4		3,00		8,76	
cond. pressure	-10	14	445,8	1523	383,7	1,18		4,03	1,02		377,6		3,14		12,33	
pc= 55/131	-5	23	594,8	2031	511,9	1,41		4,81	1,21		422,7		3,28		16,52	
return gas temp	0	32	768,7	2625	661,5	1,65		5,62	1,42		466,8		3,41		21,47	
RGT= 32/90	5	41	970,8	3316	835,5	1,91		6,52	1,64		508,5		3,54		27,28	
liquid temp	15	59	1473,9	5034	1268,5	2,54		8,67	2,19		580,5		3,76		42,09	
Tliq= 55/131	20	68	1781,8	6085	1533,4	2,93		10,00	2,52		608,5		3,85		51,41	

Model				
Designation	SC12GH	208-230V/60Hz	Conf. 3	Sales code: 104G8261



Configuration		Electrical accessories / wiring diagram		
Motorconfiguration	CSIR	CSIR		
Power supply (nominal)	208-230V/60Hz 1~			
Refrigerant	R134a			
Application	HBP			
Voltage range	198-254V			
Starting torque	HST			
Approvals	VDE			
	UL			
	KC			

Ambient/ machine room temperatures minimum /maximum

Ambient temperature range:	10 - 43°C / 50 - 110°F
Machine room temperature range:	10 - 48°C / 50 - 119°F
Compressor cooling:	fan 3m/s

Operation Limits

Operation pressure range



Components

a2	relay	117U6011
c	start capacitor (80μF)	117U5017
d	cord relief	103N1004
b	plastic cover	103N2008

Model

Designation	SC12GH	208-230V/60Hz	Conf. 3	Sales code:	104G8261
-------------	--------	---------------	---------	-------------	----------

Optimization + standard conditions

R134a, 230V/60Hz, CSIR, fan 3m/s, VDE, UL, KC

Evaporating pressure (saturation temperature)					Condensing pressure (saturation temperature)						Power consumption																																																																															
					Return gas temp.						Current consumption																																																																															
					Liquid temp.						Ref. mass flow																																																																															
					Cooling capacity						COP				EER				P1				I				ṁ																																																															
					[W]						[Btu/h]						[kcal/h]						[W/W]						[Btu/Wh]						[kcal/Wh]						[W]						[A]						[kg/h]																																					
pe					pc					RGT					Tliq																																																																											
[°C]					7,2					54					35					46					1370,3						4680						1179,3						2,38						8,13						2,05						575,7						3,36						30,40						ASHRAE HBP											
[°F]					45					130					95					115																																																																						
																														ASHRAE HBP																																																												
																														cecomaf HBP																																																												
																														EN12900 HBP																																																												
																														ASHRAE MBP																																																												
																														cecomaf MBP																																																												
																														EN12900 MBP																																																												

Performance tables

R134a, 230V/60Hz, CSIR, fan 3m/s, VDE, UL, KC

	pe		Cooling capacity			COP		EER			P1		I		m	
	[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]		[Btu/Wh]	[kcal/Wh]		[W]		[A]		[kg/h]	
[°C / °F]	-15	5	469,7	1604	404,2	1,41		4,80	1,21		334,0		2,39		10,24	
cond. pressure	-10	14	631,6	2157	543,5	1,67		5,69	1,43		378,9		2,57		13,82	
pc= 45/113	-5	23	824,5	2816	709,6	1,95		6,67	1,68		422,3		2,74		18,13	
return gas temp.	0	32	1052,5	3594	905,8	2,27		7,75	1,95		463,8		2,90		23,28	
RGT= 32/90	5	41	1319,7	4507	1135,7	2,62		8,96	2,26		502,8		3,05		29,38	
liquid temp	10	50	1630,1	5567	1402,9	3,03		10,34	2,60		538,6		3,19		36,58	
Tliq= 45/113	15	59	1987,8	6789	1710,7	3,48		11,90	3,00		570,6		3,33		45,03	
[°C / °F]	-15	5	371,0	1267	319,3	1,12		3,81	0,96		332,3		2,37		8,93	
cond. pressure	-10	14	511,2	1746	440,0	1,31		4,49	1,13		388,9		2,61		12,36	
pc= 55/131	-5	23	679,5	2321	584,8	1,53		5,21	1,31		445,5		2,84		16,52	
return gas temp	0	32	879,9	3005	757,2	1,76		5,99	1,51		501,3		3,06		21,52	
RGT= 32/90	5	41	1116,4	3813	960,8	2,01		6,86	1,73		555,8		3,28		27,51	
liquid temp	10	50	1393,1	4758	1199,0	2,29		7,82	1,97		608,3		3,49		34,63	
Tliq= 55/131	15	59	1714,2	5854	1475,3	2,60		8,89	2,24		658,4		3,68		43,06	

Model				
Designation	SC12GH	208-230V/60Hz	Conf. 4	Sales code: 104G8261

Configuration		Electrical accessories / wiring diagram		
Motorconfiguration	CSIR	CSIR		
Power supply (nominal)	208-230V/60Hz 1~			
Refrigerant	R513A			
Application	HBP			
Voltage range	198-254V			
Starting torque	HST			
Approvals	VDE			
	UL			

Ambient/ machine room temperatures minimum /maximum



Ambient temperature range: 10 - 43°C / 50 - 110°F

Machine room temperature range: 10 - 48°C / 50 - 119°F

Compressor cooling: fan 3m/s

Operation Limits

Operation pressure range



Components

a2	relay	117U6011
c	start capacitor (80μF)	117U5017
d	cord relief	103N1004
b	plastic cover	103N2008

Model

Designation	SC12GH	208-230V/60Hz	Conf. 4	Sales code:	104G8261
-------------	--------	---------------	---------	-------------	----------

Optimization + standard conditions


R513A, 230V/60Hz, CSIR, fan 3m/s, VDE, UL

Evaporating pressure (saturation temperature)					Condensing pressure (saturation temperature)					Power consumption																								
Return gas temp.					Current consumption					Ref. mass flow																								
Liquid temp.					Cooling capacity					COP					EER					P1					I					r _m				
pe	pc	RGT	T _{liq}	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[kcal/Wh]	[W]	[A]	[kg/h]																						
[°C]	7,2	54	35	46	1410,5	4817	1213,9	2,35	8,03	2,02	600,1	3,45	35,04																					
[°F]	45	130	95	115																														
																		ASHRAE HBP																
[°C]	5	55	32	55	1132,3	3867	974,4	1,95	6,66	1,68	580,5	3,37	31,82																					
[°F]	41	131	90	131																														
																		cecomaf HBP																
[°C]	5	50	20	50	1182,1	4037	1017,4	2,14	7,32	1,85	551,3	3,25	33,90																					
[°F]	41	122	68	122																														
																		EN12900 HBP																
[°C]	-7	54	35	46	724,1	2473	623,2	1,61	5,50	1,39	449,8	2,85	17,74																					
[°F]	20	130	95	115																														
																		ASHRAE MBP																
[°C]	-10	55	32	55	531,8	1816	457,7	1,29	4,40	1,11	412,8	2,70	14,70																					
[°F]	14	131	90	131																														
																		cecomaf MBP																
[°C]	-10	45	20	45	637,4	2177	548,6	1,59	5,43	1,37	401,1	2,65	16,89																					
[°F]	14	113	68	113																														
																		EN12900 MBP																

Performance tables




R513A, 230V/60Hz, CSIR, fan 3m/s, VDE, UL


	pe		Cooling capacity			COP		EER			P1		I		m	
	[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]		[Btu/Wh]	[kcal/Wh]		[W]		[A]		[kg/h]	
[°C / °F]	-15	5	500,7	1710	430,9	1,41		4,81	1,21		355,4		2,47		12,27	
cond. pressure	-10	14	666,6	2276	573,6	1,66		5,68	1,43		401,1		2,65		16,39	
pc= 45/113	-5	23	862,7	2946	742,4	1,94		6,62	1,67		444,9		2,83		21,30	
return gas temp.	0	32	1092,8	3732	940,5	2,25		7,68	1,93		486,3		2,99		27,11	
RGT= 32/90	5	41	1361,0	4648	1171,3	2,59		8,86	2,23		524,7		3,15		33,95	
liquid temp	10	50	1670,9	5706	1438,0	2,98		10,19	2,57		559,8		3,29		41,95	
Tliq= 45/113	15	59	2026,4	6921	1744,0	3,43		11,71	2,95		591,0		3,41		51,27	
[°C / °F]	-15	5	390,4	1333	335,9	1,10		3,76	0,95		354,8		2,47		10,75	
cond. pressure	-10	14	531,8	1816	457,7	1,29		4,40	1,11		412,8		2,70		14,70	
pc= 55/131	-5	23	700,0	2391	602,5	1,49		5,09	1,28		470,1		2,93		19,44	
return gas temp	0	32	898,9	3070	773,6	1,71		5,83	1,47		526,2		3,15		25,10	
RGT= 32/90	5	41	1132,3	3867	974,4	1,95		6,66	1,68		580,5		3,37		31,82	
liquid temp	10	50	1404,0	4795	1208,3	2,22		7,58	1,91		632,6		3,58		39,75	
Tliq= 55/131	15	59	1717,8	5867	1478,4	2,52		8,60	2,17		682,0		3,78		49,06	



SC Compressors

SECOP







SC Compressors

Service/Repair – R290

SECOP



8545



Secop accepts no responsibility for possible errors in catalogs, brochures, and other printed material. Secop reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary to specifications already agreed. All trademarks in this material are the property of the respective companies. Secop and the Secop logotype are trademarks of Secop GmbH. All rights reserved. www.secop.com