Hisense



WINDOW **AIR CONDITIONER**With Heat

Model **AW1822DR3W 1000 Sq. Ft**.



- 4 modes (Heating, Cooling, Fan, Dehumidifier) for versatile comfort
- Sleek and easy electronic touch controls
- · Remote control for easy, convenient operation
- 2-year warranty provides peace of mind
- Washable, removable filter for quick, easy cleaning
- 4-way air direction provides even, consistent comfort
- Low-noise airflow system ensures quiet operation







Sleek Electronic Touch Controls



Remote Control Included



4 Modes – heating, cooling, dehumidify and ventilate



230 Volt / 20 Amps





The Hisense AW1822CW3W Window Air Conditioner with Heat is best suited for larger rooms (1000 sq. ft. or less), delivering 18,000 BTU of cooling power and 11,000 BTU of heating power. It provides four modes of comfort – heating, cooling, fan, or dehumidifier – allowing you to choose the comfort you want at any time. The washable air filter is easy to remove and easy to clean, keeping it fresh and free from unwanted odors and bacteria. A convenient remote control puts easy operation right at your fingertips. Backed by a 2-year warranty on both parts and labor.

Hisense



Window Air Conditioner 18,000 BTU

| Mada | AW1822DR3W |
|------|-------------|
| | LAWISZZIKSW |

| Model # | AW1822DR3W | |
|------------------------------|-------------------------------|--|
| Performance | | |
| Cooling Capacity (BTUs/ hr) | 17700/ 18000 | |
| CEER | 10.7 | |
| Coverage | 1000 sq ft | |
| Dehumidification Pint/ 24 hr | 64.8 | |
| Refrigerant | R-32/630g | |
| Airflow (CFM) (High/ LOW) | 360-450 | |
| Noise Level in dB | 52/ 57 | |
| Electrical | • | |
| Voltage/ Freq/ Amps | 208/ 230 - 60/ 8.3/ 7.6*, N/A | |
| Plug Type/ NEMA# | C/ 6-20P | |
| Watts-cooling | 1640/ 1670 | |
| Electrical Receptacle | 230V/ 20A | |
| Power Cord Length (feet) | 6ft. (1.8m) | |
| Control Features | | |
| Thermostat Type | Electronic | |
| Fan Speeds - Cool/Fan | 3/3 | |
| Display Type | LED | |
| Timer | YES | |
| Unit Features | | |
| Chassis Type | Slide-out | |
| Air Deflection | 4-Way | |
| Air Discharge Type | Тор | |
| Washable Filter | YES, Easy Access | |
| Accessories | | |
| Installation Kit | YES | |
| Remote Control | YES | |
| Approvals | | |
| Safety | cULus | |
| Energy Star | NO | |

| Product Dimensions | | |
|--------------------------------------|-------------------|--|
| Unit Dimension W x H x D (mm) | 600×455×640 | |
| Net Weight (kg) (fits Not included) | 50 | |
| Unit Dimension W x H x D (inch) | 23.62×17.91×25.20 | |
| Net Weight (lbS) (fits Not included) | 110.2 | |
| Product | | |
| Parts & Labor | 2 years | |
| UPC | 819130029900 | |

Note:


*: Rated Amps(A) / accorded UL 60335 Safety

Product Images

Sleek Design with Touch Control



Window Opening



A: 18 1/2" (47cm) min B: 29 3/5" (75.2cm) - 42 1/10" (106.9cm)



All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2021 Hisense USA, All rights reserved

Hisense USA Corporation 7310 McGinnis Ferry Road, Suwanee, GA,30024 1-888-935-8880 www.hisense-usa.com