

Shunt trip release MX, ComPacT NSX, 220/240VAC 50/60Hz, 208/277VAC 60Hz, screwless spring terminal connections

LV429387

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

ComPacT
ComPact NSX100250
ComPacT NSX100250
ComPact NSX400630
ComPacT NSX400630
ComPact NSX100250 DC
ComPacT NSX100250 DC
ComPact NSX100250 DC PV
ComPacT NSX100250 DC PV
ComPact NSX400630 DC
ComPacT NSX400630 DC
ComPact NSX400630 DC PV
ComPacT NSX400630 DC PV
MX
Voltage release
Control
Opening coil
Shunt trip release
220240 V AC 50/60 Hz
208277 V AC 60 Hz
ComPacT ComPacT NSX
ComPacT ComPacT NSX DC
ComPact ComPact NSX
ComPact ComPact NSX DC
EasyPact EasyPact CVS
PowerPact PowerPact Multistandard

Complementary

Operating threshold	0.71.1 x Un opening	
Response time	50 ms	
Control signal type	Impulse Maintained	
Impulse duration	>= 20 ms	
Supply inrush power	10 VA	
Auxiliary connection terminal	spring 0.00080.002 in² (0.51.5 mm²) AWG 20AWG 16)	
Wire stripping length	0.3 in (7 mm)	

Ordering and shipping details

Category	US10NET01081
Discount Schedule	ONET

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

GTIN	3606480019098
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.77 in (4.500 cm)
Package 1 Width	1.93 in (4.900 cm)
Package 1 Length	2.48 in (6.300 cm)
Package 1 Weight	4.162 oz (118.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	2.91 in (7.400 cm)
Package 2 Width	4.17 in (10.600 cm)
Package 2 Length	9.37 in (23.800 cm)
Package 2 Weight	2.734 lb(US) (1.240 kg)
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Height	11.81 in (30.000 cm)
Package 3 Width	11.81 in (30.000 cm)
Package 3 Length	15.75 in (40.000 cm)
Package 3 Weight	17.364 lb(US) (7.876 kg)

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better

Recycled metal content at CR level	0
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	81ad7b79-ef4f-4746-bccc-1c5b358db33b
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Product contains halogen above thresholds
PVC free	Yes
Silicon free	No

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.