

NDA Compliant Product List - August 2025

	Model code	Short description	Full Description	Prod. page
Hanwha Product				
4K Cameras & up				
Camera - Network	PNM-C34404RQPZ	4K 4CH PTRZ + 2MP 40x PTZ AI Multi-directional camera	P series network AI based multi-directional 5 channel sensor outdoor vandal camera with 3 Point twist connection for quick and easy mount, Channel 1-4: 4 x 4K @ 15fps (H.265, H.264) AI ON, 20fps with AI OFF, IR 20m (65ft), Integrated 3.3~5.7mm(1.7x) motorized varifocal lenses, Channel 5: 2MP @ 60FPS PTZ with 40x zoom, WiselR 200m (656ft), PTZ Auto Tracking, SmartZoom to Preset / IVA Trigger (NOTE: AI object classif and IVA firmware upgrade comming soon), Channel 1-4 Analytics AI Object detection with classification: Person, Face, Vehicle, License plate and vehicle attributes Car, Bus, Truck, Motorcycle, Bicycle, Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit), BestShot, Motion detection, Defocus detection, Tampering, 2slot Max. 1TB(S12GBx2), HPOE(IEEE802.3bt type 4, Class 8) HPOE: Max 64.00W, typical 45.00W Includes HPOE Injector, TPM 2.0 (FIPS 140-2), IP66, NEMA4X, IK10. Compatible with SPM-4210 I/O IP box to connect alarms/audio devices and support camera's audio detection and sound classification analytics. Includes: Hanging mount adapter	Info
Camera - Network	PNM-C32083RVQ	32MP 4K x 4 Channel, AI, IR Multi-directional outdoor camera	P series network AI based multi-directional 4 channel sensor outdoor vandal camera, 4 x 4K @ 15fps (H.265, H.264) AI ON, 20fps with AI OFF, PoE+, WiselR 15m(49.2ft), HPOE: WiselR 20m(65.62ft), integrated 3.3~5.7mm(1.7x) motorized varifocal lenses, WiseStream III, Hallway View, Analytics AI Object detection with classification: Person, Face, Vehicle, License plate and vehicle attributes Car, Bus, Truck, Motorcycle, Bicycle, Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit), BestShot, Motion detection, Defocus detection, Tampering, 2slot Max. 1TB(S12GBx2), PoE+, TPM 2.0 (FIPS 140-2), IP66, NEMA4X, IK10, 2 configurable alarm I/O, Audio In/Out connectivity requires purchase of cable SPP-C7400, also compatible with SPM-4210 (sold separately) I/O IP box to connect alarms/audio devices and support camera's audio detection and sound classification analytics. PoE+ Injector can be purchased separately, part number SPO-6011	Info
Camera - Network	TNB-9000	8K AI Box	T series network 8K Box camera, 43.3 full frame CMOS sensor, 32MP @ 15fps, Autofocus, EF lens mount, triple codec: H.265/H.264/MJPEG with WiseStream II, Multiple streaming, BLC/DWDR, Auto Day & Night (ICR), new Deep Learning based Video Analytics (object classification), Motion detection, Directional detection, Defocus detection, Enter/Exit, Loitering, Virtual line, Tampering, Appear/Disappear, Audio detection, Sound classification, Bi-directional audio and micro SD/SDHC/SDXC slot, HPOE/12VDC ※ The lens is not included	Info
Camera - Network	TNO-A26081	26MP Ultra High Resolution AI Bullet Camera	T series network 26MP AI Bullet Camera, 1.8" APS CMOS image sensor, Max. 30fps, 0.2/0.02Lux D/N 55~250mm manual v lens, Supported Video Analytics based on AI: Traffic Pack, Factory Pack (no license key required), 2-way audio, 2x micro SD card, Operating temperature: -40°C~+50°C, HPOE (802.3bt type3, class6)/12VDC, 100/1000 SFP slot, IP66/IP67, IK10, NEMA4X (No PoE injector included)	Info
Camera - Network	PNM-C32083RQZ	32MP 4Kx 4, AI, IR, PTRZ, Multi-directional outdoor camera	P series network vandal outdoor Multi-Directional camera [AI ON] 4CH x 8MP @ 15FPS / [AI OFF] 4CH x 8MP @ 20FPS, Motorized Varifocal Lens with PTRZ function 4.38~9.33mm (FoV H: 112.1°~47.5°, V: 58°~26.6°), triple codec H.265/H.264/MJPEG, 120dB WDR; IR viewable length [PoE++ 25m(82ft), PoE+ 15m(49ft)], Analytics events based on AI engine: Classified object type: Person/Face/Vehicle/License plate; Attributes: Vehicle(Type and color: car/bus/truck/motorcycle/bicycle), Person (upper and bottom clothing color), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Appear/Disappear, WiselNR II(using AI engine), WiseStreamIII(Based on AI engine), I/O Box compatibility: TPM with FIPS 140-2 level2, micro SD card 512GB x2, IP66, IK10, NEMA4X, Operating Temperature: -40°C~+55°C(-40°F~+131°F), PoE++/PoE+, Hard-coated dome bubble	Info
Camera - Network	PNM-C2000QB	AI Remote head 2MP/5MP x 4CH camera	P series network remote head camera 4CH x 2MP @ 30FPS or 4CH x 5MP @ 15FPS, Triple codec H.265/H.264/MJPEG, 120dB WDR, Analytics events based on AI engine: Classified object type: Person/Face/Vehicle/License plate, Attributes: Vehicle(Type and color: car/bus/truck/motorcycle/bicycle), Person (upper and bottom clothing color), IVA (Virtual line/Area, Enter/Exit, Loitering, intrusion), Appear/Disappear, Business intelligence based on AI engine: People counting, Vehicle counting, Queue management, Heatmap, WiselNR II(Based on AI engine), WiseStreamIII(Based on AI engine), USB-C for easy installation, 4 x Selectable I/O, 4 x Audio inputs, 1 Audio Out, TPM with FIPS 140-3 level3, Built-in microSD card slots (Up to 512GB x2), 12VDC/PoE+, Compatible with SLA-T4680A/T4680VA, SLA-T2480A/T2480VA, SLA-T1080FA [Future compatibility with 5MP lenses]	Info
Camera - Network	PNM-C16083RVQ	16MP 4MP x 4 Channel, AI, IR Multi-directional outdoor camera	P series network AI based multi-directional 4 channel sensor outdoor vandal camera, 4 x 4MP @ 30fps, WiselR 15m IR, integrated 3.3~5.7mm(1.7x) motorized varifocal lenses, WiseStream III, Hallway View, Analytics AI Object detection with classification: Person, Face, Vehicle, License plate and vehicle attributes Car, Bus, Truck, Motorcycle, Bicycle, Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit), BestShot, Motion detection, Defocus detection, Tampering, 2slot Max. 1TB(S12GBx2), PoE+, TPM 2.0 (FIPS 140-2), IP66, NEMA4X, IK10, 2 configurable alarm I/O, Audio In/Out connectivity requires purchase of cable SPP-C7400, also compatible with SPM-4210 (sold separately) I/O IP box to connect alarms/audio devices and support camera's audio detection and sound classification analytics. PoE+ Injector can be purchased separately, part number SPO-6011	Info
Camera - Network	PNM-C16013RVQ	16MP 4MP x 4, AI, IR mini multi-directional camera	P series network vandal outdoor mini Multi-Directional camera 4CH x 4MP @ 15FPS, Fix Lens 3.19mm (FoV H: 97° V: 54°), triple codec H.265/H.264/MJPEG, 120dB WDR; IR viewable length 20m (65.6ft), USB port for easy installation, Analytics events based on AI engine: Object detection (Person/Vehicle (car/truck/bus/bicycle/bike)), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Appear/Disappear, WiselNR II(using AI engine), WiseStreamIII(Based on AI engine), I/O Box compatibility: TPM with FIPS 140-2 level2, micro SD card 512GB x2, IP66, IK10, NEMA4X, PoE+, Ø: 200mm, H: 80mm, (HPOE Injector is not included)	Info
Camera - Network	PNM-C16083RQZ	16MP 4MP x 4, AI, IR PTRZ, Multi-directional outdoor camera	P series network vandal outdoor Multi-Directional camera 4CH x 4MP @ 30FPS, Motorized PTRZ support, Motorized varifocal Lens 3.3~10.2mm (FoV H: 93°~29.8°, V: 53°~17.5°), triple codec H.265/H.264/MJPEG, 120dB WDR; IR viewable length [PoE+] 15m (49ft) / [PoE+++] 20m (65ft), Analytics events based on AI engine: Object detection [Person/Vehicle with color attributes (Car/Bus/Truck/Motorcycle/Bicycle)], IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Appear/Disappear, WiselNR II(using AI engine), WiseStreamIII(Based on AI engine), I/O Box compatibility: TPM with FIPS 140-2 level2, micro SD card 512GB x2, IP66, IK10, NEMA4X, Operating Temperature: -40°C~+55°C(-40°F~+131°F); PoE+ /PoE+++, Hard-coated dome bubble	Info
Camera - Network	PNM-C12083RVD	12MP 6MP x 2CH AI Multi-directional	P series network AI based multi-directional dual sensor outdoor vandal dome camera, 2 x 6MP @ 15fps, 360 degree 25m IR, 3.54~6.69mm motorised varifocal lenses, WisenR II, Auto prefer shutter control, WiseStream II, ExtremeWDR (120dB), Hallway View, Analytics AI Object detection with classification: Person, Face, Vehicle, License plate and vehicle attributes Car, Bus, Truck, Motorcycle, Bicycle, Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit), BestShot, Motion detection, Defocus detection, Tampering, SD Card slot 512GB max, PoE+, Secure by Default, TPM 2.0 (FIPS 140-2), IP66, NEMA4X, IK10. Compatible with SPM-4210 I/O IP box to connect alarms/audio devices and support camera's audio detection and sound classification analytics	Info
Camera - Network	PNM-C9022RV	8MP AI IR Panoramic Outdoor Vandal Dome	P series network AI based panoramic multi-sensor outdoor dome camera, 4 sensors x 2MP, 209° panoramic stitching, WiselR 20m, 8MP @ 20fps, 2.8mm fixed lens, triple codec H.265/H.264/MJPEG with WiseStream III, 120dB WDR, Auto Day & Night (ICR), Analytics AI Object detection (Person/Vehicle), Defocus detection, Motion detection, Tampering, Audio detection, Sound classification, Virtual area(Appear/Disappear), Handover to PTZ, Secure by Default, TPM 2.0 (FIPS 140-2), Audio In/Out, dual SD card slot, PoE+, 12VDC, IP66, IK10, NEMA4X	Info
Camera - Network	XNF-9013RV	12MP AI IR Fisheye Camera	X series powered by Wisenet 7 network 12M AI IR fisheye camera, 12MP @ 30fps, 1.08mm fixed lens, simple focus, triple codec H.265/H.264/MJPEG with WiseStream III (Based on AI engine, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), IR viewable length 8m with PoE 12m with PoE+, Wise IR, Next level Cybersecurity, Licence-free onboard Intelligent Video Analytics, People counting, Heatmap, Queue management, Handover, Variable View Mode, On Board Video Analytics, People counting, Heatmap, Queue management, Handover, Variable View Mode, On Board Dewarping, Digital PTZ, Bi-directional audio, 2x microSD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA 4X, PoE/12VDC	Info
Camera - Network	QNF-C9010	12MP Indoor AI Fisheye	Q Series Network Indoor Fisheye Dome Camera, 12MP sensor, Max resolution 3008x3008 @ 20fps, 1.76mm fixed lens, H185°/V185°, H.265/H.264/MJPEG codec, WiseStreamIII (Based on AI engine), WisenR II (Based on AI engine), extremeWDR (120dB), Digital rotation, AI based motion detection, Classified object type: Person/Vehicle, Object attributes (Person: Top/Bottom Clothing Color, Vehicle: Color), IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit(Dis)Appear), BestShot, Analytics events (Defocus, Tampering), AI-based business intelligence (Heatmap, Queue management, People counting), Built-in microSD Card slot (Up to 256GB), IP42, Operating temp: -10°C~+40°C (+14°F~+104°F), Power: PoE, RJ45.	Info
Camera - Network	QNF-C9010V	12MP Outdoor AI Fisheye	Q Series Network Outdoor Fisheye Dome Camera, 12MP sensor, Max resolution 3008x3008 @ 20fps, 1.76mm fixed lens, H185°/V185°, H.265/H.264/MJPEG codec, WiseStreamIII (Based on AI engine), WisenR II (Based on AI engine), extremeWDR (120dB), Digital rotation, AI based motion detection, Classified object type: Person/Vehicle, Object attributes (Person: Top/Bottom Clothing Color, Vehicle: Color), IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit(Dis)Appear), BestShot, Analytics events (Defocus, Tampering), AI-based business intelligence (Heatmap, Queue management, People counting), Built-in microSD Card slot (Up to 256GB), IP66, IK10, NEMA 4X, Operating temp: -40°C~+55°C (-40°F~+131°F), Power: PoE, RJ45.	Info
Camera - Network	XNO-9083R	8MP AI IR Bullet	X series powered by Wisenet 7 network AI IR outdoor vandal bullet camera, 8MP @ 30fps, 4.4~9.3mm motorized varifocal lens (2.1x), triple codec H.265/H.264/MJPEG with WiseStream III, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), IR viewable length 50m, Next level Cybersecurity, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection Audio detection, Sound classification, Shock detection, Appear/Disappear, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP66/IP67, IK10, NEMA4X, PoE+/12VDC	Info
Camera - Network	XNV-9083R	8MP AI IR Outdoor Vandal Dome	X series powered by Wisenet 7 network AI IR outdoor vandal dome camera, Modular structure X PLUS, 8MP @ 30fps, 4.4 ~ 9.3mm motorized varifocal lens (2.1x) (112.1°~47.5°), triple codec H.265/H.264 /MJPEG with WiseStream III, Multiple streaming, 120dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 50m, Analytics events based on AI engine (NPU) : Object detection (Person /Face/Vehicle – car, truck, bus, bicycle, motorcycle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC /SDXC slot, ONVIF S/G/T, USB port for easy installation, IP67/IP66/IP6K9K, IK10+, Nema 4X, PoE+/12VDC, white colour skins included	Info
Camera - Network	XNV-9083RZ	8MP AI IR Vandal Dome	X series powered by Wisenet 7 network AI IR vandal dome camera, Modular structure X PLUS, 8MP @ 30fps, 4.4 ~ 9.3mm motorized varifocal lens (2.1x), Colour 0.03 Lux (F1.3, 1/30sec, 30IRE), BW 0 Lux (IR LED on), IR viewable length: 30m(98.43ft) based on scene, Day & Night (ICR), extremeWDR (120 dB), WisenR II, WiseStreamIII, Analytics events based on AI engine (NPU) : Object detection (Person /Face/Vehicle – car, truck, bus, bicycle, motorcycle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP66/IP67/IP6K9K, NEMA4X, IK10+, Hard-coated dome bubble	Info

Camera - Network	XND-9083RV	8MP AI IR Dome	X series powered by Wisenet 7 network AI IR indoor vandal dome camera, Modular structure X PLUS, 8MP @30fps, 4.4 ~ 9.3mm motorized varifocal lens (2.1x) (112.1°~47.5°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 50m, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC /SDXC slot, ONVIF S/G/T, USB port for easy installation, IP52, IK10, PoE+/12VDC, white colour skins included	info
Camera - Network	XND-A9084RV	8MP AI IR Indoor Dome	Powered by WN9, Indoor Network AI IR Dome Camera, 8MP resolution @ 30FPS, 4.4~9.3mm (2.1x), (113°~47°) motorized varifocal lens, H.265/H.264/MJPEG codec, IR viewable length 40m (131.2ft), USB-C port for easy installation, Day & Night (ICR), extremeWDR (120dB), Hard-coated dome bubble, DIS with built-in gyro sensor, Handover, AI-based WiseStream, WiseNR II (using AI engine), Dynamic privacy mask, I/A events based on AI engine (Motion & Object detection, Line crossing, I/A area, Slip & Fall, Sound classification), Classified object types (Person/Face/Vehicle/License plate), Object attributes (Person: Gender/Top/Bottom clothing color/Bag, Face: Age/Gender/Mask/Glasses, Vehicle: type/color), BestShot, Analytics events (Defocus, Motion, Tampering, Fog, Audio & Shock detection), AI-based business intelligence (People/Vehicle/Crowd counting, Queue management, Heatmap), Built-in microSD card slot (Up to 1TB), IP52, IK10, Operating temperature: -10°C~+50°C (14°F~+122°F), Power: PoE, Metal shielded RJ-45.	info
Camera - Network	XNO-A9084R	8MP AI IR Bullet	Powered by WN9, Outdoor Network AI IR Vandal Bullet Camera, 8MP resolution @ 30FPS, 4.4~9.3mm(2.1x), (113°~47°) motorized varifocal lens, H.265/H.264/MJPEG codec, IR viewable length 40m (131.2ft), USB-C port for easy installation, Day & Night (ICR), extremeWDR (120dB), Hard-coated dome bubble, DIS with built-in gyro sensor, Handover, AI-based WiseStream, WiseNR II (using AI engine), Dynamic privacy mask, I/A events based on AI engine (Motion & Object detection, Line crossing, I/A area, Slip & Fall, Sound classification), Classified object types (Person/Face/Vehicle/License plate), Object attributes (Person: Gender/Top/Bottom clothing color/Bag, Face: Age/Gender/Mask/Glasses, Vehicle: type/color), BestShot, Analytics events (Defocus, Motion, Tampering, Fog, Audio & Shock detection), AI-based business intelligence (People/Vehicle/Crowd counting, Queue management, Heatmap), Built-in microSD card slot (Up to 1TB), IP66/IP67, IK10, NEMA 4X, NEMA-TS 2(2.2.7.2.8, 2.2.8, 2.2.9), Operating temp: -40°C~+60°C (-40°F~+140°F), Power: PoE, Metal shielded RJ-45.	info
Camera - Network	XNV-A9084R	8MP AI IR Outdoor Vandal Dome	Powered by WN9, Outdoor Network AI IR Vandal Dome Camera, 8MP resolution @ 30FPS, 4.4~9.3mm (2.1x), (113°~47°) motorized varifocal lens, H.265/H.264/MJPEG codec, IR viewable length 40m (131.2ft), USB-C port for easy installation, Day & Night (ICR), extremeWDR (120dB), Hard-coated dome bubble, DIS with built-in gyro sensor, Handover, AI-based WiseStream, WiseNR II (using AI engine), Dynamic privacy mask, I/A events based on AI engine (Motion & Object detection, Line crossing, I/A area, Slip & Fall, Sound classification), Classified object types (Person/Face/Vehicle/License plate), Object attributes (Person: Gender/Top/Bottom clothing color/Bag, Face: Age/Gender/Mask/Glasses, Vehicle: type/color), BestShot, Analytics events (Defocus, Motion, Tampering, Fog, Audio & Shock detection), AI-based business intelligence (People/Vehicle/Crowd counting, Queue management, Heatmap), Built-in microSD card slot (Up to 1TB), IP66/IP67, IK10, NEMA 4X, NEMA-TS 2(2.2.7.2.8, 2.2.8, 2.2.9), Operating temp: -40°C~+50°C (-40°F~+122°F), Power: PoE, Metal shielded RJ-45.	info
Camera - Network	XNB-9003	8MP AI Box	X series powered by Wisenet 7 network AI box camera, 1/1.8" progressive CMOS, 8MP @30fps, 0.03 Lux@F1.2 (Color), 0.03 Lux@F1.2 (B/W), 30IRE simple focus, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, Digital Image Stabilization with built-in Gyro sensor, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, PoE/12VDC ※ The lens is not included	info
Camera - Network	XNO-C9083R	8MP AI IR Bullet	X series powered by Wisenet 7 network AI outdoor vandal bullet camera, 8MP @30fps, 4.4~9.3mm motorized varifocal lens (2.1x), triple codec H.265/H.264/MJPEG with WiseStream III, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), IR viewable length 40m, Next level Cybersecurity, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66/IP67, IK10, NEMA4X, PoE/12VDC	info
Camera - Network	XNV-C9083R	8MP AI IR Vandal Dome	X series powered by Wisenet 7 network AI IR outdoor vandal dome camera, 8MP @30fps, 4.4 ~ 9.3mm motorized varifocal lens (2.1x) (112.1°~47.5°), triple codec H.265/H.264 /MJPEG with WiseStream III, Multiple streaming, 120dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 40m, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and single microSD/SDHC /SDXC slot, ONVIF S/G/T, USB port for easy installation, IP67/IP66, IK10, Nema 4x, PoE/12VDC, white colour skins included	info
Camera - Network	XND-C9083RV	8MP AI IR Dome	X series powered by Wisenet 7 network AI IR indoor vandal dome camera, 8MP @30fps, 4.4 ~ 9.3mm motorized varifocal lens (2.1x) (112.1°~47.5°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 40m, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and single microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP52, IK10, PoE/12VDC, white skins included	info
Camera - Network	XNP-C9310R	8MP 31x AI Focus IR PTZ	X series Powered by WN7 and AI, 8MP (4K UHD) @ 30FPS resolution, 6.91mm~214.64mm (31x) lens with Wise AF intelligent autofocus, adaptive Wise IR (250m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG triple codec with WiseStream II (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Face/Vehicle/License plate), Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW I/O box), AI object auto-tracking (Person/Vehicle) with target lock tracking, BL, HLC, SSDR, lens heater for water/snow removal, IP66, IP67, IK10, NEMA4X, NEMA-TS 2(2.2.8, 2.2.9), FIPS 140-2, HPoE injector included, Operating Temperature -50°C~+55°C (-58°F ~ +131°F), (Compatible with I/O Box SPM-4210)	info
Camera - Network	XNP-C9303RW	8MP 30x IR AI PTZ with built-in wiper	X series powered by Wisenet 7 AI network outdoor IR PTZ camera, 8MP @30fps, 30x Optical Zoom Lens (5 ~ 150mm) (57.42° ~ 2.19°), 360° Endless Pan range, 500°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), IR viewable length 200m, Analytics events based on AI engine, Defocus / Motion / Fog / Shock detection, Tampering, Virtual area, Classified object (Person/Face/Vehicle/License plate), Attributes (Vehicle type), Object auto tracking (Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, NEMA-TS2, PoE+, Built-in wiper * Alarm outputs, Audio detection, Sound classification (with NW I/O Box which can be purchased separately)	info
Camera - Network	XNP-C9253R	8MP 25x IR AI PTZ	X series powered by Wisenet 7 network outdoor AI IR PTZ camera, 8MP @30fps, 25x Optical Zoom Lens (5 ~ 125mm) (57.42° ~ 2.71°), 360° Endless Pan range, 700°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), IR viewable length 200m, Analytics events based on AI engine, Defocus / Motion / Fog / Shock detection, Tampering, Virtual area, Classified object (Person/Face/Vehicle/License plate), Attributes (Vehicle type), Object auto tracking (Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, NEMA-TS2, PoE+ * Alarm outputs, Audio detection, Sound classification (with NW I/O Box which can be purchased separately)	info
Camera - Network	XNP-C9253	8MP 25x AI PTZ	X series powered by Wisenet 7 network outdoor AI PTZ camera, 8MP @30fps, 25x Optical Zoom Lens (5 ~ 125mm) (57.42° ~ 2.71°), 360° Endless Pan range, 700°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), Analytics events based on AI engine, Defocus / Motion / Fog / Shock detection, Tampering, Virtual area, Classified object (Person/Face/Vehicle/License plate), Attributes (Vehicle type), Object auto tracking (Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, NEMA-TS2, PoE+ * Alarm outputs, Audio detection, Sound classification (with NW I/O Box which can be purchased separately)	info
Camera - Network	PNO-A9311R	8MP AI IR 31x Zoom Bullet	P seriesNetwork AI IR 31x Zoom Bullet Camera, Max 8M resolution @ 30FPS, 0.075Lux@F1.36 (Color), 0Lux (B/W, IR LED on), Day & Night (ICR), 6.91~214.7mm(31x) zoom lens, WiseIR 70m (229.66ft), WDR(120dB) H.265, H.264, MJPEG codec, WiseStream II, WiseStream III (Using AI engine), Video Analytics based on AI (Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Slip&Fall detection, Attribute, BestShot People counting, Heatmap, Queue management based on AI, Face Mask Detection, Social Distancing Detection, Compatible with Wisenet Retail Insight v2.0 for Business Intelligence, Age/gender based People counting, Heatmap, Queue management, Modular structure for easy installation, 2x micro SD card (512GB x2), Operating temperature: -40°C~+55°C(-40°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45, IP66/IP67/IP6K9K, IK10, NEMA4X	info
Camera - Network	PNO-A9081R	8MP AI IR Bullet	P series network 8MP AI IR outdoor vandal bullet camera, 8MP @30fps, 4.5~10mm motorized varifocal lens (2.2x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 30m, Classified object type : Person/Face/Vehicle/License plate with attributes, BestShot per object, Analytics events based on AI engine : Object detection, Directional detection, Digital auto tracking, Enter/Exit, Loitering, Virtual line, Analytics events : Defocus detection, Motion detection, Appear/Disappear, Tampering, Audio detection, Sound classification, Shock detection, Business Analytics, Hallway view, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP66/IP67, IK10+, NEMA4X, PoE+/12VDC	info
Camera - Network	PNV-A9081R	8MP AI IR Outdoor Vandal Dome	P series network 8MP AI IR outdoor vandal dome camera, Modular structure X PLUS, 8MP @30fps, 4.5~10mm motorized varifocal lens (2.2x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 30m, Classified object type : Person/Face/Vehicle/License plate with attributes, BestShot per object, Analytics events based on AI engine : Object detection, Directional detection, Digital auto tracking, Enter/Exit, Loitering, Virtual line, Analytics events : Defocus detection, Motion detection, Appear/Disappear, Tampering, Audio detection, Sound classification, Shock detection, Business Analytics, Hallway view, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP66/IP67/ IP6K9K, IK10+, NEMA4X, PoE+/12VDC	info
Camera - Network	PND-A9081RV	4K AI IR Indoor vandal dome	P series network 8MP AI IR indoor dome camera, Modular structure X PLUS, 8MP @30fps, 4.5~10mm motorized varifocal lens (2.2x), triple codec H.265/H.264/MJPEG with WiseStream II, WiseStream III, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 30m, Classified object type : Person/Face/Vehicle/License plate with attributes, BestShot per object, Analytics events based on AI engine : Object detection, Directional detection, Digital auto tracking, Enter/Exit, Loitering, Virtual line, Analytics events : Defocus detection, Motion detection, Appear/Disappear, Tampering, Audio detection, Sound classification, Shock detection, Business Analytics, Hallway view, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP52, IK10, PoE+/12VDC	info

Camera - Network	PND-A9081RF	8MP AI IR Flush Mount Indoor Dome	P series network 8MP AI IR indoor flush mount dome camera, Modular structure X PLUS, 8MP @30fps, 4.5–10mm motorized varifocal lens (2.2x), triple codec H.265/H.264/MJPEG with WiseStream II, WiseStream III, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 30m, Classified object type : Person/Face/Vehicle/License plate with attributes, BestShot per object, Analytics events based on AI engine : Object detection, Directional detection, Digital auto tracking, Enter/Exit, Loitering, Virtual line, Analytics events : Defocus detection, Motion detection, Appear/Disappear, Tampering, Audio detection, Sound classification, Shock detection, Business Analytics, Hallway view, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP52, IK10, Plenum rate, PoE+/12VDC	Info
Camera - Network	PNB-A9001	8MP AI Box	P series network 8MP AI box camera, 8MP @30fps, triple codec H.265/H.264/MJPEG with WiseStream II, WiseStream III, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), Classified object type : Person/Face/Vehicle/ License plate with attributes, BestShot per object, Analytics events based on AI engine : Object detection, Directional detection, Digital auto tracking, Enter/Exit, Loitering, Virtual line, Analytics events : Defocus detection, Motion detection, Appear/Disappear, Tampering, Audio detection, Sound classification, Shock detection, Business Analytics, Hallway view, Bi-directional audio and dual microSD/SDHC/SDXC slot, PoE+/12VDC ※ The lens is not included	Info
Camera - Network	QNE-C9013RL	8MP Dual Light AI Outdoor FlatEye	Q series network AI outdoor flat-eye camera, 8MP @ 30fps, 3mm fixed focal lens (H: 108°/ V: 59°), triple codec H.265/H.264/MJPEG with Wisestream III, 120dB WDR, Dual Light – White LED range 30m (98ft), IR viewable length 30m (98ft), Motion Detection based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/Dis/Appear), defocus detection, hallway View, SD card, video analytics, IP66/IP67, IK10, PoE, Operating temperature -40°C→+60°C(-40°F ~ +140°F) white color	Info
Camera - Network	QNO-C9083R	8MP AI IR Bullet	Q series AI network IR outdoor bullet camera, 8MP @30fps, 3.2 – 10.2mm motorized varifocal lens (3.2x), triple codec H.265/H.264/MJPEG with WiseStream I, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 30m, Object detection (Person/Vehicle), Vehicle Type AI attributes, Analytics events based on AI engine (motion detection, object detection, virtual line, virtual area), WiseMD (AI Motion detection), LDC (Lens Distortion Correction), Hard coated dome bubble, Gore valve, SD/SDHC/SDXC slot, IP66, IK10, PoE	Info
Camera - Network	QNV-C9083R	8MP AI IR Vandal Dome	Q series AI network IR outdoor vandal dome camera, 8MP @30fps, 3.2 – 10.2mm motorized varifocal lens (3.2x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 30m, Object detection (Person/Vehicle), Vehicle Type AI attributes, Analytics events based on AI engine (motion detection, object detection, virtual line, virtual area), WiseMD (AI Motion detection), LDC (Lens Distortion Correction), Hard coated dome bubble, Gore valve, SD/SDHC/SDXC slot, IP66, IK10, PoE	Info
Camera - Network	QNV-C9011R	8MP AI IR Micro Vandal Dome	Q series AI network IR Micro vandal dome camera, 8MP @30fps, 3.0mm fixed lens, triple codec H.265/H.264/MJPEG, Multiple streaming up to 5 profiles, 120dB WDR, Day & Night (ICR), High Powered IR LEDs with IR viewable length 20m, Analytics events based on AI engine: Object detection (Person/Vehicle – car, truck, bus, bicycle, motorcycle)/IVA (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion)/Analytics events : Defocus detection, Tampering, single microSD/SDHC/SDXC slot, ONVIF S/G/T/M, USB port for easy installation, IP66, IK10, NEMA4X, PoE, white	Info
Camera - Network	PNO-A9081RLP	8MP AI ANPR IR Bullet	P series network 8MP AI IR outdoor vandal bullet camera with embedded Wisenet Road AI application for ANPR, MMCR (make, model, colour recognition) and vehicle classification analytics, smart search, black/white list, statistics, barrier control, VMS/JSON integration support, Pre-installed with 32GB Micro SD to support 10,000 ANPR images, 8MP @30fps, 4.5–10mm motorized varifocal P iris lens (2.2x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, True Day & Night (ICR), IR viewable length 30m, other analytics events: Shock detection, Motion detection, Tampering detection, Defocus detection, Audio detection, Sound classification, Bi-directional audio, 1 Input/1 Output, PoE+/12VDC, IP66/IP67, IK10+, NEMA4X	Info
Camera - Network	PNO-A9311RLP	8MP, AI IR Zoom (31x), Bullet Camera with Wisenet Road AI	P series 8MP AI IR 31x Bullet Camera with Wisenet Road AI application and 32GB SD card - high-speed traffic surveillance with coverage of up to two traffic lanes at speeds of up to 100kmh (65mph) 4K resolution @ 30FPS, 0.05Lux@F1.6 (Color), 0Lux (B/W, IR LED on), Day & Night(ICR), 6.91–214.64mm (31x) zoom lens, WDR(120dB) H.265, H.264, MJPEG codec, Operating temperature: -40°C→+55°C(-40°F ~ +131°F), Power: PoE+/12VDC, Metal shielded RJ-45, IP66/IP67, IK10, NEMA4X. Wisenet Road AI application (Pre-installed) includes: Licence Plate Recognition, Make/Model/Colour Recognition, Vehicle class recognition (Unidentified, Car, SUV, VAN, LCV, Truck, Bus, Bike), List notification, Direction detection (high performance mode only), Smart Search (plate, country, brand, model, colour, vehicle type), Vehicle statistics (by day, week, top 5 brands, top 5 models and types)	Info
Camera - Network	PNV-A9081RLP	8MP AI ANPR IR Outdoor Vandal Dome	P series network 4K AI IR outdoor vandal dome camera with embedded Wisenet Road AI application for ANPR, MMCR (make, model, colour recognition) and vehicle classification analytics, smart search, black/white list, statistics, barrier control, VMS/JSON integration support, Pre-installed with 32GB Micro SD to support 10,000 ANPR images, Modular structure X PLUS, 8MP @30fps, 4.5–10mm motorized varifocal P iris lens (2.2x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, True Day & Night (ICR), IR viewable length 30m, other analytics events: Shock detection, Motion detection, Tampering detection, Defocus detection, Audio detection, Sound classification, Bi-directional audio, 1 Input/1 Output, PoE+/12VDC, IP66/IP67/IP6K9K, IK10+, NEMA4X	Info
Camera - Network	PNB-A9001LP	8MP AI ANPR Box	P series network 8MP AI box camera with embedded Wisenet Road AI application for ANPR, MMCR (make, model, colour recognition) and vehicle classification analytics, smart search, black/white list, statistics, barrier control, VMS/JSON integration support, Pre-installed with 32GB Micro SD to support 10,000 ANPR images, 8MP @30fps, Excludes lens (C mount, CS mount), DC auto iris, P iris, Manual, I-CS, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Auto Day & Night (ICR), other analytics events: Shock detection, Motion detection, Tampering detection, Defocus detection, Audio detection, Sound classification, Bi-directional audio, 1 Input/1 Output, PoE+/12VDC ※ The lens is not included	Info
Camera - Network	PNM-9085RQZ1	20MP 5MP x 4 Outdoor IR PTRZ Dome	P series network outdoor Multi-sensor Multi-Directional IR PTRZ dome camera with Digital Image Stabilization, 4 sensors x 5MP, max 8MP @30fps, 4 x 4.13 – 9.4mm motorized varifocal lenses (2.3x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, WDR 120dB, Auto Day & Night (ICR), IR viewable length 30m, Advanced Video Analytics and Sound Classification, Motion detection, Hallway view, Fog detection, HLC, Digital Image Stabilization, 4x SD/SDHC/SDXC slot, IP66, IK10, NEMA4X, HPoE/12VDC. Includes HPoE Injector.	Info
Camera - Network	PNM-9031RV	15MP IR Panoramic Outdoor Vandal Dome	P series network panoramic multi-sensor outdoor dome camera, 4 sensors x 5MP, 192° panoramic stitching, WiseIR 20m, 15MP @20fps, 4.3mm fixed lens, triple codec H.265/H.264/MJPEG with WiseStream II, 120dB WDR, Auto Day & Night (ICR), Advanced Video Analytics, Motion detection, Handover to PTZ, Sound classification, Heatmap, LDC (Lens Distortion Correction), Auto In/Out, dual SD card slot, PoE+, 12VDC, IP66, IK10, NEMA4X	Info
Camera - Network	XNF-9010RVM	12MP IR Fisheye Camera	X series powered by Wisenet 7 network 12M AI IR fisheye camera, 12MP @30fps, 1.08mm fixed lens, simple focus, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), IR viewable length 10m, Next level Cybersecurity, Licence-free onboard Intelligent Video Analytics, People counting, Heatmap, Queue management, Handover, Variable View Mode, On Board Dewarping, Digital PTZ, Bi-directional audio, 2x microSD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA 4X, PoE/12VDC, M12 Connector	Info
Camera - Network	XNF-9010RV	12MP IR Fisheye Camera	X series powered by Wisenet 7 network 12M AI IR fisheye camera, 12MP @30fps, 1.08mm fixed lens, simple focus, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), IR viewable length 10m, Next level Cybersecurity, Licence-free onboard Intelligent Video Analytics, People counting, Heatmap, Queue management, Handover, Variable View Mode, On Board Dewarping, Digital PTZ, Bi-directional audio, 2x microSD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA 4X, PoE/12VDC	Info
Camera - Network	XNF-9010RS	12MP IR Outdoor Stainless Steel Vandal Fisheye	X series powered by Wisenet 7 network 4K IR indoor fisheye stainless steel camera, 12MP @30fps, 1.08mm fixed lens, simple focus, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), IR viewable length 10m, Next level Cybersecurity, Licence-free onboard Intelligent Video Analytics, People counting, Heatmap, Queue management, Handover, Variable View Mode, On Board Dewarping, Digital PTZ, Bi-directional audio, 2x microSD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA 4X, PoE/12VDC	Info
Camera - Network	PNM-9084RQZ1	8MP 2MP x 4 Outdoor IR PTRZ Dome	P series network outdoor Multi-sensor Multi-Directional IR PTRZ dome camera with Digital Image Stabilization, 4 sensors x 2MP, max 8MP @60fps, 4 x 3.2 – 10mm motorized varifocal lenses (3.1x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, WDR 120dB, Auto Day & Night (ICR), IR viewable length 30m, Advanced Video Analytics and Sound Classification, Motion detection, Hallway view, Fog detection, HLC, Digital Image Stabilization, 4x SD/SDHC/SDXC slot, IP66, IK10, NEMA4X, HPoE/12VDC. Includes HPoE Injector.	Info
Camera - Network	PNM-9084QZ1	8MP 2MP x 4 Outdoor PTRZ Dome	P series network outdoor Multi-sensor Multi-Directional PTRZ dome camera with Digital Image Stabilization, 4 sensors x 2MP, max 8MP @60fps, 4 x 3 – 6mm motorized varifocal lenses (2x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, WDR 120dB, Auto Day & Night (ICR), Advanced Video Analytics, Motion detection, Hallway view, Fog detection, HLC, Digital Image Stabilization, 4x SD/SDHC/SDXC slot, IP66, IK10, NEMA4X, HPoE Only. NOTE: HPoE Injector must be purchased separately, please refer to SPO-6011	Info
Camera - Network	PNM-12082RVD	12MP 6MP x 2CH Multi-directional	P series network multi-directional dual sensor outdoor vandal dome camera, 2 x 6MP @15fps, 360 degree 25m IR, 3.54–6.69mm motorised varifocal lenses, WiseNR, WiseStream II, ExtremeWDR (150dB), Defog, Hallway View, Analytics Virtual line (Crossing/Direction), Virtual area (Loitering/Enter/Exit), Motion detection, Defocus detection, Tampering, SD Card slot 512GB max, PoE+, Secure by Default, TPM 2.0 (FIPS 140-2), IP66, NEMA4X, IK10. Compatible with SPM-4210 I/O IP box to connect alarms/audio devices and support camera's audio detection and sound classification analytics	Info
Camera - Network	PNM-9002VQ	Quad Lens Multi-sensor Outdoor Vandal Dome	P series network outdoor Multi-sensor Multi-Directional dome camera, 4 sensors x 2MP/5MP, 8MP ~20MP (2MP @ 60fps or 5MP @30fps), 4 fixed lense modules, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR @2MP or 120dB WDR @5MP, Auto Day & Night (ICR), Advanced Video Analytics, Motion detection, Hallway view, Fog detection, HLC, Digital Image Stabilization, 4x SD/SDHC/SDXC slot, IP66, IK10, PoE+ 2MP Lens modules (sold separately): SLA-2M2400Q (2.4mm), SLA-2M2800Q (2.8mm), SLA-2M3600Q (3.6mm), SLA-2M6000Q (6mm) 5MP Lens modules (sold separately): SLA-5M3700Q (3.7mm), SLA-5M4600Q (4.6mm), SLA-5M7000Q (7.0mm)	Info
Camera - Network	XNO-9082R	8MP IR Bullet	X series powered by Wisenet 7 network outdoor vandal bullet camera, 8MP @30fps, 2.8–8.4mm motorized varifocal lens (3x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), IR viewable length 40m, Next level Cybersecurity, Licence-free onboard Advanced Video Analytics and Business Analytics, Sound Classification, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, Face/upper body detection, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP66/IP67, IK10, NEMA4X, PoE/12VDC/24VAC	Info

Camera - Network	XNV-9082R	8MP IR Outdoor Vandal Dome	X series powered by Wisenet 7 network outdoor vandal dome camera, Modular structure X PLUS, 8MP @30fps, 2.8-8.4mm motorized varifocal lens (3x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), IR viewable length 40m, Next level Cybersecurity, Licence-free onboard Advanced Video Analytics and Business Analytics, Sound Classification, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, Face/upper body detection, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP66/IP67/IP6K9K, IK10+, NEMA4X, PoE/12VDC	Info
Camera - Network	XND-9082RF	8MP IR Flush Mount Indoor Dome	X series powered by Wisenet 7 network indoor flush mount dome camera, Modular structure X PLUS, 8MP @30fps, 2.8-8.4mm motorized varifocal lens (3x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), IR viewable length 40m, Next level Cybersecurity, Licence-free onboard Advanced Video Analytics and Business Analytics, Sound Classification, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, Face/upper body detection, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP52, IK10, Plenum rate, PoE/12VDC	Info
Camera - Network	XND-9082RV	8MP IR Indoor Dome	X series powered by Wisenet 7 network indoor vandal dome camera, Modular structure X PLUS, 8MP @30fps, 2.8-8.4mm motorized varifocal lens (3x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), IR viewable length 40m, Next level Cybersecurity, Licence-free onboard Advanced Video Analytics and Business Analytics, Sound Classification, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, Face/upper body detection, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP52, IK10, PoE/12VDC	Info
Camera - Network	XNB-9002	8MP Box	X series powered by Wisenet 7 network box camera, 8MP @30fps, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), Next level Cybersecurity, Licence-free onboard Advanced Video Analytics and Business Analytics, Sound Classification, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, Face/upper body detection, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, PoE/12VDC/24VAC ※ The lens is not included	Info
Camera - Network	XNP-9300RW	4K 30x IR Outdoor PTZ	X series powered by Wisenet 7 network IR outdoor PTZ camera with built-in wiper, 8MP @30fps, 30X Optical Zoom Lens (5 ~ 150mm) (57.42° ~ 2.19°), 360° Endless Pan range, 500°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), IR viewable length 200m, Intelligent Video Analytics, Motion detection, Fog detection, Tampering, Object auto tracking(Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, HPoE * Alarm outputs, Audio detection, Sound classification(with NW I/O Box which can be purchased separately)	Info
Camera - Network	XNP-9250R	4K 25x IR Outdoor PTZ	X series powered by Wisenet 7 network IR outdoor PTZ camera, 8MP @30fps, 25x Optical Zoom Lens (5 ~ 125mm) (57.42° ~ 2.71°), 360° Endless Pan range, 700°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), IR viewable length 200m, Intelligent Video Analytics, Motion detection, Fog detection, Tampering, Object auto tracking(Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, NEMA-TS2, HPoE * Alarm outputs, Audio detection, Sound classification (with NW I/O Box which can be purchased separately)	Info
Camera - Network	XNP-9250	4K 25x Outdoor PTZ	X series powered by Wisenet 7 network outdoor PTZ camera, 8MP @30fps, 25x Optical Zoom Lens (5 ~ 125mm) (57.42° ~ 2.71°), 360° Endless Pan range, 700°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), Intelligent Video Analytics, Motion detection, Fog detection, Tampering, Object auto tracking(Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, NEMA-TS2, HPoE * Alarm outputs, Audio detection, Sound classification (with NW I/O Box which can be purchased separately)	Info
Camera - Network	PNM-9000QB	4x 2MP Covert Main Module	P series powered by Wisenet 7 remote head cam, 4CHx 2MP @60fps, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Advanced Video Analytics and Sound Classification and Business Analytics, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and SD/SDHC/SDXC slot, USB port for easy installation, PoE/12VDC, Compatible with following lens modules SLA-T2480A, SLA-T2480VA, SLA-T4680A, SLA-T4680VA, SLA-T1080FA (not included) ※ The lens is not included	Info
Camera - Network	QNF-9010	12MP Indoor Fisheye	Q series network indoor fisheye, 12MP CMOS sensor, 3008x3008 @ 30fps, 1.08mm fixed lens(187°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, defocus, motion detection, tampering, people counting, heatmap, SD/SDHC/SDXC slot, HLC, PoE, IP42	Info
Camera - Network	TNF-9010	12MP Sensor Fisheye Parking Guidance	T series powered by Wisenet 7 network 12MP sensor Fisheye Camera - For parking guidance, 12MP @30fps, Stereographic type lens, 360° monitoring with onboard dewarping, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), up to 16 lots, various LED colours & single/split mode, Central/side roadway installations AI based parking detection, Variable/View Mode, Digital PTZ, Defocus/audio detection and tampering, microSD/SDHC/SDXC 1 slot up to 512GB, PoE/12VDC	Info
6MP Cameras				
Camera - Network	XNV-8093R	6MP AI IR Vandal Dome	X series powered by Wisenet 7 AI network IR outdoor vandal dome camera, Modular structure X PLUS, 6MP @30fps, 10.9 ~ 29mm motorized varifocal lens (2.7x) (42°~15°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 70m, Analytics events based on AI engine (NPU) : Object detection (Person /Face/Vehicle – car, truck, bus, bicycle, motorcycle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Lottering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC /SDXC slot, ONVIF S/G/T, USB port for easy installation, IP67/IP66/IP6K9K, IK10+, Nema 4X, PoE+/12VDC, white colour skins included	Info
Camera - Network	XND-8093RV	6MP AI IR Dome	X series powered by Wisenet 7 AI network IR indoor vandal dome camera, Modular structure X PLUS, 6MP @30fps, 10.9 ~ 29.0mm motorized varifocal lens (2.7x) (42.0~15.0°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 70m, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Lottering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC /SDXC slot, ONVIF S/G/T, USB port for easy installation, IP52, IK10, PoE+/12VDC, white colour skins included	Info
Camera - Network	XNO-8083R	6MP AI IR Bullet	X series powered by Wisenet 7 AI network outdoor vandal bullet camera, 6MP @30fps, 4.4~9.3mm motorized varifocal lens (2.1x), triple codec H.265/H.264/MJPEG with WiseStream III, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), IR viewable length 50m, Next level Cybersecurity, Analytics events based on AI engine (NPU) : Object detection (Person /Face/Vehicle – car, truck, bus, bicycle, motorcycle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Lottering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC /SDXC slot, IP66/IP67, IK10, NEMA4X, PoE+/12VDC	Info
Camera - Network	XNV-8083R	6MP AI IR Vandal Dome	X series powered by Wisenet 7 AI network IR outdoor vandal dome camera, Modular structure X PLUS, 6MP @30fps, 4.4 ~ 9.3mm motorized varifocal lens (2.1x) (112.1°~47.5°), triple codec H.265/H.264/MJPEG with WiseStream III, Multiple streaming, 120dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 50m, Analytics events based on AI engine (NPU) : Object detection (Person /Face/Vehicle – car, truck, bus, bicycle, motorcycle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Lottering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC /SDXC slot, ONVIF S/G/T, USB port for easy installation, IP67/IP66/IP6K9K, IK10+, Nema 4X, PoE+/12VDC, white colour skins included	Info
Camera - Network	XNV-8083RZ	6MP AI IR Vandal Dome	X series powered by Wisenet 7 AI network IR vandal dome camera, Modular structure X PLUS, 6MP @30fps, 4.4 ~ 9.3mm motorized varifocal lens (2.1x), Colour 0.03 Lux (F1.3, 1/30sec, 30IRE), BW 0 Lux (IR LED on), IR viewable length: 30m(98.43ft) based on scene, Day & Night (ICR), extremeWDR (120 dB), WiseNR II, WiseStreamIII, Analytics events based on AI engine (NPU) : Object detection (Person /Face/Vehicle – car, truck, bus, bicycle, motorcycle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Lottering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP66/IP67/IP6K9K, NEMA4X, IK10+, Hard-coated dome bubble	Info
Camera - Network	XNV-8083Z	6MP AI Vandal Dome	X series powered by Wisenet 7 AI network non IR vandal dome camera, Modular structure X PLUS, 6MP @30fps, 4.4 ~ 9.3mm motorized varifocal lens (2.1x), Colour 0.03 Lux (F1.3, 1/30sec, 30IRE), BW 0 Lux (IR LED on), Day & Night (ICR), extremeWDR (120 dB), WiseNR II, WiseStreamIII, Analytics events based on AI engine (NPU) : Object detection (Person /Face/Vehicle – car, truck, bus, bicycle, motorcycle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Lottering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC /SDXC slot, ONVIF S/G/T, USB port for easy installation, IP66/IP67/IP6K9K, NEMA4X, IK10+, Hard-coated dome bubble	Info
Camera - Network	XND-8083RV	6MP AI IR Dome	X series powered by Wisenet 7 AI network IR indoor vandal dome camera, Modular structure X PLUS, 6MP @30fps, 4.4 ~ 9.3mm motorized varifocal lens (2.1x) (112.1°~47.5°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 50m, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/Licence plate), IVA (Virtual line/Area, Enter/Exit, Lottering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC /SDXC slot, ONVIF S/G/T, USB port for easy installation, IP52, IK10, PoE+/12VDC, white colour skins included	Info

Camera - Network	XNB-8003	6MP AI Box	X series AI powered by Wisenet 7 AI network box camera, 1/1.8" progressive CMOS, 6MP @30fps, 0.03 Lux@F1.2 (Color), 0.03 Lux@F1.2 (B/W), 30IRE simple focus, triple codec H.265/H.264/MJPEG with WiseStream III, Multiple streaming, 120dB WDR, True Day & Night (ICR), Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/Licence plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear,Digital Image Stabilization with built-in Gyro sensor, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, PoE/12VDC ※ The lens is not included	Info
Camera - Network	XNO-C8083R	6MP AI IR Bullet	X series powered by Wisenet 7 AI network outdoor vandal bullet camera, 6MP @30fps, 4.4~9.3mm motorized varifocal lens (2.1x), triple codec H.265/H.264/MJPEG with WiseStream III, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), IR viewable length 40m, Next level Cybersecurity, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/Licence plate),I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66/IP67, IK10, NEMA4X, PoE+/12VDC	Info
Camera - Network	XNV-C8083R	6MP AI IR Vandal Dome	X series powered by Wisenet 7 AI network IR outdoor vandal dome camera,6MP @30fps, 4.4 ~ 9.3mm motorized varifocal lens (2.1x) (12.1°~47.5°), triple codec H.265/H.264 MJPEG with WiseStream III, Multiple streaming, 120dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 40m, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/Licence plate),I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion),Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and single microSD/SDHC /SDXC slot, ONVIF S/G/T, USB port for easy installation, IP67/IP66, IK10, Nema 4X, PoE/12VDC, white colour skins included	Info
Camera - Network	XND-C8083RV	6MP AI IR Dome	X series powered by Wisenet 7 AI network IR indoor vandal dome camera,6MP @30fps, 4.4 ~ 9.3mm motorized varifocal lens (2.1x) (12.1°~47.5°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 40m, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/Licence plate),I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion),Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and single microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP52, IK10, PoE/12VDC, white skins included	Info
Camera - Network	XNP-C8303RW	6MP 30x IR AI PTZ with built-in wiper	X series powered by Wisenet 7 AI network outdoor IR PTZ camera, 6MP @30fps, 25x Optical Zoom Lens (5 ~ 150mm) (57.42° ~ 2.19°), 360° Endless Pan range, 350°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), Viewable IR length 200m, Analytics events based on AI engine, Defocus / Motion / Fog / Shock detection, Tampering, Virtual area, Classified object (Person/Face/Vehicle/Licence plate), Attributes (Vehicle type), Object auto tracking(Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, NEMA-TS2, HPoE, Built-in wiper * Alarm outputs, Audio detection, Sound classification(with NW I/O Box which can be purchased separately)	Info
Camera - Network	XNP-C8253R	6MP 25x IR AI PTZ	X series powered by Wisenet 7 AI network outdoor IR PTZ camera, 6MP @30fps, 25x Optical Zoom Lens (5 ~ 125mm) (57.42° ~ 2.71°), 360° Endless Pan range, 700°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), Viewable IR length 200m, Analytics events based on AI engine, Defocus / Motion / Fog / Shock detection, Tampering, Virtual area, Classified object (Person/Face/Vehicle/Licence plate), Attributes (Vehicle type), Object auto tracking(Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, NEMA-TS2, HPoE * Alarm outputs, Audio detection, Sound classification(with NW I/O Box which can be purchased separately)	Info
Camera - Network	XNP-C8253	6MP 25x AI PTZ	X series powered by Wisenet 7 AI network outdoor PTZ camera, 6MP @30fps, 25x Optical Zoom Lens (5 ~ 125mm) (57.42° ~ 2.71°), 360° Endless Pan range, 700°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), Analytics events based on AI engine, Defocus / Motion / Fog / Shock detection, Tampering, Virtual area, Classified object (Person/Face/Vehicle/Licence plate), Attributes (Vehicle type), Object auto tracking(Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, NEMA-TS2, PoE+ * Alarm outputs, Audio detection, Sound classification(with NW I/O Box which can be purchased separately)	Info
Camera - Network	XNO-8082R	6MP IR Bullet	X series powered by Wisenet 7 network outdoor vandal bullet camera, 6MP @30fps, 2.8~8.4mm motorized varifocal lens (3x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), IR viewable length 40m, Next level Cybersecurity, Licence-free onboard Advanced Video Analytics and Business Analytics, Sound Classification, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, Face/upper body detection, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP66/IP67, IK10, NEMA4X, PoE/12VDC/24VAC	Info
Camera - Network	XNV-8082R	6MP IR Outdoor Vandal Dome	X series powered by Wisenet 7 network outdoor vandal dome camera, Modular structure X PLUS, 6MP @30fps, 2.8~8.4mm motorized varifocal lens (3x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), IR viewable length 40m, Next level Cybersecurity, Licence-free onboard Advanced Video Analytics and Business Analytics, Sound Classification, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, Face/upper body detection, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP66/IP67/IP6K9K, IK10+, NEMA4X, PoE/12VDC	Info
Camera - Network	XND-8082RF	6MP IR Flush Mount Dome	X series powered by Wisenet 7 network indoor flush mount dome camera, Modular structure X PLUS, 6MP @30fps, 2.8~8.4mm motorized varifocal lens (3x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), IR viewable length 40m, Next level Cybersecurity, Licence-free onboard Advanced Video Analytics and Business Analytics, Sound Classification, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, Face/upper body detection, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP52, IK10, Plenum rate, PoE/12VDC	Info
Camera - Network	XND-8082RV	6MP IR Indoor Dome	X series powered by Wisenet 7 network indoor vandal dome camera, Modular structure X PLUS, 6MP @30fps, 2.8~8.4mm motorized varifocal lens (3x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), IR viewable length 40m, Next level Cybersecurity, Licence-free onboard Advanced Video Analytics and Business Analytics, Sound Classification, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, Face/upper body detection, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP52, IK10, PoE/12VDC	Info
Camera - Network	XNB-8002	6MP Box	X series powered by Wisenet 7 network box camera, 6MP @30fps, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), Next level Cybersecurity, Licence-free onboard Advanced Video Analytics and Business Analytics, Sound Classification, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, Face/upper body detection, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, PoE/12VDC/24VAC ※ The lens is not included	Info
Camera - Network	XNF-8010RVM	6MP Mobile IR Vandal Fisheye	X series powered by Wisenet 5 network mobile vandal fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49°, simple focus, dual SD card, HLC, defog detection, DIS, For Mobile Application (M12 Connector) RJ45 to M12 adapter is NOT included, 12VDC/PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)	Info
Camera - Network	XNF-8010RV	6MP IR Vandal Fisheye	X series powered by Wisenet 5 network outdoor vandal fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49°, simple focus, dual SD card, HLC, defog detection, DIS, 12VDC/PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)	Info
Camera - Network	XNF-8010R	6MP IR Indoor Fisheye	X series powered by Wisenet 5 network indoor fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.6mm fixed lens (192°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, advanced video, sound classification and business analytics, high powered IR LEDs range of 49°, simple focus, dual SD card, HLC, defog detection, DIS, 12VDC/PoE	Info
Camera - Network	XNP-8300RW	6MP 30x IR Outdoor PTZ	X series powered by Wisenet 7 network IR outdoor PTZ camera with built-in wiper, 6MP @30fps, 30x Optical Zoom Lens (5 ~ 150mm) (57.42° ~ 2.19°), 360° Endless Pan range, 500°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), IR viewable length 200m, Intelligent Video Analytics, Motion detection, Fog detection, Tampering, Object auto tracking(Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, HPoE * Alarm outputs, Audio detection, Sound classification(with NW I/O Box which can be purchased separately)	Info
Camera - Network	XNP-8250R	6MP 25x IR Outdoor PTZ	X series powered by Wisenet 7 network IR outdoor PTZ camera, 6MP @30fps, 25x Optical Zoom Lens (5 ~ 125mm) (57.42° ~ 2.71°), 360° Endless Pan range, 700°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (120dB), True Day & Night (ICR), IR viewable length 200m, Intelligent Video Analytics, Motion detection, Fog detection, Tampering, Object auto tracking(Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, NEMA-TS2, HPoE * Alarm outputs, Audio detection, Sound classification(with NW I/O Box which can be purchased separately)	Info
Camera - Network	PNM-8082VT	3x 2MP Outdoor Dome	P series powered by Wisenet 7 network outdoor Multi-sensor Multi-Directional dome camera, 3 sensors x 2MP, max 6MP @30fps, 3 x 3 ~ 6mm motorized varifocal lenses (2x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extremeWDR 150dB, Auto Day & Night (ICR), Advanced Video Analytics, Motion detection, Hallway view, HLC, Digital Image Stabilization, 2x SD/SDHC/SDXC slot, IP66, IK10, NEMA4X, PoE+	Info
Camera - Network	QNF-8010	6MP Indoor Fisheye	Q series network indoor fisheye, 6MP CMOS sensor, 2048x2048 @ 30fps, 1.14mm fixed lens (187°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, defocus, motion detection, tampering, people counting, heatmap, SD/SDHC/SDXC slot, HLC, PoE, IP42	Info

5MP Cameras

Camera - Network	XND-A8084RV	5MP AI IR Indoor Dome	Powered by WN9. Indoor Network AI IR Dome Camera, 5MP resolution @ 30FPS, 3.3-9.3mm (2.8x), (99°-31°) motorized varifocal lens, H.265/H.264/MJPEG codec, IR viewable length 40m (131.2ft), USB-C port for easy installation, Day & Night (ICR), extreme WDR (120dB), Hard-coated dome bubble, DIS with built-in gyro sensor, Handover, AI-based WiseStream, WiseNR II (using AI engine), Dynamic privacy mask, I/A events based on AI engine (Motion & Object detection, Line crossing, I/A area, Slip & Fall, Sound classification), Classified object types (Person/Face/Vehicle/License plate), Object attributes (Person: Gender/Top/Bottom clothing color/Bag, Face: Age/Gender/Mask/Glasses, Vehicle: type/color), BestShot, Analytics events (Defocus, Motion, Tampering, Fog, Audio & Shock detection), AI-based business intelligence (People/Vehicle/Crowd counting, Queue management, Heatmap), Built-in microSD card slot (Up to 1TB), IP52, IK10, Operating temperature: -10°C~+50°C (14°F~+122°F), Power: PoE, Metal shielded RJ-45.	Info
Camera - Network	XNO-A8084R	5MP AI IR Bullet	Powered by WN9. Outdoor Network AI IR Vandal Bullet Camera, 5MP resolution @ 30FPS, 3.3-9.3mm (2.8x) (113°-47°) motorized varifocal lens, H.265/H.264/MJPEG codec, IR viewable length 40m (131.2ft), USB-C port for easy installation, Day & Night (ICR), extreme WDR (120dB), Hard-coated dome bubble, DIS with built-in gyro sensor, Handover, AI-based WiseStream, WiseNR II (using AI engine), Dynamic privacy mask, I/A events based on AI engine (Motion & Object detection, Line crossing, I/A area, Slip & Fall, Sound classification), Classified object types (Person/Face/Vehicle/License plate), Object attributes (Person: Gender/Top/Bottom clothing color/Bag, Face: Age/Gender/Mask/Glasses, Vehicle: type/color), BestShot, Analytics events (Defocus, Motion, Tampering, Fog, Audio & Shock detection), AI-based business intelligence (People/Vehicle/Crowd counting, Queue management, Heatmap), Built-in microSD card slot (Up to 1TB), IP66/IP67, IK10, NEMA 4X, NEMA-TS 2(2.2.7.2-8, 2.2.8, 2.2.9), Operating temp: -40°C~+60°C (-40°F~+140°F), Power: PoE, Metal shielded RJ-45.	Info
Camera - Network	XNV-A8084R	5MP AI IR Outdoor Vandal Dome	Powered by WN9. Outdoor Network AI IR Vandal Dome Camera, 5MP resolution @ 30FPS, 3.3-9.3mm (2.8x), (113°-47°) motorized varifocal lens, H.265/H.264/MJPEG codec, IR viewable length 40m (131.2ft), USB-C port for easy installation, Day & Night (ICR), extreme WDR (120dB), Hard-coated dome bubble, DIS with built-in gyro sensor, Handover, AI-based WiseStream, WiseNR II (using AI engine), Dynamic privacy mask, I/A events based on AI engine (Motion & Object detection, Line crossing, I/A area, Slip & Fall, Sound classification), Classified object types (Person/Face/Vehicle/License plate), Object attributes (Person: Gender/Top/Bottom clothing color/Bag, Face: Age/Gender/Mask/Glasses, Vehicle: type/color), BestShot, Analytics events (Defocus, Motion, Tampering, Fog, Audio & Shock detection), AI-based business intelligence (People/Vehicle/Crowd counting, Queue management, Heatmap), Built-in microSD card slot (Up to 1TB), IP66/IP67, IK10, NEMA 4X, NEMA-TS 2(2.2.7.2-8, 2.2.8, 2.2.9), Operating temp: -40°C~+50°C (-40°F~+122°F), Power: PoE, Metal shielded RJ-45.	Info
Camera - Network	QNE-C8013RL	5MP Dual Light AI Outdoor FlatEye	Q series AI network outdoor flat eye camera, 5MP @ 30fps, 3mm fixed focal lens (H: 97° / V: 53°), triple codec H.265/H.264/MJPEG with WiseStream III, 120dB WDR, Dual Light – White LED range 30m (98ft), IR viewable length 30m (98ft), Motion Detection based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle), I/A events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/Dis/Appear), defocus detection, hallway View, SD card, video analytics, IP66/IP67, IK10, PoE, Operating temperature -40°C~+60°C(-40°F ~ +140°F) white color	Info
Camera - Network	QND-C8013R	5MP AI IR Indoor Dome	Q series AI network indoor dome camera, 5MP @ 30fps, fix lens 3mm (H:100°/V: 73°), triple codec H.265/H.264/MJPEG with WiseStream III technology, WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 25m(82.02ft), built-in mic, Motion detection based on AI engine, Analytics events based on AI engine: Classified object type: [Person/Vehicle]; Attributes: Vehicle [Type and color: (car/bus/truck/motorcycle/bicycle)], Person [upper and bottom clothing color]; BestShot, Virtual line, [Virtual area], defocus detection, hallway view, Dynamic privacy masking, built-in SD card slot (1x256GB) , video analytics, USB for easy installation, open platform, PoE, Operating temperature -10°C~+45°C(+14°F ~ +113°F) white color. * Alarm I/O is supported through an optional cable (SPP-C7200)	Info
Camera - Network	QND-C8023R	5MP AI IR Indoor Dome	Q series AI network indoor dome camera, 5MP @ 30fps, fix lens 4mm (H:80°/V: 59°), triple codec H.265/H.264/MJPEG with WiseStream III technology, WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 30m(98.42ft), built-in mic, Motion detection based on AI engine, Analytics events based on AI engine: Classified object type: [Person/Vehicle]; Attributes: Vehicle [Type and color: (car/bus/truck/motorcycle/bicycle)], Person [upper and bottom clothing color]; BestShot, Virtual line, [Virtual area], defocus detection, hallway view, Dynamic privacy masking, built-in SD card slot (1x256GB) , video analytics, USB for easy installation, open platform, PoE, Operating temperature -10°C~+45°C(+14°F ~ +113°F) white color. * Alarm I/O is supported through an optional cable (SPP-C7200)	Info
Camera - Network	QNO-C8083R	5MP AI IR Bullet	Q series AI network outdoor vandal bullet camera, 5MP @ 30fps, motorized vari-focal lens 3.2-10.2mm (H: 95°-29° / V: 69°-21°), triple codec H.265/H.264/MJPEG with WiseStream III (Based on AI engine), WDR 120dB, IR viewable length 30m(98.42ft), built-in mic, Motion detection based on AI engine, Analytics events based on AI engine: Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); I/A events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/Dis/Appear), Audio: Selectable(mic in/line in), defocus detection, hallway View, built-in SD card slot (1x256GB), video analytics, USB for easy installation, open platform, IP66, IK10, PoE, Operating temperature -30°C~+55°C(-22°F ~ +131°F) white color.	Info
Camera - Network	QNO-C8013R	5MP AI IR Bullet	Q series AI network outdoor vandal bullet camera, 5MP @ 30fps, fix lens 3mm (H:100°/V: 73°), triple codec H.265/H.264/MJPEG with WiseStream III technology, WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 25m(82.02ft), Motion detection based on AI engine, Analytics events based on AI engine: Classified object type: [Person/Vehicle]; Attributes: Vehicle [Type and color: (car/bus/truck/motorcycle/bicycle)], Person [upper and bottom clothing color]; BestShot, Virtual line, [Virtual area], defocus detection, hallway view, Dynamic privacy masking, built-in SD card slot (1x256GB), video analytics, USB for easy installation, open platform, IP66, IK10, PoE, Operating temperature -30°C~+55°C(-22°F ~ +131°F) white color.	Info
Camera - Network	QNO-C8023R	5MP AI IR Bullet	Q series AI network outdoor vandal bullet camera, 5MP @ 30fps, fix lens 4mm (H:80°/V: 59°), triple codec H.265/H.264/MJPEG with WiseStream III technology, WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 30m(98.42ft), Motion detection based on AI engine, Analytics events based on AI engine: Classified object type: [Person/Vehicle]; Attributes: Vehicle [Type and color: (car/bus/truck/motorcycle/bicycle)], Person [upper and bottom clothing color]; BestShot, Virtual line, [Virtual area], defocus detection, hallway view, Dynamic privacy masking, built-in SD card slot (1x256GB), video analytics, USB for easy installation, open platform, IP66, IK10, PoE, Operating temperature -30°C~+55°C(-22°F ~ +131°F) white color.	Info
Camera - Network	QNV-C8083R	5MP AI IR Vandal Dome	Q series AI network outdoor vandal dome camera, 5MP @ 30fps, motorized vari-focal lens 3.2-10.2mm (H: 95°-29° / V: 69°-21°), triple codec H.265/H.264/MJPEG with WiseStream III (Based on AI engine), WDR 120dB, IR viewable length 30m(98.42ft), built-in mic, Motion detection based on AI engine, Analytics events based on AI engine: Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); I/A events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/Dis/Appear), Audio: Selectable(mic in/line in), defocus detection, hallway View, built-in SD card slot (1x256GB), video analytics, USB for easy installation, open platform, IP66, IK10, PoE, Operating temperature -30°C~+55°C(-22°F ~ +131°F) white color. * Alarm I/O and audio is supported through an optional cable (SPP-C7400)	Info
Camera - Network	QNV-C8013R	5MP AI IR Vandal Dome	Q series AI mini network outdoor vandal dome camera, 5MP @ 30fps, fix lens 3mm (H:100°/V: 73°), triple codec H.265/H.264/MJPEG with WiseStream III technology, WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 25m(82.02ft), Motion detection based on AI engine, Analytics events based on AI engine: Classified object type: [Person/Vehicle]; Attributes: Vehicle [Type and color: (car/bus/truck/motorcycle/bicycle)], Person [upper and bottom clothing color]; BestShot, Virtual line, [Virtual area], defocus detection, hallway view, Dynamic privacy masking, built-in SD card slot (1x256GB), video analytics, USB for easy installation, open platform, IP66, IK10, PoE, Operating temperature -30°C~+55°C(-22°F ~ +131°F) white color. * Alarm I/O and audio is supported through an optional cable (SPP-C7400)	Info
Camera - Network	QNV-C8023R	5MP AI IR Vandal Dome	Q series AI mini network outdoor vandal dome camera, 5MP @ 30fps, fix lens 4mm (H:80°/V: 59°), triple codec H.265/H.264/MJPEG with WiseStream III technology, WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 30m(98.42ft), Motion detection based on AI engine, Analytics events based on AI engine: Classified object type: [Person/Vehicle]; Attributes: Vehicle [Type and color: (car/bus/truck/motorcycle/bicycle)], Person [upper and bottom clothing color]; BestShot, Virtual line, [Virtual area], defocus detection, hallway view, Dynamic privacy masking, built-in SD card slot (1x256GB), video analytics, USB for easy installation, open platform, IP66, IK10, PoE, Operating temperature -30°C~+55°C(-22°F ~ +131°F) white color. * Alarm I/O and audio is supported through an optional cable (SPP-C7400)	Info
Camera - Network	QNV-C8011R	5MP AI IR Micro Vandal Dome	Q series AI network IR Micro vandal dome camera, 5MP @30fps, 3.0mm fixed lens, triple codec H.265/H.264/MJPEG, Multiple streaming up to 5 profiles, 120dB WDR, Day & Night (ICR), High Powered IR LEDs with IR viewable length 20m, Analytics events based on AI engine: Object detection (Person/Vehicle – car, truck, bus, bicycle, motorcycle), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Tampering, single microSD/SDHC/SDXC slot, ONVIF S/G/T/M, USB port for easy installation, IP66, IK10, NEMA4X, PoE, white	Info
Camera - Network	QNV-C8012	5MP AI Micro Vandal Dome	Q series AI network Micro vandal dome camera, 5MP @30fps, 2.4 mm fixed lens, triple codec H.265/H.264/MJPEG, Multiple streaming up to 5 profiles, 120dB WDR, Day & Night (ICR), Analytics events based on AI engine: Object detection (Person/Vehicle – car, truck, bus, bicycle, motorcycle), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Tampering, single microSD/SDHC/SDXC slot, ONVIF S/G/T/M, USB port for easy installation, IP66, IK10, NEMA4X, PoE, white	Info
Camera - Network	TNV-C8011RW	5MP AI IR Wall Mount	T Series, wall mount AI panoramic camera, 5MP @ 30 FPS, 1.6mm fixed focal lens (HfOV: 175°, VfoV: 125°), Triple CODEC (H.265/H.264/MJPEG) with WiseStream III (based on AI engine) support, 120dB WDR, IR viewable length 15m (49ft), WiseMD based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); I/A events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/Dis/Appear), virtual area (Intrusion/enter/exit), virtual line (crossing/direction), Business analytics: People Counting, Queue Management, Heatmap, Occupancy, Tamper detection, built-in mic, SD card, IP66, PoE, white.	Info
Camera - Network	TNV-C8014RM	5MP AI IR Mobile Camera	T Series AI Mobile IR vandal dome camera, 5MP, (2592x1944) 30fps, triple codec H.265/H.264/MJPEG with WiseStream technology, Fixed focal Lens 3mm (H:100°/V: 73°), Built in Mic, 120dB WDR, built-in IR range of 30m(98.43ft), Motion detection based on AI engine, Video Analytics based on AI/Object detection and Classification (Person/top/bottom clothing color), Vehicle (Type, color); BestShot, Virtual line, [Virtual area], defocus detection, shock detection, hallway View, Heater, DIS with built-in Gyro sensor, Dynamic privacy masking, built-in SD card slot (1x256GB), IP66, IK10, Operating temperature: -40°C~+55°C(-40°F~+131°F), M12 Network connector (M12 connector to RJ-45 adaptor is not included)	Info
Camera - Network	TNV-C8034RM	5MP AI IR Mobile Camera	T Series AI Mobile IR vandal dome camera, 5MP, (2592x1944) 30fps, triple codec H.265/H.264/MJPEG with WiseStream technology, Fixed focal Lens 6mm (H:50°/V: 37°), Built in Mic, 120dB WDR, built-in IR range of 30m(98.43ft), Motion detection based on AI engine, Video Analytics based on AI/Object detection and Classification (Person/top/bottom clothing color), Vehicle (Type, color); BestShot, Virtual line, [Virtual area], defocus detection, shock detection, hallway View, Heater, DIS with built-in Gyro sensor, Dynamic privacy masking, built-in SD card slot (1x256GB), IP66, IK10, Operating temperature: -40°C~+55°C(-40°F~+131°F), M12 Network connector (M12 connector to RJ-45 adaptor is not included)	Info
Camera - Network	XND-8081VZ	5MP PTRZ Indoor Dome	X series powered by Wisenet 5 network indoor vandal dome camera, Modular structure X PLUS, 5MP @30fps, 3.6 ~ 9.4mm motorized varifocal lens (2.6x) (102.5°~38.7°), Motorized Pan/Tilt/Rotate/Zoom, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification and Business Analytics, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP52, IK10, PoE/12VDC, white & ivory colour skins included, optional black skin cover	Info

Camera - Network	QNO-8010R	5MP IR Bullet	Q series network IR outdoor vandal bullet camera, 5MP @30fps, 2.8mm fixed lens (104.7°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 20m, Advanced Video Analytics, Hallway View, Motion detection, LDC (Lens Distortion Correction), SD/SDHC/SDXC slot, CVBS for easy installation, IP66, IK10, PoE	Info
Camera - Network	QND-8080R	5MP IR Indoor Dome	Q series network IR indoor dome camera, 5MP @30fps, 3.2 ~ 10.0mm motorized varifocal lens (3.1x) (100.3°~31.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 20m, Advanced Video Analytics, Hallway View, Motion detection, LDC (Lens Distortion Correction), SD/SDHC/SDXC slot, CVBS for easy installation, PoE	Info
Camera - Network	QND-8020R	5MP IR Indoor Dome	Q series network IR indoor dome camera, 5MP @30fps, 4.0mm fixed lens (79.8°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 20m, Advanced Video Analytics, Hallway View, Motion detection, LDC (Lens Distortion Correction), SD/SDHC/SDXC slot, CVBS for easy installation, PoE	Info
Camera - Network	QND-8010R	5MP IR Indoor Dome	Q series network IR indoor dome camera, 5MP @30fps, 2.8mm fixed lens (104.7°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 20m, Advanced Video Analytics, Hallway View, Motion detection, LDC (Lens Distortion Correction), SD/SDHC/SDXC slot, CVBS for easy installation, PoE	Info
Camera - Network	QND-8021	5MP Mini Dome	Q series network indoor mini dome camera, 5MP @30fps, 4.0mm fixed lens (80.14°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), Business Analytics (People counting), Motion detection, Tampering, Defocus detection, Hallway View, microSD/SDHC/SDXC slot, HDMI output for public view monitor, LDC support (Lens Distortion Correction), IP42, IK08, PoE, Compact size 99 x 56mm/165gr	Info
Camera - Network	QND-8011	5MP Mini Dome	Q series network indoor mini dome camera, 5MP @30fps, 2.8mm fixed lens (104.4°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), Business Analytics (People counting), Motion detection, Tampering, Defocus detection, Hallway View, microSD/SDHC/SDXC slot, HDMI output for public view monitor, LDC support (Lens Distortion Correction), IP42, IK08, PoE, Compact size 99 x 56mm/165gr	Info
Camera - Network	QNV-8080R	5MP IR Outdoor Vandal Dome	Q series network IR outdoor vandal dome camera, 5MP @30fps, 3.2 ~ 10.0mm motorized varifocal lens (3.1x) (100.3°~31.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 30m, Advanced Video Analytics, Hallway View, Motion detection, LDC (Lens Distortion Correction), SD/SDHC/SDXC slot, CVBS for easy installation, IP66, IK10, PoE	Info
Camera - Network	QNV-8020R	5MP IR Outdoor Vandal Dome	Q series network IR outdoor vandal dome camera, 5MP @30fps, 4.0mm fixed lens (79.8°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 25m, Advanced Video Analytics, Hallway View, Motion detection, LDC (Lens Distortion Correction), SD/SDHC/SDXC slot, CVBS for easy installation, IP66, IK10, PoE	Info
Camera - Network	QNV-8010R	5MP IR Outdoor Vandal Dome	Q series network IR outdoor vandal dome camera, 5MP @30fps, 2.8mm fixed lens (104.7°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 20m, Advanced Video Analytics, Hallway View, Motion detection, LDC (Lens Distortion Correction), SD/SDHC/SDXC slot, CVBS for easy installation, IP66, IK10, PoE	Info
Camera - Network	QNB-8002	5MP Box	Q series network box camera, 5MP @30fps, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), Advanced Video Analytics, Hallway View, Motion detection, Tampering, Defocus detection, Bi-directional audio and dual SD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), PoE/12VDC ※ The lens is not included	Info
Camera - Network	QNE-8011R	5MP IR Flateye	Q series network IR outdoor vandal flateye camera, 5MP @30fps, 2.8mm fixed lens (104.4°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), Advanced Video Analytics, Hallway View, Motion detection, Tampering, Defocus detection, Hallway View, microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP67, IK10, PoE	Info
Camera - Network	TNV-8011C	5MP Corner Mount	T series network outdoor anti-ligature corner mount camera, 5MP @30fps, 2.3mm fixed lens, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), Advanced Video Analytics, Hallway View, Motion detection, Lens Distortion Correction, Digital Image Stabilization, Audio In/Out, 1 Input/1 Output, SD Card slot, PoE, IP66, IK10, IP6K9K	Info
Camera - Network	XNV-8081RE	5MP IR Outdoor Vandal Dome	X series powered by Wisenet 5 network IR outdoor vandal dome camera, Modular structure X PLUS, PoE+ in / PoE out, 5MP @30fps, 3.9 ~ 9.4mm motorized varifocal lens (2.4x) (92.1°~38.7°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 50m, Advanced Video Analytics and Sound Classification and Business Analytics, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, HLC, Digital Image Stabilization with built-in Gyro sensor, Bi-directional audio and dual micro SD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP67/IP66/IP6K9K, IK10+, Nema 4X, PoE+	Info
Camera - Network	XND-8081REV	5MP IR Indoor Vandal Dome	X series powered by Wisenet 5 network IR indoor vandal dome camera, Modular structure X PLUS, PoE+ in / PoE out, 5MP @30fps, 3.9 ~ 9.4mm motorized varifocal lens (2.4x) (92.1°~38.7°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 50m, Advanced Video Analytics and Sound Classification and Business Analytics, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP52, IK10, PoE+	Info
4MP Cameras				
Camera - Network	XNO-C7083R	4MP AI IR Bullet	X series powered by Wisenet 7 AI network outdoor vandal bullet camera, 4MP @60fps, 2.8-10mm motorized varifocal lens (3.6x), triple codec H.265/H.264/MJPEG with WiseStream III, Multiple streaming, extreme WDR (120dB), Auto Day & Night (ICR), IR viewable length 40m, Next level Cybersecurity, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection Audio detection, Sound classification, Shock detection, Appear/Disappear, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66/IP67, IK10, NEMA4X, PoE+/12VDC	Info
Camera - Network	XNV-C7083R	4MP AI IR Vandal Dome	X series powered by Wisenet 7 AI network IR outdoor vandal dome camera, 4MP @60fps, 2.8 ~ 10.0mm motorized varifocal lens (3.6x) (109.7°~30.4°), triple codec H.265/H.264/MJPEG with WiseStream III, Multiple streaming, 120dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 40m, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and single microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP67/IP66, IK10, Nema 4X, PoE/12VDC, white colour skins included	Info
Camera - Network	XND-C7083RV	4MP AI IR Dome	X series powered by Wisenet 7 AI network IR indoor vandal dome camera, 4MP @60fps, 2.8 ~ 10.0mm motorized varifocal lens (3.6x) (109.7°~30.4°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 40m, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and single microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP52, IK10, PoE/12VDC, white skins included	Info
Camera - Network	XNP-C7310R	4MP AI Focus IR PTZ	X series Powered by WN7 and AI, 4MP @ 30FPS resolution, 6.91mm-214.64mm (31x) lens with Wise AF intelligent autofocus, adaptive Wise IR (300m), extreme WDR 120dB, Day & Night ICR, H.265, H.264, MJPEG triple codec with WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Face/ Vehicle/License plate), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification (with NW IO box), AI object auto-tracking (Person/Vehicle) with target lock tracking, BLC, HLC, SDDR, lens heater for water/snow removal, IP66, IP67, IK10, NEMA4X, NEMA-TS 2(2.2.8, 2.2.9), FIPS 140-2, HPoE injector included, Operating Temperature - 50°C~+55°C(-58°F ~ +131°F), (Compatible with IO Box SPM-4210)	Info
Camera - Network	PNM-C7083RVD	2x 2MP AI Multi-directional	P series network AI based multi-directional dual sensor outdoor vandal dome camera, 2 x 2MP @25/30fps, 360 degree 25m IR, 3-6mm motorised varifocal lenses, WiseNR II, Auto prefer shutter control, WiseStream III, ExtremeWDR (120dB), Hallway View, Analytics AI Object detection with classification: Person, Face, Vehicle, License plate and vehicle attributes Car, Bus, Truck, Motorcycle, Bicycle, Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit), BestShot, Motion detection, Defocus detection, Tampering, SD Card slot 512GB max, PoE+, Secure by Default, TPM 2.0 (FIPS 140-2), IP66, NEMA4X, IK10. Compatible with SPM-4210 IO IP box to connect alarms/audio devices and support camera's audio detection and sound classification analytics	Info

Camera - Network	PNM-7082RVD	2x 2MP Multi-directional	P series network multi-directional dual sensor outdoor vandal dome camera, 2 x 2MP @25/30fps, 360 degree 25m IR, 3–6mm motorised varifocal lenses, WiseNR, WiseStream II, ExtremeWDR (150dB), Defog, Hallway View, Defocus detection, Motion detection, Tampering, Virtual line(Crossing/Direction), Virtual area(Loitering/Enter/Exit), SD Card slot 512GB max, PoE+, Secure by Default, TPM 2.0 (FIPS 140-2), IP66, NEMA4X, IK10. Compatible with SPM-4210 I/O IP box to connect alarms/audio devices and support camera's audio detection and sound classification analytics	Info
Camera - Network	QNO-7082R	4MP IR Bullet	Q series network IR outdoor vandal bullet camera, 4MP @30fps, 3.2 ~ 10.0mm motorized varifocal lens (4.3x) (109.7°~26°), triple codec H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 30m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNO-7032R	4MP IR Bullet	Q series network IR outdoor vandal bullet camera, 4MP @30fps, 6mm fixed lens, H.265/H.264/ MJPEG with WiseStream, Multiple streaming, 120dB WDR, Day & Night (Auto ICR), IR viewable length 30m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNO-7022R	4MP IR Bullet	Q series network IR outdoor vandal bullet camera, 4MP @30fps, 4.0mm fixed lens (81°), triple codec H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 25m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNO-7012R	4MP IR Bullet	Q series network IR outdoor vandal bullet camera, 4MP @30fps, 2.8mm fixed lens, H.265/H.264/ MJPEG with WiseStream, Multiple streaming, 120dB WDR, Auto(ICR), IR viewable length 20m, Defocus detection, Directional detection, Motion detection, Enter/Exit, Tampering, Virtual line, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QND-7082R	4MP IR Dome	Q series network IR indoor dome camera, 4MP @30fps, 3.2 ~ 10.0mm motorized varifocal lens, 1/3" CMOS, triple codec H.265/H.264/Main/High/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (Auto ICR), IR viewable length 20m, SSNR, Motion detection, Tampering, Defocus detection, n, Directional detection, Motion detection, Enter/Exit Hallway View, Built-in MIC and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), PoE/12VDC	Info
Camera - Network	QND-7032R	4MP IR Dome	Q series network IR indoor dome camera, 4MP @30fps, 6mm fixed lens, H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, Day & Night (Auto ICR), IR viewable length 20m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), PoE/12VDC	Info
Camera - Network	QND-7022R	4MP IR Dome	Q series network IR indoor dome camera, 4MP @30fps, 4.0mm fixed lens, H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 20m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), PoE/12VDC, RAL9003	Info
Camera - Network	QND-7012R	4MP IR Dome	Q series network IR indoor dome camera, 4MP @30fps, 2.8mm fixed lens (110°), triple codec H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 20m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), PoE/12VDC	Info
Camera - Network	QNV-7082R	4MP IR Vandal Dome	Q series network IR outdoor vandal dome camera, 4MP @30fps, 3.2 ~ 10.0mm motorized varifocal lens (4.3x) (109.7°~26°), triple codec H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 30m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), SSNR, IP66, IK10, PoE/12VDC	Info
Camera - Network	QNV-7032R	4MP IR Vandal Dome	Q series network IR outdoor vandal dome camera, 4MP @30fps, 6mm fixed lens, triple codec H.265/H.264/Main/High/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 30m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio, Analytics, Network disconnect, Alarm input and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNV-7022R	4MP IR Vandal Dome	Q series network IR outdoor vandal dome camera, 4MP @30fps, 4.0mm fixed lens (81°), triple codec H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 25m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNV-7012R	4MP IR Vandal Dome	Q series network IR outdoor vandal dome camera, 4MP @30fps, 2.8mm fixed lens (110°), triple codec H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 20m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	ANE-L7012L	4MP White Light Flateye	A Series White Light turret camera, 4MP @ 30 FPS, 3mm fixed focal lens, FoV H: 107.7° / V: 59.0°, WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, White Light LED 20m(65.62ft), Flashing and Constant warning, virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.	Info
Camera - Network	ANE-L7012R	4MP Turret	A Series turret camera, 4MP @ 30 FPS, 3mm fixed focal lens, WiseStream II, Triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 20m(65.62ft), day & night (ICR), FoV H: 98.3° / V: 54.2°, virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.	Info
Camera - Network	ANO-L7012R	4MP IR Bullet	A Series bullet camera, 4MP @ 30 FPS, 3mm fixed focal lens, WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 20m(65.62ft), day & night (ICR), FoV H: 98.3° / V: 54.2°, virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.	Info
Camera - Network	ANO-L7022R	4MP IR Bullet	A Series bullet camera, 4MP @ 30 FPS, 4mm fixed focal lens, WiseStreamII, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 25m(82.02ft), day & night (ICR), FOV H: 78.3° / V: 42.9°, virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.	Info
Camera - Network	ANO-L7082R	4MP IR Bullet	A Series bullet camera, 4MP @ 30 FPS, motorized varifocal lens 3.1x (3.3~10.3mm) (94.8° ~ 28.1°), WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 30m (98.43ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.	Info
Camera - Network	ANV-L7012R	4MP IR Vandal Dome	A Series outdoor vandal dome camera, 4MP @ 30 FPS, 3mm fixed focal lens, WiseStreamII, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 20m(65.62ft), day & night (ICR), FoV H: 98.3° / V: 54.2°, virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, IK10, PoE, white.	Info
Camera - Network	ANV-L7082R	4MP IR Vandal Dome	A Series outdoor vandal dome camera, 4MP @ 30 FPS, motorized varifocal lens 3.1x (3.3~10.3mm) (94.8° ~ 28.1°), WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 30m (98.43ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, IK10, PoE, white.	Info
3MP Cameras				
Camera - Network	TNV-C7013RC	3MP AI IR Anti-ligature Corner Mount	T series network outdoor AI anti-ligature corner mount camera, 3MP @30fps, 2.39mm fixed focal lens, invisible 940nm wavelength Wise IR 15m(49.21ft), triple codec H.265/H.264/MJPEG with WiseStreamIII(Based on AI engine), 120dB WDR, Flip, Mirror, Hallway view(90°/270°), Classified object type - Person/Face/Vehicle/License plate, Support DetectionShot, Analytics events based on AI engine - Object detection, Virtual line(Crossing/Direction), Virtual area(Loitering/Intrusion/Enter/Exit) Analytics events - Defocus detection, Motion detection, Tampering, Audio detection, Sound classification, Virtual area(Appear/Disappear), Clothes color detection(Orange/Black/Red, @400lux), Audio In/Out/Built-in mic, 1 Input/1 Output, MicroSD/SDHC/SDXC memory slot (1TB), PoE/12VDC, IP66, IK10+, IP6K9K	Info

Camera - Network	TNO-7180RLP	Road AI 3MP High Speed Global Shutter Camera	T series Road AI 3MP High Speed Global Shutter Camera, 3MP Global Shutter Sensor, Maximum 55fps @3MP and 50fps @2MP on all resolutions, 6.8–120mm(18x) motorized varifocal, WiseIR 50m (164.04ft), Embedded Wisenet Road AI application with ANPR and MMCR Analytics, Recognition for up to 2 traffic lanes at speeds of up to 200kmh (125mph), List Management, Smart Search, Statistics, Installation aids LRP Setup Tool, Road AI Setup Wizard, USB/CVBS video output, PoE++, 12VDC (HPoE Injector is not included), * IP66, IK10, NEMA 4X, NEMA TS 2	Info
Camera - Network	TNV-7011RC	3MP IR Anti-ligature Corner Mount	T series network outdoor anti-ligature corner mount camera, 3MP @30fps, 2.8mm fixed lens, 940nm IR 10m, triple codec H.265/H.264/MJPEG with WiseStream II, 120dB WDR, Hallway View, Lens Distortion Correction, Digital Image Stabilization, Licence-free onboard Advanced Video Analytics: Tampering, Loitering, Directional detection, Defocus detection, Fog detection, Virtual line, Enter/Exit, Appear/Disappear, Audio detection, Face detection, Motion detection, Digital auto tracking, Sound classification, Shock detection, Audio In/Out/Built-in mic, 1 Input/1 Output, SD Card slot, PoE/12VDC, IP66, IK10+, IP6K9K	Info
2MP Cameras				
Camera - Network	XNO-6123R	2M AI IR Bullet	X series powered by Wisenet 7 AI network IR outdoor vandal bullet camera, 2MP @60fps, Full HD (1080p), 5.2 – 62.4mm optical zoom lens (12x), H.265/H.264/MJPEG with WiseStream III, Multiple streaming, 150dB WDR, True Day & Night (ICR), IR viewable length 90m, Classified object types: Person/Face/Vehicle/License plate; Attributes: Vehicle (Type: car/bus/truck /motorcycle/bicycle); Analytics events based on AI engine - Object detection, Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit); Analytics events - Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Virtual area (Appear/Disappear); HLC, PTZ Handover; Digital Image Stabilization with built-in Gyro sensor, Micro SD/SDHC/SDXC 2 slot Max. 1TB (512GB * 2), IP66/IP67, IK10, Nema 4X, PoE+/12VDC	Info
Camera - Network	XNO-6083R	2MP AI IR Bullet	X series powered by Wisenet 7 AI network outdoor vandal bullet camera, 2MP @120fps, 2.8–12mm motorized varifocal lens (4.3x), triple codec H.265/H.264/MJPEG with WiseStream III, Multiple streaming, extreme WDR (150dB), Auto Day & Night (ICR), IR viewable length 50m, Next level Cybersecurity, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP66/IP67, IK10, NEMA4X, PoE+/12VDC	Info
Camera - Network	XNV-6123R	2M AI IR outdoor Dome	X series powered by Wisenet 7 AI network IR outdoor vandal dome camera, 2MP @60fps, Full HD (1080p), 5.2 – 62.4mm optical zoom lens (12x), H.265/H.264/MJPEG with WiseStream III, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 90m, Classified object types: Person/Face/Vehicle/License plate; Attributes: Vehicle (Type: car/bus/truck /motorcycle/bicycle); Analytics events based on AI engine - Object detection, Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit); Analytics events - Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Virtual area (Appear/Disappear); HLC, PTZ Handover; Digital Image Stabilization with built-in Gyro sensor, Micro SD/SDHC/SDXC 2 slot Max. 1TB (512GB * 2), IP66/IP67/IP6K9K, NEMA4X, IK10+, PoE+/12VDC	Info
Camera - Network	XNV-6083RZ	2MP AI IR Vandal Dome	X series powered by Wisenet 7 AI network IR vandal dome camera, Modular structure X PLUS, 2MP @120fps, 2.8 – 12mm motorized varifocal lens (4.3x), Colour 0.01 Lux (F1.4, 1/30sec, 30IRE), BW 0 Lux (IR LED on), IR viewable length: 30m(98.43ft) based on scene, Day & Night (ICR), extremeWDR (150 dB), WiseNR II, WiseStream III, Analytics events based on AI engine (NPU) : Object detection (Person /Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP66/IP67/IP6K9K, NEMA4X, IK10+, Hard-coated dome bubble	Info
Camera - Network	XNV-6083R	2MP AI IR Vandal Dome	X series powered by Wisenet 7 AI network IR outdoor vandal dome camera, Modular structure X PLUS, 2MP @120fps, 2.8 – 12.0mm motorized varifocal lens (4.3x) (119.5°~27.9°), triple codec H.265/H.264 /MJPEG with WiseStream III, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 50m, Analytics events based on AI engine (NPU) : Object detection (Person /Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP66/IP67/IP6K9K, NEMA4X, IK10+, Hard-coated dome bubble	Info
Camera - Network	XNV-6083Z	2MP AI Vandal Dome	X series powered by Wisenet 7 AI network non IR vandal dome camera, Modular structure X PLUS, 2MP @120fps, 2.8 – 12mm motorized varifocal lens (4.3x), Colour 0.01 Lux (F1.4, 1/30sec, 30IRE), BW 0.001 Lux, Day & Night (ICR), extremeWDR (150 dB), WiseNR II, WiseStream III, Analytics events based on AI engine (NPU) : Object detection (Person /Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP66/IP67/IP6K9K, NEMA4X, IK10+, Hard-coated dome bubble	Info
Camera - Network	XND-6083RV	2MP AI IR Dome	X series powered by Wisenet 7 AI network IR indoor vandal dome camera, Modular structure X PLUS, 2MP @60fps, 2.8 – 12.0mm motorized varifocal lens (4.3x) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 50m, Analytics events based on AI engine (NPU) : Object detection (Person/Face/ Vehicle – car, truck, bus, bicycle, motorcycle/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion),Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC /SDXC slot, ONVIF S/G/T, USB port for easy installation, IP52, IK10, PoE+/12VDC, white colour skins included	Info
Camera - Network	XNB-6003	2MP AI Box	X series powered by Wisenet 7 AI network box camera, 1/2.8" progressive CMOS, 2MP @120fps, 0.007 Lux@F1.2 (Color), 0.0007 Lux@F1.2 (B/W), 30IRE simple focus, triple codec H.265/H.264/MJPEG with WiseStream III, Multiple streaming, 150dB WDR, True Day & Night (ICR), Analytics events based on AI engine : Object detection(Person/Face/Vehicle(car/bus/truck/motorcycle/bicycle)/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, direction, Appear/Disappear, intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Based on AI engine : People counting, Queue management, Heatmap, Handover, Digital Image Stabilization with built-in Gyro sensor, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, PoE/12VDC ※ The lens is not included	Info
Camera - Network	XNO-C6083R	2MP AI IR Bullet	X series powered by Wisenet 7 AI network outdoor vandal bullet camera, 2MP @60fps, 2.8–12mm motorized varifocal lens (4.3x), triple codec H.265/H.264/MJPEG with WiseStream III, Multiple streaming, extreme WDR (150dB), Auto Day & Night (ICR), IR viewable length 40m, Next level Cybersecurity, Analytics events based on AI engine (NPU) : Object detection (Person/Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66/IP67, IK10, NEMA4X, PoE/12VDC	Info
Camera - Network	XNV-C6083	2MP AI Vandal Dome	X series powered by Wisenet 7 AI network non IR vandal dome camera, Modular structure X PLUS, 2MP @60fps, 2.8 – 12mm motorized varifocal lens (4.3x), Colour 0.01 Lux (F1.4, 1/30sec, 30IRE), BW 0 Lux, Day & Night (ICR), extremeWDR (150 dB), DIS with built-in Gyro sensor, WiseNR II, WiseStream III, Analytics events based on AI engine (NPU) : Object detection (Person /Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion), Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP66/IP67, NEMA4X, IK10, Hard-coated dome bubble	Info
Camera - Network	XNV-C6083R	2MP AI IR Vandal Dome	X series powered by Wisenet 7 AI network IR outdoor vandal dome camera, 2MP @60fps, 2.8 – 12.0mm motorized varifocal lens (4.3x) (119.5°~27.9°), triple codec H.265/H.264 /MJPEG with WiseStream III, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 40m, Analytics events based on AI engine (NPU) : Object detection (Person /Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion),Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and single microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP67/IP66, IK10, Nema 4X, PoE/12VDC, white colour skins included	Info
Camera - Network	XND-C6083RV	2MP AI IR Dome	X series powered by Wisenet 7 AI network IR indoor vandal dome camera, 2MP @60fps, 2.8 – 12.0mm motorized varifocal lens (4.3x) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 40m, Analytics events based on AI engine (NPU) : Object detection (Person /Face/Vehicle – car, truck, bus, bicycle, motorcycle/License plate), I/A (Virtual line/Area, Enter/Exit, Loitering, Direction, Intrusion),Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and single microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP52, IK08, PoE/12VDC, white skins included	Info
Camera - Network	XNP-C6403RW	2MP 40x IR PTZ with built-in wiper	X series powered by Wisenet 7 AI network outdoor PTZ camera, 2MP @ 60fps, 40x Optical Zoom lens (4.25 – 170mm) (65.66° – 1.88°), 60° Endless Pan range, 500°/sec Pan speed, Tilt: -20° – 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (150dB), True Day & Night (ICR), Viewable IR length 200m, Analytics events based on AI engine, Defocus / Motion / Fog / Shock detection, Tampering, Virtual area, Classified object (Person/Face/Vehicle/License plate), Attributes (Vehicle type), Object auto tracking(Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, NEMA-TS2, HPoE, Built-in wiper * Alarm outputs, Audio detection, Sound classification(with NW I/O Box which can be purchased separately)	Info
Camera - Network	XNP-C6403R	2MP IR AI PTZ	X series powered by Wisenet 7 AI network outdoor PTZ camera, 2MP @ 60fps, 40x Optical Zoom lens (4.25 – 170mm) (65.66° – 1.88°), 60° Endless Pan range, 700°/sec Pan speed, Tilt: -20° – 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (150dB), True Day & Night (ICR), Viewable IR length 200m, Analytics events based on AI engine, Defocus / Motion / Fog / Shock detection, Tampering, Virtual area, Classified object (Person/Face/Vehicle/License plate), Attributes (Vehicle type), Object auto tracking(Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, NEMA-TS2, HPoE * Alarm outputs, Audio detection, Sound classification(with NW I/O Box which can be purchased separately)	Info
Camera - Network	XNP-C6403	2MP AI PTZ	X series powered by Wisenet 7 AI network outdoor PTZ camera, 2MP @ 60fps, 40x Optical Zoom lens (4.25 – 170mm) (65.66° – 1.88°), 60° Endless Pan range, 700°/sec Pan speed, Tilt: -20° – 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (150dB), True Day & Night (ICR), Analytics events based on AI engine, Defocus / Motion / Fog / Shock detection, Tampering, Virtual area, Classified object (Person/Face/Vehicle/License plate), Attributes (Vehicle type), Object auto tracking(Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, NEMA-TS2, HPoE * Alarm outputs, Audio detection, Sound classification(with NW I/O Box which can be purchased separately)	Info
Camera - Network	PNO-A6081R	2MP AI IR Bullet	P series network 2MP AI IR outdoor vandal bullet camera, 2MP @120fps, 4.38–9.33mm motorized varifocal lens (2.13x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 40m, Classified object type : Person/Face/Vehicle/License plate with attributes, BestShot per object, Analytics events based on AI engine : Object detection, Face mask detection, Social distancing detection, Directional detection, Digital auto tracking, Enter/Exit, Loitering, Virtual line, Analytics events : Defocus detection, Motion detection, Appear/Disappear, Tampering, Audio detection, Sound classification, Shock detection, Business Analytics, Hallway view, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP66/IP67, IK10+, NEMA4X, PoE+/12VDC	Info

Camera - Network	PNV-A6081R	2MP AI IR Outdoor Vandal Dome	P series network 2MP AI IR outdoor vandal dome camera, Modular structure X PLUS, 2MP @120fps, 4.38-9.33mm motorized varifocal lens (2.13x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 40m, Classified object type : Person/Face/Vehicle/License plate with attributes, BestShot per object, Analytics events based on AI engine : Object detection, Face mask detection, Social distancing detection, Directional detection, Digital auto tracking, Enter/Exit, Loitering, Virtual line, Analytics events : Defocus detection, Motion detection, Appear/Disappear, Tampering, Audio detection, Sound classification, Shock detection, Business Analytics, Hallway view, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP66/IP67/ IP6K9K, IK10+, NEMA4X, PoE+/12VDC	Info
Camera - Network	PND-A6081RV	2MP AI IR Indoor Dome	P series network 2MP AI IR indoor dome camera, Modular structure X PLUS, 2MP @120fps, 4.38-9.33mm motorized varifocal lens (2.13x), triple codec H.265/H.264/MJPEG with WiseStream II, WiseStream III, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 40m, Classified object type : Person/Face/Vehicle/License plate with attributes, BestShot per object, Analytics events based on AI engine : Object detection, Face mask detection, Social distancing detection, Directional detection, Digital auto tracking, Enter/Exit, Loitering, Virtual line, Analytics events : Defocus detection, Motion detection, Appear/Disappear, Tampering, Audio detection, Sound classification, Shock detection, Business Analytics, Hallway view, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP52, IK10, PoE+/12VDC	Info
Camera - Network	PND-A6081RF	2MP AI IR Flush Mount Indoor Dome	P series network 2MP AI IR indoor flush mount dome camera, Modular structure X PLUS, 2MP @120fps, 4.38-9.33mm motorized varifocal lens (2.13x), triple codec H.265/H.264/MJPEG with WiseStream II, WiseStream III, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 40m, Classified object type : Person/Face/Vehicle/License plate with attributes, BestShot per object, Analytics events based on AI engine : Object detection, Face mask detection, Social distancing detection, Directional detection, Digital auto tracking, Enter/Exit, Loitering, Virtual line, Analytics events : Defocus detection, Motion detection, Appear/Disappear, Tampering, Audio detection, Sound classification, Shock detection, Business Analytics, Hallway view, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP52, IK10, Plenum rate, PoE+/12VDC	Info
Camera - Network	PNB-A6001	2MP AI Box	P series network 2MP AI box camera, 2MP @120fps, triple codec H.265/H.264/MJPEG with WiseStream II, WiseStream III, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), Classified object type : Person/Face/Vehicle/ License plate with attributes, BestShot per object, Analytics events based on AI engine : Object detection, Face mask detection, Social distancing detection, Directional detection, Digital auto tracking, Enter/Exit, Loitering, Virtual line, Analytics events : Defocus detection, Motion detection, Appear/Disappear, Tampering, Audio detection, Sound classification, Shock detection, Business Analytics, Hallway view, Bi-directional audio and dual microSD/SDHC/SDXC slot, PoE+/12VDC ※ The lens is not included	Info
Camera - Network	QNO-C6083R	2MP AI IR Bullet	Q series network IR outdoor vandal bullet camera, 2MP @30fps, motorized varifocal lens 3.2-10.2mm (H: 102.0° - 32.2° / V: 54.2° - 18.3°), triple codec H.265/H.264/MJPEG with WiseStream III (Based on AI engine), WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 40m (131.23th), Motion Detection based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/(Dis)Appear), *Audio: Selectable(mic in/line in), defocus detection, hallway View, SD card, video analytics, USB for easy installation, open platform, IP66, IK10, PoE, Operating temperature -40°C~+55°C(-40°F ~ +131°F) white color.	Info
Camera - Network	QNV-C6083R	2MP AI IR Vandal Dome	Q series network IR outdoor vandal dome camera, 2MP @30fps, motorized varifocal lens 3.2-10.2mm (H: 102.0° - 32.2° / V: 54.2° - 18.3°), triple codec H.265/H.264/MJPEG with WiseStream III (Based on AI engine), WiseNR II (Based on AI engine), WDR 120dB, IR viewable length 40m (131.23th), Motion Detection based on AI engine, Classified object type: Person/Vehicle (vehicle type: car/bus/truck/motorcycle/bicycle); IVA events based on AI engine: Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit/(Dis)Appear), *Audio: Selectable(mic in/line in), defocus detection, hallway View, SD card, video analytics, USB for easy installation, open platform, IP66, IK10, PoE, Operating temperature -40°C~+55°C(-40°F ~ +131°F) white color. * Alarm I/O and Audio is supported through an optional cable (PDR-C7400).	Info
Camera - Network	PNV-A6081R-E1T	2MP AI IR Outdoor Vandal Dome with 1TB SolidEDGE WAVE Recording Solution	SolidEDGE is powerful 2MP AI camera with embedded 1TB Solid State Drive (SSD) storage, includes pre-installed Hanwha WAVE VMS with 1 Channel License, capable of recording up to 5 additional cameras for a total recording solution of 6 cameras (32Mbps total recording throughput), P series network IR outdoor vandal dome camera, Modular structure, 2MP @120fps, 4.38-9.33mm motorized varifocal lens (2.13x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 40m, Motion detection, Hallway view, Bi-directional audio, IP66/IP67/ IP6K9K, IK10+, NEMA4X, PoE+/12VDC. NOTE: to record additional cameras, additional license needs to be purchased WAVE-PRO-XX.	Info
Camera - Network	PNV-A6081R-E2T	2MP AI IR Outdoor Vandal Dome with 2TB SolidEDGE WAVE Recording Solution	SolidEDGE is powerful 2MP AI camera with embedded 2TB Solid State Drive (SSD) storage, includes pre-installed Hanwha WAVE VMS with 1 Channel License, capable of recording up to 5 additional cameras for a total recording solution of 6 cameras (32Mbps total recording throughput), P series network IR outdoor vandal dome camera, Modular structure, 2MP @120fps, 4.38-9.33mm motorized varifocal lens (2.13x), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 40m, Motion detection, Hallway view, Bi-directional audio, IP66/IP67/ IP6K9K, IK10+, NEMA4X, PoE+/12VDC. NOTE: to record additional cameras, additional license needs to be purchased WAVE-PRO-XX.	Info
Camera - Network	XND-6081VZ	2MP Indoor PTRZ Dome	X series powered by Wisenet 5 network indoor vandal dome camera, Modular structure X PLUS, 2MP @60fps, 2.8 - 12.0mm motorized varifocal lens (4.3x) (119.5°-27.9°), Motorized Pan/Tilt/Rotate/Zoom, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification and Business Analytics, Shock Detection, Audio Playback, Half View, Motion detection, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP52, IK10, PoE/12VDC, white & ivory colour skins included, optional black skin cover	Info
Camera - Network	XND-6081RF	2MP IR Flush Mount Dome	X series powered by Wisenet 5 network IR flush mount dome camera, Modular structure X PLUS, 2MP @60fps, 2.8 - 12.0mm motorized varifocal lens (4.3x) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 50m, Advanced Video Analytics and Sound Classification and Business Analytics, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP52, Plenum rate (UL2820), PoE/12VDC	Info
Camera - Network	XNV-6081Z	2MP Outdoor PTRZ Dome	X series powered by Wisenet 5 network outdoor vandal dome camera, Modular structure X PLUS, 2MP @60fps, 2.8 - 12.0mm motorized varifocal lens (4.3x) (119.5°-27.9°), Motorized Pan/Tilt/Rotate/Zoom, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification and Business Analytics, Shock Detection, Audio Playback, Half View, Motion detection, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP67/IP66/IP6K9K, IK10+, Nema 4X, PoE/12VDC, optional 24VAC, white & ivory colour skins included, optional black skin cover	Info
Camera - Network	XNV-6081R	2MP IR Outdoor Dome	X series powered by Wisenet 5 network IR outdoor vandal dome camera, Modular structure X PLUS, 2MP @60fps, 2.8 - 12.0mm motorized varifocal lens (4.3x) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 70m, Advanced Video Analytics and Sound Classification and Business Analytics, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP67/IP66/IP6K9K, IK10+, Nema 4X, PoE/12VDC, optional 24VAC, white & ivory colour skins included, optional black skin cover	Info
Camera - Network	XNV-6081RE	2MP IR Indoor Dome	X series powered by Wisenet 5 network IR outdoor vandal dome camera, Modular structure X PLUS, PoE+ in/PoE out, 2MP @60fps, 2.8 - 12.0mm motorized varifocal lens (4.3x) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 50m, Advanced Video Analytics and Sound Classification and Business Analytics, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP67/IP66/IP6K9K, IK10+, Nema 4X, PoE+	Info
Camera - Network	XND-6081REV	2MP IR Indoor Dome	X series powered by Wisenet 5 network IR indoor vandal dome camera, Modular structure X PLUS, PoE+ in/PoE out, 2MP @60fps, 2.8 - 12.0mm motorized varifocal lens (4.3x) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 50m, Advanced Video Analytics and Sound Classification and Business Analytics, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP52, IK10, PoE+	Info
Camera - Network	XNV-6081	2MP Outdoor Dome	X series powered by Wisenet 5 network outdoor vandal dome camera, Modular structure X PLUS, 2MP @60fps, 2.8 - 12.0mm motorized varifocal lens (4.3x) (119.5°-27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification and Business Analytics, Shock Detection, Audio Playback, Hallway View, Motion detection, Fog detection, HLC, Digital Image Stabilization with Gyro sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, ONVIF S/G/T, USB port for easy installation, IP67/IP66/IP6K9K, IK10+, Nema 4X, PoE/12VDC, optional 24VAC, white & ivory colour skins included, optional black skin cover	Info
Camera - Network	XNB-6005	eXtraLUX Box	X series powered by Wisenet 5 network box camera, eXtraLUX features 1/2" sensor, 2MP @60fps, 0.006 Lux@F1.2 (Color), 0.0006 Lux@F1.2 (B/W), simple focus, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization with built-in Gyro sensor, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, PoE/12VDC/24VAC ※ The lens is not included	Info
Camera - Network	XNB-6000	2MP Box	X series powered by Wisenet 5 network box camera, 2MP @60fps, simple focus, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization with built-in Gyro sensor, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, PoE/12VDC/24VAC ※ The lens is not included	Info
Camera - Network	XNB-6001	2MP Covert Main Module	X series powered by Wisenet 5 remote head cam, 2MP @60fps, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Advanced Video Analytics and Sound Classification and Business Analytics, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization with built-in Gyro sensor, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, PoE/12VDC, Compatible with following lens modules SLA-T2480, SLA-T2480V, SLA-T4680, SLA-T4680V, SLA-T1080F, SLA-T4680D, SLA-T4680DS, SLA-T4680DW (not included) ※ The lens is not included	Info
Camera - Network	XNB-6002	2MP Covert Main Module	X series powered by Wisenet 7 remote head cam, 2MP @60fps, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Advanced Video Analytics and Sound Classification and Business Analytics, Motion detection, Handover, Digital Image Stabilization with built-in Gyro sensor, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, PoE/12VDC, Compatible with following lens modules SLA-T2480FA, SLA-T2480A, SLA-T2480VA, SLA-T4680A, SLA-T4680VA (not included) ※ The lens is not included	Info
Camera - Network	XNO-6120	2M 12X Bullet	X series powered by Wisenet 5 network outdoor vandal bullet camera, 2MP @60fps, Full HD(1080p), 5.2 - 62.4mm optical zoom lens (12x) (54.58°-5.30°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization with built-in Gyro sensor, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, IP67, IK10, Nema 4X, PoE/12VDC/24VAC	Info

Camera - Network	XNO-6120R	2M 12X IR Bullet	X series powered by Wisenet 5 network IR outdoor vandal bullet camera, 2MP @60fps, Full HD(1080p), 5.2 – 62.4mm optical zoom lens (12x) (54.58°~5.30°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 70m, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization with built-in Gyro sensor, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, IP67, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	XNO-6085	eXtraLUX Bullet	X series powered by Wisenet 5 network outdoor vandal bullet camera, eXtraLUX features 1/2" sensor with F0.94 Lens, 2MP @60fps, 4.1 – 16.4mm motorized varifocal lens (optical 4x) (100°~26.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification and Business Analytics, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, IP67, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	XNO-6085R	eXtraLUX IR Bullet	X series powered by Wisenet 5 network IR outdoor vandal bullet camera, eXtraLUX features 1/2" sensor with F0.94 Lens, 2MP @60fps, 4.1 – 16.4mm motorized varifocal lens (optical 4x) (100°~26.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 70m, Advanced Video Analytics and Sound Classification and Business Analytics, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, IP67, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	XNO-6080R	2MP IR Bullet	X series powered by Wisenet 5 network IR outdoor vandal bullet camera, 2MP @60fps, 2.8 – 12.0mm motorized varifocal lens (4.3x) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 50m, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, IP67, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	XNO-L6080R	2MP IR Bullet	X series powered by Wisenet 5 network IR outdoor vandal bullet camera, 2MP @60fps, Full HD(1080p), 3.2 – 10mm motorized varifocal lens (3.1x) (109°~33.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 30m, Tampering, Defocus detection, Motion Detection, Fog detection, Hallway View, HLC, Digital Image Stabilization, single SD/SDHC/SDXC slot, USB port for easy installation, IP66, IK10, PoE	Info
Camera - Network	XNO-6010R	2MP IR Bullet	X series powered by Wisenet 5 network IR outdoor vandal bullet camera, 2MP @60fps, 2.4mm fixed lens (139°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 20m, Advanced Video Analytics and Sound Classification and Business Analytics, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, IP67, IK10, Nema 4X, PoE/12VDC	Info
Camera - Network	XNO-6020R	2MP IR Bullet	X series powered by Wisenet 5 network IR outdoor vandal bullet camera, 2MP @60fps, 4mm fixed lens (88.6°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 30m, Advanced Video Analytics and Sound Classification and Business Analytics, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, IP67, IK10, Nema 4X, PoE/12VDC	Info
Camera - Network	XND-6085	eXtraLUX Indoor Dome	X series powered by Wisenet 5 network indoor dome camera, eXtraLUX features 1/2" sensor, 2MP @60fps, 0.004 Lux@F0.94 (Color), 0.0004 Lux@F0.94 (B/W), 4.1 – 16.4mm motorized varifocal lens (optical 4x) (100.0°~26.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization with built-in Gyro sensor, , Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, PoE/12VDC	Info
Camera - Network	XND-6080	2MP Indoor Dome	X series powered by Wisenet 5 network indoor dome camera, 2MP @60fps, 2.8 – 12.0mm motorized varifocal lens (4.3x) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and dual microSD/SDHC/SDXC slot, USB port for easy installation, IK08, PoE/12VDC	Info
Camera - Network	XND-6080V	2MP Indoor Vandal Dome	X series powered by Wisenet 5 network indoor vandal dome camera, 2MP @60fps, 2.8 – 12.0mm motorized varifocal lens (4.3x) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and dual microSD/SDHC/SDXC slot, USB port for easy installation, IK08, PoE/12VDC	Info
Camera - Network	XND-6080R	2MP IR Indoor Dome	X series powered by Wisenet 5 network IR indoor dome camera, 2MP @60fps, 2.8 – 12.0mm motorized varifocal lens (4.3x) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 30m, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and dual microSD/SDHC/SDXC slot, USB port for easy installation, IK08, PoE/12VDC	Info
Camera - Network	XND-6080RV	2MP IR Indoor Vandal Dome	X series powered by Wisenet 5 network IR indoor vandal dome camera, 2MP @60fps, 2.8 – 12.0mm motorized varifocal lens (4.3x) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 30m, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and dual microSD/SDHC/SDXC slot, USB port for easy installation, IK08, PoE/12VDC	Info
Camera - Network	XND-L6080R	2MP IR Indoor Dome	X series powered by Wisenet 5 network IR indoor dome camera, 2MP @60fps, 3.2 – 10.0mm motorized varifocal lens (3.1x) (109.0°~33.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 20m, Tampering, Defocus detection, Motion Detection, Fog detection, Hallway View, HLC, Digital Image Stabilization, single SD/SDHC/SDXC slot, USB port for easy installation, IK08, PoE	Info
Camera - Network	XND-6020R	2MP IR Indoor Dome	X series powered by Wisenet 5 network IR indoor dome camera, 2MP @60fps, 4mm fixed lens (88.6°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 30m, Advanced Video Analytics and Sound Classification and Business Analytics, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and dual microSD/SDHC/SDXC slot, USB port for easy installation, IK08, PoE/12VDC	Info
Camera - Network	XND-6011F	2MP Flush Mount	X series powered by Wisenet 5 network flush mount dome camera, 2MP @60fps, 2.8mm fixed lens (112°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, Electronic Day & Night , Advanced Video Analytics and Sound Classification and Business Analytics, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Built-in Mic, 1-directional audio and SD/SDHC/SDXC slot, USB port for easy installation, PoE	Info
Camera - Network	XND-6010	2MP Indoor Dome	X series powered by Wisenet 5 network indoor dome camera, 2MP @60fps, 2.4mm fixed lens (139°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification and Business Analytics, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and dual SD/SDHC/SDXC slot, IK08, PoE/12VDC	Info
Camera - Network	XNV-6120	2M 12X Outdoor Dome	X series powered by Wisenet 5 network outdoor vandal dome camera, 2MP @60fps, Full HD(1080p), 5.2 – 62.4mm optical zoom lens (12x) (54.58°~5.30°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, HLC, Handover, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, USB port for easy installation, IP67, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	XNV-6120R	2M 12X IR outdoor Dome	X series powered by Wisenet 5 network IR outdoor vandal dome camera, 2MP @60fps, Full HD(1080p), 5.2 – 62.4mm optical zoom lens (12x) (54.58°~5.30°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 70m, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and dual microSD/SDHC/SDXC slot, USB port for easy installation, IP67, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	XNV-6085	eXtraLUX Outdoor PTRZ Dome	X series powered by Wisenet 5 network outdoor vandal dome camera, eXtraLUX features 1/2" sensor, 2MP @60fps, 0.004 Lux@F0.94 (Color), 0.0004 Lux@F0.94 (B/W), 4.1 – 16.4mm motorized varifocal lens (optical 4x) (100.0°~26.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization with built-in Gyro sensor, , Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, IP67, IK10, Nema 4X, PoE/12VDC/24VAC	Info

Camera - Network	XNV-6080	2MP Outdoor Dome	X series powered by Wisenet 5 network outdoor vandal dome camera, 2MP @60fps, 2.8 ~ 12.0mm motorized varifocal lens (4.3x) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and dual microSD/SDHC/SDXC slot, USB port for easy installation, IP67/IP66, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	XNV-6080R	2MP IR Outdoor Dome	X series powered by Wisenet 5 network IR outdoor vandal dome camera, 2MP @60fps, 2.8 ~ 12.0mm motorized varifocal lens (4.3x) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 50m, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and dual microSD/SDHC/SDXC slot, USB port for easy installation, IP67/IP66, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	XNV-6080RSA	2MP Stainless Steel IR Dome	X series powered by Wisenet 5 network IR outdoor stainless steel vandal dome camera, 2MP @60fps, 2.8 ~ 12.0mm motorized varifocal lens (4.3x) (119.5°~27.9°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 50m, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and dual microSD/SDHC/SDXC slot, USB port for easy installation, IP66, IP66K9K, IK10+, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	XNV-L6080	2MP Outdoor Dome	X series powered by Wisenet 5 network outdoor vandal dome camera, 2MP @60fps, 3.2 ~ 10.0mm motorized varifocal lens (3.1x) (109.0°~33.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), Tampering, Defocus detection, Motion Detection, Fog detection, Hallway View, HLC, Digital Image Stabilization, single SD/SDHC/SDXC slot, USB port for easy installation, IP66, IK10, PoE	Info
Camera - Network	XNV-L6080R	2MP IR Outdoor Dome	X series powered by Wisenet 5 network IR outdoor vandal dome camera, 2MP @60fps, 3.2 ~ 10.0mm motorized varifocal lens (3.1x) (109.0°~33.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 30m, Tampering, Defocus detection, Motion Detection, Fog detection, Hallway View, HLC, Digital Image Stabilization, single SD/SDHC/SDXC slot, USB port for easy installation, IP66, IK10, PoE	Info
Camera - Network	XNV-6022R	2MP Mobile Vandal Dome	X series powered by Wisenet 5 network IR outdoor vandal dome camera, 2MP @60fps, 3.6mm fixed lens (94.8°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), IR viewable length 15m, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and SD/SDHC/SDXC slot, USB port for easy installation, IP66, IK10, NEMA 4X, PoE	Info
Camera - Network	XNV-6022RM	2MP Mobile Vandal Dome	X series powered by Wisenet 5 network IR outdoor vandal dome camera, 2MP @60fps, 3.6mm fixed lens (94.8°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), IR viewable length 15m, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and SD/SDHC/SDXC slot, USB port for easy installation, IP66, IK10, NEMA 4X, PoE, M12 connector (M12 to RJ45 is not included)	Info
Camera - Network	XNV-6020R	2MP IR Outdoor Dome	X series powered by Wisenet 5 network IR outdoor vandal dome camera, 2MP @60fps, 4mm fixed lens (88.6°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), High Powered IR LEDs with IR viewable length 30m, Advanced Video Analytics and Sound Classification and Business Analytics, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and dual microSD/SDHC/SDXC slot, USB port for easy installation, IP67/IP66, IK10, PoE/12VDC	Info
Camera - Network	XNV-6013M	2MP Mobile Vandal Dome	X series powered by Wisenet 5 network outdoor vandal dome camera, 2MP @60fps, 2.8mm fixed lens (107.4°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, Electrical Day & Night, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and SD/SDHC/SDXC slot, IP67, IP66K9K, IK10, NEMA 4X, PoE This camera was designed to be mounted outside of the vehicle, M12 connector (M12 to RJ45 is not included)	Info
Camera - Network	XNV-6012M	2MP Mobile Vandal Dome	X series powered by Wisenet 5 network outdoor vandal dome camera, 2MP @60fps, 2.4mm fixed lens (135.4°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, Electrical Day & Night, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and SD/SDHC/SDXC slot, IP66, IK10, NEMA 4X, PoE, M12 connector (M12 to RJ45 is not included)	Info
Camera - Network	XNV-6012	2MP Mobile Vandal Dome	X series powered by Wisenet 5 network outdoor vandal dome camera, 2MP @60fps, 2.4mm fixed lens (135.4°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, Electrical Day & Night, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and SD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE	Info
Camera - Network	XNV-6011	2MP Compact Vandal Dome	X series powered by Wisenet 5 network outdoor compact vandal dome camera, 2MP @60fps, 2.8mm fixed lens (112°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, Electronic Day & Night, Advanced Video Analytics and Business Analytics, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, SD/SDHC/SDXC slot, USB port for easy installation, IP66, IK10, Nema 4X, PoE	Info
Camera - Network	XNV-6010	2MP Outdoor Dome	X series powered by Wisenet 5 network outdoor vandal dome camera, 2MP @60fps, 2.4mm fixed lens (139°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Classification and Business Analytics, Hallway View, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP67/IP66, IK10, Nema 4X, PoE/12VDC	Info
Camera - Network	XNP-6400RW	2MP 40x IR Outdoor PTZ	X series powered by Wisenet 7 network IR outdoor PTZ camera with built-in wiper, 2MP @60fps, 40X Optical Zoom Lens (4.25 ~ 170mm) (65.66° ~ 1.88°), 360° Endless Pan range, 500°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (150dB), True Day & Night (ICR), IR viewable length 200m, Intelligent Video Analytics, Motion detection, Fog detection, Tampering, Object auto tracking(Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, HPoE * Alarm outputs, Audio detection, Sound classification(with NW I/O Box which can be purchased separately)	Info
Camera - Network	XNP-6400R	2MP 40x IR Outdoor PTZ	X series powered by Wisenet 7 network IR outdoor PTZ camera, 2MP @60fps, 40X Optical Zoom Lens (4.25 ~ 170mm) (65.66° ~ 1.88°), 360° Endless Pan range, 700°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (150dB), True Day & Night (ICR), IR viewable length 200m, Intelligent Video Analytics, Motion detection, Fog detection, Tampering, Object auto tracking(Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, NEMA-TS2, HPoE * Alarm outputs, Audio detection, Sound classification(with NW I/O Box which can be purchased separately)	Info
Camera - Network	XNP-6400	2MP 40x Outdoor PTZ	X series powered by Wisenet 7 network outdoor PTZ camera, 2MP @60fps, 40X Optical Zoom Lens (4.25 ~ 170mm) (65.66° ~ 1.88°), 360° Endless Pan range, 700°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, extreme WDR (150dB), True Day & Night (ICR), Intelligent Video Analytics, Motion detection, Fog detection, Tampering, Object auto tracking(Person/Vehicle), Target lock tracking, Digital Image Stabilization with Built-in Gyro sensor, 2x Micro SD/SDHC/SDXC slots up to 1TB, IP66, IK10, NEMA4X, NEMA-TS2, HPoE * Alarm outputs, Audio detection, Sound classification(with NW I/O Box which can be purchased separately)	Info
Camera - Network	XNP-6550RH	2MP 55x IR PTZ	X series powered by Wisenet 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 55X optical zoom lens (4.75mm ~ 261.4mm) (58.6° ~ 1.23°), Pan: 360° endless. Tilt: -5°~ 185°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, built-in IR 1640ft (500m), USB port for easy installation, advanced video analytics and sound classification, Day & Night (ICR), dual SD card, HLC, defog (optical) DiS(Gyro),24VAC/HPoE, IP66/IK10, -58°F ~ +131°F W/ 24VAC power supply	Info
Camera - Network	XNP-6371RH	2MP 37x IR PTZ	X series powered by Wisenet 5 network IR outdoor PTZ camera, 2MP @60fps, 37X Optical Zoom Lens (6 ~ 222mm) (59.3° ~ 1.9°), 360° Endless Pan range, 400°/sec Pan speed, Tilt: -5° ~ 185°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), IR viewable length 350m, Intelligent Video Analytics, Motion detection, Fog detection, Auto Tracking, HLC, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and SD/SDHC/SDXC slot, IP66, IK10, 24VAC	Info
Camera - Network	XNP-6120H	2MP 12X PTZ	X series powered by Wisenet 5 network outdoor PTZ camera, 2MP @ 60fps, Full HD(1080p), 12X optical zoom lens (5.2mm ~62.4mm) (54.58° ~ 5.3°), 360° Endless Pan range, Tilt: -5° ~ 185°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Vlassification, Motion detection, Fog detection, Auto Tracking, HLC, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual SD/SDHC/SDXC slot, USB port for easy installation, IP66, IK10, PoE/12VDC	Info
Camera - Network	XNP-6040H	2MP 4.3X PTZ	X series powered by Wisenet 5 network outdoor PTZ camera, 2MP @ 60fps, Full HD(1080p), 4.3X optical zoom lens (2.8mm ~12mm) (119.5° ~ 27.9°), Pan: 0°~350°, Tilt: 0°~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 150dB WDR, True Day & Night (ICR), Advanced Video Analytics and Sound Vlassification, Motion detection, Fog detection, Defocus detection, Auto Tracking, HLC, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and SD/SDHC/SDXC slot, USB port for easy installation, IP66, IK10, PoE/12VDC	Info

Camera - Network	XNZ-6320A	2MP 32x Zoom Box	X series powered by Wisenet 5 network zoom box camera, 2MP @60fps, 4.44 ~ 142.6mm optical zoom lens (32x), H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), Slips slot, Defocus detection, Directional detection, Fog detection, Face detection, Motion detection, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line, Audio detection, Sound classification, Shock detection, HLC, Digital Image Stabilization with built-in Gyro sensor, Bi-directional audio and Micro SD/SDHC/SDXC 2 slot 512GB, USB port for easy installation, PoE/12VDC	Info
Camera - Network	XNZ-L6320A	2MP 32x Zoom Box	X series powered by Wisenet 5 network zoom box camera, 2MP @60fps, 4.44 ~ 142.6mm optical zoom lens (32x), H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), Defocus detection, Directional detection, Fog detection, Face detection, Motion detection, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line, Audio detection, Sound classification, HLC, Digital Image Stabilization, Bi-directional audio and Micro SD/SDHC/SDXC 1 slot 256GB, PoE/12VDC	Info
Camera - Network	QNO-6082R	2MP IR Bullet	Q series network IR outdoor vandal bullet camera, 2MP @30fps, 3.2 ~ 10.0mm motorized varifocal lens (3.1x) (109.0°~33.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 30m, Motion detection, Tampering, Defocus detection, Hallway View, Bi-directional audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNO-6082R1	2MP IR Bullet	Q series network IR outdoor vandal bullet camera (No Audio), 2MP @30fps, 3.2 ~ 10.0mm motorized varifocal lens (3.1x), H.265/H.264/MJPEG, Multiple streaming, 120dB WDR, Day & Night (auto ICR), IR viewable length 30m, Motion detection, Tampering, Defocus detection, Hallway View (90°/270°), micro SD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNO-6022R	2MP IR Bullet	Q series network IR outdoor vandal bullet camera, 2MP @30fps, 4mm fixed lens (87.6°), triple codec H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 25m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNO-6022R1	2MP IR Bullet	Q series network IR outdoor vandal bullet camera (No Audio), 2MP @30fps, 4mm fixed lens, triple codec H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 25m, Motion detection, Tampering, Defocus detection, Hallway View (90°/270°), micro SD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNO-6012R	2MP IR Bullet	Q series network IR outdoor vandal bullet camera, 2MP @30fps, 2.8mm fixed lens (113.74°), triple codec H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 20m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNO-6012R1	2MP IR Bullet	Q series network IR outdoor vandal bullet camera (No Audio), 2MP @30fps, 2.8mm fixed lens, triple codec H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 20m, Motion detection, Tampering, Defocus detection, Hallway View (90°/270°), microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QND-6082R	2MP IR Dome	Q series network IR indoor dome camera, 2MP @30fps, 3.2 ~ 10.0mm motorized varifocal lens (3.1x) (109.0°~33.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 20m, Motion detection, Tampering, Defocus detection, Hallway View, Bi-directional audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), PoE/12VDC	Info
Camera - Network	QND-6082R1	2MP IR Dome	Q series network IR indoor dome camera (No Audio), 2MP @30fps, 3.2 ~ 10.0mm motorized varifocal lens (3.1x), H.265/H.264/MJPEG, Multiple streaming, 120dB WDR, Day & Night (auto ICR), IR viewable length 20m, Motion detection, Tampering, Defocus detection, Hallway View(90°/270°), microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), PoE/12VDC	Info
Camera - Network	QND-6022R	2MP IR Dome	Q series network IR indoor dome camera, 2MP @30fps, 4mm fixed lens (87.6°), triple codec H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 20m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), PoE/12VDC	Info
Camera - Network	QND-6022R1	2MP IR Dome	Q series network IR indoor dome camera(No Audio), 2MP @30fps, 4mm fixed lens, H.265/H.264/ MJPEG, Multiple streaming, 120dB WDR, Day & Night (auto ICR), IR viewable length 20m, Motion detection, Tampering, Defocus detection, Hallway View(90°/270°), microSD/ SDHC/ SDXC slot, LDC support (Lens Distortion Correction), PoE/12VDC	Info
Camera - Network	QND-6012R	2MP IR Dome	Q series network IR indoor dome camera, 2MP @30fps, 2.8mm fixed lens (113.74°), triple codec H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 20m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), PoE/12VDC	Info
Camera - Network	QND-6012R1	2MP IR Dome	Q series network IR indoor dome camera (No Audio), 2MP @30fps, 2.8mm fixed lens , H.265/H.264/ MJPEG with WiseStream, Multiple streaming, 120dB WDR, Day & Night (auto ICR), IR viewable length 20m, Motion detection, Tampering, Defocus detection, Hallway View(90°/270°), microSD/ SDHC/SDXC slot, LDC support (Lens Distortion Correction), PoE/12VDC	Info
Camera - Network	QND-6021	2MP Mini Dome	Q series network indoor mini dome camera, 2MP @30fps, 4.0mm fixed lens (87.6°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), Business Analytics (People counting), Motion detection, Tampering, Defocus detection, Hallway View, microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP42, IK08, PoE, Compact size 99 x 56mm/145gr	Info
Camera - Network	QND-6011	2MP Mini Dome	Q series network indoor mini dome camera, 2MP @30fps, 2.8mm fixed lens (113.74°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), Business Analytics (People counting), Motion detection, Tampering, Defocus detection, Hallway View, microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP42, IK08, PoE, Compact size 99 x 56mm/145gr	Info
Camera - Network	QNV-6082R	2MP IR Vandal Dome	Q series network IR outdoor vandal dome camera, 2MP @30fps, 3.2 ~ 10.0mm motorized varifocal lens (3.1x) (109.0°~33.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 30m, Motion detection, Tampering, Defocus detection, Hallway View, Bi-deirectional audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNV-6082R1	2MP IR Vandal Dome	Q series network IR outdoor vandal dome camera (No Audio), 2MP @30fps, 3.2 ~ 10.0mm motorized varifocal lens (3.1x), H.265/H.264/MJPEG, Multiple streaming, 120dB WDR, Day & Night (Auto ICR), IR viewable length 30m, Motion detection, Tampering, Defocus detection, Hallway View(90°/270°), micro SD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNV-6023R	2MP Mobile IR Vandal Dome	Q series network IR outdoor vandal Dome camera, 2MP @60fps, 3.6mm fixed lens (94.8°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 15m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, NEMA4X, PoE	Info
Camera - Network	QNV-6022R	2MP IR Vandal Dome	Q series network outdoor vandal dome camera, 2MP @30fps, 4mm fixed lens (87.6°), triple codec H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 25m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNV-6022R1	2MP IR Vandal Dome	Q series network outdoor vandal dome camera (No Audio), 2MP @30fps, 4mm fixed lens, H.265/H.264/MJPEG, Multiple streaming, 120dB WDR, Day & Night (Auto ICR), IR viewable length 25m, Motion detection, Tampering, Defocus detection, Hallway View (90°/270°), micro SD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNV-6012R	2MP IR Vandal Dome	Q series network IR outdoor vandal dome camera, 2MP @30fps, 2.8mm fixed lens (113.74°), triple codec H.265/H.264/MJPEG with WiseStream, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 20m, Motion detection, Tampering, Defocus detection, Hallway View, 1-way audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info

Camera - Network	QNV-6012R1	2MP IR Vandal Dome	Q series network IR outdoor vandal dome camera (No Audio), 2MP @30fps, 2.8mm fixed lens, H.265/H.264/MJPEG, Multiple streaming, 120dB WDR, Day & Night (auto ICR), IR viewable length 20m, Motion detection, Tampering, Defocus detection, Halfway View (90°/270°), micro SD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, PoE/12VDC	Info
Camera - Network	QNV-6024RM	2MP Mobile IR Vandal Dome	Q series network IR outdoor vandal flateye camera, 2MP @60fps, 3.6mm fixed lens (94.8°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 15m, Motion detection, Tampering, Defocus detection, Halfway View, Bi-directional audio and microSD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), IP66, IK10, NEMA4X, PoE, M12 connector	Info
Camera - Network	QNP-6320	2MP 32x PTZ	Q series network indoor PTZ camera, 2MP @30fps, Full HD(1080p), 32X Optical Zoom Lens (4.44 ~ 142.6mm) (64.66° ~ 2.29°), 360° Endless Pan range, 700°/sec Pan speed, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), Directional detection, Motion detection, Enter/Exit, Tampering, Virtual line, Audio detection, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and SD/SDHC/SDXC slot, PoE+	Info
Camera - Network	QNP-6320R	2MP 32x IR PTZ	Q series network IR outdoor PTZ camera, 2MP @60fps, 32X Optical Zoom Lens (4.44 ~ 142.6mm) (64.66° ~ 2.29°), 360° Endless Pan range, 700°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 100m (Wise IR), Motion detection, Tampering detection, Defocus detection, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual SD/SDHC/SDXC slot, IP66, IK10, PoE+, NEMA4X	Info
Camera - Network	QNP-6320H	2MP 32x PTZ	Q series network outdoor PTZ camera, 2MP @30fps, Full HD(1080p), 32X Optical Zoom Lens (4.44 ~ 142.6mm), 360° Endless Pan range, 700°/sec Pan speed, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), Directional detection, Motion detection, Enter/Exit, Tampering, Virtual line Audio detection (with NW I/O Box), Digital Image Stabilization with Built-in Gyro sensor and SD/SDHC/SDXC slot, IP66, IK10, PoE+	Info
Camera - Network	QNP-6250	2MP 25x PTZ	Q series network indoor PTZ camera, 2MP @30fps, Full HD(1080p), 25X Optical Zoom Lens (4.44~111mm) (64.66° ~ 2.99°), 360° Endless Pan range, 700°/sec Pan speed, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), Directional detection, Motion detection, Enter/Exit, Tampering, Virtual line, Audio detection, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and SD/SDHC/SDXC slot, PoE+	Info
Camera - Network	QNP-6250R	2MP 25x IR PTZ	Q series network IR outdoor PTZ camera, 2MP @30fps, 25X Optical Zoom Lens (4.44 ~ 142.6mm) (61.8° ~ 3.08°), 360° Endless Pan range, 400°/sec Pan speed, Tilt: -20° ~ 90°, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), IR viewable length 100m (Wise IR), Motion detection, Tampering detection, Defocus detection, Digital Image Stabilization with Built-in Gyro sensor, Bi-directional audio and dual SD/SDHC/SDXC slot, IP66, IK10, PoE+, NEMA4X	Info
Camera - Network	QNP-6250H	2MP 25x PTZ	Q series network outdoor PTZ camera, 2MP @30fps, Full HD(1080p), 25X Optical Zoom Lens (4.44 ~ 111mm), 360° Endless Pan range, 700°/sec Pan speed, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), Directional detection, Motion detection, Enter/Exit, Tampering, Virtual line Audio detection (with NW I/O Box), Digital Image Stabilization with Built-in Gyro sensor and SD/SDHC/SDXC slot, IP66, IK10, PoE+	Info
Camera - Network	QNP-6320HS	2MP 32x Stainless steel PTZ	Q series network stainless steel PTZ camera, 2MP @ 30fps, Full HD (1080p), 32X optical zoom lens (4.44mm ~142.6mm), 360° Endless Pan range, 700°/sec Pan speed, H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), Directional detection, Motion detection, Enter/Exit, Tampering, Virtual line, Audio detection (with NW I/O Box), HLC, Digital Image Stabilization with Built-in Gyro sensor, Micro SD/SDHC/SDXC slot, IP67, IP66, NEMA4X, IK10, PoE+, Max. 23W, Typ. 14W	Info
Camera - Network	QNB-6002	2MP Box	Q series network box camera, 2MP @30fps, triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), Advanced Video Analytics, Halfway View, Motion detection, Tampering, Defocus detection, Bi-directional audio and dual SD/SDHC/SDXC slot, LDC support (Lens Distortion Correction), PoE/12VDC ※ The lens is not included	Info
Camera - Network	XNB-H6461H	2MP Pinhole Camera with 4.6mm lens in Height Strip enclosure	X series powered by Wisenet 5 remote head cam, 2MP @60fps, 4.6mm fixed lens (73°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Advanced Video Analytics and Sound Classification and Business Analytics, Motion detection, Fog detection, HLC, Handover, Digital Image Stabilization, Bi-directional audio and SD/SDHC/SDXC slot, USB port for easy installation, PoE/12VDC, height strip enclosure	Info
Camera - Network	TID-600R	2MP Intercom	T series network Intercom, 2MP@60fps, 1.6mm fixed lens, IR 5m, True Day & Night (ICR), backlit call button, option for touchless call, built-in mic and speaker, echo cancellation and noise reduction, corridor mode, camera handover, SIP 2.0 support for integration with VoIP systems, H.265/H.264/MJPEG with WiseStream II, Open Platform, Licence-free onboard Advanced Video Analytics: Directional detection, Motion detection, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line, Audio detection, Shock detection, Sound classification, 1 Micro SD card slot, 2 Inputs/1 Output/1 Relay, IP65, IK08, NEMA4X, Safety(UL), EMC(FCC, CE)	Info
Camera - Network	TNU-6321	2MP 32x Positioning	T series network Positioning camera, 2MP @60fps, 4.44 ~ 142.6mm 32x optical zoom lens (61.8° ~ 2.19°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, True Day & Night (ICR), Advanced Video Analytics, Face detection, Motion detection, Fog detection, Handover, HLC, Digital Image Stabilization, Bi-directional audio and dual microSD/SDHC/SDXC slot, IP66, Safety (UL, KC-SDOC), EMC (FCC, CE, VCCI, RCM, KC), 24VAC	Info
Camera - Network	TNB-6030	PVM Camera	T series PVM camera powered by Wisenet 5, 1080p (1920x1080), micro HDMI output, 16:9 aspect ratio, face detection display for visual deterrent, customizable text overlay, 4.6mm fixed lens(73.8°H), 150dB WDR, H.265/H.264/MJPEG, WiseStream II compression technology, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode	Info
Camera - Network	ANE-L6012R	2MP Turret Camera	Wisenet A Series turret camera, 2MP @ 30 FPS, 3mm fixed focal lens, FoV H: 107.7° / V: 59.0°, WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 20m(65.62ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.	Info
Camera - Network	ANO-L6012R	2MP IR Bullet	A Series bullet camera, 2MP @ 30 FPS, 2.8mm fixed focal lens, FoV H: 113.7° / V: 61.5°, WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 30m(98.43ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual Line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.	Info
Camera - Network	ANO-L6022R	2MP IR Bullet	A Series bullet camera, 2MP @ 30 FPS, 4mm fixed focal lens, FoV H: 84.3° / V: 45.6° WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 30m(98.43ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.	Info
Camera - Network	ANO-L6082R	2MP IR Bullet	A Series bullet camera, 2MP @30FPS, motorized varifocal lens 3.1x (3.3~10.3mm) (105.2°~ 30.6°), WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 30m(98.43ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.	Info
Camera - Network	ANV-L6012R	2MP IR Vandal Dome	A Series outdoor vandal dome camera, 2MP @ 30 FPS, 2.8mm fixed focal lens, FoV H: 113.7°/ V: 61.5°, WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 30m(98.43ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, IK10, PoE, white.	Info
Camera - Network	ANV-L6023R	2MP IR Vandal Dome	A Series outdoor vandal mini dome camera, 2MP @ 30 FPS, 3.6mm fixed focal lens, FoV H: 94.8°/ V: 49.3°, WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 15m(49.21ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, PoE, white.	Info
Camera - Network	ANV-L6082R	2MP IR Vandal Dome	A Series outdoor vandal dome camera, 2MP @ 30fps, motorized vari-focal lens 3.1x (3.3~10.3mm) (105.2°~ 30.6°), WiseStream II, triple codec (H.265/H.264/MJPEG), 120dB WDR, IR LEDs 30m(98.43ft), day & night (ICR), virtual area (intrusion/enter/exit), virtual line (crossing/ direction), motion detection, tampering, hallway view, SD card, IP66, IK10, PoE, white.	Info

Camera - Network	LNO-6072R	2MP IR Bullet	L series network IR outdoor vandal bullet camera, 2MP @30fps, 3.2 ~ 10.0mm varifocal lens (3.1x) (101.6"~ 31.3"), H.264/MJPEG with WiseStream II, Multiple streaming, 120dB WDR, Auto Day & Night (ICR), IR viewable length 30m, Motion detection, Tampering, Halway View, microSD/SDHC slot, LDC support (Lens Distortion Correction), IP66, PoE	Info
Explosion-proof Cameras				
Camera - Network	TNO-C8083E	5MP AI Compact Explosion-proof Camera	5MP AI Compact Explosion-proof Camera with SUS316L stainless steel construction up to 30fps@5MP resolution with 1/2.8" 5MP CMOS sensor, 3.2x motorized vari-focal lens, 1/2" cable gland, H.264/H.265 & MJPEG codescs, Digital Noise Reduction SSNR V , WDR 120db, Electronic Shutter Min ~ Max / Anti Flicker (5~1/2,000sec), Video Rotation Flip, Mirror, Halway view(90/270), Analytics Classified object type: Person/Vehicle, Attributes: Vehicle, Support Detection/Spot, Analytics events based on AI engine, Motion detection, Object detection, Virtual line(Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit) Analytics events : Defocus, Business Intelligence Based on AI engine: People/Vehicle counting, Queue management, Heatmap, WiseStreamIII(Based on AI engine), Unicast(20 users) / Multicast (Up to 5/profiles), ONVIF Profile S/T/M, SUNAPI(HTTP API), Operating Temperature / Humidity -30°C~+55°C(-22°F ~ +131°F) / 0~95% RH(non-condensing), Certification CE, KC, IP66, IK10,ATEX,II 2 G Ex db IIc T6 Gb II 2 D Ex tb IIIC T80°C Db, IECEx, Ex db IIc T6 Gb, Ex tb IIIC T80°C Db	Info
Camera - Network	TNO-6322ER	Explosion Proof Stainless Steel Bullet Camera with Built-in Wiper and IR 70m	Explosion Proof Stainless Steel 316L Bullet Camera with Built-in Wiper and IR 70m, 2MP@60fps, 4.44 ~ 142.6mm (32X) zoom lens, 120dB WDR, Auto Day & Night (ICR), WiseStream II, Defocus detection, Directional detection, Fog detection, Face detection, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line, Audio detection, Digital Image Stabilization, ONVIF S/G/T, 1 Input/1 Output, 24VAC, IP67, IK10, IECEx, ATEX, KCs, KC, CE	Info
Camera - Network	TNU-6322E	Explosion Proof Stainless Steel Positioning Bullet Camera with Built-in Wiper	Explosion Proof Stainless Steel 316L Positioning Bullet Camera with Built-in Wiper, 360 Endless Pan, 2MP@60fps, 4.44 ~ 142.6mm (32X) zoom lens, 120dB WDR, Auto Day & Night (ICR), WiseStream II, Defocus detection, Directional detection, Fog detection, Face detection, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line, Audio detection, Digital Image Stabilization, ONVIF S/G/T, 1 Input/1 Output, 24VAC, IP67, IK10, IECEx, ATEX, KCs, KC, CE	Info
Camera - Network	TNU-6322ER	Explosion Proof Stainless Steel Positioning Bullet Camera with Built-in Wiper and IR	Explosion Proof Stainless Steel 316L Positioning Bullet Camera with Built-in Wiper and IR 200m, 360 Endless Pan, 2MP@60fps, 4.44 ~ 142.6mm (32X) zoom lens, 120dB WDR, Auto Day & Night (ICR), WiseStream II, Defocus detection, Directional detection, Fog detection, Face detection, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line, Audio detection, Digital Image Stabilization, ONVIF S/G/T, 1 Input/1 Output, 24VAC, IP67, IK10, IECEx, ATEX, KCs, KC, CE	Info
Thermal Cameras				
Camera - Network	TNO-C3032TRA	Lower Frame Rate, QVGA Radiometric AI Thermal Camera	T series network Radiometric compact bullet camera, 384 x 288 (uncooled); < 30mK (NETD), Max 768 x 576 @ 8fps resolution support, 9.7mm fixed focal lens (FoV: 37.9°), Triple triple codec H.265/H.264/MJPEG with Wisestream II and WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Vehicle), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), PTZ handover, Radiometrics: whole FoV area or up to 10 user programmable polygonal ROIs, temperature detection range from -40°C to 550°C (-40°F to 1022°F), SD card, integrated back box, IP66, NEMA4X, IK10, PoE/12VDC, white color	Info
Camera - Network	TNO-C3022TRA	Lower Frame Rate, QVGA Radiometric AI Thermal Camera	T series network Radiometric compact bullet camera, 384 x 288 (uncooled); < 30mK (NETD), Max 768 x 576 @ 8fps resolution support, 6.6mm fixed focal lens (FoV: 60.0°), Triple triple codec H.265/H.264/MJPEG with Wisestream II and WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Vehicle), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), PTZ handover, Radiometrics: whole FoV area or up to 10 user programmable polygonal ROIs, temperature detection range from -40°C to 550°C (-40°F to 1022°F), SD card, integrated back box, IP66, NEMA4X, IK10, PoE/12VDC, white color	Info
Camera - Network	TNO-C3012TRA	Lower Frame Rate, QVGA Radiometric AI Thermal Camera	T series network Radiometric compact bullet camera, 384 x 288 (uncooled); < 30mK (NETD), Max 768 x 576 @ 8fps resolution support, 4.4mm fixed focal lens (FoV: 90.0°), Triple triple codec H.265/H.264/MJPEG with Wisestream II and WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Vehicle), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), PTZ handover, Radiometrics: whole FoV area or up to 10 user programmable polygonal ROIs, temperature detection range from -40°C to 550°C (-40°F to 1022°F), SD card, integrated back box, IP66, NEMA4X, IK10, PoE/12VDC, white color.	Info
Camera - Network	TNO-C3030TRA	QVGA Radiometric AI Thermal Camera	T series network Radiometric compact bullet camera, 384 x 288 (uncooled); < 30mK (NETD), Max 768 x 576 @ 30fps resolution support, 9.7mm fixed focal lens (FoV: 37.9°), Triple triple codec H.265/H.264/MJPEG with Wisestream II and WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Vehicle), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), PTZ handover, Radiometrics: whole FoV area or up to 10 user programmable polygonal ROIs, temperature detection range from -40°C to 550°C (-40°F to 1022°F), SD card, integrated back box, IP66, NEMA4X, IK10, PoE/12VDC, white color. This product is subject to the Thermal agreement.	Info
Camera - Network	TNO-C3020TRA	QVGA Radiometric AI Thermal Camera	T series network Radiometric compact bullet camera, 384 x 288 (uncooled); < 30mK (NETD), Max 768 x 576 @ 30fps resolution support, 6.6mm fixed focal lens (FoV: 60.0°), Triple triple codec H.265/H.264/MJPEG with Wisestream II and WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Vehicle), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), PTZ handover, Radiometrics: whole FoV area or up to 10 user programmable polygonal ROIs, temperature detection range from -40°C to 550°C (-40°F to 1022°F), SD card, integrated back box, IP66, NEMA4X, IK10, PoE/12VDC, white color.This product is subject to the Thermal agreement.	Info
Camera - Network	TNO-C3010TRA	QVGA Radiometric AI Thermal Camera	T series network Radiometric compact bullet camera, 384 x 288 (uncooled); < 30mK (NETD), Max 768 x 576 @ 30fps resolution support, 4.4mm fixed focal lens (FoV: 90.0°), Triple triple codec H.265/H.264/MJPEG with Wisestream II and WiseStream III (based on AI engine) support, Analytics events based on AI engine: Object detection (Person/Vehicle), Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events: Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), PTZ handover, Radiometrics: whole FoV area or up to 10 user programmable polygonal ROIs, temperature detection range from -40°C to 550°C (-40°F to 1022°F), SD card, integrated back box, IP66, NEMA4X, IK10, PoE/12VDC, white color. This product is subject to the Thermal agreement.	Info
Camera - Network	TNM-C4960TD	Bi-Spectrum AI Thermal Camera, AI, Thermal 25mm / Visible 10.9~29mm M-V/F	T series network bi-spectrum AI thermal camera bullet camera, Thermal sensor: 25mm fixed focal, VGA (640x480 - can be scaled up to SVGA 1280x960), H.265/H.264: Max. 30fps/25fps (AI 2CH ON - 15fps), MJPEG: Max. 3fps, NETD < 60mK, Pixel Size 12μm, 7 x Color Palettes, Analytics events based on AI engine: Object detection (Person/Vehicle), Bestshot, IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Stopped vehicle, Traffic jam, Vehicle counting, Analytics events: Motion detection, Visible sensor: 10.9~29mm(2.6x) motorized varifocal, 4K (3840x2160), H.265/H.264: Max. 30fps/25fps (AI 2CH ON - 15fps), MJPEG: Max. 1fps, Analytics events based on AI engine Object detection (Person, face, ehicle(car/bus/truck/motorcycle/bicycle), License plate), Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events : Defocus detection, Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), Camera features: 4 x I/O ports, 1 x Metal shielded RJ-45(10/100/1000BASE-T), TPM 2.0 (FIPS 140-2 level 2) HTTPS(SSL) login authentication, 2 x Micro SD slots each max 512GB, PoE+(IEEE802.3at, Class4), 12VDC, IP66/IP67, IK10, NEMA4X, NEMA TS 2(2.2.8, 2.2.9), includes pole/mount bracket, excludes Stainless Steel Straps (SBP-100S)	
Camera - Network	TNM-C4950TD	Bi-Spectrum AI Thermal Camera, AI, Thermal 13.5mm / Visible 10.9~29mm M-V/F	T series network bi-spectrum AI thermal camera bullet camera, Thermal sensor: 13.5mm fixed focal, VGA (640x480 - can be scaled up to SVGA 1280x960), H.265/H.264: Max. 30fps/25fps (AI 2CH ON - 15fps), MJPEG: Max. 3fps, NETD < 60mK, Pixel Size 12μm, 7 x Color Palettes, Analytics events based on AI engine: Object detection (Person/Vehicle), Bestshot, IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Stopped vehicle, Traffic jam, Vehicle counting, Analytics events: Motion detection, Visible sensor: 10.9~29mm(2.6x) motorized varifocal, 4K (3840x2160), H.265/H.264: Max. 30fps/25fps (AI 2CH ON - 15fps), MJPEG: Max. 1fps, Analytics events based on AI engine Object detection (Person, face, ehicle(car/bus/truck/motorcycle/bicycle), License plate), Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events : Defocus detection, Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), Camera features: 4 x I/O ports, 1 x Metal shielded RJ-45(10/100/1000BASE-T), TPM 2.0 (FIPS 140-2 level 2) HTTPS(SSL) login authentication, 2 x Micro SD slots each max 512GB, PoE+(IEEE802.3at, Class4), 12VDC, IP66/IP67, IK10, NEMA4X, NEMA TS 2(2.2.8, 2.2.9), includes pole/mount bracket, excludes Stainless Steel Straps (SBP-100S)	Info
Camera - Network	TNM-C4940TD	Bi-Spectrum AI Thermal Camera, AI, IR, Thermal 9.1mm / Visible 4.4~9.3mm M-V/F	T series network bi-spectrum AI thermal camera bullet camera, Thermal sensor: 9.1mm fixed focal, VGA (640x480 - can be scaled up to SVGA 1280x960), H.265/H.264: Max. 30fps/25fps (AI 2CH ON - 15fps), MJPEG: Max. 3fps, NETD < 60mK, Pixel Size 12μm, 7 x Color Palettes, Analytics events based on AI engine: Object detection (Person/Vehicle), Bestshot, IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Stopped vehicle, Traffic jam, Vehicle counting, Analytics events: Motion detection, Visible sensor: 4.4~9.3mm(2.2x) motorized varifocal, IR 30m (98.42ft), 4K (3840x2160), H.265/H.264: Max. 30fps/25fps (AI 2CH ON - 15fps), MJPEG: Max. 1fps, Analytics events based on AI engine Object detection (Person, face, ehicle(car/bus/truck/motorcycle/bicycle), License plate), Virtual line (Crossing/Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Analytics events : Defocus detection, Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), Camera features: 4 x I/O ports, 1 x Metal shielded RJ-45(10/100/1000BASE-T), TPM 2.0 (FIPS 140-2 level 2) HTTPS(SSL) login authentication, 2 x Micro SD slots each max 512GB, PoE+(IEEE802.3at, Class4), 12VDC, IP66/IP67, IK10, NEMA4X, NEMA TS 2(2.2.8, 2.2.9), includes pole/mount bracket, excludes Stainless Steel Straps (SBP-100S)	Info
Camera - Network	TNM-C4942TDR	Bi-spectrum AI Radiometric Camera VGA thermal / 4K visible	T series network Bi-spectrum AI Radiometric Camera, Thermal: 640 x 480 (uncooled) @ 8fps, <60mK (NETD), built-in 9.1mm fixed lens (H-FoV: 50°), Visible: 4K, built-in 4.4~9.3mm motorized varifocal lens (H-FoV: 112.1"~47.5"), Max. 3840 x 2160 resolution @ 30fps, Triple codec H.265/H.264/MJPEG with Wisestream II and WiseStream III (based on AI engine) support, WDR 120dB, IR viewable length 30m (98ft), AI object detection (thermal): Person/Vehicle, AI object detection (visible): Person/Face/Vehicle (car, bus, truck, motorcycle, bicycle)/License Plate, Analytics events based on AI engine: Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Additional analytics events (thermal): Motion detection, Additional analytics events (visible): Motion detection, Defocus detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), Alarm events: Image upload (e-mail/TP), Notification (e-mail), Recording (edge/NAS), Alarm output, Handover (PTZ preset, HTTP/HTTPS/TCP message), Audio clip playback, MQTT (publication), Radiometrics: whole FoV area or up to 10 user programmable quadrangle ROIs, temperature detection range from -20oC to 130oC (-4oF to 266oF), FIPS 140-2, 2x micro SD card slots supporting up to 512GB each, IP66/IP67, IK10, NEMA4X, NEMA TS 2(2.2.8, 2.2.9), PoE+/12VDC	Info

Camera - Network	TNM-C4940TDR	Bi-spectrum AI Radiometric Camera VGA thermal / 4K visible	T series network Bi-spectrum AI Radiometric Camera, Thermal: 640 x 480 (uncooled) @ 30fps, <60mK (NETD), built-in 9.1mm fixed lens (HfOV: 50°), Visible: 4K, built-in 4.4–9.3mm motorized varifocal lens (HfOV: 112.1°~47.5°), Max. 3840 x 2160 resolution @ 30fps, Triple codec H.265/H.264/MJPEG with Wisestream II and WiseStream III (based on AI engine) support, WDR 120dB, IR viewable length 30m (98ft), AI object detection (thermal): Person/Vehicle, AI object detection (visible): Person/Face/Vehicle (car,bus,truck, motorcycle, bicycle)/License Plate, Analytics events based on AI engine: Virtual line (Crossing/ Direction), Virtual area (Loitering/Intrusion/Enter/Exit), Additional analytics events (thermal): Motion detection, Additional analytics events (visible): Motion detection, Defocus detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), Alarm events: Image upload (e-mail/FTP), Notification (e-mail), Recording (edge/NAS), Alarm output, Handover (PTZ preset, HTTP/HTTPS/TCP message), Audio clip playback, MQTT (publication), Radiometrics: whole FoV area or up to 10 user programmable quadrangle ROIs, temperature detection range from -20oC to 130oC (-4oF to 266oF), FIPS 140-2, 2x micro SD card slots, supporting up to 512GB each, IP66/IP67, IK10, NEMA4X, NEMA TS 2(2.8, 2.2.9), PoE+/12VDC This product is subject to the Thermal agreement.	Info
Camera - Network	TNM-C3622TDR	Bi-spectrum AI Radiometric Camera QVGA thermal / 2MP visible	T series network Bi-spectrum AI Radiometric Camera, Thermal: 320 x 240 (uncooled) @ 8fps, <50mK (NETD), built-in 4.7mm fixed lens (HfOV: 50°), Visible: 2MP, built-in 4mm fixed (HfOV: 87.6°), Max. 1920 x 1080 resolution @ 30fps, Triple codec H.265/H.264/MJPEG with Wisestream II support, extremeWDR 150dB, AI object detection (visible only) Person/Face, Analytics events: Directional detection, Motion detection, Enter/Exit, Tampering, Virtual line, Audio detection, Alarm events: Image upload (e-mail/FTP), Notification (e-mail), Recording (edge/NAS), Alarm output, Handover (PTZ preset, HTTP/HTTPS/TCP message), Audio clip playback, MQTT (publication), Radiometrics: whole FoV area or up to 10 user programmable quadrangle ROIs, temperature detection range from -20oC to 130oC (-4oF to 266oF), FIPS 140-2, 1 x micro SD card slot supporting up to 256GB, PoE+/12VDC. Compatible with sold separately accessories mounts for wall SBP-142WMW and ceiling SBP-142CMW	Info
Camera - Network	TNM-C3620TDR	Bi-spectrum AI Radiometric Camera QVGA thermal / 2MP visible	T series network Bi-spectrum AI Radiometric Camera, Thermal: 320 x 240 (uncooled) @ 30fps, <50mK (NETD), built-in 4.7mm fixed lens (HfOV: 50°), Visible: 2MP, built-in 4mm fixed (HfOV: 87.6°), Max. 1920 x 1080 resolution @ 30fps, Triple codec H.265/H.264/MJPEG with Wisestream II support, extremeWDR 150dB, AI object detection (visible only) Person/Face, Analytics events: Directional detection, Motion detection, Enter/Exit, Tampering, Virtual line, Audio detection, Alarm events: Image upload (e-mail/FTP), Notification (e-mail), Recording (edge/NAS), Alarm output, Handover (PTZ preset, HTTP/HTTPS/TCP message), Audio clip playback, MQTT (publication), Radiometrics: whole FoV area or up to 6 user programmable quadrangle ROIs, temperature detection range from -20oC to 130oC (-4oF to 266oF), FIPS 140-2, 1 x micro SD card slot supporting up to 256GB, PoE+/12VDC This product is subject to the Thermal agreement. Compatible with sold separately accessories mounts for wall SBP-142WMW and ceiling SBP-142CMW	Info
Camera - Network	TNO-4050T	VGA Thermal	T series network outdoor thermal bullet camera, VGA @30fps, 35mm fixed lens (17.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Hallway View, Motion detection, Tampering detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	TNO-4040T	VGA Thermal	T series network outdoor thermal bullet camera, VGA @30fps, 19mm fixed lens (32°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Hallway View, Motion detection, Tampering detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	TNO-4030T	VGA Thermal	T series network outdoor thermal bullet camera, VGA @30fps, 13mm fixed lens (48.6°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Hallway View, Motion detection, Tampering detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	TNO-3010T	QVGA Thermal	T series network outdoor thermal bullet camera, QVGA @30fps, 2.7mm fixed lens (92°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Shock detection, Temperature detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	TNO-3020T	QVGA Thermal	T series network outdoor thermal bullet camera, QVGA @30fps, 4.7mm fixed lens (50°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Shock detection, Temperature detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	TNO-3030T	QVGA Thermal	T series network outdoor thermal bullet camera, QVGA @30fps, 13.7mm fixed lens (16°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Shock detection, Temperature detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	TNO-3040T	QVGA Thermal	T series network outdoor thermal bullet camera, QVGA @30fps, 19mm fixed lens (11.5°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Shock detection, Temperature detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	TNO-3050T	QVGA Thermal	T series network outdoor thermal bullet camera, QVGA @30fps, 35mm fixed lens (6.3°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Shock detection, Temperature detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	TNO-L3030T	QVGA Thermal	T series network outdoor thermal bullet camera, QVGA @8fps, 13.7mm fixed lens (16°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Advanced Video Analytics and Sound Classification, Hallway View, Motion detection, Shock detection, Temperature detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	TNO-L4030T	VGA Thermal	T series network outdoor thermal bullet camera, VGA @8fps, 13mm fixed lens (48.6°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Hallway View, Motion detection, Tampering detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	TNO-4040TR	VGA Thermal Radiometric	T series network outdoor thermal radiometric bullet camera, VGA @30fps, 19mm fixed lens (32°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Hallway View, Motion detection, Tampering detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Radiometry, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	TNO-4030TR	VGA Thermal Radiometric	T series network outdoor thermal radiometric bullet camera, VGA @30fps, 13mm fixed lens (48.6°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Hallway View, Motion detection, Tampering detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Radiometry, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	TNU-4051T	VGA Thermal Positioning	T series network outdoor thermal positioning camera, VGA @30fps, 35mm fixed lens (17.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Tampering, Loitering, Directional detection, Audio detection, Sound classification, Shock detection, Temperature change detection, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, 24VAC	Info
Camera - Network	TNU-4041T	VGA Thermal Positioning	T series network outdoor thermal positioning camera, VGA @30fps, 19mm fixed lens (32°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Tampering, Loitering, Directional detection, Audio detection, Sound classification, Shock detection, Temperature change detection, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, 24VAC	Info
Camera - Network	TNO-4041TR	VGA Thermal Radiometric	T series network outdoor thermal radiometric bullet camera, VGA @30fps, 19mm fixed lens (32°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Hallway View, Motion detection, Tampering detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Radiometry, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE/12VDC/24VAC, PT type	Info
Camera - Network	TNO-4051T	VGA Thermal	T series network outdoor thermal bullet camera, VGA @30fps, 35mm fixed lens (17.2°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Hallway View, Motion detection, Tampering detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE/12VDC/24VAC, PT type	Info
Camera - Network	TNO-4041T	VGA Thermal	T series network outdoor thermal bullet camera, VGA @30fps, 19mm fixed lens (32°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Hallway View, Motion detection, Tampering detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE/12VDC/24VAC, PT type	Info
Camera - Network	TNO-L4030TR	VGA Thermal	T series network outdoor thermal radiometric bullet camera, VGA @8fps, 13mm fixed lens (48.6°), triple codec H.265/H.264/MJPEG with WiseStream II, Multiple streaming, Hallway View, Motion detection, Tampering detection, Handover, 7 colour palettes, Digital Image Stabilization with built-in Gyro Sensor, Radiometry, Bi-directional audio and microSD/SDHC/SDXC slot, IP66, IK10, Nema 4X, PoE/12VDC/24VAC	Info
Camera - Network	TNO-L4040TR	VGA Thermal	T series network outdoor vandal Radiometric bullet camera (uncooled), 640x480 @ 8.3fps, 19mm fixed focal lens (32°), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 6 user programmable temperature detection areas, temperature detection range is from (-4°F ~ 266°F), open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color.	Info

Camera - Network	TNO-L4040T	VGA Thermal	T series network outdoor vandal thermal bullet camera (uncooled), 640x480 @ 8.3fps, 19mm fixed focal lens (32"), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color.	Info
Camera - Network	TNO-L4050T	VGA Thermal	T series network outdoor vandal thermal bullet camera (uncooled), 640x480 @ 8.3fps, 35mm fixed focal lens (17.2"), triple codec H.265/H.264/MJPEG with Wisestream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color.	Info
NVRs				
Recording - Network	XRN-426S-1T	4CH AI NVR	4 channel PoE solid state fanless NVR with 1TB SSD built in	Info
Recording - Network	XRN-6420DB4	64CH NVR with 12th gen. Intel® Processor	X series 8K NVR (Intel based), 64Ch, 16 SATA HDD bays (up to 10TB per HDD), H265/H264/MJPEG, SUNAPI, ONVIF, ARB (Automatic Recovery Backup) & Failover (N+1), Up To 520 Mbps Recording / Up To 200 Mbps Playback, Dual Stream Recording, iSCSI, WiseStream Support, HDMI(x2) Dual Display, Alarm I/O, 2-way Audio, Maximum Camera Resolution of 32MP Recording/Display, Fisheye Dewarping (Local/CMS), AI Search (Wisenet AI Cameras Only), P2P QR Code, Support for RAID 5/6 (NOTE: RAID Cannot Be Configured With This HDD Configuration), HDD Hot Swap is available in RAID Mode. No HDD included	Info
Recording - Network	XRN-6420B4	64CH NVR with 12th gen. Intel® Processor	X series 8K NVR (Intel based), 64Ch, 16 SATA HDD bays (up to 10TB per HDD), H265/H264/MJPEG, SUNAPI, ONVIF, ARB (Automatic Recovery Backup) & Failover (N+1), Up To 520 Mbps Recording / Up To 200 Mbps Playback, Dual Stream Recording, iSCSI, WiseStream Support, HDMI(x2) Dual Display, Alarm I/O, 2-way Audio, Maximum Camera Resolution of 32MP Recording/Display, Fisheye Dewarping (Local/CMS), AI Search (Wisenet AI Cameras Only), P2P QR Code, Support for RAID 5/6 (NOTE: RAID Cannot Be Configured With This HDD Configuration), HDD Hot Swap is available in RAID Mode. No HDD included	Info
Recording - Network	XRN-6410B2	64CH 32MP 400Mbps 8 Bay NVR	X series 64CH 32MP NVR, triple codec H.265/H.264/MJPEG compression, 400Mbps network camera recording / 32Mbps playback throughput, ARB (Automatic Recovery Backup) & Failover (N+1), up to 8 SATA HDD (80TB max), iSCSI storage, HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), AI search support when working with Wisenet AI camera. No HDD included	Info
Recording - Network	XRN-3210B4	32CH 32MP 400Mbps 16 Bay NVR w/ RAID5/6	X series 32CH 32MP NVR, triple codec H.265/H.264/MJPEG compression, 400Mbps network camera recording / 64Mbps playback throughput, ARB (Automatic Recovery Backup) & Failover (N+1), up to 16 SATA HDD (160TB max), iSCSI storage, RAID-5/6 support, HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), AI search support when working with Wisenet AI camera. No HDD included	Info
Recording - Network	XRN-3210B2	32CH 32MP 400Mbps 8 Bay NVR	3X series 2CH 32MP NVR, triple codec H.265/H.264/MJPEG compression, 400Mbps network camera recording / 32Mbps playback throughput, ARB (Automatic Recovery Backup) & Failover (N+1), up to 8 SATA HDD (80TB max), iSCSI storage, HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), AI search support when working with Wisenet AI camera. No HDD included	Info
Recording - Network	XRN-3220B4	32CH NVR with 12th gen. Intel® Processor	X series 8K NVR (Intel based), 32Ch, 16 SATA HDD bays (up to 10TB per HDD), H.265/H.264/MJPEG, SUNAPI, ONVIF, ARB (Automatic Recovery Backup) & Failover (N+1), Up To 520 Mbps Recording / Up To 200 Mbps Playback, Dual Stream Recording, iSCSI, WiseStream Support, HDMI(x2) Dual Display, Alarm I/O, 2-Way Audio, Maximum Camera Resolution of 32MP Recording/Display, Fisheye Dewarping (Local/CMS), AI Search (Wisenet AI Cameras Only), P2P QR Code, Support for RAID 5/6 (NOTE: RAID Cannot Be Configured With This HDD Configuration), HDD Hot Swap is available in RAID Mode. No HDD included	Info
Recording - Network	PRN-3205B4	32CH 32MP 400Mbps 16 Bay AI NVR	P series 32CH 32MP NVR, triple codec H.265/H.264/MJPEG compression, 400Mbps network camera recording / 32Mbps playback throughput, ARB (Automatic Recovery Backup) & Failover (N+1), up to 16 SATA HDD (160TB max), HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), AI search. No HDD included	Info
Recording - Network	XRN-1620B2	16CH 32MP 140Mbps 8 Bay NVR	X series 16CH 32MP NVR, triple codec H.265/H.264/MJPEG compression, 140Mbps network camera recording / 32Mbps playback throughput, ARB (Automatic Recovery Backup) & Failover (N+1), up to 8 SATA HDD (80TB max), HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), AI search support when working with Wisenet AI camera. No HDD included	Info
Recording - Network	XRN-1620B2-4TB-S	16CH 32MP 140Mbps 8 Bay NVR - 4TB HDD	X series 16CH 32MP NVR, triple codec H.265/H.264/MJPEG compression, 140Mbps network camera recording / 32Mbps playback throughput, ARB (Automatic Recovery Backup) & Failover (N+1), up to 8 SATA HDD (80TB max), HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), AI search support when working with Wisenet AI camera, 4TB Seagate SkyHawk HDD included (ST4000VX016)	Info
Recording - Network	XRN-1620B2-6TB-S	16CH 32MP 140Mbps 8 Bay NVR - 6TB HDD	X series 16CH 32MP NVR, triple codec H.265/H.264/MJPEG compression, 140Mbps network camera recording / 32Mbps playback throughput, ARB (Automatic Recovery Backup) & Failover (N+1), up to 8 SATA HDD (80TB max), HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), AI search support when working with Wisenet AI camera, 6TB Seagate SkyHawk HDD included (ST6000VX009)	Info
Recording - Network	XRN-1620B2-8TB-S	16CH 32MP 140Mbps 8 Bay NVR - 8TB HDD	X series 16CH 32MP NVR, triple codec H.265/H.264/MJPEG compression, 140Mbps network camera recording / 32Mbps playback throughput, ARB (Automatic Recovery Backup) & Failover (N+1), up to 8 SATA HDD (80TB max), HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), AI search support when working with Wisenet AI camera, 8TB Seagate SkyHawk HDD included (ST8000VX010)	Info
Recording - Network	XRN-1620SB1	16CH 32MP 140Mbps 4 Bay PoE NVR	X series 16CH 32MP NVR, triple codec H.265/H.264/MJPEG compression, 140Mbps network camera recording / 32Mbps playback throughput, Plug & play by 16 PoE Ports, ARB (Automatic Recovery Backup) & Failover (N+1), up to 4 SATA HDD (24TB max), HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), AI search support when working with Wisenet AI camera. No HDD included	Info
Recording - Network	XRN-1620SB1-4TB-S	16CH 32MP 140Mbps 4 Bay PoE NVR - 4TB HDD	X series 16CH 32MP NVR, triple codec H.265/H.264/MJPEG compression, 140Mbps network camera recording / 32Mbps playback throughput, Plug & play by 16 PoE Ports, ARB (Automatic Recovery Backup) & Failover (N+1), up to 4 SATA HDD (24TB max), HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), AI search support when working with Wisenet AI camera, 4TB Seagate SkyHawk HDD included (ST4000VX016)	Info
Recording - Network	XRN-1620SB1-6TB-S	16CH 32MP 140Mbps 4 Bay PoE NVR - 6TB HDD	X series 16CH 32MP NVR, triple codec H.265/H.264/MJPEG compression, 140Mbps network camera recording / 32Mbps playback throughput, Plug & play by 16 PoE Ports, ARB (Automatic Recovery Backup) & Failover (N+1), up to 4 SATA HDD (24TB max), HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), AI search support when working with Wisenet AI camera, 6TB Seagate SkyHawk HDD included (ST6000VX009)	Info
Recording - Network	XRN-3220B2	32CH 8K	8K NVR (Intel based), 32Ch, No HDD, 8 SATA HDD bays (up to 10TB per HDD), H.265/H.264/MJPEG, Up To 520 Mbps Recording, HDMI(x2) Dual Display, Alarm I/O, 2-Way Audio	Info
Recording - Network	XRN-3220RB2	32CH 8K	8K NVR (Intel based), 32Ch, No HDD, 8 SATA HDD bays (up to 10TB per HDD), H.265/H.264/MJPEG, Up To 520 Mbps Recording, HDMI(x2) Dual Display, Alarm I/O, 2-Way Audio, Support for RAID 5/6 (NOTE: Requires a minimum number of HDDs per RAID type)	Info
Recording - Network	XRN-6420B2	64CH 8K	8K NVR (Intel based), 64Ch, No HDD, 8 SATA HDD bays (up to 10TB per HDD), H.265/H.264/MJPEG, Up To 520 Mbps Recording, HDMI(x2) Dual Display, Alarm I/O, 2-Way Audio	Info
Recording - Network	XRN-6420RB2	64CH 8K	8K NVR (Intel based), 64Ch, No HDD, 8 SATA HDD bays (up to 10TB per HDD), H.265/H.264/MJPEG, Up To 520 Mbps Recording, HDMI(x2) Dual Display, Alarm I/O, 2-Way Audio Support for RAID 5/6 (NOTE: Requires a minimum number of HDDs per RAID type)	Info
Recording - Network	XRN-820S	8CH 32MP 100Mbps 2 Bay PoE NVR	X series 8CH 32MP NVR, triple codec H.265/H.264/MJPEG compression, 100Mbps network camera recording / 32Mbps playback throughput, Plug & play by 8 PoE Ports, ARB (Automatic Recovery Backup) & Failover (N+1), up to 2 SATA HDD (12TB max), HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), AI search support when working with Wisenet AI camera. No HDD included	Info
Recording - Network	XRN-820S-4TB-S	8CH 32MP 100Mbps 2 Bay PoE NVR - 4TB HDD	X series 8CH 32MP NVR, triple codec H.265/H.264/MJPEG compression, 100Mbps network camera recording / 32Mbps playback throughput, Plug & play by 8 PoE Ports, ARB (Automatic Recovery Backup) & Failover (N+1), up to 2 SATA HDD (12TB max), HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), AI search support when working with Wisenet AI camera, 4TB Seagate SkyHawk HDD included (ST4000VX016)	Info
Recording - Network	XRN-820S-6TB-S	8CH 32MP 100Mbps 2 Bay PoE NVR - 6TB HDD	X series 8CH 32MP NVR, triple codec H.265/H.264/MJPEG compression, 100Mbps network camera recording / 32Mbps playback throughput, Plug & play by 8 PoE Ports, ARB (Automatic Recovery Backup) & Failover (N+1), up to 2 SATA HDD (12TB max), HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), AI search support when working with Wisenet AI camera, 6TB Seagate SkyHawk HDD included (ST6000VX009)	Info
Recording - Network	XRN-815S	8CH 12MP 100Mbps 2 Bay PoE NVR	X series 8CH 12MP NVR, Triple codec H.265/H.264/MJPEG compression, AI Search: Object Attribute (When integrated with Wisenet AI Camera), 100Mbps network camera recording, Plug & play by 8 PoE(LAN, 10/100), 1PoE(WAN, 1Gbps), ARB (Automatic Recovery Backup) & Failover (N+1), up to 2 SATA HDD (20TB max), HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), No HDD included	Info
Recording - Network	XRN-815S-4TB-S	8CH 12MP 100Mbps 2 Bay PoE NVR - 4TB HDD	X series 8CH 12MP NVR, Triple codec H.265/H.264/MJPEG compression, AI Search: Object Attribute (When integrated with Wisenet AI Camera), 100Mbps network camera recording, Plug & play by 8 PoE(LAN, 10/100), 1PoE(WAN, 1Gbps), ARB (Automatic Recovery Backup) & Failover (N+1), up to 2 SATA HDD (20TB max), HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), 4TB Seagate SkyHawk HDD included (ST4000VX016)	Info

Recording - Network	XRN-815S-8TB-S	8CH 12MP 100Mbps 2 Bay PoE NVR - 8TB HDD	X series 8CH 12MP NVR, Triple codec H.265/H.264/MJPEG compression, AI Search: Object Attribute (When integrated with Wisenet AI Camera), 100Mbps network camera recording, Plug & play by 8 PoE(LAN, 10/100), 1PoE(WAN, 1Gbps), ARB (Automatic Recovery Backup) & Fallover (N+1), up to 2 SATA HDD (20TB max), HDMI local dual monitor, SUNAPI, ONVIF, Easy configuration (P2P), 2 x 4TB Seagate SkyHawk HDD included (ST4000VX016)	Info
Recording - Network	XRN-420S	4CH PoE+ NVR	X series 4CH 4K NVR, 4CH @8MP each, triple codec H.265/H.264/MJPEG with WiseStream technology, AI search features: 50Mbps network camera recording, Plug & play by 4 PoE/PoE+ Ports, ARB (Automatic Recovery Backup), 1 fixed internal SATA HDD (6TB max), HDMI, VGA local monitor, SUNAPI, ONVIF, No HDD included	Info
Recording - Network	QRN-430S	4CH PoE NVR	Q series 4CH 8MP NVR, Triple codec H.265/H.264/MJPEG with WiseStream technology, Dual track recording, 40Mbps network camera recording, Plug & play by 4 PoE ports, ARB (Automatic Recovery Backup), 1 fixed internal SATA HDD (6TB max), HDMI local monitor, SUNAPI, ONVIF, P2P service (QR code connect) supported, No HDD included	Info
Recording - Network	QRN-430S-4TB-S	4CH PoE NVR - 4TB HDD	Q series 4CH 8MP NVR, Triple codec H.265/H.264/MJPEG with WiseStream technology, Dual track recording, 40Mbps network camera recording, Plug & play by 4 PoE ports, ARB (Automatic Recovery Backup), 1 fixed internal SATA HDD (6TB max), HDMI local monitor, SUNAPI, ONVIF, P2P service (QR code connect) supported, 4TB Seagate SkyHawk HDD included (ST4000VX016)	Info
Recording - Network	QRN-830S	8CH PoE NVR	Q series 8CH 8MP NVR, 8CH @8MP each, triple codec H.265/H.264/MJPEG with WiseStream technology, Dual track recording, 80Mbps network camera recording, Plug & play by 8 PoE ports, ARB (Automatic Recovery Backup), 1 fixed internal SATA HDD (6TB max), HDMI local monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), No HDD included	Info
Recording - Network	QRN-830S-4TB-S	8CH PoE NVR - 4TB HDD	Q series 8CH 8MP NVR, 8CH @8MP each, triple codec H.265/H.264/MJPEG with WiseStream technology, Dual track recording, 80Mbps network camera recording, Plug & play by 8 PoE ports, ARB (Automatic Recovery Backup), 1 fixed internal SATA HDD (6TB max), HDMI local monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), 4TB Seagate SkyHawk HDD included (ST4000VX016)	Info
Recording - Network	QRN-1630S	16CH 2 Bay PoE NVR	Q series 16CH 8MP NVR, Triple codec H.265/H.264/MJPEG with WiseStream technology, Dual track recording, 128Mbps network camera recording, Plug & play by 16 PoE(LAN, 10/100), 1PoE(WAN, 1Gbps), ARB (Automatic Recovery Backup), 2 fixed internal SATA HDD (20TB max), HDMI local monitor, SUNAPI, ONVIF, P2P service (QR code connect) supported, No HDD included	Info
Recording - Network	QRN-1630S-4TB-S	16CH 2 Bay PoE NVR - 4TB HDD	Q series 16CH 8MP NVR, Triple codec H.265/H.264/MJPEG with WiseStream technology, Dual track recording, 128Mbps network camera recording, Plug & play by 16 PoE(LAN, 10/100), 1PoE(WAN, 1Gbps), ARB (Automatic Recovery Backup), 2 fixed internal SATA HDD (20TB max), HDMI local monitor, SUNAPI, ONVIF, P2P service (QR code connect) supported, 4TB Seagate SkyHawk HDD included (ST4000VX016)	Info
Recording - Network	ARN-410S	4CH PoE NVR	A Series 4CH PoE NVR, Embedded Linux, H.265, H.264, MJPEG codec, Plug & play by 4 PoE (LAN, 10/100), 1 RJ-45(WAN, 10/100), 40Mbps Recording Throughput, Supported HDD (Maximum 1 x 6TB), HDMI local monitor, ARB supported, P2P service support. No HDD included	Info
Recording - Network	ARN-810S	8CH PoE NVR	A Series 8CH PoE NVR, Embedded Linux, H.265, H.264, MJPEG codec, Plug & play by 8 PoE (LAN, 10/100), 1 RJ-45(WAN, 10/100), 60Mbps Recording Throughput, Supported HDD (Maximum 1 x 6TB), HDMI local monitor, ARB supported, P2P service support. No HDD included	Info
Recording - Network	ARN-1610S	16CH PoE NVR	A Series 16CH PoE NVR, Embedded Linux, H.265, H.264, MJPEG codec, Plug & play by 16 PoE (LAN, 10/100), 1 RJ-45(WAN, 1Gbps), 1 RJ-45(WAN, 10/100), 80Mbps Recording Throughput, Supported HDD (Maximum 2 x 6TB), HDMI / VGA local monitor, ARB supported 80Mbps network camera recording, P2P service support. No HDD included	Info
Encoders and Decoders				
Encoder - Network	SPE-420	4CH Video Encoder	4CH Network Video Encoder, H.265/H.264/MJPEG, 12fps@5MP, 15fps@4MP, 30fps@2MP or lower, Dual Streaming, AHD/CVI/TVI/CVBS(Pelco-C) compatible, RS-485 Interface (SAMSUNG-T, PELCO-P/D), ONVIF protocol support, HDMI output, Alarm I/O 4/2, Bi-directional Audio, PoE/12VDC	Info
Encoder - Network	SPE-1630	16CH Video Encoder	16CH Network Video Encoder, Max resolution 5MP, Max frame-rate 12fps@5MP, 15fps@4MP, 30fps@1080p, H.265/H.264/MJPEG codec support, Multiple streaming (up to 3 profiles per channel), CVBS(Pelco-C)/AHD/TVI/CVI, 1 RJ-45 10/100/1000 Base-T, Alarm 16 Input/ 4 Output, Alarm Triggers - Motion Detection, Alarm Input, Video Loss, Tampering, Network disconnect, File Upload Via FTP/E-mail, Audio 4 Line Input / 1 Line Output, 1 HDMI OUT (16 multi image, 1920x1080), 4 privacy zones, ONVIF profile S, SUNAPI (HTTP API)	Info
Decoder - Network	SPD-152	64CH Video Decoder	64CH Network Video Decoder, up to 64 cameras, Dual HDMI display port(HDMI1 UHD, HDMI#2 FHD), Max. 8M resolution, 8M@60fps, 2M@360fps, triple codec H.265/H.264/MJPEG, ONVIF, SUNAPI, RTSP, Various installation: Monitor-Back and Pole mount, PoE/12VDC	Info
IP Audio Systems				
Speaker	SPA-C100B	IP Ceiling Speaker	IP Ceiling Speaker, Built-in 10W Class D amplifier, PoE & PoE+, 1GBytes internal Memory, 99dB max Sound Pressure, 120Hz ~ 20kHz Frequency range, 90dB Sensitivity, IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP protocol Support, TTS (English, German, French, Spanish, Audio Monitoring (Speaker, connection test), Multi-source Dynamic PA control (Up to 48 ch., 256 Zone, 255 Groups) Black	Info
Speaker	SPA-C100W	IP Ceiling Speaker	IP Ceiling Speaker, Built-in 10W Class D amplifier, PoE & PoE+, 1GBytes internal Memory, 99dB max Sound Pressure, 120Hz ~ 20kHz Frequency range, 90dB Sensitivity, IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP protocol Support, TTS (English, German, French, Spanish, Audio Monitoring (Speaker, connection test), Multi-source Dynamic PA control (Up to 48 ch., 256 Zone, 255 Groups) White	Info
Speaker	SPA-P100B	IP Pendant Speaker	IP Pendant Speaker, Built-in 10W Class D amplifier, PoE & PoE+, 1GBytes internal Memory, 99dB max Sound Pressure, 130Hz ~ 20kHz Frequency range, 91dB Sensitivity, IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP protocol Support, TTS (English, German, French, Spanish, Audio Monitoring (Speaker, connection test), Multi-source Dynamic PA control (Up to 48 ch., 256 Zone, 255 Groups), White	Info
Speaker	SPA-P100W	IP Pendant Speaker	IP Pendant Speaker, Built-in 10W Class D amplifier, PoE & PoE+, 1GBytes internal Memory, 99dB max Sound Pressure, 130Hz ~ 20kHz Frequency range, 91dB Sensitivity, IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP protocol Support, TTS (English, German, French, Spanish, Audio Monitoring (Speaker, connection test), Multi-source Dynamic PA control (Up to 48 ch., 256 Zone, 255 Groups), Black	Info
Speaker	SPA-W100B	IP Wall Speaker	IP Wall Speaker, Built-in 10W Class D amplifier, PoE & PoE+, 1GBytes internal Memory, 99dB max Sound Pressure, 120Hz ~ 20kHz Frequency range, 90dB Sensitivity, IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP protocol Support, TTS (English, German, French, Spanish, Audio Monitoring (Speaker, connection test), Multi-source Dynamic PA control (Up to 48 ch., 256 Zone, 255 Groups), IP54, Black	Info
Speaker	SPA-W100W	IP Wall Speaker	IP Wall Speaker, Built-in 10W Class D amplifier, PoE & PoE+, 1GBytes internal Memory, 99dB max Sound Pressure, 120Hz ~ 20kHz Frequency range, 90dB Sensitivity, IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP protocol Support, TTS (English, German, French, Spanish, Audio Monitoring (Speaker, connection test), Multi-source Dynamic PA control (Up to 48 ch., 256 Zone, 255 Groups), IP54, White	Info
Speaker	SPA-H100B	IP Horn Speaker	IP Horn Speaker, Built-in 10W Class D amplifier, PoE & PoE+, 1GBytes internal Memory, 99dB max Sound Pressure, 650Hz ~ 5.3kHz Frequency range, 111dB Sensitivity, IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP protocol Support, TTS (English, German, French, Spanish, Audio Monitoring (Speaker, connection test), Multi-source Dynamic PA control (Up to 48 ch., 256 Zone, 255 Groups), IP66, Black	Info
Speaker	SPA-H100W	IP Horn Speaker	IP Horn Speaker, Built-in 10W Class D amplifier, PoE & PoE+, 1GBytes internal Memory, 99dB max Sound Pressure, 650Hz ~ 5.3kHz Frequency range, 111dB Sensitivity, IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP protocol Support, TTS (English, German, French, Spanish, Audio Monitoring (Speaker, connection test), Multi-source Dynamic PA control (Up to 48 ch., 256 Zone, 255 Groups), IP66, White	Info
Audio Module	SPA-D1000	IP Audio Module	IP Audio Module, +6dBV ±3dB Output level, 20Hz ~ 20kHz Frequency Response, Built-in 10W Class D amplifier, PoE & PoE+, 1GBytes internal Memory, IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP protocol Support, TTS (English, German, French, Spanish, Audio Monitoring (Speaker, connection test), Multi-source Dynamic PA control (Up to 48 ch., 256 Zone, 255 Groups)	Info
Microphone	SPA-M1000	IP Microphone	IP Microphone, +10dBV ±3dB Output level, 100Hz ~ 18kHz Frequency Response, PoE	Info
Microphone	SPA-M2000	IP Microphone	IP Microphone, +10dBV ±3dB Output level, 100Hz ~ 18kHz Frequency Response, PoE, SIP Protocol	Info
Audio Bridge	SPA-B1000	IP Audio Bridge	Analogue to IP Audio Bridge, POE 15w/24 VDC	Info
Audio Server	SPA-S1000	IP Audio Server	IP Audio Server, 10/100 Base-T Ethernet, PoE, IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP protocols support, Multi source Dynamic PA control (Up to 48 ch., 256 Zone, 255 Groups)	Info
Analog HD+ Cameras				

Camera - Analog HD	HCO-7070RA	4MP Analog HD+ Bullet	HD+ series 4MP IR bullet camera, AHD or CVBS formats are available, manual varifocal Lens (3.1X) (3.2-10mm), Day & Night (ICR), 24VAC/12VDC, IR distance 30m, IP66/IK10	Info
Camera - Analog HD	HCO-7010RA	4MP Analog HD+ Bullet	HD+ series 4MP IR bullet camera, AHD or CVBS formats are available, 2.8 mm fixed lens, Day & Night (ICR), 12VDC, IR distance 20m, IP66/IK10	Info
Camera - Analog HD	HCO-7020RA	4MP Analog HD+ Bullet	HD+ series 4MP IR bullet camera, AHD or CVBS formats are available, 4.0 mm fixed lens, Day & Night (ICR), 12VDC, IR distance 25m, IP66/IK10	Info
Camera - Analog HD	HCO-7030RA	4MP Analog HD+ Bullet	HD+ series 4MP IR bullet camera, AHD or CVBS formats are available, 6.0 mm fixed lens, Day & Night (ICR), 12VDC, IR distance 30m, IP66/IK10	Info
Camera - Analog HD	HCV-7070RA	4MP Analog HD+ Outdoor Dome	HD+ series 4MP IR outdoor dome camera, AHD or CVBS formats are available, manual varifocal Lens (3.1X) (3.2-10mm), Day & Night (ICR), 24VAC/12VDC, IR distance 30m, IP66/IK10	Info
Camera - Analog HD	HCV-7010RA	4MP Analog HD+ Outdoor Dome	HD+ series 4MP IR outdoor dome camera, AHD or CVBS formats are available, 2.8 mm fixed lens, Day & Night (ICR), 12VDC, IR distance 20m, IP66/IK10	Info
Camera - Analog HD	HCV-7020RA	4MP Analog HD+ Outdoor Dome	HD+ series 4MP IR outdoor dome camera, AHD or CVBS formats are available, 4.0 mm fixed lens, Day & Night (ICR), 12VDC, IR distance 25m, IP66/IK10	Info
Camera - Analog HD	HCV-7030RA	4MP Analog HD+ Outdoor Dome	HD+ series 4MP IR outdoor dome camera, AHD or CVBS formats are available, 6.0 mm fixed lens, Day & Night (ICR), 12VDC, IR distance 30m, IP66/IK10	Info
Camera - Analog HD	HCD-7070RA	4MP Analog HD+ Indoor Dome	HD+ series 4MP IR indoor dome camera, AHD or CVBS formats are available, manual varifocal Lens (3.1X) (3.2-10mm), Day & Night (ICR), 24VAC/12VDC, IR distance 20m	Info
Camera - Analog HD	HCD-7010RA	4MP Analog HD+ Indoor Dome	HD+ series 4MP IR indoor dome camera, AHD or CVBS formats are available, 2.8 mm fixed lens, Day & Night (ICR), 12VDC, IR distance 20m	Info
Camera - Analog HD	HCD-7020RA	4MP Analog HD+ Indoor Dome	HD+ series 4MP IR indoor dome camera, AHD or CVBS formats are available, 4.0 mm fixed lens, Day & Night (ICR), 12VDC, IR distance 25m	Info
Camera - Analog HD	HCD-7030RA	4MP Analog HD+ Indoor Dome	HD+ series 4MP IR indoor dome camera, AHD or CVBS formats are available, 6.0 mm fixed lens, Day & Night (ICR), 12VDC, IR distance 30m	Info
Camera - Analog HD	HCB-7000A	4MP Analog HD+ Box	HD+ series analogue box camera, 4MP, AHD, Manual focus, AHD/CVBS/RS-485, BLC/HLC/DWDR, True Day & Night (ICR), Motion detection, Transmission distance upto 500m, 24VAC/12VDC ※ The lens is not included	Info
Camera - Analog HD	HCB-7000PHA	4MP Analog HD+ Box	HD+ series analogue box camera, 4MP, AHD, Manual focus, AHD/CVBS/RS-485, BLC/HLC/DWDR, True Day & Night (ICR), Motion detection, Transmission distance upto 500m, 230VAC ※ The lens is not included	Info
Camera - Analog HD	HCO-6080R	2MP Analog HD+ IR Bullet	HD+ series 2MP, Full HD(1080p) 30fps IR outdoor bullet camera, AHD/TVI/CVI/CVBS, motorized varifocal lens (3.1X) (3.2-10mm), 120 dB true WDR, Day & Night (ICR), 24VAC/12VDC, IR distance 30m, IP66/IK10	Info
Camera - Analog HD	HCO-6080	2MP Analog HD+ Bullet	HD+ series 2MP, Full HD(1080p) 30fps outdoor bullet camera, AHD/TVI/CVI/CVBS, motorized varifocal lens (3.1X) (3.2-10mm), 120 dB true WDR, Day & Night (ICR), 24VAC/12VDC, IP66/IK10	Info
Camera - Analog HD	HCO-6070R	2MP Analog HD+ IR Bullet	HD+ series 2MP, Full HD(1080p) 30fps IR outdoor bullet camera, AHD/TVI/CVI/CVBS, manual varifocal Lens (3.1X) (3.2-10mm), 120 dB true WDR, Day & Night (ICR), 24VAC/12VDC, IR distance 30m, IP66/IK10	Info
Camera - Analog HD	HCO-6020R	2MP Analog HD+ IR Bullet	HD+ series 2MP, Full HD(1080p) 30fps IR outdoor bullet camera, AHD/TVI/CVI/CVBS, Fixed Lens (4mm), 120 dB true WDR, Day & Night (ICR), 12VDC, IR distance 30m, IP66/IK10	Info
Camera - Analog HD	HCV-6080R	2MP Analog HD+ IR Outdoor Dome	HD+ series 2MP, Full HD(1080p) 30fps IR outdoor dome camera, AHD/TVI/CVI/CVBS, motorized varifocal lens (3.1X) (3.2-10mm), 120 dB true WDR, Day & Night (ICR), 24VAC/12VDC, IR distance 30m, IP66/IK10	Info
Camera - Analog HD	HCV-6080	2MP Analog HD+ Outdoor Dome	HD+ series 2MP, Full HD(1080p) 30fps outdoor dome camera, AHD/TVI/CVI/CVBS, motorized varifocal lens (3.1X) (3.2-10mm), 120 dB true WDR, Day & Night (ICR), 24VAC/12VDC, IP66/IK10	Info
Camera - Analog HD	HCV-6070R	2MP Analog HD+ IR Outdoor Dome	HD+ series 2MP, Full HD(1080p) 30fps IR outdoor dome camera, AHD/TVI/CVI/CVBS, manual varifocal Lens (3.1X) (3.2-10mm), 120 dB true WDR, Day & Night (ICR), 24VAC/12VDC, IR distance 30m, IP66/IK10	Info
Camera - Analog HD	HCD-6080R	2MP Analog HD+ IR Indoor Dome	HD+ series 2MP, Full HD(1080p) 30fps IR indoor dome camera, AHD/TVI/CVI/CVBS, motorized varifocal lens (3.1X) (3.2-10mm), 120 dB true WDR, Day & Night (ICR), 24VAC/12VDC, IR distance 20m	Info
Camera - Analog HD	HCD-6070R	2MP Analog HD+ IR Indoor Dome	HD+ series 2MP, Full HD(1080p) 30fps IR indoor dome camera, AHD/TVI/CVI/CVBS, manual varifocal Lens (3.1X) (3.2-10mm), 120 dB true WDR, Day & Night (ICR), 24VAC/12VDC, IR distance 20m	Info
Camera - Analog HD	HCD-6010	2MP Analog HD+ Indoor Dome	HD+ series 2MP, Full HD(1080p) 30fps IR indoor dome camera, AHD/TVI/CVI/CVBS, 2.8 mm fixed lens, 120 dB true WDR, Day & Night (ICR), 12VDC	Info
Camera - Analog HD	HCD-6020R	2MP Analog HD+ IR Indoor Dome	HD+ series 2MP, Full HD(1080p) 30fps IR indoor dome camera, AHD/TVI/CVI/CVBS, 4.0 mm fixed lens, 120 dB true WDR, Day & Night (ICR), 12VDC, IR distance 20m	Info
Camera - Analog HD	HCB-6001	2MP Analog HD+ Box	HD+ series analogue box camera, 2MP, Full HD(1080p) resolution, Simple focus, AHD/CVBS/RS-485, 120 dB WDR, True Day & Night (ICR), Motion detection, Transmission distance up to 500m, 24VAC/12VDC ※ The lens is not included	Info
Camera - Analog HD	HCB-6000	2MP Analog HD+ Box	HD+ series analogue box camera, 2MP, Full HD(1080p) resolution, Manual focus, AHD/CVBS/CCP/TCP/RS-485, 120 dB WDR, True Day & Night (ICR), Motion detection, Transmission distance up to 500m, 24VAC/12VDC ※ The lens is not included	Info
Camera - Analog HD	HCB-6000PH	2MP Analog HD+ Box	HD+ series analogue box camera, 2MP, Full HD(1080p) resolution, Manual focus, AHD/CVBS/CCP/TCP/RS-485, 120 dB WDR, True Day & Night (ICR), Motion detection, Transmission distance up to 500m, 220VAC ※ The lens is not included	Info
Camera - Analog HD	HCP-6320A	AHD PTZ	HD+ series 2MP, Full HD(1080p) 30fps PTZ camera, Optical zoom lens 32X (4.44~142.6mm), true WDR 120dB, RS485/Up coax (ACP protocol only) PTZ control, Day & Night (ICR), 24VAC	Info
Camera - Analog HD	HCP-6320HA	AHD Outdoor PTZ	HD+ series 2MP, Full HD(1080p) 30fps PTZ camera, Optical zoom lens 32X (4.44~142.6mm), RS485/Up coax (ACP protocol only) PTZ control, true WDR 120dB, Day & Night (ICR), 24VAC, IP66 IK10	Info
DVRs				
Recording - Analog	HRX-835A	8CH Pentabrid (AHD, HDTV, HDCVI, CVBS, IP) Recorder	5-in-1 8CH+2CH (up to 10CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 5MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 50Mbps recording / max. 32Mbps playback throughput, up to 4 internal SATA HDD (24TB max), 8CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), No HDD included	Info
Recording - Analog	HRX-835A-4TB-S	8CH Pentabrid (AHD, HDTV, HDCVI, CVBS, IP) Recorder - 4TB HDD	5-in-1 8CH+2CH (up to 10CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 5MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 50Mbps recording / max. 32Mbps playback throughput, up to 4 internal SATA HDD (24TB max), 8CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), 4TB Seagate SkyHawk HDD included (ST4000VX016)	Info

Recording - Analog	HRX-835A-6TB-S	8CH Pentabrid (AHD, HDTVI, HDCVI, CVBS, IP) Recorder - 6TB HDD	5-in-1 8CH+2CH (up to 10CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 5MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 50Mbps recording / max. 32Mbps playback throughput, up to 4 internal SATA HDD (24TB max), 8CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), 6TB Seagate SkyHawk HDD included (ST6000VX009)	Info
Recording - Analog	HRX-1635	16CH Pentabrid (AHD, HDTVI, HDCVI, CVBS, IP) Recorder	5-in-1 16CH (up to 18CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 8MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 128Mbps recording / max. 32Mbps playback throughput, up to 8 internal SATA HDD, (48TB max), 16CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), No HDD included	Info
Recording - Analog	HRX-1635-3TB-S	16CH Pentabrid (AHD, HDTVI, HDCVI, CVBS, IP) Recorder - 3TB HDD	5-in-1 16CH (up to 18CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 8MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 128Mbps recording / max. 32Mbps playback throughput, up to 2 internal SATA HDD, (12TB max), 16CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), 3TB Seagate SkyHawk HDD included (ST3000VX015)	Info
Recording - Analog	HRX-1635-4TB-S	16CH Pentabrid (AHD, HDTVI, HDCVI, CVBS, IP) Recorder - 4TB HDD	5-in-1 16CH (up to 18CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 8MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 128Mbps recording / max. 32Mbps playback throughput, up to 8 internal SATA HDD, (48TB max), 16CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), 4TB Seagate SkyHawk HDD included (ST4000VX016)	Info
Recording - Analog	HRX-1634	16CH Pentabrid (AHD, HDTVI, HDCVI, CVBS, IP) Recorder	5-in-1 16CH (up to 18CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 8MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 128Mbps recording / max. 32Mbps playback throughput, up to 2 internal SATA HDD, (12TB max), 16CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), No HDD included	Info
Recording - Analog	HRX-1634-3TB-S	16CH Pentabrid (AHD, HDTVI, HDCVI, CVBS, IP) Recorder - 3TB HDD	5-in-1 16CH (up to 18CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 8MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 30Mbps recording / max. 32Mbps playback throughput, up to 2 internal SATA HDD, (12TB max), 16CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), 3TB Seagate SkyHawk HDD included (ST3000VX015)	Info
Recording - Analog	HRX-1634-4TB-S	16CH Pentabrid (AHD, HDTVI, HDCVI, CVBS, IP) Recorder - 4TB HDD	5-in-1 16CH (up to 18CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 8MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 128Mbps recording / max. 32Mbps playback throughput, up to 2 internal SATA HDD, (12TB max), 16CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), 4TB Seagate SkyHawk HDD included (ST4000VX016)	Info
Recording - Analog	HRX-435	4CH Pentabrid (AHD, HDTVI, HDCVI, CVBS, IP) Recorder	5-in-1 4CH+2CH (up to 6CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 5MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 30Mbps recording / max. 32Mbps playback throughput, up to 2 internal SATA HDD (12TB max), 4CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), No HDD included	Info
Recording - Analog	HRX-435-4TB-S	4CH Pentabrid (AHD, HDTVI, HDCVI, CVBS, IP) Recorder - 4TB HDD	5-in-1 4CH+2CH (up to 6CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 5MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 30Mbps recording / max. 32Mbps playback throughput, up to 2 internal SATA HDD (12TB max), 4CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), 4TB Seagate SkyHawk HDD included (ST4000VX016)	Info
Recording - Analog	HRX-435-6TB-S	4CH Pentabrid (AHD, HDTVI, HDCVI, CVBS, IP) Recorder - 6TB HDD	5-in-1 4CH+2CH (up to 6CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 5MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 30Mbps recording / max. 32Mbps playback throughput, up to 2 internal SATA HDD (12TB max), 4CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), 6TB Seagate SkyHawk HDD included (ST6000VX009)	Info
Recording - Analog	HRX-435-12TB-S	4CH Pentabrid (AHD, HDTVI, HDCVI, CVBS, IP) Recorder - 2x 6TB HDD	5-in-1 4CH+2CH (up to 6CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 5MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 30Mbps recording / max. 32Mbps playback throughput, up to 2 internal SATA HDD (12TB max), 4CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), 2x 6TB Seagate SkyHawk HDD included (ST6000VX009)	Info
Recording - Analog	HRX-434	4CH Pentabrid (AHD, HDTVI, HDCVI, CVBS, IP) Recorder	5-in-1 4CH+2CH (up to 6CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 5MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 30Mbps recording / max. 32Mbps playback throughput, 1 internal SATA HDD (6TB max), 1CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), No HDD included	Info
Recording - Analog	HRX-434-4TB-S	4CH Pentabrid (AHD, HDTVI, HDCVI, CVBS, IP) Recorder - 4TB HDD	5-in-1 4CH+2CH (up to 6CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 5MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 30Mbps recording / max. 32Mbps playback throughput, 1 internal SATA HDD (6TB max), 1CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), 4TB Seagate SkyHawk HDD included (ST4000VX016)	Info
Recording - Analog	HRX-434-6TB-S	4CH Pentabrid (AHD, HDTVI, HDCVI, CVBS, IP) Recorder - 6TB HDD	5-in-1 4CH+2CH (up to 6CH NW) Embedded DVR, Analog HD (max. 8MP), TVI (max. 8MP), CVI (max. 5MP), CVBS, IP (max. 8MP), triple codec H.265/H.264/MJPEG, max. 30Mbps recording / max. 32Mbps playback throughput, 1 internal SATA HDD (6TB max), 1CH Audio input/ 1CH Audio output, Coaxial Cable (Pelco-C), HDMI/VGA local dual monitor, SUNAPI, ONVIF, Easy configuration (Setup Wizard, P2P), Smartphone support (iOS & Android), 6TB Seagate SkyHawk HDD included (ST6000VX009)	Info
Lens modules for Multi-Sensor and Box Cameras				
Lens	SLA-T4680	4.6mm Lens/imager straight body for XNB-6001 (8.0m cable)	1/2.8" 2MP CMOS with a 4.6mm fixed lens module for XNB-6001, FoV: H: 73°, V: 39°, 0.06Lux, WDR (120dB), Electrical Day&Night	Info
Lens	SLA-T4680V	4.6mm Lens/imager right angle body for XNB-6001 (8.0m cable)	1/2.8" 2MP CMOS with a 4.6mm fixed lens module for XNB-6001, FoV: H: 73°, V: 39°, 0.06Lux, WDR (120dB), Electrical Day&Night	Info
Lens	SLA-T2480	2.4mm Lens/imager straight body for XNB-6001 (8.0m cable)	1/2.8" 2MP CMOS with a 2.4mm fixed lens module for XNB-6001, FoV: H: 138°, V: 73°, 0.45Lux, WDR (120dB), Electrical Day&Night	Info
Lens	SLA-T2480V	2.4mm Lens/imager right angle body for XNB-6001 (8.0m cable)	1/2.8" 2MP CMOS with a 2.4mm fixed lens module for XNB-6001, FoV: H: 138°, V: 73°, 0.45Lux, WDR (120dB), Electrical Day&Night	Info
Lens	SLA-T1080F	1.6mm Lens/imager straight body for XNB-6001 (8.0m cable)	1/2.8" 2MP CMOS with a 1.6mm fixed lens module for XNB-6001, FoV: H: 187°, V: 113.9°, 0.03Lux, WDR (120dB), Electrical Day&Night	Info
Lens	SLA-T4680A	4.6mm Lens/imager straight body for PNM-9000QB (8.0m cable)	1/2.8" 2MP CMOS with a 4.6mm fixed lens module for PNM-9000QB, XNB-6002, FoV: H: 73°, V: 39°, 0.06Lux, WDR (120dB), Electrical Day&Night	Info
Lens	SLA-T4680VA	4.6mm Lens/imager right angle body for PNM-9000QB (8.0m cable)	1/2.8" 2MP CMOS with a 4.6mm fixed lens module for PNM-9000QB, XNB-6002, FoV: H: 73°, V: 39°, 0.06Lux, WDR (120dB), Electrical Day&Night	Info
Lens	SLA-T2480A	2.4mm Lens/imager straight body for PNM-9000QB (8.0m cable)	1/2.8" 2MP CMOS with a 2.4mm fixed lens module for PNM-9000QB, XNB-6002, FoV: H: 138°, V: 73°, 0.45Lux, WDR (120dB), Electrical Day&Night	Info
Lens	SLA-T2480VA	2.4mm Lens/imager right angle body for PNM-9000QB (8.0m cable)	1/2.8" 2MP CMOS with a 2.4mm fixed lens module for PNM-9000QB, XNB-6002, FoV: H: 138°, V: 73°, 0.45Lux, WDR (120dB), Electrical Day&Night	Info
Lens	SLA-T1080FA	1.6mm Lens/imager straight body for PNM-9000QB (8.0m cable)	1/2.8" 2MP CMOS with a 1.6mm fixed lens module for PNM-9000QB, XNB-6002, FoV: H: 187°, V: 113.9°, 0.03Lux, WDR (120dB), Electrical Day&Night	Info
Lens	SLA-T4680D	Door Jamb Lens (black)	2MP Door Jamb Pinhole lens module with a 4.6mm fixed lens, compatible with XNB-6001 (not included), FoV: H: 73°, V: 39°, 0.06Lux, WDR (120dB), Electrical Day&Night, black colour	Info

Lens	SLA-T4680DS	Door Jamb Lens (silver)	2MP Door Jamb Pinhole lens module with a 4.6mm fixed lens, compatible with XNB-6001 (not included), FoV: H: 73°, V: 39°, 0.06Lux, WDR (120dB), Electrical Day&Night, silver colour	Info
Lens	SLA-T4680DW	Door Jamb Lens (white) Special order ONLY	2MP Door Jamb Pinhole lens module with a 4.6mm fixed lens, compatible with XNB-6001 (not included), FoV: H: 73°, V: 39°, 0.06Lux, WDR (120dB), Electrical Day&Night, white colour	Info
Lens	SLA-T2480WA	2MP Lens Module	1/2.8" 2MP CMOS with a 2.4mm fixed lens module, FoV: H: 138°, V: 73°, Color: 0.045Lux@F2.0, 1/30sec, 30IRE) BW: 0.045Lux@F2.0, 1/30sec, 30IRE) with PNM-9000QB, XNB-6002, Product Dimensions / Weight: ø24x49.8mm(ø0.94x1.96"), 101g(0.22lb), IP66, NEMA 4X, compatible with PNM-9000QB, XNB-6002	Info
Lens	SLA-T2480WDA	2MP Waterproof Dome Lens Module	1/2.8" 2MP CMOS with a 2.4mm fixed lens module, FoV: H: 138°, V: 73°, Color: 0.045Lux@F2.0, 1/30sec, 30IRE) BW: 0.045Lux@F2.0, 1/30sec, 30IRE) with PNM-9000QB, XNB-6002, Product Dimensions / Weight: ø110.0x77.0mm(ø3.54x3.03"), 450g(0.99lb), EN IEC 63000, IEC 60529 IP66, IEC 62262 IK10, NEMA 250 type 4X, compatible with PNM-9000QB, XNB-6002	Info
Lens	SLA-T4680DA	Door Jamb Lens (black)	2MP Door Jamb Pinhole lens module with a 4.6mm fixed lens, compatible with XNB-6002 (not included), FoV: H: 73°, V: 39°, 0.06Lux, WDR (120dB), Electrical Day&Night, Black colour, compatible with PNM-9000QB, XNB-6002, XNB-6001	Info
Lens	SLA-T4680DSA	Door Jamb Lens (silver)	2MP Door Jamb Pinhole lens module with a 4.6mm fixed lens, compatible with XNB-6002 (not included), FoV: H: 73°, V: 39°, 0.06Lux, WDR (120dB), Electrical Day&Night, Silver colour, compatible with PNM-9000QB, XNB-6002, XNB-6001	Info
Lens	SLA-5M3700Q	PNM-9002VQ Lens module	1/1.8" 5MP CMOS with a 3.7mm fixed lens module for PNM-9000VQ, FoV: H: 97.5°, V: 71.9°, 0.16Lux@F1.6 (Color, B/W), WDR (120dB), Electrical Day&Night, compatible with PNM-9002VQ	Info
Lens	SLA-2M2400Q	PNM-9002VQ Lens module	1/2.8" 2MP CMOS with a 2.4mm fixed lens module for PNM-9000VQ, FoV: H: 135.4°, V: 71.2°, 0.055Lux@F2.0 (Color, B/W), WDR (150dB), Electrical Day&Night, compatible with PNM-9002VQ	Info
Lens	SLA-2M3600Q	PNM-9002VQ Lens module	1/2.8" 2MP CMOS with a 3.6mm fixed lens module for PNM-9000VQ, FoV: H: 94.8°, V: 49.3°, 0.055Lux@F2.0 (Color, B/W), WDR (150dB), Electrical Day&Night, compatible with PNM-9002VQ	Info
Lens	SLA-2M6000Q	PNM-9002VQ Lens module	1/2.8" 2MP CMOS with a 6.0mm fixed lens module for PNM-9000VQ, FoV: H: 50.4°, V: 28.8°, 0.055Lux@F2.0 (Color, B/W), WDR (150dB), Electrical Day&Night, compatible with PNM-9002VQ	Info
Lens	SLA-5M3700P	PNM-9322VQP Lens module	1/1.8" 5MP CMOS with a 3.7mm fixed lens module for PNM-9320VQP, FoV: H: 97.5°, V: 71.9°, 0.16Lux@F1.6 (Color, B/W), WDR (120dB), Electrical Day&Night, compatible with PNM-9320VQP	Info
Lens	SLA-5M4600P	PNM-9322VQP Lens module	1/1.8" 5MP CMOS with a 4.6mm fixed lens module for PNM-9320VQP, FoV: H: 77.9°, V: 57.9°, 0.16Lux@F1.6 (Color, B/W), WDR (120dB), Electrical Day&Night, compatible with PNM-9320VQP	Info
Lens	SLA-5M7000P	PNM-9322VQP Lens module	1/1.8" 5MP CMOS with a 7.0mm fixed lens module for PNM-9320VQP, FoV: H: 50.7°, V: 37.8°, 0.16Lux@F1.6 (Color, B/W), WDR (120dB), Electrical Day&Night, compatible with PNM-9320VQP	Info
Lens	SLA-2M2400P	PNM-9322VQP Lens module	1/2.8" 2MP CMOS with a 2.4mm fixed lens module for PNM-9320VQP, FoV: H: 135.4°, V: 71.2°, 0.055Lux@F2.0 (Color, B/W), WDR (150dB), Electrical Day&Night, compatible with PNM-9320VQP	Info
Lens	SLA-2M3600P	PNM-9322VQP Lens module	1/2.8" 2MP CMOS with a 3.6mm fixed lens module for PNM-9320VQP, FoV: H: 94.8°, V: 49.3°, 0.055Lux@F2.0 (Color, B/W), WDR (150dB), Electrical Day&Night, compatible with PNM-9320VQP	Info
Lens	SLA-2M6000P	PNM-9322VQP Lens module	1/2.8" 2MP CMOS with a 6.0mm fixed lens module for PNM-9320VQP, FoV: H: 50.4°, V: 28.8°, 0.055Lux@F2.0 (Color, B/W), WDR (150dB), Electrical Day&Night, compatible with PNM-9320VQP	Info
Lens	SLA-2M1200P	PNM-9322VQP Lens module	1/2.8" 2MP CMOS with a 12.0mm fixed pinhole lens for PNM-9320VQP, FoV: H: 26.3°, V: 14.9°, 0.055Lux@F2.0 (Color, B/W), WDR (150dB), Electrical Day&Night, compatible with PNM-9320VQP	Info
Lens	SLA-M8550D	Lens, 1/2.8" 8.5-50mm V/F DC Iris CS-Mount	Lens, 1/2.8", Max. resolution 3MP, varifocal (8.5-50.0mm), Auto DC Iris, CS-Mount	Info
Lens	SLA-M2890DN	Megapixel DC-iris Lens	Lens, 1/2.8", Max. resolution 3MP, varifocal (2.8-9.0mm), Auto DC Iris, CS-Mount	Info
Lens	SLA-M2890PN	Megapixel P-iris Lens	Lens, 1/2.8", Max. resolution 3MP, varifocal (2.8-9.0mm), Auto P Iris, CS-Mount	Info

Accessories

Accessory	SPI-50	IR Illuminators for the TNU-6320 (discontinued) and TNU-6321	IR emitter up to 200m (656 feet), 25° IR angle, 850nm wave length, 24VAC, IP67, -40°C ~ +60°C (-40°F ~ 140°F). Compatible with the TNU-6320 (discontinued) and TNU-6321 * 2 IR Illuminator body and mounting bracket included	Info
Accessory	SPM-4210	I/O box	Network I/O Box for PTZ plus, 4-configurable I/O ports, Audio I/O, PoE. Compatible with XNP-9300RW/9250R/9250 XNP-8300RW/8250R/8250, XNP-6400RW/6400R/6400	Info
Accessory	SPO-6011	PoE injector - 60W	60W HPoE Injector, Fully compliant with IEEE802.3at/at/bt, PoE++, Built-in SFP slot, Compatible with XNP-9250R / XNP-8250R / XNP-6400R / TNB-9000	Info
Accessory	SPO-8315	PoE injector - 83W	83W HPoE Injector, Fully compliant with IEEE802.3at/at/bt, PoE++, Built-in SFP slot, Compatible with XNP-9300RW / XNP-8300RW / XNP-6400RW, PNM-9085RQZ / PNM-9085RQZ1 / PNM-9084RQZ / PNM-9084RQZ1 / PNM-9322VQP	Info
Accessory	SHP-1563FPW	In-ceiling Mount	Plenum rated PTZ-Plus flush mount, white color. Compatible with XNP-9250/9250R/8250/8250R/6400/6400R, QNP-6320R/6250R, XNP-C6403/C8253/C9253, XNP-C6403R/C8253R/C9253R	Info
Accessory	SHP-1563FW	Flush mount	PTZ-Plus flush mount, white color. Compatible with XNP-9250/9250R/8250/8250R/6400/6400R, QNP-6320R/6250R, XNP-C6403/C8253/C9253, XNP-C6403R/C8253R/C9253R	Info
Accessory	SHP-1520FW	Flush mount	Plastic In-ceiling Flush Mount PTZ cameras. Compatible with XNP-6320/XNP-6321/QNP-6230, White	Info

Accessory	SHP-1680F	Flush mount	Polycarbonate In-ceiling Flush Mount for PTZ and Dome cameras. Compatible with XNP-6120H, XNV-6120/6120R/6085, XND-6085/6085V, Ivory	Info
Accessory	SHP-1680FPW	Plenum flush mount	White color PTZ flush mount. Compatible with HCP-6320/6320A, QNP-6230/6250/6320, XNP-6320/6321/6120H	Info
Accessory	SHP-1680FW	Flush mount	Polycarbonate In-ceiling Flush Mount PTZ and Dome cameras. Compatible with XNP-6120H, XNV-6120/6120R/6085, XND-6085/6085V, White	Info
Accessory	SHP-1730FPW	Flush mount	Plenum rated In-ceiling mount compatible with: XNP-C7310R & C9310R	Info
Accessory	SHD-1128FPW	Flush mount	Polycarbonate In-ceiling Flush Mount for Dome cameras. Compatible with QND-8021/8011/6021/6011 XND-8040R/8030R/8020R/6020R/6010, White, RAL9003	Info
Accessory	SHD-1198FW	Flush mount	Polycarbonate In-ceiling Flush Mount for Dome cameras. Compatible with QND-6070R/6082R/7080R/8080R, HCD-6070R/6080R/7070R/7080R, White	Info
Accessory	SHD-1200FW	Flush mount	Lite In-ceiling mount compatible with QNV-C8013R/8023R	Info
Accessory	SHD-1200FPW	In-ceiling housing	Aluminum in-ceiling housing, compatible with QNV-C8011R/C9011R, QNV-C8012	Info
Accessory	SHD-1201FPW	In-ceiling housing	Plenum In-ceiling mount compatible with QNV-C8013R/C8023R	Info
Accessory	SHD-1350P	In-Ceiling Housing	In-ceiling Retrofit Spacer, Compatible with SHD-3000F4 (In-ceiling Mount) / XND-6083RV, PND-A6081RV	Info
Accessory	SHD-1350FPW	In-Ceiling Housing	Aluminum In-Ceiling Housing, RAL9003, Compatible with XND-6083RV/8083RV/8093RV/9083RV XND-8093RV/9083RV	Info
Accessory	SHD-1370FPW	In-ceiling Housing	Aluminum In-Ceiling Housing, RAL9003, Compatible with PNV-A6081R/A9081R, XNV-8082R/9082R, XNV-6083R/8083R/8093R/9083R, XNV-6123R, XNV-6083Z/8083Z, XNV-6083RZ/8083RZ/9083RZ	Info
Accessory	SHD-1400FPW	In-ceiling Mount	In-ceiling mount plenum for QNV-C8083R/C9083R	Info
Accessory	SHD-1400FW	In-ceiling Mount	In-ceiling mount for QNV-C8083R/C9083R	Info
Accessory	SHD-1408FW	Flush mount	Polycarbonate In-ceiling Flush Mount for Dome cameras. Compatible with PND-9080R, XND-6080/6080R/6080RV/6080V/8080R/8080RV/L6080R/L6080RV/L6080V, HCV-6070R/6080/6080R/7070R/7080R, QNV-6082R1, White	Info
Accessory	SHD-1408FPW	In-ceiling Housing	Polycarbonate In-ceiling Flush Mount for Dome cameras. White, Compatible with HCD-6080R/7070RA, QND-6082R/8080R, XNV-6010/6020R/8020R/8030R/8040R, HCV-7010RA/7020RA/7030RA/6080R/6070R, LNV-6012R/6022R/6032R/6072R, QNV-6012R/6022R/6032R/6082R/8010R/8020R/8030R/8080R, XND-6080V/6080RV/8080RV, XND-L6080V/6080RV, XNP-6040H	Info
Accessory	SHD-1101FW	Flush mount	Lite In-ceiling mount compatible with QND-C8013R/C8023R	Info
Accessory	SHD-1100FPW	Plenum flush mount	Plenum In-ceiling mount compatible with QND-C8013R/C8023R	Info
Accessory	SHD-1000F1	In-ceiling Mount	Lite typed In-ceiling Mount compatible with QNF-9010/8010	Info
Accessory	SHD-1600FPW	Flush mount	Polycarbonate In-ceiling Flush Mount for Dome cameras. Compatible with PNV-9080R XNF-9010RV/8010R/8010RV XND-6085/6085V XNV-6085/6120/6120R/8080R/6080R/6080 XNV-L6080R/L6080, White, RAL9003	Info
Accessory	SHD-1600FW	In-ceiling Mount	In-ceiling mount compatible with XND-C6083RV, XND-C7083RV, XND-C8083RV, XND-C9083RV	Info
Accessory	SHD-2000FPW	In-ceiling Mount	Plenum rated In-ceiling mount compatible with: PNM-C16013RVQ	Info
Accessory	SHD-2500FPW	In-ceiling Mount	In-ceiling Mount for PNM-C32083RVQ and PNM-C16083RVQ	Info
Accessory	SHD-2510FPW	Flush mount	Aluminum In-ceiling Flush Mount for Multisensor cameras. Compatible with PNM-9084QZ1/ PNM-8082VT, White	Info
Accessory	SHD-3000F1	Flush mount	Polycarbonate In-ceiling Flush Mount for Dome cameras. Compatible with PNV-9080R, XNV-6080/6080R/L6080/L6080R/8080R, SCD-6081R, SCV-6081R, SND-7084R/7084/6084R/6084/6083/5084R/5084/5083, SNV-7084R/7084/6084R/6084/5084, Ivory	Info

Accessory	SHD-3000F3	Flush mount	Polycarbonate In-ceiling Flush Mount for Outdoor dome cameras. Compatible with QNV-7080R/6070R, HCV-7070R/7080R/6070R/6080R/6080, SNV-L6083R/L5083R, SCV-5082/5083/5083R/5085, Ivory	Info
Accessory	SHD-3000F4	Flush mount	Polycarbonate In-ceiling Flush Mount for Indoor Dome cameras. Compatible with PND-9080R, XND-6080/6080R/6080RV/6080V/L6080R/L6080RV/L6080V/8080R/8080RV, Ivory	Info
Accessory	SHD-3000F5	In-ceiling Mount	Polycarbonate In-ceiling Flush Mount, Aluminum, UL2820 Plenum rated, White, Compatible with Compatible with the PNM-9000VQ & PNM-9002VQ ※ For further compatible models, please visit our website or use Toolbox	Info
Accessory	SHP-3701H	PTZ Outdoor Housing	Outdoor Housing for PTZ cameras, IP66, IK10, Built-in Heater -58°F. Compatible with XNP-6320, QNP-6230, HCP-6320/6320A, SCP-3370/2370/2330/2270/2250/3371/2371/2271, SNP-6200/5200/5300/3371/3302, Ivory	Info
Accessory	SHF-1500F	Flush Mount	Polycarbonate In-ceiling Flush Mount for Fisheye cameras. Compatible with XNF-8010R/RV/RVM, PNF-9010R/RV/RVM, Ivory	Info
Accessory	SBC-140WB	Skin cover in black	Skin cover in black compatible with TNV-C8011RW	Info
Accessory	SBC-170C	Skin cover in silver	Skin cover in silver, polycarbonate material, compatible with TNV-8011C	Info
Accessory	SBC-170CW	Skin cover in white	Skin cover in white, polycarbonate material, compatible with TNV-8011C	Info
Accessory	SBC-170CB	Skin cover in black	Skin cover in black, polycarbonate material, compatible with TNV-8011C	Info
Accessory	SBC-165W	skin cover in white	Skin cover in white for TID-600R Intercom	Info
Accessory	SBS-165B	Back Box	Back Box for TID-600R intercom	Info
Accessory	SBS-165TM	Tilt Mount	Tilt mount in black for TID-600R Intercom	Info
Accessory	SHS-165F	Flush Mount with cover	Flush mount with two covers (dark gray and white) for TID-600R Intercom	Info
Accessory	SBC-160B	Skin Cover	Skin cover for Indoor Vandal Dome cameras. Compatible with XND-8081VZ/8081RV/8081REV/6081VZ/6081V/6081RV/6081REV, PND-A9081RV, Black Pack of 3	Info
Accessory	SBC-160BF	Skin cover in black	Skin cover in Black, polycarbonate material, compatible with XNF-9013RV, XNF-9010RV TBD, XNF-8010RV TBD Pack of 6	Info
Accessory	SBC-180B	Skin Cover	compatible with XNF-9013RV, XNF-9010RV TBD, XNF-8010RV TBD Pack of 3	Info
Accessory	SBC-200B	Skin Cover	Black Skin Cover for PNM-C16013RVQ Pack of 3	Info
Accessory	SBC-XNP-6400	PTZ Skin Cover, Paint Ready	This skin has been developed for XNP version only non RW series, such as XNP-6400, XNP-6400R, XNP-C6403, XNP-C6403R, XNP-8250, XNP-8250R, XNP-C8253, XNP-C8253R, XNP-9250, XNP-9250R, XNP-C9253, XNP-C9253R and QNP-6320R, QNP-6250R. Skin is Paint ready. Manufactured In the UK	
Accessory	SBC-XNV-C9083R	XNV-Skin Cover	This skin has been developed for XNV core version only such as XNV-C9083R (T), Other Version still to be Tested. Skin is Paint ready. Manufactured In the UK	
Accessory	SBL-101C	Remote Head Housing	Polycarbonate Remote Head Camera Ceiling Housing, white, RAL9003. Compatible with SLA-T2480, SLA-T2480A, SLA-T4680, SLA-T4680A	Info
Accessory	SBL-100D	Remote Head Housing	Remote Head Camera Ceiling Mount Housing. Compatible with SLA-T2480, SLA-T2480A, SLA-T4680, SLA-T4680A, White	Info
Accessory	SBP-099HMMW	Hanging Mount	Aluminum Hanging Mount for Fisheye Cameras. Compatible with QND-8021/8011/6021/6011, QNF-8010/9010, White	Info
Accessory	SBP-120HMMW	Hanging Mount	Hanging Mount, White, plastic cap, compatible with QNV-C8011R/C9011R, QNF-8010/9010, QND-6011/6021, QND-8011/8021	Info
Accessory	SBP-122HM	Hanging Mount	Aluminum Hanging Mount for Dome Cameras. Compatible with QND-7080R/6070R, QNV-7010R/7020R/7030R/6010R/6020R/6030R, XNV-8020R/8030R/8040R/6010/6020R, HCV-7010R/7020R/7030R, Ivory	Info
Accessory	SBP-122HMMW	Hanging Mount	Aluminum Hanging mount for Dome cameras. Compatible with QNV-8010R/8020R/8030R/6012R/6022R/6032R, QND-8080R/6082R, LNV-6010R/6020R/6030R, LND-6070R, White, QNV-6012R1/6022R1/6032R1	Info

Accessory	SBP-140HWW	Hanging Mount	Hanging Mount, White, plastic cap, compatible with QNV-C8083R/9083R	Info
Accessory	SBP-125HWW	Hanging Mount	Aluminum Hanging mount for Dome cameras. Compatible with QNE-8011R, QNE-8021R, White	Info
Accessory	SBP-156HWW	Hanging Mount	Aluminum Hanging Mount for Outdoor PTZ cameras. Compatible with XNP-9300RW/9250R/8250/8300RW/8250R/8250/6400RW/6400R/6400, White	Info
Accessory	SBP-156HWWP	Hanging Adaptor	Aluminum Hanging Mount Housing. Us SNI-1MC or SNI-1MC-PS. SNI Bracket not included. This also can be used with the SPO-8315, Compatible with PNM-C3440RQPZ	Info
Accessory	SBP-156HWWR	Hanging Adaptor	Aluminum Hanging Mount Housing. Developed for Fiber Cable Network and Poe Injector. Us SNI-1MC or SNI-1MC-PS. SNI Bracket not included Compatible with XNP-6400/8250/9250,XNP-C6403/C8253/C9253/C7310R/C9310R	Info
Accessory	SBP-160HWW1	Hanging Mount	Core : Aluminum / Cap : Plastic, White, Supported products : XND-C6083RV/7083RV/8083RV, XND-6083RV/8083RV/8093RV/9083RV, PND-A6081RV/9081RV, XNV-C6083R/7083R/8083R/9083R, XNF-9013RV/9010RV, XND-8082RV/9082RV	Info
Accessory	SBP-167HM	Hanging Mount	Aluminum Hanging Mount for Indoor Vandal Dome cameras. Compatible with XND-8081VZ/8081RV/8081REV/6081VZ/6081V/6081RV/6081REV, PND-A9081RV, Ivory	Info
Accessory	SBP-168HM	Hanging Mount	Cap Adapter. Compatible with XNP-6120H, Ivory	Info
Accessory	SBP-180HWW1	Hanging Mount	Core : Aluminum / Cap : Plastic, White, Supported products : XNV-6083R/8083R/8093R/9083R, XNV-6083RZ/8083RZ/9083RZ, XNV-6123R, PNV-A6081R/9081R, XNV-8082R/9082R	Info
Accessory	SBP-187HM	Hanging Mount	Aluminum Hanging Mount for Outdoor Dome cameras. Compatible with XNV-8081Z/8081RE/8081R/6081Z/6081R/6081RE, PNV-A9081RV, Ivory	Info
Accessory	SBP-200HWW	Hanging Mount	Aluminum Hanging Mount, White, compatible with PNM-C16013RVQ	Info
Accessory	SBP-215HWW	Hanging Mount	Hanging mount for PNM-C7083RVD/7082RVD and PNM-C12083RVD/12082RVD	Info
Accessory	SBP-250HWW	Hanging Mount	Hanging Cap for PNM-9084QZ / PNM-9084QZ1 / PNM-C16083RVQ / PNM-C32083RVQ, Mount thread size : PF 1 1/2" Male, Aluminum, White	Info
Accessory	SBP-250WMW	Wall&Pole Mount	Wall Mount White Pack of 5 Compatible with 1. Camera Direct : QNV-C8083R/C9083R, XND-C6083RV/C7083RV/C8083RV/C9083RV, XNV-C6083R/C7083R/C8083R/C9083R, XND-6083RV/8083RV/9083RV, XNV-6083R/8083R/8093R/9083R, PNV-A9081R/A6081R/A6081R-E1T/A6081R-E2T, XNV-6083RZ/8083RZ/9083RZ, etc.	Info
Accessory	SBP-115PFA	Wall&Pole Adaptor	Adapter for mount SBP-250WMW & SBP-400WMW Compatible with SBP-180HWW1/200HWW/215HWW/250HWW/315HWW Pack of 3	Info
Accessory	SBP-115PA	Wall&Pole Mount	PTZ adapter for SBP-250WMW & SBP-400WMW Compatible with XNP-C7310R/C9310R, XNP-C6403/C8253/C9253, XNP-6400/8250/9250 Pack of 3	Info
Accessory	SBP-276HWW	Hanging Mount	Aluminum Hanging Mount for Multi-Directional Cameras. Compatible with PNM-9084QZ1, White	Info
Accessory	SBP-300HM5	Hanging Mount	Aluminum Hanging Mount for Fisheye and Flateye cameras. Compatible with XNF-8010R/8010RV/8010RVM, PNF-9010R/9010RV/9010RVM, QNE-7080RV/6080RV, Ivory	Info
Accessory	SBP-300HM6	Hanging Mount	Aluminum Hanging Mount for Dome and Multi-Directional cameras. Compatible with PNM-7000VD, PNV-9080R, XNV-8080R/6120/6120R/6085/6080/6080R/L6080/L6080R, XND-6085/6085V, Ivory	Info
Accessory	SBP-300HMS6	Hanging Mount	Stainless steel Hanging Mount for Stainless steel Dome cameras. Compatible with XNV-8080RS/6120RS/6080RS	Info
Accessory	SBP-300HM7	Hanging Mount	Stainless steel Hanging Mount for Stainless steel Dome cameras. Compatible with XNV-8080RS/6120RS/6080RS	Info
Accessory	SBP-300HWW7	Hanging Mount	Aluminum Hanging Mount for Dome Cameras. Compatible with XNV-6011, QND-8010R/8020R/8030R/6012R/6022R/6032R, LND-6010R/6020R/6030R, QND-6012R1/6022R1,6033R1, White	Info
Accessory	SBP-300HM8	Hanging Mount	Aluminum Hanging Mount for Indoor Dome cameras. Compatible with PND-9080R, XND-8080RV/8080R/6080/6080R/6080V/6080RV/L6080/L6080V/L6080RV, Ivory	Info
Accessory	SBP-300HWW8	Hanging Mount	Aluminum Hanging Mount for Indoor Dome cameras. Compatible with PND-9080R, XND-8080RV/8080R/6080/6080R/6080V/6080RV/L6080/L6080V/L6080RV, White	Info
Accessory	SBP-301HWW3	Hanging Mount	Aluminum Hanging Mount for Indoor Dome cameras. Replacing SBP-301HM3 and Compatible with QNP-6230, XNP-6320/6321 HCP-6230/6320/6320A, SCP-3371, SNP-6320/6321/6201/5430/5321/L6233/L5233/5300, SNV-7082/7080R/7080/5080R/5080/3120, White	Info

Accessory	SBP-301HWM2	Hanging Mount	Aluminum Hanging mount for Outdoor Dome Cameras. Compatible with QNV-8080R/6082R/6082R1, LNV-6070R, White	Info
Accessory	SBP-301HM5	Hanging Mount	Aluminum Hanging Mount for Dome and PTZ cameras. Compatible with XNP-6040H, QNV-7080R/6070R, HCV-7070R/6070R/6080R/6080, Ivory	Info
Accessory	SBP-315HWM	Hanging Mount	Aluminum Hanging Mount, Supported products: PNM-9084RQZ/9084RQZ1/9085RQZ/9085RQZ1	Info
Accessory	SBP-317HWM	Hanging Mount	Aluminum Hanging Mount for Multi-Directional cameras. Compatible with PNM-9084RQZ1/PNM-9085RQZ1, White	Info
Accessory	SBP-200C	Mounting Hole Cover	Mount Plate Pack of 5 for SBP-250WMW & SBP-400WMW compatible with PNM-C16013RVQ	Info
Accessory	SBP-250C	Mounting Hole Cover	Mount Plate Pack of 5 for SBP-250WMW & SBP-400WMW compatible with PNM-C16083RVQ/C32083RVQ, PNM-8082VT, PNM-9084QZ/QZ1, PNM-9022V, PNM-C9022RV, PNM-9031RV	Info
Accessory	SBP-315C	Mounting Hole Cover	Mount Plate Pack of 5 for SBP-250WMW & SBP-400WMW compatible with PNM-9084RQZ/RQZ1, PNM-9085RQZ/RQZ1	Info
Accessory	SBP-120WM	Wall Mount	Plastic Wall mount for Indoor dome cameras. Compatible with XND-6010/6020R/8020R/8030R/8040R, QND-7080R/7030R/7020R/7010R/6070R/6030R/6020R/6010R, HCD-7020R/7030R/7070R, SND-L6083R/L6014R/L6013R/L6012/L5083R/L5013, SCD-6083R/6023R/6021/5083R/5083/5082/5080, Ivory	Info
Accessory	SBP-120WMW	Wall Mount	Plastic Wall mount for Indoor dome nad Fisheye cameras. Compatible with QNF-8010/9010, QND-8080R/8010R/8011/8020R/8021/8030R/6082R/6011/6012R/6021/6022R/6032R, QND-6012R1/6022R1/6032R1/6082R1White	Info
Accessory	SBP-125WMW1	Wall Mount	Plastic/Aluminium Wall mount (Body- Aluminum, Cover- Polycarbonate), White, Compatible with QNV-C8011R/C8012/C9011R, QND-6011/6021/8011/8021, QND-6012R/22R, QND-6072R/82R, QNE-8011R/21R, LND-6012R/22R/72R, QND-7012R/22R/82R	Info
Accessory	SBP-137WM	Wall Mount	Plastic/Aluminum Wall mount for Outdoor dome cameras. Compatible with XNV-6010/6020R/8020R/8030R/8040R, QNV-6010R/6020R/6030R/6070R/7010R/7020R/7030R/7080R, HCV-6080R/6080/6070R/7010R/7020R/7030R/7070R, SNV-L5083R/L6083R, SCV-5082/5082R/5083/5083R/5085/6023R/6083R, Ivory	Info
Accessory	SBP-137WMW	Wall Mount	Plastic/Aluminum Wall mount for Outdoor dome cameras. Compatible with QNV-6012R/6022R/6032R/6082R/8010R/8020R/8030R/8080R, White	Info
Accessory	SBP-137WM1	Wall Mount	Plastic/Aluminum Wall mount for Outdoor dome cameras. Compatible with XNV-6010/6020R/8020R/8030R/8040R, QNV-6010R/6020R/6030R/6070R/7010R/7020R/7030R/7080R, HCV-6080R/6080/6070R/7010R/7020R/7030R/7070R, SNV-L5083R/L6083R, SCV-5082/5082R/5083/5083R/5085/6023R/6083R, Ivory	Info
Accessory	SBP-137WMW1	Wall Mount	Plastic/Aluminum Wall mount for Outdoor dome cameras. Compatible with QNV-6012R/6022R/6032R/6082R1/8010R/8020R/8030R/8080R, White	Info
Accessory	SBP-156WMW	Wall Mount	Aluminum Wall mount for Outdoor dome cameras, White. Compatible with XNP-9300RW/9250R/9250/8300RW/8250R/8250/6400RW/6400R/6400	Info
Accessory	SBP-187WMW	Wall Mount	Wall & Pole Mount for (TNO-7180RLP) High Speed Global shutter LPR camera (Steel strap sold separately)	Info
Accessory	SBD-110GPA	Installation Kit	Installation kit for TNV-C8014RM & TNV-C8034RM, includes mount plate and M12 to RJ45 adapter	Info
Accessory	SBP-156WA	PTZ Plus Adaptor	PTZ adaptor. Compatible with XNP-6400RW, XNP-8300RW, XNP-9300RW	Info
Accessory	SBP-060S	Steel Strap	Stainless steel mount strap (QTY of 2) for a wall/pole mount: Length: 600mm (23.6"), Width : 12.6mm (0.5")	Info
Accessory	SBP-060BA	Conduit Hole Adaptor	Conduit Hole Adaptor, Aluminum, Dimensions: 54.1x43.5x40mm (2.13x1.72x1.57"), Weight: 27g (0.06lb), Conduit hole: 19.1mm(3/4") (M25), White, compatible with QNV-C8083R/C9083R, XNO-C6083R/C7083R/C8083R/C9083R, PNM-C16013RVQ	Info
Accessory	SBP-150S	Steel Strap	Stainless steel mount strap (QTY of 2) for wall pole mount: Length: 1,500mm (59.1"), Width : 12.6mm (0.5")	Info
Accessory	SBE-100WM	Wall Mount	Wall Mount for Explosion-proof Cameras, compatible with TNO-6322ER, TNU-6322E and TNU-6322ER	Info
Accessory	SBP-300WM	Wall Mount	Gooseneck Wall Mount. Compatible with XNP-6371RH/6370RH/6320H, SHP-3701H, SCP-3430H/2430H/3370TH/3370H/2370TH/2370H/3250H/2250H/3120VH, SNP-5430H/6320H/6320RH/6200H/3302H/6321H/6321H/L6233H/L5233H/L6233RH/3371TH/3371H/3120VH, All Hanging Mounts, Ivory	Info
Accessory	SBP-300WMW	Wall Mount	Gooseneck Wall Mount. Compatible with XNP-6371RH/6370RH/6320H, SHP-3701H, SCP-3430H/2430H/3370TH/3370H/2370TH/2370H/3250H/2250H/3120VH, SNP-5430H/6320H/6320RH/6200H/3302H/6321H/6321H/L6233H/L5233H/L6233RH/3371TH/3371H/3120VH, QNV-6012R1/6022R1/6032R1/6082R1, QND-6012R1/6022R1/6032R1/6082R1, All Hanging Mounts, White	Info
Accessory	SBP-300WMS	Stainless Steel Wall Mount (Gooseneck)	Stainless Steel Gooseneck Wall Mount. Compatible with XNP-6320HS, XNV-6080RS/8080RS/6120RS (need to purchase a separate cap SBP-300HMS6 for the dome cameras)	Info

Accessory	SBP-300WM1	Wall Mount	Wall Mount, Compatible with SCP-3430H/2430H, SCP-3370TH/3370H, SCP-2370TH/2370H, SCP-3250H/2250H, SCP-3120VH, SNP-5430H/6320H/6320RH, SNP-5200H/3302H, SNP-6321H/5321H/SNP-L6233H/L5233H/L6233RHH/SNP-3371TH/3371H,SNP-3120VH, All caps except SBP-329HM, SHP-3701H	Info
Accessory	SBP-300WMW1	Wall Mount	Aluminum Wall Mount compatible with XNV-6081/XNV-8081/XND-6081V /XND-8081V, QNV-6012R1/6022R1/6032R1/6082R1, QND-6012R1/6022R1/6032R1/6082R1 and white hanging caps, White	Info
Accessory	SBP-300WMS1	Stainless Steel Wall Mount	Stainless Steel wall mount for PTZ XNP-6320HS and dome XNV-6080RS, XNV-8080RS, XNV-6120RS (need to purchase a separate cap SBP-300HMS6 for the dome cameras)	Info
Accessory	SBP-390WM2	Wall Mount	Aluminum Wall mount compatible with PNM-7000VD/9000VQ/9020V/9030V/9080VQ/9081VQ/9320VQP, Ivory	Info
Accessory	SBP-400WMW	Outdoor Wall & Pole Mount	Wall & Pole Mount (White) Compatible with SBP-200C, SBP-250C, SBP-315C, SBP-115PFA, SBP-115PA, SPO-8315, SPO-6011	Info
Accessory	SBU-500PM	Pole Mount	Pole Mount compatible with SBU-500WM	Info
Accessory	SBU-500WM	Wall Mount for the TNU-6320 (discontinued) and TNU-6321	Wall mount for the TNU-6320 (discontinued) and TNU-6321, Colour: White, Material: Aluminium	Info
Accessory	SBP-300NB	Installation Box	Installation Back box compatible with SBP-300WM, SBP-300WM1, SBP-300KM, SBP-300PM, IP66, Ivory	Info
Accessory	SBP-300NBW	Installation Box	Installation Back box compatible with SBP-300WMW, SBP-300WMW1, SBP-300KMW, SBP-300PMW, IP66, QNV-6012R1/6022R1/6032R1/6082R1, QND-6012R1/6022R1/6032R1/6082R1White	Info
Accessory	SBP-300B	Mount Base	Wall Mount Base compatible with Mounts SBP-300WM/300WM1, Ivory	Info
Accessory	SBP-300BW1	Wall Mount Bracket	Top Mount Bracket, Aluminum, White, weight 700g(1.54lb), compatible with TNO-7180RLP	Info
Accessory	SBP-156LMW	Parapet Mount	Aluminum Parapet Mount for Outdoor PTZ PLUS cameras. Compatible with XNP-9300RW/9250R/9250/8300RW/8250R/8250/6400RW/6400R/6400, White	Info
Accessory	SBP-156LMW1	Telescopic Parapet Mount	Aluminum Telescopic Parapet Mount, cameras. Dimensions: 835 ~ 1098x1000x95mm (32.9~43.2x39.4x3.8"), Compatible with any 1.5 NOT mounts, White, RAL9003	Info
Accessory	SBP-300LM	Parapet Mount	Parapet Mount Accessory, compatible with all full size outdoor PTZs and all caps, Ivory color	Info
Accessory	SBP-300LMW	Parapet Mount	Aluminum Parapet Mount Accessory, QNV-6012R1/6022R1/6032R1/6082R1, White	Info
Accessory	SBP-300PM1	Pole Mount Adaptor	Pole Mount Adaptor, aluminium, XNV-6120R, Ivory	Info
Accessory	SBP-300PMW2	Pole Mount Adaptor	Pole Mount Bracket, Aluminum, White, compatible with QNV-6012R1/6022R1/6032R1/6082R1,QND-6012R1/6022R1/6032R1/6082R1 and TNO-7180RLP	Info
Accessory	SBB-300PMW1	Pole Mount Adaptor	Pole Mount Adaptor, aluminium, Compatible with SHB-4200H, SHB-4300HP, SHB-4301H2, SBP-300PMW1, White	Info
Accessory	SBP-300PMS	Stainless Steel Pole Mount Adaptor	Stainless Steel Pole mount adaptor, Compatible with SBP-300WMS and SBP-300WMS1	Info
Accessory	SBP-302PM	Pole Mount Base	Pole Mount Adapter compatible with SBO-100B1, PNO-9080R, SNO-8081R, QNO-7080R/6070R, QNO-7010R/7020R/7030R/6010R/6020R/6030R, QNO-6012R1/6022R1/6032R1	Info
Accessory	SBP-303PM	Pole Mount Base	Pole mount adapter accessory for thermal bullet cameras, compatible with TNO-4040T, TNO-4030T, TNO-4050T, TNO-4030TR, TNO-4040TR, TNO-3010T/3020T/3030T	Info
Accessory	SBD-180PMW	Pole Mount	Pole Mount (Core: Aluminum, Cap : Plastic), white, Supported products : PNV-A6081R/A9081R, XNV-8082R/9082R, XNV-6083R/8083R/8093R/9083R,XNV-6123R, XNV-6083Z/8083Z, XNV-6083RZ/8083RZ/9083RZ,PND-A6081RV/A9081RV, XND-8082RV/9082RV, XNF-9010RV/9013RV,XND-6083RV/8083RV/8093RV/9083RV, XNO-6083R/8083R/9083R, XND-C6083RV/C7083RV/C8083RV/C9083RV, XNO-C6083R/C8083R/C9083R, XNV-C6083R/C7083R/C8083R/C9083R	Info
Accessory	SBD-140PMW	Pole Mount	Pole Mount (Core: Aluminum, Cap : Plastic), white, Supported products : QNV-C8083R/C9083R, QNV-C8011R/C8012/C9011R, QND-6012R(1)/22R(1)/72R(1)/82R(1), QND-7012R/22R/82R, QNE-8011R/21R	Info
Accessory	SBD-140KMB	Corner Mount	Corner Mount, SUS304, White, Supported products : QNV-C8011R/C8012/C9011R, QNV-C8083R/C9083R, QND-6011/6021, QND-8011/8021, QNF-8010/9010, QND-6012R(1)/6022R(1)/6072R(1)/6082R(1), QND-7012R/7022R/7082R, QNE-8011R/8021R, LND-6012R/6022R/6072R,ANE-L6012R/L7012R	Info
Accessory	SBD-140PMB	Pole Mount	Pole Mount, SUS304, White, Supported products : QNV-C8011R/C8012/C9011R, QNV-C8083R/C9083R, QND-6011/6021, QND-8011/8021, QNF-8010/9010, QND-6012R(1)/6022R(1)/6072R(1)/6082R(1), QND-7012R/7022R/7082R, QNE-8011R/8021R, LND-6012R/6022R/6072R,ANE-L6012R/L7012R	Info

Accessory	SBD-110GP1	Wall Adaptor	Adaptor plate for Single, Double, 4" Octagon, supported cameras: QNV-C8011R/C8012/C9011R, QND-6011/21, 8011/21, QNF-8010, 9010, LND-6012R/22R, QND-6012R/22R, 7012R/22R, QNE-8011R/21R, ANE-L6012R, L7012R	Info
Accessory	SBO-090GP	Wall Adaptor	Gang plate (for bullet) Adaptor plate for Single, Double, 4" Octagon Compatible with QNO-C8083R / QNO-C9083R / ANO-L6012R / ANO-L6022R / ANO-L6082R / ANO-L7012R / ANO-L7022R / ANO-L7082R	Info
Accessory	SBD-137WMA	Wall Adaptor	Wall adaptor plate to make a Q-Core camera compatible with SBP-137WMW and SBP-137WMW1	Info
Accessory	SBE-100PM	Pole Mount	Pole Mount for Explosion-proof Cameras, compatible with TNO-6322ER, TNU-6322E and TNU-6322ER	Info
Accessory	SBP-156KMW	Corner Mount Base	Corner Mount Adapter compatible with SBP-156WMW for XNP-9300RW/9250R/9250/8300RW/8250R/8250/6400RW/6400R/6400, White	Info
Accessory	SBP-300KM1	Corner Mount Adaptor	Corner Mount Adaptor, aluminium, ivory	Info
Accessory	SBP-300KMW1	Corner Mount Adaptor	Corner Mount Adaptor, aluminium, QNV-6012R1/6022R1/6032R16082R1, QND-6012R1/6022R1/6032R1/6082R1white	Info
Accessory	SBP-300KMS	Stainless Steel Corner Mount Adaptor	Stainless Steel Corner mount adaptor, Compatible with SBP-300WMS and SBP-300WMS1	Info
Accessory	SBP-156CMW	Pendant Mount	Aluminum Pendant Mount Accessory. Compatible with XNP-9300RW/9250R/9250/8300RW/8250R/8250/6400RW/6400R/6400 and other accessories with 1-1/2" PF thread, White	Info
Accessory	SBP-302CMBW	Ceiling Mount	Back box made to fit SBP-302CMW telescopic pendant mount, White color	Info
Accessory	SBP-300CM	Ceiling Mount	Aluminum Pendant Mount Accessory, Ivory, Can be used with hanging mount and outdoor PTZ	Info
Accessory	SBP-300CMW	Ceiling Mount	Aluminum Ceiling Mount Accessory, can be used with hanging mount and outdoor PTZ, QNV-6012R1/6022R1/6032R1/6082R1, QND-6012R1/6022R1/6032R1/6082R1, White	Info
Accessory	SBP-300CMW1	Ceiling Mount	Ceiling Mount, Aluminum, White, compatible with Hanging Adaptors such as SBP-120HMMW/140HMMW/160HMMW1/180HMMW1, etc and Pipe extensions such as SBP-C15P, SBP-150CMP/300CMP/900CMP ※ For further compatible models, please visit our website or use Toolbox	Info
Accessory	SBP-900CMW	Ceiling Mount	Ceiling Mount, Aluminum, White, compatible with Hanging Adaptors such as SBP-120HMMW/140HMMW/160HMMW1/180HMMW1, etc and Pipe extensions such as SBP-C15P, SBP-150CMP/300CMP/900CMP ※ For further compatible models, please visit our website or use Toolbox	Info
Accessory	SBP-150CMI	Ceiling Mount	Ceiling Mount, Aluminum, White, compatible with Hanging Adaptors such as SBP-120HMMW/140HMMW/160HMMW1/180HMMW1, etc. ※ For further compatible models, please visit our website or use Toolbox	Info
Accessory	SBP-300CMI	Ceiling Mount	Ceiling Mount, Aluminum, White, compatible with Hanging Adaptors such as SBP-120HMMW/140HMMW/160HMMW1/180HMMW1, etc. ※ For further compatible models, please visit our website or use Toolbox	Info
Accessory	SBP-140CMB	Ceiling Mount	Ceiling Mount, Aluminum, White, competible with SBP-150CMP, SBP-300CMP, SBP-900CMP etc ※ For further compatible models, please visit our website or use Toolbox	Info
Accessory	SBP-140CMT	Tile Grid Ceiling Mount	Tile Grid Ceiling Mount Pack of 4 , Compatible with QND-6011/6021, QND-8011/8021 QNF-8010/9010, QND-6012R/6022R/6082R, QNV-C9011R/C8011R/C8012, LND-6012R/6022R/6072R, QNE-8011R/8021R, ANE-L6012R/L7012R/L7012L, QNV-C8083R/C9083R, XND-8082RV/9082RV, X plus indoor dome, P AI indoor dome	Info
Accessory	SBP-180CMB	Ceiling Mount	Ceiling Mount, Aluminum, White, competible with SBP-C15P, SBP-150CMP/300CMP/900CMP etc. (Pipe extention can be supported only 1 time) ※ For further compatible models, please visit our website or use Toolbox	Info
Accessory	SBP-180CMS	Ball Head Ceiling Mount Base	Ball Head Ceiling Mount Base, Aluminum, White, competible with SBP-C15P, SBP-150CMP/300CMP/900CMP etc. (Pipe extention can be supported only 1 time) ※ For further compatible models, please visit our website or use Toolbox	Info
Accessory	SBP-150CMP	Ceiling Mount	Ceiling Mount, Aluminum, White, competible with - Base : SBP-140CMB, SBP-180CMB, - Pipe extention : SBP-C15P, SBP-150CMP/300CMP/900CMP ※ Extention should be done with SBP-180CMB ※ For further compatible models, please visit our website or use Toolbox	Info
Accessory	SBP-150NBW	Cabinet	Installation Cabinet compatible with SBP-250WMMW, SBP-156WMMW, SBP-400WMMW, SBP-150PMW. Direct camera compatible with QNV-C8083R/C9083R, XND-C6083RV/C7083RV/C8083RV/C9083RV, XNV-C6083R/C7083R/C8083R/C9083R, XND-6083RV/8083RV/9083RV, XNV-6083R/8083R/8093R/9083R,	Info
Accessory	SBP-150PMW	Pole Mount	Pole mount compatible with TNU-6321 & TNU-4041T/4051T	Info
Accessory	SBP-300CMP	Ceiling Mount	Ceiling Mount, Aluminum, White, competible with- Base : SBP-140CMB, SBP-180CMB, - Pipe extention : SBP-C15P, SBP-150CMP/300CMP/900CMP ※ Extention should be done with SBP-180CMB ※ For further compatible models, please visit our website or use Toolbox	Info
Accessory	SBP-300CMTW	Telescopic Ceiling Mount	Telescopic Ceiling Mount, Aluminum, White, competible Accessories- Hanging Adaptor : SBP-120HMMW/140HMMW/160HMMW1/180HMMW1, etc., - Pipe extension : SBP-C15P, SBP-150CMP/300CMP/900CMP ※ For further compatible models, please visit our website or use Toolbox	Info

Accessory	SBP-300CMTS	Ball Head Ceiling Mount	Ball Head Ceiling Mount, Aluminum, White, compatible with - Hanging Adaptor : SBP-120HMMW/140HMMW/160HMMW1/180HMMW1, etc.,- Pipe extension : SBP-C15P, SBP-150CMP/300CMP/900CMP ※ For further compatible models, please visit our website or use Toolbox	Info
Accessory	SBP-900CMP	Ceiling Mount	Ceiling Mount, Aluminum, White, competeble with - Base : SBP-140CMB, SBP-180CMB, - Pipe extention : SBP-C15P, SBP-150CMP/300CMP/900CMP ※ Extension should be done with SBP-180CMB ※ For further compatible models, please visit our website or use Toolbox	Info
Accessory	SBP-C15P	Ceiling Mount	Ceiling Mount base, Aluminum, White, competeble with SBP-150CMP, SBP-300CMP, SBP-900CMP ※ For further compatible models, please visit our website or use Toolbox	Info
Accessory	SBP-C35H	Ceiling Mount Coupler	Ceiling mount coupler (for pipe extension), compatible with SBP-150CMP, SBP-300CMP, SBP-900CMP Pack of 4	Info
Accessory	SBP-C15NP	Thread Converter	1.5" NPT to PF thread converter, to support compatibility with NPT threaded pipes	Info
Accessory	SBP-C15H	1.5" coupler (White)	1.5" Coupler (White) Pack of 4 compatible with Ceiling mount SBP-140CMB, SBP-180CMB, SBP-180CMS Hanging Adaptor SBP-099HMMW, SBP-120HMMW, SBP-140HMMW, SBP-160HMMW1, SBP-180HMMW1, SBP-200HMMW, SBP-250HMMW, SBP-315HMMW, SBP-156HMMW	Info
Accessory	SBP-303HF	Fiber Optic for PTZ	Aluminum Built-in Sfps Install Base for PTZ Cameras XNP-6550RH, XNP-6320H and QNP-6230H, RJ-45 to Fiber, 4 Weeks lead Time	Info
Accessory	SBP-099TMW	Tilted Mount Adapter	Tilted Wall Mount (Poly Carbonate), Compatible with QNF-8010, QNF-9010	Info
Accessory	SBP-160TM	Tilted Mount Adapter	Tilted Wall Mount (Poly Carbonate), 23° Tilt , Compatible with XND-6085/6085V, XNV-6080/R/6085/R/8080R, XNV-L6084/R, PNV-9080R, SNV-8081/8080/7084/R/6084/R/6085R/5084/R, SCV-6081R	Info
Accessory	SBP-160WMW1	Wall Mount	Wall Mount (Aluminum) , RAL9003; Indoor use only; Compatible with XND-C6083RV/C7083RV/ C8083RV/C9083RV XND-6083RV/8083RV/9083RV XNV-C6083R/C7083R/C8083R/C9083R, XND-8082RV/9082RV, XNF-9010RV/9013RV, PNF-A6081RV/A9081RV	Info
Accessory	SBP-140WMW	Wall Mount	Wall Mount (Aluminum) , RAL9003; Indoor use only; Compatible with QNV-C8083R/9083R, white	Info
Accessory	SBP-142CMW	Ceiling Mount	Ceiling Mount compatible with TNMC3620TDR/C3622TDR	Info
Accessory	SBP-142WMW	Wall Mount	Wall Mount compatible with TNMC3620TDR/C3622TDR	Info
Accessory	SBP-160TMW1	Tilted Mount Adapter	Tilted Wall Mount (Poly Carbonate), 23° Tilt , Compatible with PND-A6081RV, PND-A9081RV, XND-6081REV, XND-6081RV, XND-6081V, XND-6081VZ, XND-8081REV, XND-8081RV, XND-8081VZ, XND-8082RV, XND-9082RV, XNF-9010RV, XNF-9010RVM, White	Info
Accessory	SBP-300TM1	Tilted Mount Adapter	Tilted Wall Mount (Poly Carbonate), 20° Tilt , Compatible with 5MP fisheye cameras (SNF-8010, SNF-8010/VM, XNF-8010R/RV/RVM, PNF-9010R/RV/RVM), Ivory	Info
Accessory	SBF-100B1	Fisheye Back Box	Aluminum Back box for Fisheye cameras, Compatible with SNF-8010/VM, XNF-8010R/RV/RVM, PNF-9010R/RV/RVM	Info
Accessory	SBF-100BW1	Fisheye Back Box	Aluminum Back box for Fisheye cameras, Compatible with SNF-8010/VM, XNF-8010R/RV/RVM, PNF-9010R/RV/RVM	Info
Accessory	SBO-100B1	Bullet Back Box	Aluminum Back box for bullet cameras, Compatible with QNO-6030R / 6020R / 6010R, QNO-6032R1/ 6022R1/ 6012R1, QNO-7030R / 7020R / 7010R, QNO-7080R/6070R, SNO-L6083R / L5083R, SCO-6083R	Info
Accessory	SBO-147B	Bullet Back Box	Aluminum Waterproof Back box for bullet camera, Compatible with QNO-6082R, IP66/IK10, QNO-6012R, QNO-6022R, QNO-6032R, QNO-7082R	Info
Accessory	SBO-147BA	Back Box	Cover- Aluminum, Top cover – Polycarbonate Back Box, White, RAL9003, Compatible with XNO-C6083R/C7083R/C8083R/C9083R	Info
Accessory	SBV-116B	Dome back box	Dome Back box with knockouts, Compatible with XNV-6011, SNV-6013	Info
Accessory	SBV-136B	Dome Back Box	Waterproof aluminum backbox with knockout panels, Compatible with XNP-6040H, QNV-7080R, QNV-6070R, HCV-6070R/6080R, HCV-6080, HCV-7070R/7080R, SNV-L6083R, SNV-L5083R, SCV-5082, SCV-5083, SCV-5085, SCV-5083R, SCV-6083R/ 6023R, Ivory	Info
Accessory	SBV-136BW	Dome Back Box	Aluminum backbox with knockout panels, Compatible with QNV-8080R, QNV-6082R/6082R1, White	Info
Accessory	SBV-138TMW	Dome Back Box	Tilt Mount Dome back box, Compatible with QNV-6072R/6082R, QNV-7082R, QNV-8080R LNV-6072R, White RAL9003	Info
Accessory	SBV-120GW	Dome Back box	Dome Back box with knockouts, Compatible with QNV-6012R/6022R/6032R, QNV-6012R1/6022R1/6032R1, QNV-8010R/8020R/8030R, White	Info

Accessory	SBV-158G	Dome Back box	Back Box for Outdoor Vandal Domes, Compatible with PNV-9080R, XNV-6080/R, XNV-8080R, XNV-6120/R, XNV-6085, XNV-L6080/R, SNV-5084/R,SNV-6084/R, SNV-7084/R, SNV-8081R, SNV-8080, Ivory	Info
Accessory	SBV-158GW	Dome Back box	Back Box for Outdoor Vandal Domes, Compatible with PNV-9080R, XNV-6080/R, XNV-8080R, XNV-6120/R, XNV-6085, XNV-L6080/R, SNV-5084/R,SNV-6084/R, SNV-7084/R, SNV-8081R, SNV-8080, White	Info
Accessory	SBV-160BW	Dome Back box	Back Box for Indoor Vandal Domes and Fisheye, Compatible with PND-A6081RV, PND-A9081RV, XND-6081REV, XND-6081RV, XND-6081V, XND-6081VZ, XND-8081REV, XND-8081RV, XND-8081VZ, XND-8082RV, XND-9082RV, XNF-9010RV, XNF-9010RVM, White	Info
Accessory	SBV-180BW	Dome Back box	Back Box for Indoor Domes and Vandal Domes, Compatible with XND-C9083RV/C8083RV/C7083RV/C6083RV, XND-C9083R/C8083R/C7083R/C6083R, XND-9083RV/8093RV/8083RV/6083RV, XNV-9083R/8093R/8083R/6083R, XND-9082RV/8082RV, XNV-9082R/8082R, White	Info
Accessory	SBV-180WW	Waterproof Back Box	Waterproof Back Box for the white Vandal X-Core and X-Plus cameras Compatible models include: XNV-6081R / XNV-8081R / XNV-6083R / XNV-8083R / XNV-8093R / XNV-9083R XNV-C6083R / XNV-C7083R / XNV-C8083R / XNV-C9083R	Info
Accessory	SBO-126B	Bullet Back Box	Back box for bullet cameras, Compatible with XNO-L6080R	Info
Accessory	SCL-150	Lens Cable	Extension cable for remote head lens, 15m (49.2ft), compatible with: PNM-9000QB, SLA-T4680A, SLA-T4680VA, SLA-T2480A, SLA-T2480VA, SLA-T1080FA, SLA-T2880BA, SLA-T4680DA, SLA-T4680DSA	Info
Accessory	SPP-C45W	Cable	RJ45 type converting cable (Plugin to Pigtail), compatible QNV-6012R(1)/6022R(1)/6072R(1)/6082R(1), QNV-7012R/7022R/7032R/7082R,QNV-8010R/20R/80R, QNV-C6083R/C8083R/C9083R Pack of 5	Info
Accessory	SPP-C45WA	Cable	RJ45 type converting cable (Plugin to Pigtail), compatible with ANV-L6012R/L6082R, ANV-L7012R/L7082R Pack of 5	Info
Accessory	SPP-C7200	Cable for audio/alarm	Audio and Alarm cable compatible with QND-C8013R/C8023R Pack of 3	Info
Accessory	SPP-C7400	Cable for audio/alarm	Audio and Alarm cable for TNV-C7013RC, QNV-C8083R/9083R, XNV-C6083R/C7083R/C8083R/C9083R, XND-C6083RV/C7083RV/C8083RV/C9083RV, Pack of 3	Info
Accessory	SPP-C1900	HDMI Cable	HDMI Cable Pack of 3 compatible with QNV-C6083R	Info
Accessory	SHB-9000H	Fixed Housing	TNB-9000 Box Camera Housing, Body/Sun shield : Aluminum, Front & Rear cap : ABS, Wall Mount Arm Included. Operating Temperature: -50°C ~ +60°C/-58°F ~ +140°F) / 10-100% RH (condensing), Weight: 6.2kg(13.67 lb), Color: White, IP66. Input Voltage 110vac, Thermostat controlled Fan and heater - UL 62368-1 Certified	Info
Accessory	SHB-4200	Fixed Housing	Dimensions/Weight: 700mm(27.56 inches) /40g(0.09lb)	Info
Accessory	SHB-4200H	Fixed Housing	Outdoor Fixed Camera Housing w/Mounting Bracket, Compatible with all box cameras, Built-in heater and fan, IP66, 24VAC, Ivory	Info
Accessory	SHB-4300H	Fixed Housing	Extreme Weatherproof Aluminum Fixed Camera Housing w/Mounting Bracket, Compatible with all box cameras, Built-in heater and fan, IP66, 24VAC, Ivory	Info
Accessory	SHB-4300H1	Fixed Housing	Extreme Weatherproof Aluminum Fixed Camera Housing w/Mounting Bracket, Compatible with all box cameras, Built-in defroster/heater and fan, IP66, 24VAC, Ivory	Info
Accessory	SHB-4301H2	Fixed Housing	Extreme Weatherproof Aluminum Fixed Camera Housing w/Mounting Bracket, Compatible with all box cameras, Built-in defroster/heater and fan, IP66, 230VAC, Ivory	Info
Accessory	SHB-4301HP	Fixed Housing	Outdoor Fixed Camera Housing w/Mounting Bracket, Compatible with all box cameras, Built-in defroster/heater and fan, IP66, PoE/12VDC, Ivory	Info
Accessory	SBB-900	Fixed Mount	Aluminum Wall Mount Adapter for box cameras enclosures, Bracket for SHB-9000H	Info
Accessory	STB-4150V	Box Mount	Aluminum Fixed Camera Mount, Compatible with Box cameras, Bracket for STH-500/200, Silver	Info
Accessory	SBV-253WCW	Weather Cap	Polycarbonate Weather Cap, White, RAL9003, Compatible with PNM-9031RV/PNM-C9022RV/PNM-9022V	Info
Accessory	SBV-120WCW	Weather Cap	Aluminum Weather cap, Compatible with XNV- 6010/6020/8020R/8030R/8040R, QNV- 6010R/6020R/6030R/7010R/7020R/7030R, White	Info
Accessory	SBV-121WCW	Weather Cap	Weather Cap Compatible with QNV-C8013R/C8023R	Info
Accessory	SBV-140WCBW	Weather Cap	Polycarbonate Weather Cap compatible with TNV-C8011RW	Info

Accessory	SBV-160WC	Weather Cap	Aluminum Weather cap, Compatible with XNV-6080/R/8080R/6120R/L6080/R,PNV-9080R,SNV-8081/8080/7084/R/6084/R/6085R/5084/R,SCV-6081R	Info
Accessory	SBV-161WCW	Weather Cap	Polycarbonate Weather Cap, White,RAL9003, Compatible with XNV-C6083R/C7083R/C8083R/C9083R	Info
Accessory	SBV-140TMW	Tilt Mount	Tilt Mount, Aluminum, White, weight 450g(0.99lb), compatible with QNV-C8083R/C9083R, QNV-C8011R/C8012/C9011R, QND-6011/21, QND-8011/21, QND-6012R/22R/72R/82R, QND-7012R/22R/82R, QNE-8011R/21R	Info
Accessory	SBV-140TBW	Tilt Mount	Tilt Mount for TNV-C8011RW	Info
Accessory	SBV-140BW	Back Box	Back Box, Almunum, White, compatible with QNV-C8083R/C9083R, QNV-C8011R/C8012/C9011R, QND-6011/21, QND-8011/21, QND-6012R/22R/72R/82R, QND-7012R/22R/82R, QNE-8011R/21R	Info
Accessory	SBV-140WW	Waterproof Back Box	Waterproof Back Box, Almunum, White, compatible with QNV-C8083R/C9083R, QNV-C8011R/C8012/C9011R, QND-6011/6021,QND-8011/8021, QND-6012R/6022R/6082R, QND-7012R/7022R/7082R, QNE-8011R/8021R	Info
Accessory	SBO-140BW	Back Box	Back Box, Almunum, White, weight 390g(0.86lb), Compatible with: QNO-C8083R/C9083R, ANO-L6012R/22R/82R, ANO-L7012R/22R/82R	Info
Accessory	SBO-140WW	Waterproof Back Box	Waterproof Back Box, Almunum, White, compatible with QNO-C8083R/C9083R, ANO-L6012R/22R/82R, ANO-L7012R/22R/82R	Info
Accessory	SBV-A14B	Back Box	Back Box for A series (ANE-L6012R, ANE-L7012R, ANO-L6012R,ANO-L6022R, ANO-L6082R, ANO-L7012R, ANO-L7022R, ANO-L7082R, ANV-L6012R, ANV-L6082R, ANV-L7012R, ANV-L7082R) and connect cables	Info
Accessory	SBV-215WCW	Weather Cap	Weather Cap, White, Material: aluminum thread, plastic cap, compatible with PNM-C7083RVD, PNM-C12083RVD and PNM-7082RVD, PNM-12082RVD	Info
Accessory	SBP-SCP/SN	Swan Neck Bracket	Swan Neck Bracket	Info
Accessory	SBP-300NM	Mounting accessory	Housing and Mount for PVM camera TNB-6030	Info
Accessory	SBE-100B	Pedestal Mount	Stainless Steel Pedestal Mount for Explosion-proof Cameras, compatible with TNU-6322E and TNU-6322ER	Info
Accessory	SPB-PTZ6	Smoked Dome Cover	Smoked Dome Cover for Indoor PTZ: XNP-6320/QNP-6230/SNP-6321/6320/5430/5321, SNP-L6233/L5233, SCP-3371/2373/2371/2273/2271	Info
Accessory	SPB-PTZ73	Smoked Dome Cover	Smoked Dome Cover for XNP-6120H	Info
Accessory	SPB-PTZ82W	Smoked Dome Cover	Smoked dome cover for QNP-6250H/6320H	Info
Accessory	SPB-PTZ95W	Smoked Dome Cover	Smoke Dome Cover compatible with XNP-C7310R & XNP-C9310R	Info
Accessory	SPB-VAN3	Smoked Dome Cover	Smoked Dome Cover for SNV-8081R, SNV-8080, SNV-5084/6084/7084, SNV-5084R/6084R/7084R, SCV-6081R, XNV-6080/R, XNV-8080R	Info
Accessory	SPB-VAN11	Smoked Dome Cover	Smoked Dome Cover for XNV- 6010/6020/ 8020R/8030R/8040R	Info
Accessory	SPB-VAN12	Smoked Dome Cover	Smoked Dome Cover for QNV- 6010R/6020R/6030R/ 7010R/7020R/7030R	Info
Accessory	SPB-VAN16W	Smoked Dome Cover	Smoke Dome compatible with QNV-C8011R/C8012/C9011R	Info
Accessory	SPB-VAN14W	Smoked Dome Cover	Smoked dome cover compatible with XNV-6012M/6022RM	Info
Accessory	SPB-VAN23W	Smoke Dome Cover	Smoke Dome for TNV-C8014RM & TNV-C8034RM	Info
Accessory	SPG-VAN23W	Dome Cover	Clear Dome for TNV-C8014RM & TNV-C8034RM	Info
Accessory	SPB-VAN72	Smoked Dome Cover	Smoked Dome Cover for QNV-6070R/7080R	Info

Accessory	SPB-VAN82W	Smoked Dome Cover	Smoke Dome for Q AI V/F Compatible with QNV-C6083R/C8083R/C9083R	Info
Accessory	SPB-VAN85W	Smoked Dome Cover	Smoked Dome Cover for XNV-6081/6081R/8081R/6081RE/8081RE, PNV-A9081R, White	Info
Accessory	SPB-VAN88W	Smoked Dome Cover	Smoked Dome Cover for XNV-C9083R, XNV-C8083R, XNV-C7083R, XNV-C6083R, White	Info
Accessory	SPB-VAN89W	Vandal Dome Backbox	Vandal Dome Backbox, Material : [Top cover] Aluminum + PC / [Dome bubble] Hard-coated Polycarbonate, Color : [Top cover]White / [Dome bubble] Transparent smoked, Supported products: XNV-6083RZ/8083RZ/9083RZ/8083Z/6083Z	Info
Accessory	SPB-FCD85W	Smoked Dome Cover	Smoked Dome Cover for XND-6081F/6081RF/8081RF, PND-A9081RF, White	Info
Accessory	SPB-VAW12	Smoked Dome Cover	Smoked Dome Cover for QNV-6012R/6022R/6032R, QNV-8010R/8020R/8030R, LNV-6012R/6022R/6032R, QNV-6012R1/6022R1/6032R1, White	Info
Accessory	SPB-VAW72	Smoked Dome Cover	Smoked Dome Cover for QNV-6082R/6082R1/8080R, LNV-6070R/6072R, White	Info
Accessory	SPB-IND6	Smoked Dome Cover	Smoked Dome Cover for SCD-6083R, SCD-5080, SCD-5082, SCD-5083, SCD-6083R, SND-6011R, SND-L6083R, SND-L5083R, HCD-6080R/6070R	Info
Accessory	SPB-IND11	Smoked Dome Cover	Smoked Dome Cover for XND-6010/6020/8020R/8030R/8040R	Info
Accessory	SPB-IND12	Smoked Dome Cover	Smoked Dome Cover for QND-6010R/6020R/6030R / 7010R/7020R/7030R, White	Info
Accessory	SPB-IND81	Smoked Dome Cover	Smoked Dome Cover for XND-6080V/XND-6080RV/ XND-8080RV	Info
Accessory	SPB-IND81V	Smoked Dome Cover	Smoked Dome Cover for XND-6080V/XND-6080RV/ XND-8080RV	Info
Accessory	SPB-IND85W	Smoked Dome Cover	Smoked Dome Cover for XND-6081V/6081RV/8081RV/6081REV/8081REV, PND-A9081RV, White	Info
Accessory	SPB-IND88W	Smoked Dome Cover	Smoked Dome Cover for XND-C9083RV, XND-C8083RV, XND-C7083RV, XND-C6083RV, white	Info
Accessory	SPG-IND12B	Black Dome Cover	Black Dome Cover with Clear Bubble for QND-6010R/6020R/6030R/7010R/7020R/7030R	Info
Accessory	SPG-IND16B	Black Dome Cover	Black Dome Cover with Clear Bubble for QND-6021/6011/8021/8011	Info
Accessory	SPG-IND72B	Black Dome Cover	Black Dome Cover with Clear Bubble for QND-6070R, QND-7080R, LND-6071R, LND-6072R	Info
Accessory	SPG-PTZ95W	Black Dome Cover	Dome Cover compatible with XNP-C7310R & XNP-C9310R	Info
Accessory	SPG-VAN13W	Conduit Dome Cover	Conduit dome cover for TNV-C7013RC, White, Aluminum, 198.3x198.6x94mm (7.81x7.82x3.70")	Info
Accessory	SPB-INW12	Smoked Dome Cover	Smoked dome cover for White Q/L fixed indoor domes (LND-6012R/6022R/6032R, QND-6012R/6022R/6032R)	Info
Accessory	SPB-INW72	Smoked Dome Cover	Smoked Dome Cover for LND-6072R, QND-6070R, QND-6082R, QND-6082R1, White	Info
Accessory	SPB-MDC51V	Smoked Dome Cover	Smoked Dome Cover for PNM-9322VQP (PTZ dome only)	Info
Accessory	SPB-MDC41	Smoked Dome Cover	Tinted dome cover for PNM-9084RQZ and PNM-9085RQZ	Info
Accessory	SPB-MDC31	Smoked Dome Cover	Tinted dome cover for PNM-9084QZ and PNM-8083VT	Info
Accessory	SPB-MDC41W	Smoked Dome Cover	Tinted dome cover for PNM-9022V	Info

Monitors				
Monitor	SMT-3231PV	32" AI PVM Monitor	32" AI Enabled, IP public view monitor (AI PVM) PIP & PBP support,1080p (1920 x 1080 60Hz), HDMI, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, AI face & Object detection. Display for visual deterrent, customizable text overlay with pre-configured "recording in progress" OSD 2MP IP camera built-in, 3.06mm fixed lens, (107.7" H and 59.0V), 120dB WDR, H.265/H.264/MJPEG, slide show & live video, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode, portrait and landscape display support, HPoE 802.3bt, DC 24V. *** Power adapter not included ***	Info
Monitor	SMT-3221PV	32" AI PVM Monitor (Non PIP/PBP)	32" AI Enabled IP public view monitor (AI PVM),1080p (1920 x 1080 60Hz), HDMI (x2), Ethernet, 16:9 Aspect Ratio, Built-in speaker (2W x2), Face Detection for Visual Deterrence, AI Analytics, Customizable Banner Overlay Messages, Built-In 2MP IP Camera, 3.06mm Fixed Lens (107.7" H, 59.0V), 120dB WDR, H.265/H.264/MJPEG, Slide Show & Live Video, Micro SD/SDHC/SDXC, VESA Compatible (100x100 / 200x100 / 200x200), Black Cabinet, Hallway View Mode, Portrait and Landscape Display Support, HPoE 802.3bt, DC 24V. *** Power adapter not included ***	Info
Monitor	SMT-2731PV	27" AI PVM Monitor	27" AI Enabled, IP public view monitor (AI PVM) PIP & PBP support,1080p (1920 x 1080 60Hz), HDMI, Ethernet, 16:9 aspect ratio, Built-in speaker (2x2 W), VESA mountable (100 x 100mm / 200 x 100mm), black casing, AI face & Object detection. Display for visual deterrent, customizable text overlay with pre-configured "recording in progress" OSD 2MP IP camera built-in, 3.06mm fixed lens, (107.7" H and 59.0V), 120dB WDR, H.265/H.264/MJPEG, slide show & live video, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode, portrait and landscape display support, HPoE 802.3bt, DC 24V. *** Power adapter not included ***	Info
Monitor	SMT-2721PV	27" AI PVM Monitor (Non PIP/PBP)	27" AI Enabled IP public view monitor (AI PVM),1080p (1920 x 1080 60Hz), HDMI (x2), Ethernet, 16:9 Aspect Ratio, Built-in speaker (2W x2), Face Detection for Visual Deterrence, AI Analytics, Customizable Banner Overlay Messages, Built-In 2MP IP Camera, 3.06mm Fixed Lens (107.7" H, 59.0V), 120dB WDR, H.265/H.264/MJPEG, Slide Show & Live Video, Micro SD/SDHC/SDXC, VESA Compatible (100x100 / 200x100 / 200x200), Black Cabinet, Hallway View Mode, Portrait and Landscape Display Support, HPoE 802.3bt, DC 24V. *** Power adapter not included ***	Info
Monitor	SMT-1030PV	10" IP PVM Monitor (Black)	10.1" IP public view monitor, 1024x600, Ethernet, 16:9 aspect ratio, VESA mountable (75 x 75mm), black casing, face detection display for visual deterrent, customizable text overlay with pre-configured "recording in progress" OSD, 2MP IP camera built-in, 4.6mm fixed lens (73.8"H), 150dB WDR, H.265/H.264/MJPEG, WiseStream II compression technology, micro SD/SDHC/SDXC, 12V DC, PoE+	Info
Monitor	SMT-1031PV	10" AI PVM Monitor (Non PIP/PBP, Black)	10.1" AI enabled IP public view monitor (AI PVM), Black Color ,1080p (1024x600 @60Hz), HDMI, Ethernet, 16:9 aspect ratio, Built-in speaker (8 Ohn, 1W x 2), VESA mountable (75 x 75mm), AI face & Object detection display for visual deterrent, OSD, Slid show and logo image support 2MP IP camera built-in, 3.06mm fixed lens(107.7" H and 59.0V), 120dB WDR, H.265/H.264/MJPEG, slide show & live video, PoE+ 802.3at, DC 24V. *** Power adapter not included ***	Info
Monitor	SMT-1031PVW	10" AI PVM Monitor (Non PIP/PBP, White)	10.1"AI enabled IP public view monitor (AI PVM), White Color ,1080p (1024x600 @60Hz), HDMI, Ethernet, 16:9 aspect ratio, Built-in speaker (8 Ohn, 1W x 2), VESA mountable (75 x 75mm), AI face & Object detection display for visual deterrent, OSD, Slid show and logo image support 2MP IP camera built-in, 3.06mm fixed lens(107.7" H and 59.0V), 120dB WDR, H.265/H.264/MJPEG, slide show & live video, PoE+ 802.3at, DC 24V. *** Power adapter not included ***	Info
Monitor	SMT-4343	43" UHD Monitor	43" UHD LED Monitor, 4K UHD (3840 x 2160), HDMI, DP, 16:9 aspect ratio, Contrast ratio 1,000 : 1, Response time 8ms, Panel life 30,000 hrs, Audio connector, VESA DPM Compatible (100x100mm, 400x200mm), Designed and tested on 24/7 operation, compatible with SBM-4343 stand (Stand can be purchased separately)	Info
Monitor	SMT-3240	32" UHD Monitor	32" UHD LED Monitor, 4K UHD (3840 x 2160), HDMI, DP, 16:9 aspect ratio, Contrast ratio 1,000 : 1, Response time 14ms, Panel life 30,000 hrs, Audio connector, VESA DPM Compatible (100x100mm, 400x200mm), Designed and tested on 24/7 operation	Info
Monitor	SMT-2740	27" UHD Monitor	27" UHD LED Monitor, 4K UHD (3840 x 2160), 300 cd/m², Contrast 1200:1, Viewing Angle 178°/178°, Response Time 14ms, HDMI, DP, two windows PIP/PBP, Designed and tested on 24/7 operation	Info
Monitor	SMT-3215	32" FHD Monitor	32" FHD LED Monitor, 1080p (1920x1080), HDMI, DP, VGA,, 16:9 aspect ratio, Built-in Speaker (2W X 2), VESA DPM Compatible (100x100mm), Designed and tested on 24/7 operation	Info
Monitor	SMT-2710	27" FHD Monitor	27" FHD LED Monitor, 1080p (1920x1080), 250 cd/m², Contrast 4000:1, Viewing Angle 178°/178°, Response Time 6.5ms, HDMI, DP, VGA, Designed and tested on 24/7 operation	Info
Monitor	SMT-2431	24" FHD Monitor	24" FHD LED Monitor, Frameless Design, Support up to 1920 x 1080 resolution, Contrast ratio 4000:1, Viewing Angle (H/V) 178°/178°, Response Time 14ms, Video Input HDMI and VGA, Designed and tested on 24/7 operation	Info
Monitor	SMT-2212	22" FHD Monitor	22" FHD LED Monitor, Frameless Design, Support up to 1920 x 1080 resolution, Contrast ratio 3000:1, Viewing Angle (H/V) 178°/178°, Response Time 6.5ms, Video Input HDMI and VGA, Designed and tested on 24/7 operation	Info
Monitor Stand	SBM-4343	Monitor Stand Compatible with SMT-4343, 3234, 3240	Monitor Stand Compatible with SMT-4343, 3234, 3240	Info
Adapter	SPU-60241	DC 24V Adapter for AI PVM	60W(24V) Adaptor + Power Cord package, compatible with PVM lineup (SMT-3221PV/3231PV, SMT-2721PV/2731PV, SMT-1031PV/1031PVW)	Info
Controllers				
Controller - Analog	SPC-2001	Controller	Controller, 3-Axis 12 button USB Joystick Controller for NVRs WAVE SSM and Wisenet Viewer	Info
Controller - Analog	SPC-2010	Controller	Controller, 3D joystick, 2 line text LCD display, built-in jog shuttle, up to 255 PTZ/zoom cameras, RS-485, DVR, supports Multi-protocol	Info
Controller - Analog	SPC-1010	Controller	Controller, PTZ joystick controller, 2 line text LCD display, up to 255 PTZ/zoom cameras, RS-485	Info
BCR Solution				
Camera - Network	TNS-9040IBC	Barcode Reader Camera	T series network BCR (Barcode Reader Camera) for Barcode Reading and Video Monitoring. Mono: 4K, Color: 4K. Max 20fps @ 4K MONO/COLOR each. 16mm machine vision lens. Removable and replaceable LED module (32 LEDs module is default) Track barcodes on high speed conveyor belt moving at 2m/s (6.5ft/s). Preinstalled WiseBCR App support 1D/2D Barcode recognition. Humidity control with AIR vent. EN 60068-2-6 (vibration resistance), EN 60068-2-27 (shock resistance). Operating temperature -40°C~+55°C, IP67, IK10, 24VDC, Max 28.6W(LED on), Typical 13.7W(LED off). Accessories available to purchase separately - M12 Ethernet Cable (2/5/10m), M12 Power Cable (2/5/10m) and Power Supply Unit 24VDC for UK and EU	Info
Camera - Network	TNS-9050IBC	Barcode Reader Camera	T series network BCR (Barcode Reader Camera) for Barcode Reading and Video Monitoring. Mono: 4K, Color: 4K. Max 20fps @ 4K MONO/COLOR each. 25mm machine vision lens. Removable and replaceable LED module (48 LEDs module is default) Track barcodes on high speed conveyor belt moving at 2m/s (6.5ft/s). Preinstalled WiseBCR App support 1D/2D Barcode recognition. Humidity control with AIR vent. EN 60068-2-6 (vibration resistance), EN 60068-2-27 (shock resistance). Operating temperature -40°C~+55°C, IP67, IK10, 24VDC, Max 28.6W(LED on), Typical 13.7W(LED off). Accessories available to purchase separately - M12 Ethernet Cable (2/5/10m), M12 Power Cable (2/5/10m) and Power Supply Unit 24VDC for UK and EU	Info
Camera - Network	TNS-9060IBC	Barcode Reader Camera	T series network BCR (Barcode Reader Camera) for Barcode Reading and Video Monitoring. Mono: 4K, Color: 4K. Max 20fps @ 4K MONO/COLOR each. 35mm machine vision lens. Removable and replaceable LED module (48 LEDs module is default) Track barcodes on high speed conveyor belt moving at 2m/s (6.5ft/s). Preinstalled WiseBCR App support 1D/2D Barcode recognition. Humidity control with AIR vent. EN 60068-2-6 (vibration resistance), EN 60068-2-27 (shock resistance). Operating temperature -40°C~+55°C, IP67, IK10, 24VDC, Max 35.4W(LED on), Typical 13.7W(LED off). Accessories available to purchase separately - M12 Ethernet Cable (2/5/10m), M12 Power Cable (2/5/10m) and Power Supply Unit 24VDC for UK and EU	Info
Accessory	SPP-C12020P	BCR Camera Cable	BCR Camera M12 Power cable, 2 meters length, IP67 rated, black colour, connector A is pre-terminated M12, connector B is unterminated cable cores. Compatible with TNS-9040IBC, TNS-9050IBC, TNS-9060IBC.	Info
Accessory	SPP-C12050P	BCR Camera Cable	BCR Camera M12 Power cable, 5 meters length, IP67 rated, black colour, connector A is pre-terminated M12, connector B is unterminated cable cores. Compatible with TNS-9040IBC, TNS-9050IBC, TNS-9060IBC.	Info

Accessory	SPP-C12100P	BCR Camera Cable	BCR Camera M12 Power cable, 10 meters length, IP67 rated, black colour, connector A is pre-terminated M12, connector B is unterminated cable cores. Compatible with TNS-9040IBC, TNS-9050IBC, TNS-9060IBC.	info
Accessory	SPP-C08020E	BCR Camera Cable	BCR Camera M12 Ethernet cable, 2 meters length, IP68 rated, blue colour, connector A is pre-terminated M12, connector B is pre-terminated RJ45. Compatible with TNS-9040IBC, TNS-9050IBC, TNS-9060IBC.	info
Accessory	SPP-C08050E	BCR Camera Cable	BCR Camera M12 Ethernet cable, 5 meters length, IP68 rated, blue colour, connector A is pre-terminated M12, connector B is pre-terminated RJ45. Compatible with TNS-9040IBC, TNS-9050IBC, TNS-9060IBC.	info
Accessory	SPP-C08100E	BCR Camera Cable	BCR Camera M12 Ethernet cable, 10 meters length, IP68 rated, blue colour, connector A is pre-terminated M12, connector B is pre-terminated RJ45. Compatible with TNS-9040IBC, TNS-9050IBC, TNS-9060IBC.	info
PSU	SNC-PS-60-EU	Hanwha PSU	Commercial Grade Desktop Power Supply, 24V Output, 60W (2.5A), 2.1mm DC Plug, EU Power Plug. Compatible with TNS-9040IBC, TNS-9050IBC, TNS-9060IBC	info
PSU	SNC-PS-60-UK	Hanwha PSU	Commercial Grade Desktop Power Supply, 24V Output, 60W (2.5A), 2.1mm DC Plug, UK Power Plug. Compatible with TNS-9040IBC, TNS-9050IBC, TNS-9060IBC	info
AI appliance				
AI appliance	AIB-800	8CH AI Box	AI appliance capable of adding AI features to non-AI cameras, Up to 8CH support, Max resolution 8K, protocols: SUNAPI, ONVIF, Video Analytics based on AI [Object detection and classification (Person, Face, Vehicle, License plate), Attribute, BestShot] People counting, Vehicle counting, Queue management, Heatmap based on AI, Operating Temperature: 0°C to 40°C (32°F to 104°F), Power: 12VDC	info
Open Platform Application License				
Open Platform Application License	AIA-C01BLK	Blocked Exit Detection x1	One Camera License for Blocked Exit Detection Open Platform Application. To be installed on Compatible P-Series Cameras (PNV-A9081R, PNO-A9081R, PND-A9081RV, PND-A9081RF, PND-A9081RVX, PNV-A9081RX, PNB-A9001, PNV-A6081R, PNO-A6081R, PND-A6081RV, PND-A6081RF, PNB-A6001) This analytics requires WiseAI application to be installed.	info
Open Platform Application License	AIA-C01FAC	Factory and Safety Pack License x1	One Camera License for Factory and Safety Open Platform Application. To be installed on Compatible P-Series Cameras (PNV-A9081R, PNO-A9081R, PND-A9081RV, PND-A9081RF, PND-A9081RVX, PNV-A9081RX, PNB-A9001, PNV-A6081R, PNO-A6081R, PND-A6081RV, PND-A6081RF, PNB-A6001)	info
Open Platform Application License	AIA-C01RET	Retail Solution Pack License x1	One Camera License for Retail & Business pack Open Platform Application. To be installed on Compatible P-Series Cameras (PNV-A9081R, PNO-A9081R, PND-A9081RV, PND-A9081RF, PND-A9081RVX, PNV-A9081RX, PNB-A9001, PNV-A6081R, PNO-A6081R, PND-A6081RV, PND-A6081RF, PNB-A6001)	info
Open Platform Application License	AIA-C01TRF	Traffic Solution Pack License x1	One Camera License for Intelligent Traffic Solution Open Platform Application. To be installed on Compatible P-Series Cameras (PNV-A9081R, PNO-A9081R, PND-A9081RV, PND-A9081RF, PND-A9081RVX, PNV-A9081RX, PNB-A9001, PNV-A6081R, PNO-A6081R, PND-A6081RV, PND-A6081RF, PNB-A6001)	info