




**Ambient light powered,
smart irrigation controller**

**EC01 MVA
EC01 ASV.075**



TOUCH ANY BUTTON TO
ACTIVATE SCREEN
+ programming mode
program
cycle

I N S T R U C T I O N M A N U A L

TABLE OF CONTENTS

INTRODUCTION	3
1. About the controller	3
2. Component identification	4
2.1 ECO 1.ASV with anti-siphon valve	4
2.2 ECO 1MVA manual valve actuator	5
3. System components	6
4. Anti-siphon valve installation	7
4.1 Changing actuator adapters	9
4.2 Manual valve actuator installation	11
5. Programming	13
6. Setting time and date	13
7. Setting watering day schedules	15
8. Setting watering start time	17
9. Setting watering run times	19
10. Setting the SimpleSmart™ option	21
11. Setting seasonal adjustment (monthly budget)	24
12. Rain delay setting	25
13. Events off setting	26
14. Manual watering	28
15. Connecting a rain sensor	29
16. Maintenance, troubleshooting and repairs	30
17. Warranty	33
18. Technical assistance	34

1. ABOUT THE CONTROLLER

Thank you for purchasing DIG's ECO 1™ Single Station Battery Operated Controller. This manual describes how to get the ECO 1 controller up and running quickly. After reading this manual and becoming familiar with the basic functionality of the controller, use the manual as a reference for less common tasks in the future.

1. ABOUT THE CONTROLLER


The is a one-station, ambient light (solar) powered smart controller that uses a patented energy management system to power the controller day and night. The controller requires no batteries, AC power or direct sunlight and can be installed above grade anywhere in the landscape.

Employing the latest in water conservation features, the ECO 1 can be pre-set to automatically adjust the watering durations according to regional seasonal changes.

2. COMPONENT IDENTIFICATION

2.1 ECO1 .ASV WITH ANTI-SIPHON VALVE


- | | | |
|---------------------------|-------------------------|------------------------|
| 1. Solar PVM | 6. Collapsible | 10. Anti-siphon cap |
| 2. LCD screen | solenoid wire | 11. Pipe thread outlet |
| 3. 7 button keypad | 7. Manual flow control | 12. Pipe thread inlet |
| 4. Rain sensor connection | 8. External bleed screw | 13. Anti-siphon valve |
| 5. Quick reference label | 9. DC Solenoid | |



2.2 ECO1 MVA MANUAL VALVE ACTUATOR


See section 4.1 to change adapters from the factory 3/4 in. assembly to the 1 in. assembly.

- Solar PVM
- LCD screen
- Quick reference label
- 7 button keypad
- Rain sensor connection
- DC Solenoid
- Collapsible solenoid wire
- Manual flow control
- External bleed screw
- Actuator stem



ASSEMBLY FOR ALL PLASTIC VALVES & 1 IN. BRASS VALVES

CHAMPION & ORBIT adapter for 1 in. brass & RAINJET, RAIN BIRD & ORBIT 3/4 in. & 1 in. plastic




AS FACTORY ASSEMBLED FOR 3/4 IN. BRASS VALVES ONLY

CHAMPION, RAIN BIRD & ORBIT 3/4 in. brass adapter



Seat washer assemblies

3. SYSTEM COMPONENTS



LCD Display

1. **Time and Date** - Indicates current time and day
2. **Set Watering Days** - Choose either specific days, odd/even days, or up to once every 30 days
3. **Start Time** - Up to 5 start times per day available
4. **Run Time** - Watering duration from 1 minute to 6 hours
5. **Manual Run** - Appears when manual button is pushed
6. **Set ET** - Used to set one of the 20 SimpleSmart™ presets
7. **Set Monthly Budget** - Seasonal adjustment setting (0%-200%) in 5% increments or to fine-tune SimpleSmart™ programming
8. **Rain Delay** - Delay irrigation setting from 1>99 days with automatic restart
9. **Events Off** - Suspends watering for any month or any specific day within the month.
10. **Power Level** - Represents current charge level
11. **Sensor** - Appears only when sensor is connected and active
12. **Watering** - Appears when valve is open

Control Buttons

- Select programming mode
- Turn ON/OFF program
- Start/stop a manual cycle
- Move left/right to select a value
- Raise/lower the selected value

4. ANTI-SIPHON VALVE INSTALLATION

The ECO1 ASV.075 can be installed directly to PVC pipe. (Inlet 3/4 in. FNPT, outlet 3/4 in. FNPT.)

Operating pressure: 10 to 125 PSI

Recommended operating pressure: 10 to 80 PSI

NOTE: Wrap all fittings with Teflon tape.

Do not use pipe cement on the valve as this will damage the valve and void the warranty.

Make sure when wrapping fittings with Teflon tape that no excess gets into the internal assembly. Tighten the fittings with a wrench, but do not over tighten.

NOTE: The ECO1 ASV.075 must be installed at least 6 in. higher than the highest sprinkler head on the system or back-drainage may occur. Additional control valves must **not** be installed downstream of the anti-siphon valve. The valve must not be operated continuously for more than 12 hours in any 24-hour period.

Consult local codes for specific details.

1. Flush main line until water runs clear before installation.
2. Shut off main water supply.
3. Install the anti-siphon valve directly to PVC pipe using 3/4 in. PVC male adapter or use Schedule 80 nipple. The arrow on valve body indicates direction of water flow (see Figure 6).

4. Turn the main water supply on and pressurize the system.
5. To test the ECO 1™, press the  button. A click will be heard, indicating the valve is open. An icon of a droplet  on the upper left of the screen and the run time remaining will appear on the display in 5 seconds. Check that the system is operating correctly and press the  button again to turn it off. A second click will be heard indicating that the valve closed. The droplet icon  and the manual icon  will disappear from the display and OFF will appear momentarily; then the display will revert to the time of day.
6. Program the ECO 1™ controller (see section 5).




FIGURE 6





FIGURE 7



4.1 CHANGING ACTUATOR ADAPTERS

The ECO 1™ with actuator is factory set to fit a 3/4 in. brass manual anti-siphon valve. To install the controller with actuator on a 1 in. manual anti-siphon valve the 3/4 in. seat washer and adapter must be removed and replaced with the 1 in. adapter and seat washer, which are included in this box.

1. Turn the actuator so that the seat washer and the 3/4 in. threaded adapter face up.
2. Using pliers, or a 5/18 in. wrench, remove the seat washer screw by turning counter clockwise and pull off the 3/4 in. seat washer assembly (see Figure A).




FIGURE A

3. Push the 3/4 in. threaded adapter down towards the actuator to ease the tension on the retainer clip (see Figure B).




FIGURE B

4. Next, place your thumb on one side of the retainer clip and with a pair of pliers grip the other side of the retainer clip and pull outwards, away from your thumb, and upwards, removing it from the base of the 3/4 in. threaded adapter then, remove the adapter (see Figure C).




FIGURE C

5. Install the 1 in. threaded adapter by pushing it onto the actuator stem and making sure the notch on the adapter lines up with the notch on the stem of the actuator (see Figure D).




FIGURE D

6. Spread the retainer clip with your thumbs and push the retainer into the adapter until it clicks (see Figure E).




FIGURE E

7. Install the 1 in. seat washer assembly as shown. Insert the seat washer screw into the bottom of the actuator stem and tighten turning clockwise (see Figure F).




FIGURE F


NOTE: Do not over-tighten.

4.2 MANUAL VALVE ACTUATOR INSTALLATION



Operating pressure: 10 to 125 PSI

Recommended operating pressure: 10 to 80 PSI

1. Shut off main water supply.
2. Remove the manual stem from the existing valve and temporarily remove the anti-siphon cap (Figure A).
3. Replace any existing worn washers with the new ones provided (Figure B).
4. Install the actuator into the manual anti-siphon valve body by turning actuator clockwise. Tighten firmly, but do not over tighten (Figure C).



- Turn actuator flow control knob clockwise until it stops to shut off flow (Figure D).
- Turn on main water supply.
- Activate the solenoid through the controller, a click will be heard indicating the valve is open. (The manual symbol will appear on the display.)
- Turn the actuator flow control knob counter clockwise to allow flow and check the system to make sure that the sprinklers or the drip system is working properly (Figure E).



- De-activate the solenoid through the controller, a faint click will be heard and the valve should close. (The manual symbols will disappear and water flow will stop). If flow continues, turn flow knob clockwise, one full turn at the time until flow is completely shut off.

- Repeat steps 7 and 9 and make sure that flow is turned on and off.

Note: Turn flow control knob clockwise to decrease flow, counter-clockwise to increase flow. For low-flow drip systems below 60 gallons per hour, flow control knob should be turned no more than 1 to 3 turns up (counter-clockwise) from the fully closed position.

- The unit is now ready to be programmed.

5. PROGRAMMING

In order to program the ECO 1™, you must first let the unit sit out in the light to charge. In bright light conditions (full sun) this will take under 30 minutes. In shaded conditions this could take up to 2 hours.

This section explains the programming features, and the steps necessary to assign irrigation schedules. To program the controller use the  to select the desired programming mode, the  to make the entry flash and the   buttons to change the value.

NOTE: Only a flashing value can be changed.

NOTE: If the last data entered stops blinking, press  again to resume programming and repeat the steps.

6. SETTING TIME AND DATE

The controller can display the time in either a 12 or 24 hour format. To change the time format, from the home screen:

- Press and hold the  button for three seconds until the display switches format (AM/PM disappears).




SETTING THE CURRENT TIME AND DATE

To enable the controller to operate properly, the current time and date must be set.

- Press the  button, until the  icon appears along with the time and the day of the week.



2. If the current time has not been set and needs to be updated press and the hour digit starts blinking.
3. To set the current hour, press or (note AM and PM designations).
4. To set the minutes, press again and the minute digit starts blinking. Press the or to set the current time in minutes.



5. Repeat the steps to set the current date including, month, day and year. When the date is selected and updated, the day of the week will be update at the same time to correspond with the date.



6. Press to proceed to the next step SET DAYS or review the program.

Press to move backward.


7. SETTING WATERING DAY SCHEDULES

Option 1 - Setting Specific Days of the Week:

This setting determines which days the ECO 1™ controller will operate. Choose either watering on specific days of the week, EVEN/ODD days or cyclical from daily up to once every 30 days. The controller's default setting is to water on all specific days of the week.


For example, if you want to water every Tuesday, Thursday and Sunday:

1. Press the button until the icon and the days of the week appear on the screen.



2. Press once and **M** (for Monday) starts blinking.
3. Press, and underscore under **M** (Monday) disappears. Monday is de-selected.
4. Press twice and **W** (for Wednesday) starts blinking.
5. Press and the underscore under **W** (Wednesday) disappears. Wednesday is de-selected.
6. Press twice and **F** (Friday) starts blinking.
7. Press and the underscore under **F** (Friday) disappears. Friday is de-selected.

8. Press  and the underscore under **Sa** (Saturday) starts blinking.
9. Press  and the underscore under **Sa** disappears. Saturday is de-selected.




10. Press the  button to proceed to the next step or to set even/odd days.

Option 2 - Setting Even or Odd Days:

To select **EVEN** days, **ODD** days or cyclical days from one day up to every 30 days refer to the following example.

Example: setting the controller to water every 10 days:


1. Press the  button until the  icon and the days of the week appear.
2. Press  and  to skip all the days of the week (underscore must be removed beneath all days).
3. Press  and **EVEN** appears blinking. (To select **ODD** days press )



4. Press  again and 1 DAY appears blinking. To select the number of days between watering of 10 days, press  until 10 appears on the display.



5. To return to a weekly schedule, Press  and the program returns to the weekly schedule for selecting the day of the week.



6. Press the  button to proceed to the next step **START TIME**  or to review the program.

8. SETTING WATERING START TIME

The ECO 1™ smart controller can have up to five separate irrigation start times per day.

To set a start time,

1. Press the  button until the  icon appears. **START 1**, displays OFF or the last start time programmed in **START 1** appears.




2. Press  and **OFF** (or the first start time programmed) begins blinking.

- To set the desired first start time hour (note AM and PM designations), press




- Press and the minutes start blinking.

- Press or and set the desired start time minutes.



- Press again, the second start time and OFF (or the last start time programmed) appear blinking.



- To set the desired second start time hour (note AM and PM designations), press



- Press again and the minutes begin blinking, press or to select the watering start time in minutes. Repeat the steps to set the third and if needed the fourth and fifth start times. During programming, the screen also shows which days the controller will operate.




Press the button to proceed to the next step RUN TIME or to review the program.

9. SETTING WATERING RUN TIMES


Note: If you have already set a SimpleSmart™ ET preset (example: SP02) and then change the run time, your SimpleSmart™ program will be turned OFF. You must reactivate the SimpleSmart™ programming each time you adjust your run time (see section 10).

This setting determines the length of time the ECO 1™ smart controller will allow the valve to remain open (duration is from 1 minute up to 6 hours). For example, setting watering run time to 10 minutes on certain days of the week will program the controller to turn the water on for 10 minutes on each of the days chosen and at every start time selected.


To set the watering run time :



- Press the button until the icon appears and OFF or the last run time setting appears.
- Press the button, and OFF (or the last run time programmed) appears with hours blinking.
- To set a desired watering run time in hours, press or and select the number of hours.



4. If only watering duration in minutes is required, press  to skip the hour digit, and the minutes will start blinking.
5. To set the desired watering duration in minutes (example of 10 minutes), press  or  to select minutes. When programming the watering duration the screen will also show the days the controller will operate.



NOTE: If the last data entered stops blinking after 10 seconds, press  again to resume or  to move backward.

Press the  button to proceed to the next step SET ET  or to review the program.

10. SETTING THE SIMPLESMART™ OPTION (SET ET)

The ECO 1™ smart controller's main feature includes twenty preset programs for sprays and drip irrigation based on three years of historical evapotranspiration (ET) from various climate regions.

How DIG's ECO 1™ smart controller operates using Historical Evapotranspiration (ET):

After programming the watering schedule, watering start time and watering duration, the user can select one of the preset SimpleSmart™ evapotranspiration (ET) programs for spray or drip irrigation systems. See the color map in the centerfold of this manual to select the appropriate pre-set for your location and type of system or reference CHART A on page 22 and choose from the region description.

Selecting SP1 through SP20 sets the ECO 1™ controller to water a predetermined number of minutes per month. The amount to water is pre-programmed into the controller and is determined by which program (SP) is selected and by the month.

If you have already set a SimpleSmart™ ET preset (example: SP02) and then change the run time, your SimpleSmart™ program will be turned OFF. You must reactivate the SimpleSmart™ programming each time you adjust your run time (see section 10).

NOTE: If using one of the SimpleSmart™ presets we recommend evaluating the plants' health for the first month and making adjustments to the system as needed. If an adjustment or fine tuning of the SimpleSmart™ programming is required, this adjustment can be made for each month in the SEASONAL ADJUSTMENT (%) SETTING (see section 11).

For example:

The user entered watering run time will be adjusted monthly based upon the forecast ET pattern for the selected region.

By selecting SP02, the controller may adjust the programmed run time of 10 minutes in the month of January to 3 minutes, or less. This reduces the irrigation run time by 7 minutes, providing a water savings of nearly 70% for the month of January.

CHART A - SELECTING HISTORICAL ET PROGRAM

PROGRAM	REGIONS	IRRIGATION METHOD
SP01	Cool Mediterranean	Drip Systems
SP02	Cool Mediterranean	Sprinkler Systems
SP03	Humid Continental	Drip Systems
SP04	Humid Continental	Sprinkler Systems
SP05	Warm Mediterranean	Drip Systems
SP06	Warm Mediterranean	Sprinkler Systems
SP07	Humid Sub-Tropical	Drip Systems
SP08	Humid Sub-Tropical	Sprinkler Systems
SP09	Highlands	Drip Systems
SP10	Highlands	Sprinkler Systems
SP11	Dry Inland Valleys	Drip Systems
SP12	Dry Inland Valleys	Sprinkler Systems
SP13	Tropical Wet & Dry	Drip Systems
SP14	Tropical Wet & Dry	Sprinkler Systems
SP15	Tropical Wet	Drip Systems
SP16	Tropical Wet	Sprinkler Systems
SP17	Semi-Arid	Drip Systems
SP18	Semi-Arid	Sprinkler Systems
SP19	Arid	Drip Systems
SP20	Arid	Sprinkler Systems

To activate the SimpleSmart™ ET feature:

1. Press the  button until the  icon appears and OFF appears.



2. Press  and OFF (or the last SP program #) appears.
3. To select a desired SimpleSmart™ preset press  or  and select one of the twenty programs from the list using one that is similar to your climate region and irrigation method (see map in centerfold or reference Chart A).



4. To deactivate the preset program, press  and the program # appears blinking.
5. Press  until OFF appears.

Press the  button to proceed to the next step SET BUDGET  or to review the program.

11. SETTING SEASONAL ADJUSTMENT (MONTHLY BUDGET)

The amount of water required by plants varies throughout the year. The Seasonal Adjustment percentage feature can be utilized to alter the programmed watering run time on a monthly basis.

This program features two options:

- A.** It can be used as an adjustment to the programmed run time by altering the programmed watering duration on a monthly basis.
- B.** It can be used to modify the total run time setting of the SimpleSmart™ programming per month by percentage.

To set seasonal adjustment in %:

1. Press the  button until 100% and the current month # appears.



2. Press the  button and the 100% appears blinking.
3. To set the desired seasonal adjustment % (0-200%), press  or .

Example, if a 20 minute duration is programmed, and then the monthly budget is changed from 100% to 50%, the duration will now be 10 minutes for the selected month.



4. Repeat the steps to set the desired seasonal adjustment % for each month by pressing  and following the previous steps for each month.

Press the  button to proceed to the next step RAIN DELAY  or to review the program.

12. RAIN DELAY SETTING

The Rain Delay setting is used to temporarily suspend all irrigation for a defined number of days. For example, during rainy weather regularly scheduled programs can be turned off from 1-99 days. At the end of the designated period, regularly scheduled programming will resume automatically.

To set a temporary suspension of the program:

1. Press the  button until the  icon appears and OFF appear.



2. Press the  button and OFF starts blinking.
3. To set the desired temporary suspension of the program (1-99 days), press  or .



4. The temporary suspension of the program can be cancelled at any time by re-entering Rain Delay screen and changing the setting to OFF. (Press  or  until OFF appears.)

Note: OFF appears in between numeric value of 99 and 1.


Press the  button to proceed to the next step EVENTS OFF  or to review the program.

13. EVENTS OFF SETTING

This mode allows the user to program the timer to not water during specific months of the year, or to program the timer to not water on specific days of the week during a specific month.


To turn off specific days of a month:

1. Push the  button until the desired month is selected and DAYS appear above the  symbol. The number of the month is on the left (1 = January, 12 = December).
2. Push the  button until the desired day of the week flashes.
3. Push the  to remove the underline under the day of the week.
During the selected month, watering will not occur on the days of the week without the underline.




To turn off an entire month:

1. Push the  button until the  icon appears.
2. Push the  button through each day of the week until the MO appears above the  icon.



3. When On is flashing for the desired month to turn off, push the  button and the word OFF will appear. The selected month is now turned off, and no watering will occur during the entire month.



The controller is now fully programmed.

Press the  button to review the program or to return to the home screen.



Here is an example of the home screen showing all the icons of the programs that are currently set and active, which is the SimpleSmart™ (SET ET), monthly budget, rain delay and events off programs.

14. MANUAL WATERING


The manual mode allows the user to test the system and water for a specified run time. The controller will automatically close the actuator or valve at the end of the defined irrigation period. The originally programmed irrigation schedule continues to function at the times assigned. The sensor condition is disregarded in this mode.

To start a manual run,

1. Press the  button, and the  icon and  icon appears. ON appears momentarily and then the last watering duration is displayed with  . The controller will open the valve and in 10 seconds a count down of the remaining irrigation duration appears, showing when the controller will close the valve.



2. Press the  button to end manual run.
3. After 10 seconds the display will revert to the current time screen.



15. CONNECTING A RAIN SENSOR


Most “normally closed” rain or soil moisture sensors can be connected to the ECO 1™ controller. The function of the sensor is to prevent automatic watering by the set program due to excessive rainfall or when the soil is too moist.

To connect the sensor to the controller, please follow these steps:

1. Cut the yellow wire loop that exits the controller in the middle of the loop.
2. Strip approximately 1/2 in. of insulation from the end of each wire.
3. Splice one yellow wire to each of the wires coming from the sensor. Use waterproof wire connectors to secure the connections.
4. Follow the sensor manufacturer's instructions for calibrating the sensor.
5. When the sensor is active and preventing automatic operation, a  icon will appear on the display.



Icon will only appear when sensor is active.




Recommended rain sensors are the Rain Bird RSD and Hunter Mini-Clik
Recommended soil moisture sensor is the Irrrometer WEM-B

16. MAINTENANCE, TROUBLESHOOTING AND REPAIRS

To restore the controller to the default settings (Budgeting and Rain Delay settings will remain):

1. Press the  button until the **START EVERY** is displayed and the  icon appears on the bottom left of the screen.
2. Press and hold down the  for three seconds.
3. The screen returns to the home screen (clock) and all the default settings are restored. The current time and date is retained.



PROBLEM: Water is flowing out under the anti-siphon cap.

CAUSE: Valve is not installed at least 6 in. above the highest outlet on the system

SOLUTION: Raise valve up so it is at least 6 in. above the highest outlet on the system

CAUSE: Anti-siphon float is obstructed or stuck

SOLUTION: Unscrew anti-siphon cap and check float assembly and clear out any debris or foreign material inside.

CAUSE: Valve is installed backwards.

SOLUTION: Reverse valve and make sure arrow on valve body is pointing away from water source.

PROBLEM: Valve/actuator is not opening automatically or manually

CAUSE: No water pressure

SOLUTION: Open main water supply valve

CAUSE: Faulty solenoid

SOLUTION: Replace solenoid

CAUSE: Flow control handle is turned down

SOLUTION: Open flow control handle on valve or actuator

PROBLEM: Valve/actuator functions in manual mode but not automatically

CAUSE: Controller is set to OFF mode

SOLUTION: Verify that controller does not show OFF in current time mode

CAUSE: AM/PM not set correctly in current time mode

SOLUTION: Check current time, change AM/PM if necessary

CAUSE: AM/PM not set correctly in start time mode

SOLUTION: Check start time(s), change AM/PM if necessary

CAUSE: Watering restriction or rain delay is preventing watering

SOLUTION: Remove watering restrictions or set rain delay to off

CAUSE: Yellow sensor wires have been cut

SOLUTION: Re-connect sensor wires together with waterproof connector

CAUSE: Sensor is installed and is in a state that prevents watering

SOLUTION: Check sensor and wire splices and verify sensor is normally closed

PROBLEM: The display is blank

CAUSE: No buttons have been pushed in the previous 15 minutes

SOLUTION: Push any button

PROBLEM: Valve/actuator fails to close

CAUSE: Valve/actuator is installed backwards

SOLUTION: Check flow arrow and verify arrows points away from water source

CAUSE: Debris is blocking solenoid port

SOLUTION: Shut off water supply, unscrew and remove solenoid, then open water supply and flush out solenoid port, re-install solenoid

PROBLEM: Rain sensor does not prevent watering

CAUSE: Rain sensor is normally open, malfunctioning, or not wired correctly

SOLUTION: Verify that sensor icon appears on display when pin is pushed down & check all wire splices

PROBLEM: Controller waters more than once per day

CAUSE: More than one start time has been programmed

SOLUTION: Change start time 2,3,4, and 5 to OFF

17. WARRANTY

DIG CORPORATION warrants these products to be free from defects in material and workmanship for a period of three years from date of purchase. This warranty does not cover damage resulting from accident, misuse, neglect, modification, improper installation or subjection to line pressure in excess of 80 lbs. per square inch for anti-siphon valves and for actuators. This warranty shall extend only to the original purchaser of the product for use by the purchaser.

The obligation of DIG CORPORATION under this warranty is limited to repairing or replacing at its factory this product which shall be returned to the factory within three years after the original purchase and which on examination is found to contain defects in material and workmanship. **DIG CORPORATION SHALL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES OF ANY KIND; THE SOLE OBLIGATION OF DIG BEING LIMITED TO REPAIR OR REPLACEMENT OF DEFECTIVE PRODUCTS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU.**

Unattended use for prolonged periods without inspection to verify proper operation is beyond the intended use of this product, and any damage resulting from such use shall not be the responsibility of DIG CORPORATION. There are no warranties, which extend beyond the description on the face hereof. In the case of purchase of the product for use other than, for irrigation purposes, DIG CORPORATION hereby disclaims any implied warranties including any warranties of merchantability and fitness for a particular purpose. In the case of the purchase of the product for personal, family or household purposes, DIG CORPORATION disclaims any such warranties to the extent permitted by law. To the extent that any such disclaimer or implied warranties shall be ineffectual, then any implied warranties shall be limited in duration to a period of three years from the date of the original purchase for use by the purchaser. Some states do not allow limitation on how long an implied warranty lasts, so the above limitation may not apply to you.

In order to obtain performance under this warranty, the unit must be returned to the factory, along with proof of purchase indicating original date of purchase, shipping prepaid, addressed as follows:

DIG CORPORATION, 1210 Activity Drive, Vista, CA 92081. Repaired or replaced units will be shipped prepaid to the name and address supplied with the unit returned under warranty. Allow four weeks for repairs and shipping time. Repair of damaged units not otherwise within warranty may be refused or done at a reasonable cost or charge at the option of DIG CORPORATION.

This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

18. TECHNICAL ASSISTANCE

Should you encounter any problem(s) with this product or if you do not understand its many features, please refer to this instruction manual first. If further assistance is required, DIG offers the following customer support:

TECHNICAL SERVICE USA

- DIG's Technical Service Team is available to answer questions in English and Spanish from 8:00 AM to 5:00 PM (PST) Monday-Friday (except holidays) at 800-344-2281.
- Questions in English and Spanish can be emailed to questions@digcorp.com or faxed to 760-727-0282.
- Specification documents and manuals are available for downloading in English and Spanish at www.digcorp.com.



1210 Activity Drive
Vista, CA 92081-8510, USA

www.digcorp.com
email: dig@digcorp.com

26-200 REVA 072314 DIGCORP
Printed in the USA

DIG is a Registered Service Mark of DIG Corp.

