

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

4000 Series Compact Utility Tractor - 4210, 4310, 4410

FILTER KIT

[LVA21194](#)

M806419, MIU804763, LVA11522, LVA10419, M131802

Each kit contains above filter, offering a complete solution for your maintenance needs to keep your tractor running at peak performance.

ENGINE

PRIMARY AIR FILTER

[M131802](#)

SECONDARY AIR FILTER

[M131803](#)

Check after every 500 hours and replace as needed.

ENGINE

FUEL FILTER

[MIU804763](#)

Replace after every 500 hours.

ENGINE

OIL FILTER

[M806419](#)

Replace initially after 50 hours and after every 200 hours.

(Click here for [capacity](#))

TRANSMISSION

OIL FILTER

[AM102723](#) – (CLUTCH HOUSING)

HYDRAULIC

OIL FILTER

[LVA10419](#) – (HST)

[LVA11522](#) – (TRANSMISSION LINES)

Replace initially after 50 hours and after every 400 hours.

(Click here for [capacity](#))



JOHN DEERE

Genuine Parts and Service

https://www.deere.com/en_US/parts/parts_by_industry/ag/fmi/filter_maintenance_information.page

CAPACITIES

4000 Series Compact Utility Tractor - 4210, 4310, 4410

CAPACITIES (Approximate):

Fuel Tank:

..... 37.9 L (10 gal)

Cooling System:

Cool-Gard™ II

4210..... 5.3 L (1.4 gal)

4310, 4410..... 5.7 L (1.51 gal)

Engine Crankcase W/ Filter:

Plus-50™ II

4210..... 3.8 L (1 gal)

4310, 4410..... 4.3 L (1.14 gal)

Transmission and Hydraulic System:

Hy-Gard™

4210, 4310, 4410 (Gear Models)..... 24 L (6.3 gal)

4210, 4310, 4410 (Hydrostatic Models)..... 26 L (6.9 gal)

FRONT AXLE:

Low Viscosity Hy-Gard™

4210, 4310, 4410..... 4.5 L (1.19 gal)

[Return to Filter Overview](#)



JOHN DEERE
Genuine Parts and Service