


Novastar Cabinet Without Door and Rear Panel

Power Utilities



Aluminum frame cabinets with attractive design, ideally suited for general electronics, test and measurement, audio/video and broadcasting applications.

CERTIFICATIONS



FEATURES

Static load-carrying capacity up to 400 kg (see specification table)

Type of protection IP 20

Cabinet width only 553 mm

Flush cladding parts

All uprights (front and rear) with 19" cut-outs

Colors: RAL 7021 or color combination RAL 7021/ RAL 7035

Bolted, die-cast frame with Al extrusions

Without door and rear panel

SPECIFICATIONS

Table 1/2

Catalog Number	Frame Material	Frame Color	Frame Color Code	Cladding Material	Cladding Color	Cladding Color Code
----------------	----------------	-------------	------------------	-------------------	----------------	---------------------

15230-001	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
16230-001	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
15230-002	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
15230-003	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
16230-002	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
16230-003	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
15230-004	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
15230-005	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
16230-004	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
16230-005	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
15230-006	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
15230-007	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
15230-008	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
16230-006	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
16230-007	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
16230-008	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
15230-009	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
15230-010	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
16230-009	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035

16230-010	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
15230-011	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
15230-012	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
16230-011	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
16230-012	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
15230-013	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
15230-014	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
16230-013	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
16230-014	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
15230-015	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
15230-016	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
16230-015	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
16230-016	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
15230-017	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
15230-018	Aluminum	Black Grey	RAL 7021	Steel	Black Grey	RAL 7021
16230-017	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035
16230-018	Aluminum	Black Grey	RAL 7021	Steel	Light Grey	RAL 7035

Table 2/2

Catalog Number	Rack Height	Height	Width	Depth	Static Load	Complies With
----------------	-------------	--------	-------	-------	-------------	---------------

15230-001	9 U	456 mm	553 mm	600 mm	200 kgf	IEC 60297-3-100
16230-001	9 U	456 mm	553 mm	600 mm	200 kgf	IEC 60297-3-100
15230-002	12 U	589 mm	553 mm	500 mm	200 kgf	IEC 60297-3-100
15230-003	12 U	589 mm	553 mm	600 mm	200 kgf	IEC 60297-3-100
16230-002	12 U	589 mm	553 mm	500 mm	200 kgf	IEC 60297-3-100
16230-003	12 U	589 mm	553 mm	600 mm	200 kgf	IEC 60297-3-100
15230-004	16 U	767 mm	553 mm	500 mm	200 kgf	IEC 60297-3-100
15230-005	16 U	767 mm	553 mm	600 mm	200 kgf	IEC 60297-3-100
16230-004	16 U	767 mm	553 mm	500 mm	200 kgf	IEC 60297-3-100
16230-005	16 U	767 mm	553 mm	600 mm	200 kgf	IEC 60297-3-100
15230-006	20 U	945 mm	553 mm	500 mm	200 kgf	IEC 60297-3-100
15230-007	20 U	945 mm	553 mm	600 mm	200 kgf	IEC 60297-3-100
15230-008	20 U	945 mm	553 mm	800 mm	200 kgf	IEC 60297-3-100
16230-006	20 U	945 mm	553 mm	500 mm	200 kgf	IEC 60297-3-100
16230-007	20 U	945 mm	553 mm	600 mm	200 kgf	IEC 60297-3-100
16230-008	20 U	945 mm	553 mm	800 mm	200 kgf	IEC 60297-3-100
15230-009	25 U	1167 mm	553 mm	600 mm	200 kgf	IEC 60297-3-100
15230-010	25 U	1167 mm	553 mm	800 mm	200 kgf	IEC 60297-3-100
16230-009	25 U	1167 mm	553 mm	600 mm	200 kgf	IEC 60297-3-100

16230-010	25 U	1167 mm	553 mm	800 mm	200 kgf	IEC 60297-3-100
15230-011	34 U	1567 mm	553 mm	600 mm	400 kgf	IEC 60297-3-100
15230-012	34 U	1567 mm	553 mm	800 mm	400 kgf	IEC 60297-3-100
16230-011	34 U	1567 mm	553 mm	600 mm	400 kgf	IEC 60297-3-100
16230-012	34 U	1567 mm	553 mm	800 mm	400 kgf	IEC 60297-3-100
15230-013	38 U	1745 mm	553 mm	600 mm	400 kgf	IEC 60297-3-100
15230-014	38 U	1745 mm	553 mm	800 mm	400 kgf	IEC 60297-3-100
16230-013	38 U	1745 mm	553 mm	600 mm	400 kgf	IEC 60297-3-100
16230-014	38 U	1745 mm	553 mm	800 mm	400 kgf	IEC 60297-3-100
15230-015	43 U	1967 mm	553 mm	600 mm	400 kgf	IEC 60297-3-100
15230-016	43 U	1967 mm	553 mm	800 mm	400 kgf	IEC 60297-3-100
16230-015	43 U	1967 mm	553 mm	600 mm	400 kgf	IEC 60297-3-100
16230-016	43 U	1967 mm	553 mm	800 mm	400 kgf	IEC 60297-3-100
15230-017	47 U	2145 mm	553 mm	600 mm	400 kgf	IEC 60297-3-100
15230-018	47 U	2145 mm	553 mm	800 mm	400 kgf	IEC 60297-3-100
16230-017	47 U	2145 mm	553 mm	600 mm	400 kgf	IEC 60297-3-100
16230-018	47 U	2145 mm	553 mm	800 mm	400 kgf	IEC 60297-3-100

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause

product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE