

ThinkSystem SR860 V2 with Intel Optane Persistent Memory Sets 22 World Records with New STAC-M3 Benchmark Result

Performance Benchmark Result

The Lenovo ThinkSystem SR860 V2 server, configured with new third-generation Intel Xeon Scalable processors (formerly codenamed “Cooper Lake-6”), new Intel Optane Persistent Memory 200 Series, and the Kx Systems kdb+ 4.0 database has set new performance world records with the Antuco and Kanaga suites of the STAC-M3 benchmark.



These new benchmark results, published in a new STAC Report ([SUT ID KDB201109](#)) on December 15, 2020, demonstrate that the SR860 V2 continues Lenovo’s leadership with world record breaking performance for the financial services industry.

The STAC-M3 Benchmark suite is the industry standard for testing solutions that enable high-speed analytics on time series data, such as tick-by-tick market data, also known as tick database stacks. STAC-M3 benchmarks are grouped into suites. The base suite, code-named “Antuco”, contains a range of test cases with varying levels of CPU and storage-I/O intensity. The optional “Kanaga” suite consists of two test sequences that extend Antuco benchmarks across larger quantities of data in order to measure the volume-scalability of a database stack. Lenovo used two “Kanaga” years (2011, 2012) of data instead of current norm of five years (2011-2015) to fit more data onto the higher performance Intel Optane persistent memory.

The SR860 V2 with Intel Optane persistent memory achieved leadership performance in 14 of 17 benchmark categories in the Antuco suite:

- STAC-M3.β1.100T.VWAB-12D-NO.TIME
- STAC-M3.β1.10T.MKTSNAP.TIME
- STAC-M3.β1.10T.STATS-AGG.TIME
- STAC-M3.β1.10T.THEOPL.TIME
- STAC-M3.β1.10T.VOLCURV.TIME
- STAC-M3.β1.1T.MOHIBID.TIME

- STAC-M3.β1.1T.NBBO.TIME
- STAC-M3.β1.1T.QTRHIBID.TIME
- STAC-M3.β1.1T.VWAB-D.TIME
- STAC-M3.β1.1T.WKHIBID.TIME
- STAC-M3.β1.1T.WRITE.TIME
- STAC-M3.β1.1T.YRHIBID-2.TIME
- STAC-M3.β1.1T.YRHIBID.TIME
- STAC-M3.β1.50T.STATS-UI.TIME

The SR860 V2 with persistent memory also achieved leadership performance in 8 of 9 benchmark categories in the Kanaga suite when using a two-year data set size. The results from this stack under test (SUT) can be compared directly to results from the Lenovo ThinkSystem SR950 which used the first-generation Intel Optane Persistent Memory 100 Series (see [SUT ID KDB190322b](#)).

- STAC-M3.β1.100T.TRUNC.YR1VWAB-12D-HO.TIME
- STAC-M3.β1.100T.TRUNC.YR2VWAB-12D-HO.TIME
- STAC-M3.β1.10T.TRUNC.YR1-MKTSNAP.TIME
- STAC-M3.β1.10T.TRUNC.YR2-MKTSNAP.TIME
- STAC-M3.β1.1T.TRUNC.YR1VWAB-12D-HO.TIME
- STAC-M3.β1.1T.TRUNC.YR2VWAB-12D-HO.TIME
- STAC-M3.β1.50T.TRUNC.YR1VWAB-12D-HO.TIME
- STAC-M3.β1.50T.TRUNC.YR2VWAB-12D-HO.TIME

The ThinkSystem SR860 V2 server was configured as follows for the benchmark audit:

- 4x Intel Xeon Platinum 8380HL processors (28 cores, 2.9GHz, 38.5MB last level cache)
- 3TB memory (24x 128GB DDR4-3200 @ 2666MHz)
- 12TB (24x 512GB) Intel Optane Persistent Memory 200 Series (PMem)
- 6x 8TB Intel DC P4510 NVMe SSDs (3D NAND)
- SLES 15 SP2 with ext4 and xfs V5
- Kx Systems kdb+ 4.0

About the ThinkSystem SR860 V2

The Lenovo ThinkSystem SR860 V2 server provides the speed and reliability you require today, with the scalability and workload versatility to you'll need to manage the explosive growth of data; its design offers considerable adaptability in order to match system configurations to projected workloads.

The ThinkSystem SR860 V2 is purpose-built to deliver affordable scalability in an industry-standard x86 platform, ideal for mission critical workloads such as SAP HANA in-memory computing, transactional databases, analytics, big data, and enterprise resource planning tasks.

Up to four 250W third-generation Intel® Xeon® Scalable CPUs configured with a mesh topology pair with up to four enterprise-class GPUs position the SR860 V2 to tackle compute-intensive applications, leveraging thousands of GPU processor cores and parallel architecture in combination with additional storage and networking that's both high-performing and flexible.

Key features:

- Up to four 250W 3rd Generation Intel Xeon Scalable CPUs configured with a mesh topology combines with up to 48 2.5" HDD or SSDs, of which 24 can be NVMe SSDs to speed database response times, reducing latency and eliminating storage as the throughput bottleneck in I/O-intensive applications such as transactional processing, HPC, and Big data applications.
- Supports two or four processors, allowing you to start with two processors and then upgrade to four when you need it.
- Capability to handle four double-width GPUs or eight single-width GPUs to accelerate AI inference and deep learning proficiencies.
- Support for up to 12TB of DDR4 memory with DIMMs operating at up to 3200 MHz at 2DPC, and Intel Optane™ Persistent Memory 200 Series accelerates performance for in-memory databases and applications, reducing downtime and increasing application availability.
- High I/O bandwidth coupled with a generous number of PCIe expansion slots provides the additional connectivity scalability as your business and workload demands increase.
- Full Lenovo XClarity and ThinkShield system support for seamless infrastructure management and improved data security.

About STAC

Securities Analysis Technology Center (STAC) is a company that coordinates a community called the STAC Benchmark Council.

The STAC Benchmark Council consists of over 350 financial institutions and more than 50 vendor organizations whose purpose is to conduct substantive discussions on important technical challenges and solutions in financial services, and to develop technology benchmark standards that are useful to financial organizations.

User firms include the largest global banks, brokerage houses, exchanges, asset managers, hedge funds, proprietary trading shops, and other market participants. Vendor firms include innovative providers of hardware, software, and cloud services.

STAC-M3 benchmarks are governed by user firms in the STAC Benchmark Council. The STAC-M3 benchmark report for the SR860 V2 is publicly available.

Learn more

To learn more about solutions for the financial services industry, please contact your Lenovo Sales Representative.

To find out more about STAC, visit the [STAC Research web site](#).

To learn more about the Lenovo ThinkSystem SR860 V2 server, visit the SR860 V2 product web page: <https://www.lenovo.com/us/en/data-center/servers/mission-critical/ThinkSystem-SR860-V2-Server/p/77XX7HS86V2>

Related product families

Product families related to this document are the following:

- [ThinkSystem SR860 V2 Server](#)
- [4-Socket Rack Servers](#)
- [STAC-M3 Benchmark Results](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2022. All rights reserved.

This document, LP1472, was created or updated on April 20, 2021.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP1472>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP1472>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ThinkShield®

ThinkSystem®

XClarity®

The following terms are trademarks of other companies:

Intel®, Intel Optane™, and Xeon® are trademarks of Intel Corporation or its subsidiaries.

Other company, product, or service names may be trademarks or service marks of others.