

20G1ANC260JA0NNNNN

Allen-Bradley PowerFlex 755 VSD 400V IP20 ND 260A 132kW or
HD 205A 110kW Frame 6



LARGE DRIVES



Allen-Bradley



Component type	Frequency converter =< 1 kV
Range	PowerFlex 755
Model	N/A
Product status	Existing

Allen-Bradley PowerFlex 755 AC Drives are a simple and high-performance motor control application, providing a variety of solutions including pumps, fans, and conveyors. Featuring a standard built-in Ethernet/IP port, making it ideal for applications requiring flexibility, connectivity, control, advanced communications, hardware. and safety options.

ELECTRICAL

Number of phases input	3
Nominal input voltage	400 V
Nominal output power AC	132 kW
Nominal output current I2N	260 A
kW rating, normal duty	132 kW
kW rating, heavy duty	110 kW
Dynamic braking transistor	Yes
Control characteristic	PID
EMC-version	Yes

COMMUNICATION

Integrated motion function	No
Suitable for safety functions	Yes

CONSTRUCTION

Contains keypad	No
Frame size	6
IP rating	IP20
Degree of protection (NEMA)	Other

DIMENSIONS

Height	665.5 mm
Width	308 mm
Depth	346.4 mm
Weight	48 kg

ENVIRONMENT

Operating temperature	-20...60 °C
Storage temperature	-40...70 °C