

WIFI OUTDOOR HUMAN DETECTION IP CAMERA C11



MAIN CHARACTERS:

- 5.0 megapixel FHD IP camera, maximum resolution 2560*1920;
- Support up to 128G TF card storage;
- Two way audio(built-in MIC and speakers);
- Waterproof level IP66;
- Full color and intelligent night vision, IR distance 10m~30m;
- Humanoid detection alarm and humanoid tracking;
- Mini size only 1.5 inch, elegant outline and easy installation;
- Support WIFI, support AP mode

SPECIFICATION

Model		C11
Video	CPU	T31X
	Sensor	1/2.7" SC5238
	Video resolution	Main stream: 2560x1920、2560x1440@15fps Sub stream: Q720P (800x600、640x480)、QQ720 (800x448、640x352@15fps
	Video compression	H.265、H264
	Lens	3.6mm
	MIN. ILLUMINATION	0.1Lux color, 0Lux night
	View angle	83°
	Night vision	8pcs array infrared & white light LEDs, irradiation distance 10m~30m;
Audio	Audio compression	G.711
	Audio code rate	8Kbps, 16bit
	Audio input/output	Built-in MIC and speakers, support two way audio
Alarm	Motion detecting alarm	Can set 4 independent detection region (1-100 sensitivity can be set)
	Humanoid detection	support humanoid detection alarm and humanoid tracking
	Alarm linkage	Alarm send pictures to the mailbox, Alarm upload pictures and videos to the FTP server, Alarm record pictures and videos to Micro SD card, Alarm mobile phone APP push
	Alarm recording	Support Micro SD card and PC client linkage alarm recording
Network	Wireless	IEEE 802.11 b/g/n
	Ethernet	RJ45 Ethernet
	Protocol	Support ONVIF 2.4 profile S (backward compatible) TCP/IP, HTTP, DHCP, DDNS, RTP,RTSP, PPPOE ,SMTP, NTP, UPNP
Storage	Micro SD card	Support up to 128G micro SD card
	Recording mode	Alarm record, timing record,
	Video playback	Support APP, IE browser, remote client play and download the video
PTZ	Rotation angle	Horizon: 0° ~ 320°, Vertical: 0° ~ 90°
	Horizontal speed	10° ~ 30°/S
	Vertical speed	8° ~ 25°/S

	Preset	Support 8 preset points
	Tracking function	Support humanoid tracking
General specification	Power	DC12V 1A
	Operating environment	Environment -10°C~+60°C, Humidity 10%~90%, non-condensing
	Shell material	All metal shell
	Waterproof level	IP66
	Product size	100mm×75mm×160mm(L×W×H)
	Product weight	0.6kg
	Package size	200mm×200mm×120mm(L×W×H)
	Package weight	0.9kg
	Reset button	Support