Invented for life





	PXY875DW4E \$38,800 80cm Extended FlexZone Hob with PerfectCook & PerfectFry
	Home Connect PerfectCook Perf
Performance	• 4 induction cooking zones • 17 stages of power setting



- 2 Extended FlexZone
- Direct Select Premium

Functions

- QuickStart
- ReStart

Features

- CruiseControl: Fresh air assured automatically thanks to the integrated Wi-Fi module, now the hob talks to the hood*
- PerfectCook: Precise temperature control prevents boiling over
- PerfectFry: For perfect browning of roasted foods
- Direct Select Premium: direct, simple selection
- Assist: 100+ recipes integrated to meet every needs#
- Extended FlexZone: Automatically extends to fit any cookware
- · Automatic setting transfer
- MoveMode with 3 power levels
- PowerBoost: Up to 50% more power for faster heating
- PanBoost for added quickness
- Energy Consumption display
- Count-down timer for each zone
- Kitchen timer
- Count-up timer for each zone

*only with compatible hoods #support by Home Connect app

Design

- SCHOTT CERAN® ceramic glass
- ComfortProfil: Beveled front and rear with side profiles
- Can be combined with all hobs in comfort design

Safety functions

- Digital 2-stage residual heat indicator for each zone
- Main switch
- Small cookware detection
- Anti overflow protection
- Wipe protection · Childproof lock
- Technical

information

· Cooking zone output

· Safety switch-off

	Zone	Output	Output without	Dimensions
		(kW)	booster (kW)	<u>(mm)</u>
	Left FlexZone	3.7	3.3	400 x 230 extendable to 300
	Front left	3.7	2.2	200 x 230
	Rear left	3.7	2.2	200 x 230
	Right FlexZone	3.7	3.3	400 x 230 extendable to 300
	Front right	3.7	2.2	200 x 230
	Rear right	3.7	2.2	200 x 230

- Total connected load: 7.4kW
 - (220V/40A single phase or 380V/20A three-phase connection)
- · Dimensions:
- Appliance (H x W x D): 51* x 816 x 527 mm
- Cut out (W x D): 750-780 x 490-500 mm

Induction hob over an oven

750-780+

(F)


-500+2

(D)

min. 45

min. 20

≥ 16 **(C)**



Optional accessories

- Wireless PerfectRoast (HEZ32WA00)
- PerfectCook wireless sensor (HEZ39050)
- Griddle Plate (HEZ390522)
- Teppan Yaki (HEZ9TY010)
- Connection strip (HEZ394301)

Country of origin

• Spain

Measurements in mm

*excl. glass thickness

51 **(B)**

≥ 40 (A)

A: Minimum distance from the hob cut-out to the wall.
 B: Recessed depth.
 C: The clearance between the surface of the worktop and the top of the front of the over must be 80 mm. See space requirements for the oven.

Induction hob over a drawe min. 65

Drawer