

8500 DC BATTERY BACKUP CAPABLE WALL MOUNT GARAGE DOOR OPENER

Wall Mount Design: The simple beauty of an open space.



KEY FEATURES

SPACE-SAVING

Design Maximizes
Versatility

LIFTING POWER

Powers 650 lbs. Doors

SMART

MyQ TECHNOLOGY ENABLES YOU TO SECURELY MONITOR AND CONTROL YOUR GARAGE DOOR OPENER AND HOUSELIGHTS WITH YOUR SMARTPHONE, TABLET OR COMPUTER. REQUIRES PURCHASE OF INTERNET GATEWAY (828LM)*

ALERTS CAN BE RECEIVED AS EMAIL OR POP-UP (PUSH) NOTIFICATIONS ON YOUR MOBILE DEVICE SO THAT YOU ALWAYS KNOW THE STATUS OF YOUR GARAGE DOOR AND HOUSELIGHTS.

RELIABLE

ULTRA-QUIET ELIMINATES SOUND AND VIBRATION THROUGH THE CEILING - PERFECT IF YOU HAVE A HOME WITH A ROOM ABOVE OR NEXT TO THE GARAGE.

BATTERY BACKUP POWERS UP EVEN WHEN THE POWER'S OUT. (REQUIRES PURCHASE OF 475LM BATTERY BACKUP).

WALL MOUNT DESIGN FREES THE GARAGE CEILING OF HANGING OPERATORS AND RAILS AND OPENS UP THE SPACE FOR ADDITIONAL STORAGE.

REMOTE LIGHT DELIVERS 200 WATTS OF LIGHT WITH ADJUSTABLE LIGHT TIME DELAY.

LIFETIME MOTOR AND 5-YEAR PARTS WARRANTY. 1-YEAR BACKUP BATTERY WARRANTY (SOLD SEPARATELY). DELAY.

SECURE

TIMER-TO-CLOSE AUTOMATICALLY CLOSES THE DOOR AFTER A PRESET AMOUNT OF TIME.

SECURITY+ 2.0® SENDS A NEW CODE WITH EVERY REMOTE CLICK.

MOTION DETECTOR AUTOMATICALLY TURNS ON THE LIGHT.

THE PROTECTOR SYSTEM® AUTO-REVERSES THE DOOR IF THERE'S AN OBSTRUCTION.

POWER LOCK DEADBOLT (041A6102) ENSURES THE DOOR CANNOT BE FORCED OPEN.

*Linking your MyQ account to a partner may require an additional accessory purchase or subscription fee.

INCLUDED ACCESSORIES:

3-BUTTON REMOTE CONTROL

Operates up to 3 openers
or MyQ Light Accessories.



893MAX

MYQ® CONTROL PANEL

Allows any garage door opener
manufactured since 1998 to be controlled
by your smartphone, tablet or computer
(when paired with the Internet Gateway)
– provides the upgrade needed to utilize
Security+ 2.0 and MyQ Technology.



888LM

REMOTE LIGHT

Light your space the way you want
to by placing this anywhere in the
garage. Uses (2) 100 watt bulbs
(not included).



380LM

POWERFUL ADD-ONS:

INTERNET GATEWAY

Connects the opener to the Internet,
enabling smartphone control..



828LM

REMOTE LIGHT CONTROL

Enables home lighting control through
the garage remote or a smartphone.



825LM

GARAGE DOOR AND GATE MONITOR

Monitors and closes up to 4 garage
doors from any room in the house..



829LM

BATTERY BACKUP

Powers up even when power is out so
you can get in your garage..



475LM

PRODUCT GUIDE 8500

DC BATTERY BACKUP CAPABLE WALL
MOUNT GARAGE DOOR OPENER

LiftMaster®

MASTERFUL ENGINEERING.

MOTOR



- Heavy-Duty 24V DC
- Automatic Thermal Protection
- Permanent Lubrication

POWER



- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL® Listed
- 6' Power Cord (3-Prong)

MECHANICS



- Steel Chassis and Plastic Cover
- Internal Chain and Sprocket Drive Mechanism (63:1 Gear Reduction)
- Auto-Force Adjustment for Changing Weather and Environmental Conditions
- Electronic Limits for Easy Setup

STANDARD SPECS.

SECURITY

SECURITY+ 2.0®

RADIO CONTROLS

Operating Range: ~200'

Operating Temperature: -40°F to 150°F

3-Button Remote Control (893MAX)

- Remote Control: 310, 315 and 390 MHz Tri-Band*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding

*Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

ENCRYPTED CONTROLS

MyQ® Control Panel® (888LM)

- MyQand Security+ 2.0 Radio
- Timer-to-Close
- Motion Detecting: Hands free opener lights on
- Light Control: Turns opener lights on/off
- Lock Mode: Locks out remote controls
- Program remote controls, keypads and MyQ Accessories
- *Because the radios reside in the control panel, alternate wired control panels should not be used with this operator.

SMART

MyQ® RADIO



- Provides 2-way communication from garage door opener and MyQ accessories*.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.**

*MyQ radio disabled in battery backup mode or when using Alternate Power System (580LM)

**Requires Internet Gateway Accessory Model (828LM)

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER***)

***May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING

REMOTE LIGHT (380LM)



- Remote light control fixture can be located anywhere in garage
- Number of bulbs: 2
- Maximum Wattage: 100 x 2
- Adjustable Time, Solid-State Delay (1.5-4.5 minutes)

SHIPPING.

SHIPPING WEIGHT (in lbs.)



CARTON

CARTONS (1)

CARTON 1: 24" x 10" x 12"

- Garage Door Opener Head (8500)
- MyQ Control Panel (888LM)
- 3-Button Remote Control (893MAX)
- The Protector System® Safety Reversing Sensors
- Power Door Lock (041A6102)
- Cable Tension Monitor
- Remote Light (380LM)

††Note: to reduce the risk of injury to persons, only use Alert-2-Close/Unattended Close Operation features when installed with a sectional door.

© 2018 LiftMaster All Rights Reserved
300 Windsor Drive, Oak Brook, IL 60523
LiftMaster.com

Wi-Fi® is a registered trademark of Wi-Fi Alliance
UL® and the UL logo are trademarks of UL LLC © 2017 All Rights Reserved.
LMGDCA8500 4/18

SAFETY AND SECURITY.

- The Protector System Safety Reversing Sensors
- Battery Backup Capable compatible model 475LM (optional accessory)
- Alert-2-Close/Unattended Close Operation††
- Motion Detection Feature on Control Panel
- Hands-Free Work Lights On
- Emergency/Quick Release
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 MyQ Devices



DC BATTERY BACKUP CABABLE WALL MOUNT GARAGE DOOR OPENER

8500



MAX. DOOR WEIGHT 650 lbs.*

16.25"

DIMENSIONS

Max. Door Size: 14 ft. High by 18 ft. Wide. Max 180 Sq Ft.
Headroom Clearance Required: 3 in. from Center of Torsion Bar

7.6"

Per second for door to move upward

SPEED

7.6"

Per second for door to move downward

LiftMaster®