

Function Description

- Easy to install and use
- Up to 48 programs per day
- Humidity: 0-95%
- Can control 1 or 2 devices at the same time
- With ON/OFF Timing manual switch
- Min. Setting: 15 minutes
- Max. Setting: 24 hours
- Operating environment: for outdoor use
- Operating Temperature: -40°F to 130°F (-40°C to 54.5°C)
- Storage Temperature: -4 °F to 140°F (-20°C to 60°C)



Input & Output
Appearance



Ratings & Approval

Input Voltage : 120VAC, 208/240VAC, 277VAC (Select by DIP switch)
Frequency : 60Hz
Resistive:120-240VAC,40A/277VAC,30A/14VDC,30A
Tungsten:120VAC,8.3A/208-277VAC,5.4A
Other Ratings: 1-2 HP



Packing



Product Measurement (inch): 7.32×3.19×9.09
Product Weight (lb): 1.60
Unit Package Measurements (inch):7.32×3.19×9.09
Unit Package Weight (lb): 1.79
Master Carton Measurements (inch): 16.54×15.87×10.16
Master Carton Weight (lbs): 19.47
Master Carton Quantity: 10 PCS
Master Carton Cube (cu.ft): 1.54

BN-LINK, INC.
11011 8th Street, Newark, California 94594
Telephone: (925) 895-8888 - Fax: (925) 895-8889
E-mail: sales@bnlink.com
Website: www.bnlink.com
Tel: 800-878-7227
©2008 BN-LINK, INC. All rights reserved.