

# ROLINE USB 2.0 Cable, C-C, M/M, 60W, silicone, orange, 1 m

|                    |               |
|--------------------|---------------|
| Product No.        | 11.02.9124    |
| Manufacturer       | ROLINE        |
| Manufacturer No.   | 11.02.9124    |
| EAN (single piece) | 7630049634879 |



**Very flexible, high-quality USB 2.0 charging cable with silicone sheath for smartphones, tablets and notebooks with reversible USB Type-C plug on both sides.**

- High quality USB 2.0 cable with improved shielding
- With the reversible Type C connectors at both ends
- Gold-plated contacts for low wear at high plugging cycles
- Suitable for data transfer rates of up to 480 Mbit/s
- Very flexible due to silicone cable sheath
- Supports charging up to 20V / 3A (60W)

| Technical specifications |                                                   |
|--------------------------|---------------------------------------------------|
| Manufacturer             | ROLINE                                            |
| Product group            | Cable                                             |
| Product type             | USB 2.0 Cable                                     |
| Colour                   | orange                                            |
| Length                   | 1 m                                               |
| Scope of delivery        | USB 2.0 Charging Cable                            |
| Transfer quality         | USB 2.0 Hi-Speed 480 Mbit/s                       |
| Connection ports         | USB Type C (USB-C) Male / USB Type C (USB-C) Male |

|                                    |                    |
|------------------------------------|--------------------|
| Side 1 Connector Type              | USB Type C (USB-C) |
| Side 1 Connector Gender            | Male               |
| Side 2 Connector Type              | USB Type C (USB-C) |
| Side 2 Connector Gender            | Male               |
| Colour (Cable)                     | orange             |
| Maximum data transfer rate         | 480 Mbit/s         |
| Area of application                | External           |
| Power (max.)                       | 60 W               |
| Cable shielding                    | Screened           |
| Operating temperature min.         | 0 °C               |
| Operating temperature max.         | 45 °C              |
| Weight                             | 35.2 g             |
| Height of packaging (single piece) | 20 mm              |
| Width of packaging (single piece)  | 80 mm              |
| Depth of packaging (single piece)  | 80 mm              |
| Package weight (single piece)      | 0.04 kg            |