

Application

A perfectly shaped sphere is one of the most important elements of design. As a fundamental geometric shape, the form is pure and timeless. These captivating pendant luminaires complement any design aesthetic, making them well suited for a multitude of space types. Also available with an impact resistant acrylic diffuser for special applications, add P as suffix.

Materials

Hand-blown opal glass
Aluminum structure
White or black connecting cable

NRTL listed to North American Standards, for interior use only

Weight: 2.6lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	12.0W
System wattage	14.7W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 90
Luminaire lumens	1287 lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

White (.1)	Stainless steel (.2)
Chrome (.3)	Brass (.4)

Type:

BEGA Product:

Project:

Modified:

Available options

FSC	Fusing
LPC	Low profile canopy



Pendant · Opal glass			
	LED	A	B
B56588	12.0W	9 7/8	79

