


Perfect Doorphone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone R28A enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.

At a Glance

- Aluminum panel with flush buttons;
- Linux operation system;
- Wide-angle camera: 110° (H), 58° (V);
- Two-way audio communication over IP networks with Echo Cancellation feature;
- Flush-mounted & surface-mounted;
- Complies with SIP & ONVIF;

**Physical & Power**

- Front panel: Aluminum
- Display: 4.3 Inch, color TFT LCD
- Camera: 2M pixels, automatic lighting
- Numeric keypad with extra buttons
- Light sensor: Support
- Motion sensor: Support
- Wiegand port: Support
- RS485 port: Support
- RF card reader: 13.56MHz & 125kHz, NFC
- Relays out: 3
- Inputs: 3
- Induction Loop Amplifier: Support
- Microphone: 1
- Speaker: 1
- Power out: 12V/400mA (Max.)
- Tamper Alarm: Support
- Ethernet port: RJ45, 10/100Mbps adaptive
- IP Rating: IP65
- Installation: Flush-mounted & Wall-mounted
- Size: 280x130x31.4mm
- Working Humidity: 10~90%
- Working Temperature: -40°C ~ +55°C
- Storage Temperature: -40°C ~ +70°C

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711μ
- Wideband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/2.8", CMOS
- Pixels: CIF, QCIF, VGA, 4CIF, 720p, 1080p
- Wide Dynamic Range (WDR)
- Video codec: H.264
- Video resolution: up to 1920x1080
- Max. image transfer rate: 1080p – 30fps
- Viewing angle: 110°(H) / 58°(V)
- High intensity IR LEDs for picture lighting during dark hours with internal light sensor
- Compatible to 3rd-Party-Video components,

Door Entry Feature

- Relays controlled individually by DTMF tones
- Camera permanently operational
- Auto-night mode with LED illumination
- White balance: auto
- Minimum illumination: 0.1LUX

Networking & Protocol

- Protocols support: IPv4, HTTP, HTTPS, FTP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)

Application Scenario

- Office door phone with on-site or hosted IP-PBX
- Remote site entry over Internet
- Apartment/flat intercom with door access control