



This chart summarizes some key technical differences between our Ezlo Plus and Ezlo Secure controllers

	 <i>Ezlo Plus (E450)</i>	 <i>Ezlo Secure (E550)</i>
Processor	Quad-Core Cortex-A7 ARM CPU	1 GHzQuad-Core Cortex-A7 ARM CPU
Flash Memory	EMMC 4GB	EMMC 16GB
RAM Memory	DDR3 512MB	DDR3 512MB
Z-Wave	Z-Wave Plus 700 series	Z-wave Plus 700 series

ZigBee	Zigbee 3.0, (backwards compatible with HA 1.2 & LL)	Zigbee 3.0, (backwards compatible with HA 1.2 & LL)
Bluetooth	(not avail)	(not avail)
Wi-Fi	Wi-Fi: 802.11 a/b/g/n/ac; 2.4 and 5GHz	Wi-Fi 802.11 a/b/g/n/ac, 2.4-5GHz
VeraLink (345 or 433MHz)	(not avail)	Built-in VeraLink
Cellular Backup (for optional Ezlo Protect)	Optional, External	Built-in (embedded) 4G Cellular Backup
Backup Battery	Optional, External	Li-ion battery 5000mAh

Expansion	1 USB Port 2.0, USB host	1 USB Port 2.0, USB host
WAN	10/100 Ethernet	1 WAN Port 10/100 Ethernet
Siren Alarm	(not avail)	Built-in Siren Alarm
Two-Way Audio	(not avail)	Built-in Microphone and Speaker for 2-Way Sound
Power Supply	Input: AC 100-240VAC,50-60Hz Output: DC 5V/2A	Input: AC 100-240VAC, 50-60Hz Output: DC 5V/3A