

5.0" PCAP Touch Screen LCD GUI Development Kit

Congratulations on the purchase of your μ EZ[®] GUI development kit!
Our goal is to ensure you have a pleasant experience familiarizing yourself with the functions and capabilities of our products.

To Begin Development with your μ EZ GUI:

1. Power on the device by connecting the 5V power adapter to one end of the USB cable and the other end to the μ EZ GUI P2. **Note:** Do not connect the μ EZ GUI to a computer USB port. Standard USB 2.0/3.0 ports will not provide sufficient power to the device.
2. Visit TeamFDI.com/StartHere to download the UEZGUI-4357-50WVN Start Here Guide. This guide will provide step-by-step instructions and supporting files for designing your first graphical user interface.



μ EZ
GUI

FDI Future Designs, Inc.

UEZGUI-4357-50WVN Kit Contents

- 5.0" PCAP Touch Screen LCD GUI Production Module
(Part number: UEZGUI-4357-50WVN-BA)
- SEGGER J-Link™ Lite Cortex-M JTAG Debugger
- 9 Pin Samtec Cable
- (2) USB Type A to USB Type Mini-B USB Cables
- Universal A/C to 5V USB Power Supply

Also Included:

- Industrial microSDHC card
- Expansion board for μ EZ GUI with 70-pin breakout and optional RS232.
Note: The 4-bit microSD card slot is not designed for this μ EZ GUI.
(Part Number: UEZGUI-EXP-BRKOUT)
- 20 Pin Flex Cable
- 50 Pin Flex Cable