
Hardware Design Checklist

1.0 INTRODUCTION

This document provides a hardware design checklist for the Microchip USB2422. These checklist items should be followed when utilizing the USB2422 in a new design. A summary of these items is provided in [Section 9.0, "Hardware Checklist Summary," on page 15](#). Detailed information on these subjects can be found in the corresponding sections:

- [General Considerations on page 1](#)
- [Power on page 1](#)
- [USB Signals on page 2](#)
- [USB Connectors on page 5](#)
- [Clock Circuit on page 9](#)
- [Power and Startup on page 10](#)
- [Configuration Options on page 12](#)
- [Hardware Checklist Summary on page 15](#)

2.0 GENERAL CONSIDERATIONS

2.1 Required References

The USB2422 implementor should have the following documents on hand:

- *USB2422 2-Port USB 2.0 Hi-Speed Hub Controller Data Sheet*
- USB2.0 Specification
- B1.2 Specification

2.2 Pin Check

- Check the pinout of the part against the data sheet. Ensure all pins match the data sheet and are configured as inputs, outputs, or bidirectional for error checking.

2.3 Ground

- The ground pins, **GND**, should be connected to the solid ground plane on the board.
- It is recommended that all ground connections be tied together to the same ground plane. Separate ground planes are not recommended.

2.4 USB-IF Compliant USB Connectors

- USB-IF certified USB Connectors with a valid Test ID (TID) are required for all USB products to be compliant and pass USB-IF product certification.

3.0 POWER

- The analog supplies (**VDD33**) are located on pins 1, 9, and 18. All these pins require a connection to a regulated 3.3V power plane.
- The **VDD33** pins 1 and 18 each should include 0.1 μF capacitors to decouple the device. The capacitor size should be SMD_0603 or smaller.
- The **VDD33** pin 9 should include 1.0 μF capacitors to decouple the device. The capacitor size should be SMD_0603 or smaller.
- Pin 10 (**CRFILT**) is a core regulator output and should connect to an external filter capacitor. A 1.0 μF capacitor is


USB2422

recommended. Do not power external circuitry from this regulator output.

- Pin 23 (**PLLFLT**) is a PLL regulator output and should connect to an external filter capacitor. A 0.1 μF capacitor is recommended. Do not power external circuitry from this regulator output.

The power and ground connections are shown in [Figure 3-1](#).

FIGURE 3-1: POWER AND GROUND CONNECTIONS



4.0 USB SIGNALS


4.1 USB PHY Interface

- **USBDP_UP** (pin 20): This pin is the positive (+) signal of the upstream USB2.0 differential pair. All necessary USB terminations and resistors are included in the internal IC. This pin can connect directly to the **D+/DP** pin of a USB Connector.
- **USBDM_UP** (pin 19): This pin is the negative (–) signal of the upstream USB2.0 differential pair. All necessary USB terminations and resistors are included in the internal IC. This pin can connect directly to the **D–/DM** pin of a USB Connector.
- **USBDP_DN1** (pin 3): This pin is the positive (+) signal of the downstream port 1 USB2.0 differential pair. All necessary USB terminations and resistors are included in the internal IC. This pin can connect directly to the **D+/DP** pin of a USB Connector.
- **USBDM_DN1** (pin 2): This pin is the negative (–) signal of the downstream port 1 USB2.0 differential pair. All necessary USB terminations and resistors are included in the internal IC. This pin can connect directly to the **D–/DM** pin of a USB Connector.
- **USBDP_DN2** (pin 5): This pin is the positive (+) signal of the downstream port 2 USB2.0 differential pair. All necessary USB terminations and resistors are included in the internal IC. This pin can connect directly to the **D+/DP** pin of an embedded device or second tier hub either directly on the PCB or through a permanently attached USB cable/wiring harness. This should not be wired to a user-accessible USB port.
- **USBDM_DN2** (pin 4): This pin is the negative (–) signal of the downstream port 2 USB2.0 differential pair. All necessary USB terminations and resistors are included in the internal IC. This pin can connect directly to the **D+/DP** pin of an embedded device or second tier hub either directly on the PCB or through a permanently attached USB cable/wiring harness. This should not be wired to a user-accessible USB port.

Note: The polarity of any USB2.0 differential pair may be inverted intentionally either due to design constraints or to correct a design error using the Microchip PortSwap feature. This feature may be configured via SMBus/I²C configuration registers.

For transmit and receive channel connections details, refer to [Figure 4-1](#).

FIGURE 4-1: USB DATA SIGNAL CONNECTIONS



4.1.1 DISABLE DOWNSTREAM PORTS IF UNUSED

- If any downstream port of the USB2422 is unused, it should be disabled. This can be achieved through hub configuration (I²C) or through a port disable strap option.

4.2 USB Protection

- The use of external protection circuitry may be required to provide additional ESD protection beyond what is included in the hub IC. These are generally grouped into three categories:

1. TVS protection diodes
 - ESD protection for IEC-61000-4-2 system level tests
2. Application targeted protection ICs or galvanic isolation devices
 - DC overvoltage protection for short to battery protection
3. Common-mode chokes
 - For EMI reduction

The USB2422 can be used in conjunction with these types of devices, but it is important to understand the negative effect on USB signal integrity that these devices may have. Users must select components accordingly and follow the implementation guidelines from the manufacturer of these devices. They may also use the following general guidelines for implementing these devices:

- Select devices that are designed specifically for high-speed applications only. Based on the USB specification, a total of 5 pF is budgeted for connector, PCB traces, and protection circuitry.
- These devices should be placed as close to the USB connector as possible.
- Never branch the USB signals to reach protection devices. Always place the protection devices directly on top of the USB differential traces.
- The effectiveness of TVS devices depends heavily on effective grounding. Always ensure a very low impedance path to a large ground plane.
- Place TVS diodes on the same layer as the USB signal trace. Avoid vias or place vias behind the TVS device if possible.

USB2422

Note: Microchip PHYBoost configuration options are available for compensating the negative effects of these devices. This feature may help overcome marginal failures. It is simplest to determine the appropriate setting using laboratory experiments, such as USB eye diagram tests, on physical hardware.

5.0 USB CONNECTORS


5.1 Upstream Port VBUS and VBUS_DET

- The upstream port VBUS line must have no more than 10 μF of total capacitance connected.
- The **VBUS_DET** pin is used by the USB2422 to detect the presence of a USB host. The USB host can also toggle the state of VBUS at any time to force a soft Reset and reconnection of the USB2422.
- It is permissible to tie **VBUS_DET** directly to 3.3V. However, this is not recommended because the ability to force a Reset of the hub from the USB host VBUS toggling is lost.

The recommended implementation is shown in Figure 5-1. Note that the precise resistor values are not critical and alternate values may be selected as long as:

- The impedance from the **VBUS** pin of the USB connector to the **VBUS_DET** pin is sufficiently high-impedance to minimize pin leakage when VBUS is present before the Hub IC is powered on.
- A sufficient voltage level is present on the **VBUS_DET** for the full range of VBUS (4.5V – 5.5V).

FIGURE 5-1: RECOMMENDED UPSTREAM PORT VBUS AND VBUS_DET CONNECTIONS



5.2 Downstream Port VBUS and PRTPWRx/OCSx_N

5.2.1 PRTPWRX

The **PRTPWRx** pin is an output pin which has the following states:

1. **PORT OFF:** **PRTPWRx** drives low. The **PRTPWRx** pin will only transition to the PORT ON state through a specific command from the USB host.
 2. **PORT ON:** **PRTPWRx** drives low. The **PRTPWRx** pin will only transition to the PORT OFF state if:
 - An overcurrent event is sensed on **OCSx_N** pin.
 - A command from the USB host is received which instructs the hub to disable power.
 - The hub is reset or experiences a POR event
- To ensure minimal BOM cost and simplicity, select a port power controller device with a 3.3V logic level, active-high input. If a device which operates from a 5V logic level is selected, the **PRTPWRx** signal may need to be boosted using external logic. If a port power controller with active low input is selected, the **PRTPWRx** signal needs to be inverted using external logic.

5.2.2 OCSX_N


The **OCSx_N** pin is an input buffer which monitors overcurrent events. The pin includes an internal pull-up resistor to the 3.3V domain, so an external pull-up resistor is not required. The pin state is ignored when the port is in the PORT OFF state. When the port is in the PORT ON state, an overcurrent event is detected if the state of the pin is detected as low (below the V_{IL} voltage). When an overcurrent event is detected, the port automatically moves to the PORT OFF state until the USB host can be notified of the overcurrent event.

USB2422

To ensure minimal BOM cost and simplicity, select a port power controller device with an active-low, open-drain fault indicator output. If a port power controller with active-high fault indicator output is selected, the OCSx_N signal needs to be inverted using external logic.

A typical VBUS port power control implementation is shown in [Figure 5-2](#).

FIGURE 5-2: DOWNSTREAM VBUS AND PRTCTL1 CONNECTIONS




Note: The implementation, as shown in [Figure 5-2](#), assumes that the port power controller has an active-high enable input, and an active-low, open-drain style fault indicator. External polarity inversion through buffers or FETs may be required if the port power controller has different I/O characteristics.

5.3 Downstream Port Type-C Support

- USB2422 may be used with Type-C as the downstream port. This requires a Type-C port controller or combined port power controller and Type-C port controller. The USB2422 simply controls the Type-C port controller in same way it would control a standard Type-A port power controller. It does not require any kind of Type-C port status information from the Type-C port controller. The P RTPWRx signal should be connected to an enable pin on the Type-C controller, and the OCSx_N signal should connect to the fault indicator output of the port power controller.
- If the Type-C controller and the port power controller are separate devices, the Type-C controller must control the enable pin of the port power controller. The P RTPWRx should not directly control the VBUS enable signal of the port power controller.
- A Type-C controller may be configured to signal a 500 mA, 1.5A, or 3.0A port power capability. The selected port power controller should be sized accordingly.

A typical implementation is shown in [Figure 5-3](#).

FIGURE 5-3: DOWNSTREAM VBUS AND PRTCTL1 CONNECTIONS WITH A TYPE-C PORT



Note: The implementation shown in [Figure 5-3](#) assumes that the Type-C controller has an active-high enable input, and the port power controller has an active-low, open-drain style fault indicator. External polarity inversion through buffers or FETs may be required if the Type-C controller and port power controller have different I/O characteristics.


5.4 GND and EARTH Recommendations

- The **GND** pins of the USB connector must be connected to the PCB with a low-impedance path directly to a large GND plane.
- The **EARTH** pins of the USB connector may be connected with one of these two ways:
 - (Recommended) To **GND** through a resistor and capacitor in parallel. An RC filter can help to decouple and minimize EMI between a PCB and a USB cable.
 - Directly to the GND plane

USB2422

The recommended implementation is shown in [Figure 5-4](#).

FIGURE 5-4: RECOMMENDED USB CONNECTOR GND AND EARTH CONNECTIONS



6.0 CLOCK CIRCUIT

6.1 Crystal and External Clock Connection


A 24.000 MHz (± 350 ppm) reference clock is the source for the USB interface and for all other functions of the device. (See [Figure 6-1](#).) For exact specifications and tolerances, refer to the latest revision of the *USB2422 Data Sheet*.

- **XTALIN** (pin 22) is the clock circuit input for the USB2422. This pin requires a capacitor to ground. One side of the crystal connects to this pin.
- **XTALOUT** (pin 21) is the clock circuit output for the USB2422. This pin requires a capacitor to ground. One side of the crystal connects to this pin.
- The crystal loading capacitor values are system dependent based on the total C_L specifications of the crystal and the stray capacitance value. The PCB design, crystal, and layout contribute to the characteristics of this circuit. A commonly used formula for calculating the appropriate physical C_1 and C_2 capacitor values is:
 - $C_L = ((C_{X1})(C_{X2}) / (C_{X1} + C_{X2}))$
 - Where: C_L is the spec from the crystal data sheet, $C_{X1} = C_{\text{stray}} + C_1$, $C_{X2} = C_{\text{stray}} + C_2$

Note: C_{stray} is the stray or parasitic capacitance due to PCB layout. It can be assumed to be very small, in the 1 pF to 2 pF range, and then verified by physical experiments in the lab if PCB simulation tools are not available.

- Alternately, a 24.000 MHz, 1.2V to 3.3V clock oscillator may be used to provide the clock source for the USB2422. When using a single-ended clock source, **XTALOUT** (pin 21) should be left floating as a No Connect (NC).

FIGURE 6-1: CRYSTAL AND OSCILLATOR CONNECTIONS



USB2422

7.0 POWER AND STARTUP

7.1 RBIAS Resistor

- **RBIAS** (pin 24) on the USB2422 must connect to ground through a 12 k Ω resistor with a tolerance of 1.0%. This is used to set up critical bias currents for the internal circuitry. This should be placed as close to the IC pin as possible, and be given a dedicated, low-impedance path to a ground plane.

7.2 Board Power Supplies

7.2.1 POWER RISE TIME

- The power rail voltage and rise time should adhere to the supply rise time specifications defined in the *USB2422 Data Sheet*.
- If a monotonic or fast power rail rise cannot be assured, then the RESET_N signal should be controlled by a Reset supervisor and only released when the power rail has reached a stable level.


7.2.2 CURRENT CAPABILITY

- It is important to size the 5V and 3.3V power rails appropriately. The 5V power supply must be capable of supplying sufficient power for all exposed USB ports concurrently without drooping below the minimum voltage permissible in the USB specifications:
 - 500 mA per-port for USB2 Ports if BC1.1 is not enabled on the port.
 - 1.5A per BC1.2-enabled port (if BC1.1 is enabled)
 - 1.5A or 3.0A per Type-C port (depending on the setting of the Type-C controller)
- The 3.3V power supply must be able to supply enough power to the USB hub IC. It is recommended that a 3.3V power rail be sized such that is able to supply the maximum power consumption specification, as displayed in the *USB2422 Data Sheet*.

7.3 Reset Circuit


- **RESET_N** (pin 15) is an active-low reset input. This signal resets all logic and registers within the USB2422. A hardware Reset (**RESET_N** assertion) is not required following power-up. Please refer to the latest copy of the *USB2422 Data Sheet* for Reset timing requirements.
- [Figure 7-1](#) shows a recommended reset circuit for powering up the USB2422 when a Reset is triggered by the power supply. The values for the “R” resistor and “C” capacitor are not critical and may be adjusted based on individual system needs and preferences.

FIGURE 7-1: RESET TRIGGERED BY POWER SUPPLY



- [Figure 7-2](#) details the recommended Reset circuit for applications where Reset is driven by an external CPU/MCU. The Reset out pin (**RST_OUT_N**) from the CPU/MCU provides the warm Reset after power-up. The values for the “R” resistor and “C” capacitor are not critical and may be adjusted based on individual system needs and preferences.

FIGURE 7-2: RESET CIRCUIT INTERFACE WITH CPU/MCU RESET OUTPUT



8.0 CONFIGURATION OPTIONS

- The USB2422 can be configured in one or 2 ways:
 1. SMBus (via external MCU/SOC)
 2. Hardware Resistor Straps (resistor pull-down/pull-up options)
- The hub must be configured completely via SMBus or hardware resistor straps. A combined or hybrid approach is not supported.

8.1 Configuration via MCU/SoC Memory


8.1.1 MCU/SOC OPERATION SUMMARY

- By default, the USB2422 executes based on internal register defaults, and an external MCU/SoC device is not explicitly required. If settings which differ from the internal defaults are required by the application, an external MCU/SoC may be used to modify the register settings. Only the specific settings which have to be modified from the default need to be changed.
- The USB2422 supports only one address option: 010_1100b

8.1.2 MCU/SOC CONNECTION DIAGRAMS

The recommended schematic connections for an MCU/SOC memory device are shown in [Figure 8-1](#).

FIGURE 8-1: RECOMMENDED CONNECTIONS IF CONFIGURED VIA MCU/SOC



8.1.3 SELF-POWERED/BUS-POWERED SETTINGS (AVAILABLE VIA SMBUS CONFIGURATION ONLY)

- In a typical USB2422 application, the hub should be configured as self-powered, which is the default configuration setting. The following guidelines can be used to determine which setting to use:
 1. If the entire system (hub included) is powered completely from the upstream USB connector's **VBUS** pin and the system is designed to operate using standard USB cabling and any standard USB host, then the hub system is bus-powered.
 2. If the entire system (hub included) is always powered by a separate power connector, then the hub system is self-powered.
 3. If the hub included is part of a larger embedded system with fixed cabling and a fixed USB host, then the hub system is most likely self-powered (even if all of the power is derived from the upstream USB connector's **VBUS** pin).
- The self-powered or bus-powered device settings do not impact the operation of the hub in any way. The settings only modify select USB descriptors which the USB host will use to budget power accordingly. Since a standard USB2.0 port is required to supply 500 mA to the downstream port, a self-powered hub and all of its downstream ports must continue to operate within that 500 mA budget. A USB host will typically limit the downstream ports of a self-powered hub to 100 mA. Any device connecting to a self-powered hub that needs more than 100 mA will be prevented from operating by the USB host.


- The USB2422 also supports dynamic self-powered and bus-powered operation via the **LOCAL_PWR** control input pin. This feature must be enabled via SMBus configuration (DYNAMIC bit in CFG1 register). Once enabled, the **LOCAL_PWR** pin works as:
 - 0: Self-Powered, and no downstream port power restrictions will be in place.
 - 1: Bus-Powered - downstream port power restrictions will be enforced by the USB host.

The **LOCAL_PWR** cannot be changed dynamically. To change the mode of operation, the pin state must be changed, then the hub must be reset for the hub to communicate the new mode of operation descriptors to the USB host.

8.2 Configuration via Hardware Resistor Straps

Follow the schematic guidance in [Figure 8-2](#) for strap configuration.

FIGURE 8-2: RECOMMENDED CONNECTIONS IF CONFIGURED VIA STRAP OPTIONS



8.2.1 BATTERY CHARGING SETTINGS

The USB2422 hub includes built-in battery charging support compliant to Charging Downstream Port (CDP) mode of the BC1.1 USB Battery Charging Specification. This allows portable device charging up to 1.5A with operational USB data. The feature is available on Port 1 only. Port 2 does not support BC1.1 operation. The BC_EN1 strap setting is sampled once at startup. The configuration strap options are described in [Table 8-1](#).

TABLE 8-1: BC_EN1 CONFIGURATION STRAP OPERATION

Hardware Setting	Effect	Additional Notes
Floating or Pull-down to GND	All Ports - BC disabled	Battery Charging is not enabled. Select this option if configuration will be done via EEPROM or from an MCU/SOC via SMBus
Pull-up to 3.3V	Port 1 BC enabled	Battery Charging is enabled on Port 1. See Note 1 .

Note 1: Dedicated Charging Port (DCP) is not supported as the mechanism for a single port to switch between CDP and DCP modes was not introduced until the BC1.2 specification was released.

8.2.2 PORT DISABLE STRAPS

- If using the port disable strap option, the **USBDP_DNx** and **USBDM_DNx** signals should be pulled high to 3.3V. This connection can be made directly to the 3.3V power net or through a pull-up resistor. The pins may also be shorted together to simplify the layout.

Note: Both USB D+ and D– signals must be pulled high to effectively disable the port. If only 1 pin is pulled to 3.3V, the port will not be disabled.

8.2.3 NON-REMOVABLE PORT SETTINGS

- In a typical USB2422 application, downstream ports are routed to a user-accessible USB connector and hence the downstream port should be configured as a removable port.
- The USB2422 has two configuration strap option pins, **NON_REM[1:0]**, which can be used to set the non-removable configurations for Ports 1 and 2. (See [Table 8-2](#).) These are located on pins 13 and 17. The strap setting is sampled once at startup. A configuration strap option must be selected if the hub is not configured via EEPROM or from an MCU/SOC via SMBus.
- Note that the **SUSP_IND/LOCAL_PWR/NON_REM0** operates in the following manner when EEPROM or SOC-based SMBus configuration is not present:
 - During hub boot, the pin is sensed to determine the **NON_REM0** setting.
 - During hub runtime, the pin operates as an output which reflects the suspend state of the hub:
 - Output Low (0V):** Hub is unconfigured (enumeration by the USB host is not complete) or in USB Suspend.
 - Output High (3.3V):** Hub is configured (enumeration by the USB host is complete), and hub is active.

The **LOCAL_PWR** Output mode is not available. This pin function requires EEPROM or SOC-based SMBus configuration settings.

TABLE 8-2: NON_REM[1:0] SETTINGS

Setting	Effect
NON_REM1 = 0, NON_REM0 = 0	Ports 1 and 2 are removable.
NON_REM1 = 0, NON_REM0 = 1	Port 1 is non-removable. Port 2 is removable.
NON_REM1 = 1, NON_REM0 = 0	Ports 1 and 2 are non-removable.
NON_REM1 = 1, NON_REM0 = 1	Undefined setting. Do not select.

The following guidelines can be used to determine which setting to use:

- If the port is routed to a user-accessible USB connector, it is removable.
- If the port is routed to a permanently attached an embedded USB device on the same PCB or non-user-accessible wiring or cable harness, it is non-removable.
- The removable and non-removable device settings do not have any impact on the hub's operations in any way. The settings only modify selected USB descriptors which the USB host may use to understand if a port is a user-accessible port, or if the device is a permanently attached device. Under standard operating conditions, the USB host may or may not modify its operations based on this information. Certain USB compliance tests are impacted by this setting, so designs required to undergo USB-compliance testing and certification must have correct configuration settings.

9.0 HARDWARE CHECKLIST SUMMARY

TABLE 9-1: HARDWARE DESIGN CHECKLIST

Section	Check	Explanation	✓	Notes
Section 2.0, "General Considerations"	Section 2.1, "Required References"	Verify that the references are on hand.		
	Section 2.2, "Pin Check"	Verify that the pins match the data sheet.		
	Section 2.3, "Ground"	Verify that the grounds are tied together.		
	Section 2.4, "USB-IF Compliant USB Connectors"	Verify that USB-IF compliant USB connectors with an assigned TID are used in the design (if USB compliance is required for the design).		
Section 3.0, "Power"		Ensure VDD33 is within the range of 3.0V to 3.6V, 0.1 μ F capacitors are connected to pins 1 and 18, and a 1.0 μ F capacitor is connected to pin 9.		
		Ensure CRFILT has a 1.0 μ F capacitor to GND .		
		Ensure PLLFILT has a 0.1 μ F capacitor to GND .		
Section 4.0, "USB Signals"	Section 4.1, "USB PHY Interface"	Verify that the USB data pins are correctly routed to the USB connectors. Pay special attention to the polarity of the USB2.0 D+ and D– data lines.		
	Section 4.2, "USB Protection"	Verify that ESD/EMI protection devices are designed specifically for high-speed data applications and that the combined parasitic capacitance the protection devices, USB traces, and USB connector do not exceed 5 pF on each USB trace.		
Section 5.0, "USB Connectors"	Section 5.1, "Upstream Port VBUS and VBUS_DET"	Verify that the Upstream Port VBUS has no more than 10 μ F capacitance and that the VBUS signal is properly divided down to a 3.3V signal and connected to the VBUS_DET pin of the hub.		
	Section 5.2, "Downstream Port VBUS and PRTPWRx/OCSx_N"	If the downstream ports are standard Type-A ports, verify that PRTPWRx and OCSx_N are properly connected to the enable pin of the downstream port power controller and the fault indicator output of the port power controller.		
	Section 5.3, "Downstream Port Type-C Support"	If the downstream ports are standard Type-C ports, verify that PRTPWRx is properly connected to the enable pin of the Type-C port controller, and OCSx_N is connected to the fault indicator output of the port power controller.		
	Section 5.4, "GND and EARTH Recommendations"	Verify that the USB connector is properly connected to PCB ground on both the GND pins and the SHIELD pins. It is recommended that an RC filter be placed between the SHIELD pins and PCB ground.		

TABLE 9-1: HARDWARE DESIGN CHECKLIST (CONTINUED)

Section	Check	Explanation	✓	Notes
Section 6.0, "Clock Circuit"	Section 6.1, "Crystal and External Clock Connection"	Confirm that the crystal or clock is 24.000 MHz (± 350 ppm).		
		If a single-ended clock is used, ensure it is connected to XTALI while leaving XTALO floating.		
		If a crystal is used, ensure the loading capacitors are appropriately sized for the crystal loading requirement.		
Section 7.0, "Power and Startup"	Section 7.1, "RBIAS Resistor"	Confirm that a 12.0 k Ω 1% resistor is connected between the RBIAS pin and the PCB ground.		
	Section 7.2, "Board Power Supplies"	Verify that the board power supplies deliver 3.0V to 3.6V to the hub power rails, and that the power-on rise time meets the requirement of the hub as defined in the data sheet.		
		If the rise time requirement cannot be met, ensure that the RESET_N line is held low until the power regulators reach a steady state.		
	Section 7.3, "Reset Circuit"	Ensure that the RESET_N signal has an external pull-up resistor, or is otherwise properly controlled by an external SOC, MCU, or Reset supervisor device.		
Section 8.0, "Configuration Options"	Section 8.1, "Configuration via MCU/ SoC Memory"	Determine which mode of configuration is required, and ensure that hardware is properly designed for either defaults, MCU/ SoC configuration via SMBus, or Hardware Configuration Strap resistors.		
	Section 8.1.3, "Self-Powered/Bus-Powered Settings (Available via SMBus Configuration Only)"	If performing hub configuration via MCU/SOC, ensure the Self-Powered/Bus-Powered settings are correct, and hardware is designed appropriately.		
	Section 8.2, "Configuration via Hardware Resistor Straps"	Ensure the RESET_N is pulled to ground and that all other configuration strap pins are configured for the intended settings.		
	Section 8.2.1, "Battery Charging Settings"	Verify if the Battery Charging configuration strap is set via hardware properly (if configuring hub via Hardware Resistor Straps).		
	Section 8.2.2, "Port Disable Straps"	Verify if the Port Disable configuration straps are set via hardware properly (if configuring hub via Hardware Resistor Straps).		
	Section 8.2.3, "Non-Removable Port Settings"	Verify if the non-removable configuration straps are set via hardware properly (if configuring hub via Hardware Resistor Straps).		

APPENDIX A: REVISION HISTORY

TABLE A-1: REVISION HISTORY

Revision Level & Date	Section/Figure/Entry	Correction
DS00004196A (09-20-21)	Initial release	

THE MICROCHIP WEB SITE

Microchip provides online support via our WWW site at www.microchip.com. This web site is used as a means to make files and information easily available to customers. Accessible by using your favorite Internet browser, the web site contains the following information:

- **Product Support** – Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** – Frequently Asked Questions (FAQ), technical support requests, online discussion groups, Microchip consultant program member listing
- **Business of Microchip** – Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

CUSTOMER CHANGE NOTIFICATION SERVICE

Microchip's customer notification service helps keep customers current on Microchip products. Subscribers will receive e-mail notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, access the Microchip web site at www.microchip.com. Under "Support", click on "Customer Change Notification" and follow the registration instructions.

CUSTOMER SUPPORT

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Field Application Engineer (FAE)
- Technical Support

Customers should contact their distributor, representative or Field Application Engineer (FAE) for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in the back of this document.

Technical support is available through the web site at: <http://microchip.com/support>

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is “unbreakable”. Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at <https://www.microchip.com/en-us/support/design-help/client-support-services>.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Trademarks

The Microchip name and logo, the Microchip logo, Adaptec, AnyRate, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, CryptoMemory, CryptoRF, dsPIC, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Klear, LANCheck, LinkMD, maxStylus, maxTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-B, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, Flashtec, Hyper Speed Control, HyperLight Load, IntelliMOS, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet-Wire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, TrueTime, WinPath, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, GridTime, IdealBridge, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, Inter-Chip Connectivity, JitterBlocker, Knob-on-Display, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, NVMe Express, NVMe, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SmartHLS, SMART-I.S., storClad, SQL, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, TSHARC, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, Symmcom, and Trusted Time are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2021, Microchip Technology Incorporated and its subsidiaries.

All Rights Reserved.

ISBN: 978-1-5224-8945-0

For information regarding Microchip's Quality Management Systems, please visit www.microchip.com/quality.

Worldwide Sales and Service

AMERICAS

Corporate Office
2355 West Chandler Blvd.
Chandler, AZ 85224-6199
Tel: 480-792-7200
Fax: 480-792-7277
Technical Support:
<http://www.microchip.com/support>
Web Address:
www.microchip.com

Atlanta
Duluth, GA
Tel: 678-957-9614
Fax: 678-957-1455

Austin, TX
Tel: 512-257-3370

Boston
Westborough, MA
Tel: 774-760-0087
Fax: 774-760-0088

Chicago
Itasca, IL
Tel: 630-285-0071
Fax: 630-285-0075

Dallas
Addison, TX
Tel: 972-818-7423
Fax: 972-818-2924

Detroit
Novi, MI
Tel: 248-848-4000

Houston, TX
Tel: 281-894-5983

Indianapolis
Noblesville, IN
Tel: 317-773-8323
Fax: 317-773-5453
Tel: 317-536-2380

Los Angeles
Mission Viejo, CA
Tel: 949-462-9523
Fax: 949-462-9608
Tel: 951-273-7800

Raleigh, NC
Tel: 919-844-7510

New York, NY
Tel: 631-435-6000

San Jose, CA
Tel: 408-735-9110
Tel: 408-436-4270

Canada - Toronto
Tel: 905-695-1980
Fax: 905-695-2078

ASIA/PACIFIC

Australia - Sydney
Tel: 61-2-9868-6733

China - Beijing
Tel: 86-10-8569-7000

China - Chengdu
Tel: 86-28-8665-5511

China - Chongqing
Tel: 86-23-8980-9588

China - Dongguan
Tel: 86-769-8702-9880

China - Guangzhou
Tel: 86-20-8755-8029

China - Hangzhou
Tel: 86-571-8792-8115

China - Hong Kong SAR
Tel: 852-2943-5100

China - Nanjing
Tel: 86-25-8473-2460

China - Qingdao
Tel: 86-532-8502-7355

China - Shanghai
Tel: 86-21-3326-8000

China - Shenyang
Tel: 86-24-2334-2829

China - Shenzhen
Tel: 86-755-8864-2200

China - Suzhou
Tel: 86-186-6233-1526

China - Wuhan
Tel: 86-27-5980-5300

China - Xian
Tel: 86-29-8833-7252

China - Xiamen
Tel: 86-592-2388138

China - Zhuhai
Tel: 86-756-3210040

ASIA/PACIFIC

India - Bangalore
Tel: 91-80-3090-4444

India - New Delhi
Tel: 91-11-4160-8631

India - Pune
Tel: 91-20-4121-0141

Japan - Osaka
Tel: 81-6-6152-7160

Japan - Tokyo
Tel: 81-3-6880-3770

Korea - Daegu
Tel: 82-53-744-4301

Korea - Seoul
Tel: 82-2-554-7200

Malaysia - Kuala Lumpur
Tel: 60-3-7651-7906

Malaysia - Penang
Tel: 60-4-227-8870

Philippines - Manila
Tel: 63-2-634-9065

Singapore
Tel: 65-6334-8870

Taiwan - Hsin Chu
Tel: 886-3-577-8366

Taiwan - Kaohsiung
Tel: 886-7-213-7830

Taiwan - Taipei
Tel: 886-2-2508-8600

Thailand - Bangkok
Tel: 66-2-694-1351

Vietnam - Ho Chi Minh
Tel: 84-28-5448-2100

EUROPE

Austria - Wels
Tel: 43-7242-2244-39
Fax: 43-7242-2244-393

Denmark - Copenhagen
Tel: 45-4485-5910
Fax: 45-4485-2829

Finland - Espoo
Tel: 358-9-4520-820

France - Paris
Tel: 33-1-69-53-63-20
Fax: 33-1-69-30-90-79

Germany - Garching
Tel: 49-8931-9700

Germany - Haan
Tel: 49-2129-3766400

Germany - Heilbronn
Tel: 49-7131-72400

Germany - Karlsruhe
Tel: 49-721-625370

Germany - Munich
Tel: 49-89-627-144-0
Fax: 49-89-627-144-44

Germany - Rosenheim
Tel: 49-8031-354-560

Israel - Ra'anana
Tel: 972-9-744-7705

Italy - Milan
Tel: 39-0331-742611
Fax: 39-0331-466781

Italy - Padova
Tel: 39-049-7625286

Netherlands - Drunen
Tel: 31-416-690399
Fax: 31-416-690340

Norway - Trondheim
Tel: 47-7288-4388

Poland - Warsaw
Tel: 48-22-3325737

Romania - Bucharest
Tel: 40-21-407-87-50

Spain - Madrid
Tel: 34-91-708-08-90
Fax: 34-91-708-08-91

Sweden - Gothenberg
Tel: 46-31-704-60-40

Sweden - Stockholm
Tel: 46-8-5090-4654

UK - Wokingham
Tel: 44-118-921-5800
Fax: 44-118-921-5820