

‘19+ RZR® DASHBOARD AMPLIFIER MOUNT

Parts list: 1 Triple Amp Mount
& 5 Self Tapping Screws

PART #: UTVS-RZR-AMPMT-DASH19



STEP 1: REMOVE THE HOOD.

STEP 2: REMOVE THE 2 SPEED CLIPS & 4 TORX SCREWS ON THE UPPER DASH AND REMOVE DASH.

STEP 3: REMOVE PASSENGER SIDE FENDER. (REFERENCE PICTURE 1)

STEP 4: REMOVE PASSENGER UPPER DASH POCKET. (REFERENCE PICTURE 2)

STEP 5: REMOVE BOTH BOLTS ON THE FRONT PASSENGER CAGE.

STEP 6: MOVE THE INNER FENDER UP AND OUT OF THE WAY. WITHOUT HAVING TO COMPLETELY REMOVE THE INNER FENDER YOU CAN ZIP TIE THE FENDER UP TO THE ROOF. (REFERENCE PICTURE 3 & 4)

STEP 7: RELOCATE GPS ANTENNA WIRE FROM THE RIDE COMMAND UNDER THE CROSS BAR AND BACK INTO THE RIDE COMMAND UNIT. (REFERENCE PICTURE 5 & 6)

STEP 8: REMOVE BOLT FROM DRIVER SIDE FENDER. (REFERENCE PICTURE 7)

STEP 9: SLIDE AMP MOUNT INTO PLACE. (REFERENCE PICTURE 8)

STEP 10: SCREW IN SELF TAPPER THROUGH THE PROVIDED HOLES ON THE AMP MOUNT. (REFERENCE PICTURE 8)